



SPECIAL PROCEDURE / PRACTICE IFR DEPARTURE

APPLICATION

- These procedures are restricted by the following:
- 1. MILITARY HELICOPTER OPERATIONS ONLY.
 - 2. NOT ASSESSED FOR INSTRUMENT METEOROLOGICAL CONDITIONS.
 - 3. VISUAL FLIGHT CONDITIONS REQUIRED TO MEA.

GENERAL

This Special Procedure allows Military helicopters to conduct "SID" like operations in a VFR environment. Military helicopters may use this Special Procedure to depart the Southport airport and clear themselves from VFR traffic while operating under IFR Flight Plans. Helicopters will depart from the helo pads as required. Pilots are to avoid traffic as per VFR procedures until completion of the Special Procedure. Upon completion, aircraft are expected to proceed direct to their next Flt Plan waypoint. Departures in strong winds may require heading adjustments to arrive by the BRIDGE, YANKEE and ZULU and to remain clear of Grabber Green and Sensitive Citizens. The navigation facility for this procedure is the YPG VOR/DME, 114.6.

ROTOR ONE DEPARTURE – TRANSITION ROUTE OVERVIEW

- PAD 1 –

BRIDGE EAST:

BRIDGE NORTH:

BRIDGE WEST:

Either RWY 27/31 ACTIVE, Pad 1 to BRIDGE, then eastbound.

RWY 02 ACTIVE, Pad 1 to BRIDGE, then north to TransCan HWY, then eastbound.

Any of RWYs 02/27/31 ACTIVE, Pad 1 to BRIDGE, then north towards Delta Beacon for westbound aircraft.
- PAD 2 –

YANKEE EAST

ZULU EAST:

YANKEE WEST:

Either RWY 13/20 ACTIVE, Pad 2 to YANKEE, then eastbound.

RWY 09 ACTIVE, Pad 2 to ZULU, then eastbound.

Either RWY 13/20 ACTIVE, Pad 2 to YANKEE, then north towards Delta Beacon for westbound aircraft.

ROTOR ONE DEPARTURE (VFRD1.)

- BRIDGE WEST:

BRIDGE NORTH:

BRIDGE EAST:

YANKEE EAST:

ZULU EAST:

YANKEE WEST:

COMMUNICATIONS:
- Climb hdg 010° to 1400' ASL. At 5.5 DME turn left hdg 340° climb to and maintain 3000' ASL BPOC.

Climb hdg 010° to 1400' ASL. At 4.0 DME right turn hdg 085°. At 5.6 DME proceed on course, climb to and maintain 3000' ASL.

Climb hdg 010° to 1400' ASL. At 2.2 DME right turn hdg 076°. At 5.0 DME proceed on course, climb to and maintain 3000' ASL.

Climb hdg 065° to 1400' ASL. At 5.5 DME proceed on course, climb to and maintain 3000' ASL.

Climb hdg 106° to 1400' ASL. At 4.0 DME proceed on course, climb to and maintain 3000' ASL.

Climb hdg 065° to 1400' ASL. At 2.6 DME left turn hdg 345°. At 5.5 DME left turn to 340° climb to and maintain 3000' ASL BPOC.

Unless otherwise directed, when initiating a climb from 1400 feet, switch CYPG TWR 126.2 and check-in. Include Transition Route Name and assigned altitude.

Communications Failure

- On recognition of a communication failure 10 minutes or less after take-off, proceed as follows:
- 1. Remain in Visual Flight Conditions;
 - 2. Transponder Mode A/3 7600.
 - 3. Recover at Southport using the appropriate "VFR Helicopter Arrival Route" via the Bridge, Yankee, Zulu or Whiskey.
 - 4. Expect/anticipate visual light signals from Tower and proceed accordingly.

