



DEPARTURE PROCEDURE

Departure Procedure

- Rwy 07 – ½:** Climb between hdg **100°** CCW to **255°** to **2900** BPOC.
Note: Trees to 679 ASL aprx 0.2 NM past departure end of rwy, 750' RIGHT of rwy centreline.
- Rwy 12 – ½:** Requires a minimum climb gradient of **400** ft/NM to **1100**. Do NOT exceed 180 kt prior to completion of initial LEFT turn. Climbing LEFT turn between hdg **095°** CCW to **305°** to **2100** BPOC.
Note: Trees to 689 ASL aprx 0.2 NM past departure end of rwy, 650' RIGHT of rwy centreline.
or
SPEC VIS - Climb in visual conditions to cross the aprt at or above **2100** BPOC.
- Rwy 25 – ½:** Climb between hdg **238°** CW to **074°** to **2100** BPOC.
Note: Trees to 689 ASL aprx 0.2 NM past departure end of rwy, 600' LEFT of rwy centreline.
- Rwy 30 – ½:** Climb between hdg **170°** CW to **100°** to **2100** BPOC.
Note: Trees to 735 ASL aprx 0.2 NM past departure end of rwy, 700' LEFT and RIGHT of rwy centreline.

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
400 FT/NM	600	800	940	1070	1200	1340	1670	2000

Source of Canadian Civil Aeronautical Data: © 2026 NAV CANADA All rights reserved

