



Departure Procedure

Rwy 10 – ½: When CYA528 is NOT active: Requires a minimum climb gradient of **290 ft/NM to 2500**.
When CYA528 is active: Requires a minimum climb gradient of **290 ft/NM to 2500**. Climb between hdg **112° CCW to 277° to 5300 BPOC**.
Note: Trees to 444 ASL aprx 0.2 NM past departure end of rwy, 240' LEFT and RIGHT of rwy centreline.
or
SPEC VIS - Climb in visual conditions to cross the aprt at or above **2300 BPOC**.

Rwy 28 – ½: When CYA528 is NOT active: Requires a minimum climb gradient of **230 ft/NM to 2900**.
When CYA528 is active: Requires a minimum climb gradient of **230 ft/NM to 2900**. Climb between hdg **188° CW to 097° to 4600 BPOC**.
or
SPEC VIS - Climb in visual conditions to cross the aprt at or above **2300 BPOC**.

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
230 FT/NM	350	460	540	620	690	770	960	1150
290 FT/NM	440	580	680	780	870	970	1210	1450

Source of Canadian Civil Aeronautical Data: © 2026 NAV CANADA All rights reserved

