

CYSF

ANNUAL RATE OF CHANGE 14' W

VAR 11° E 2012

DEPARTURE CLIMB RATE V/V (FPM)								
GROUND SPEED	90	120	140	160	180	200	250	300
260 FT/NM	390	520	610	700	780	870	1090	1300

894

59 15.2

59 15.2

59 14.8

59 14.8

105 51

105 50

105 51

105 50

ELEV 801

ELEV 779

063°

243°

24

06

5052 x 100

CYSF
N59 15.02
W105 50.48

Down 0.44%

TAKE-OFF MINIMA

Rwys 06; 24: *

SCALE IN FEET

1000 0 1000

* DEPARTURE PROCEDURE

Rwy 06 - 1/2

Note: Trees to 814 ASL aprx 0.2 NM past departure end of rwy, both LEFT and RIGHT of rwy centreline.

Rwy 24 - 1/2 Requires a minimum climb gradient of **260** ft/NM to **1900**.

Note: Trees to 886 ASL aprx 500' past departure end of rwy, both LEFT and RIGHT of rwy centreline.

or

SPEC VIS - Climb in visual conditions to cross the apt at or above **1800** BPOC.

Source of Canadian Civil Aeronautical Data: © 2026 NAV CANADA All rights reserved

CYSF