

Departure Route Description

- Rwy 17:**
- 1. Climb hdg **172°** to **1100**. Continue climbing direct to AGNEX.
  - 2. Maintain **3400** or as assigned.
  - 3. At AGNEX, hold NE on **290°** INBD track all turns RIGHT. Do not exceed 230 kt.
  - 4. Expect further clearance 10 minutes after take off.

**Note:** Trees to 623 ASL aprx 850' past departure end of rwy, 300' LEFT and RIGHT of centreline.

- Rwy 35:**
- 1. Requires a minimum climb gradient of **280 ft/NM** to **1100**. Do not exceed 210 kt until AGNEX. Climb hdg **352°** to **1100**. Climbing RIGHT turn direct to AGNEX.
  - 2. Maintain **3400** or as assigned.
  - 3. At AGNEX, hold NE on **290°** INBD track all turns RIGHT. Do not exceed 230 kt.
  - 4. Expect further clearance 10 minutes after take off.

**Note:** Trees to 623 ASL aprx 0.2 NM past departure end of rwy, 600' LEFT of centreline.

DEPARTURE CLIMB RATE V/V (FPM)

|              |     |     |     |     |     |     |      |      |
|--------------|-----|-----|-----|-----|-----|-----|------|------|
| GROUND SPEED | 90  | 120 | 140 | 160 | 180 | 200 | 250  | 300  |
| 280 FT/NM    | 420 | 560 | 660 | 750 | 840 | 940 | 1170 | 1400 |

Communication Failure

On recognition of failure 10 minutes or less after take-off and in IFR weather conditions proceed as follows:

- 1. Select transponder 7600;
- 2. Proceed directly on course 5 minutes after selecting 7600, then;
- 3. Climb to flight planned altitude.

**Note:** If communication failure occurs more than 10 minutes after take-off, comply with appropriate procedures for enroute communications failure.