

Departure Route Description

Unless otherwise assigned by ATC

- Rwy 06:

1. Turn right hdg **150°** for RADAR vectors to assigned route.

2. Climb to and maintain **3000'** ASL until 15 DME then climb to **5000'** ASL or flight planned altitude, whichever is lower.

Rwy 24:

1. Turn left hdg **150°** for RADAR vectors to assigned route.

2. Climb to and maintain **3000'** ASL until 15 DME then climb to **5000'** ASL or flight planned altitude, whichever is lower.
- Communication Failure
- Transponder mode A/3 code 7600
- On recognition of a failure 20 minutes or less after takeoff and in IFR weather condition proceed as follows:
1. Upon reaching last assigned altitude proceed on course;

2. Do not climb above last assigned altitude for 5 minutes after recognition of failure, then;

3. Climb to flight planned altitude.
- NOTE:** If communication failure occurs more than 20 minutes after take-off, comply with the appropriate procedure for communication failure enroute.
- COUNTY ONE DEP

(COUNTY1.)(DND)
- CYTR-SID-1A
- CYTR
- EFF 24 JUL 14
- Canada Air Pilot

Effective 0901Z 14 MAY 2026 to 0901Z 9 JUL 2026
- Source of Canadian Civil Aeronautical Data: © 2026 NAV CANADA All rights reserved