

## Departure Route Description

**Rwy 16 - ½:** Requires a minimum climb gradient of **500 ft/NM** to **1800**. Climb track **160°** to cross AVRAM at or above **1800**, then proceed via assigned transition. Maintain **5000** or flight planned altitude, whichever is lower. Expect on course when RADAR identified.

DEPARTURE CLIMB RATE V/V (FPM)

| GROUND SPEED | 90  | 120  | 140  | 160  | 180  | 200  | 250  | 300  |
|--------------|-----|------|------|------|------|------|------|------|
| 500 FT/NM    | 750 | 1000 | 1170 | 1340 | 1500 | 1670 | 2090 | 2500 |

**TASKO TRANSITION:** Do not exceed 220 kt until ROSNU. At AVRAM, climbing LEFT turn direct to ROSNU. Then climbing LEFT turn track **359°** to TASKO to the assigned route.

**AGNIG TRANSITION:** At AVRAM, climbing LEFT turn direct to AGNIG to the assigned route.

**PURIK TRANSITION:** At AVRAM, climb direct to PURIK to the assigned route.

**SEKEN TRANSITION:** At AVRAM, climbing RIGHT turn direct to SEKEN to the assigned route.

**TULIV TRANSITION:** Do not exceed 220 kt until BOMIL. At AVRAM, climbing RIGHT turn direct to BOMIL. Then climbing RIGHT turn track **321°** to TULIV to the assigned route.

## Communication Failure

On recognition of failure 10 minutes or less after take-off and in IFR weather conditions, proceed as follows:

1. Select transponder code 7600.
2. Maintain last assigned altitude until assigned transition waypoint.
3. Upon reaching assigned transition waypoint, proceed directly on course.
4. Climb to flight planned altitude.

**NOTE:** If communication failure occurs more than 10 minutes after take-off, comply with the appropriate procedure for communication failure enroute.