

Departure Route Description

Rwy 34 - 1/2: Requires a minimum climb gradient of **500** ft/NM to **1800**. Climb track **340°** to cross PELKA at or above **1800**, then proceed via assigned transition. Maintain **5000** or flight planned altitude, whichever is lower. Expect on course when RADAR identified.

DEPARTURE CLIMB RATE V/V (FPM)								
GROUND SPEED	90	120	140	160	180	200	250	300
500 FT/NM	750	1000	1170	1340	1500	1670	2090	2500

SEKEN TRANSITION: Do not exceed 220 kt until ELOTI. At PELKA, climbing LEFT turn direct to ELOTI. Then climbing LEFT turn track **179°** to SEKEN to the assigned route.

TULIV TRANSITION: At PELKA, climbing LEFT turn direct to TULIV to the assigned route.

RESIR TRANSITION: At PELKA, climb direct to RESIR to the assigned route.

TASKO TRANSITION: At PELKA, climbing RIGHT turn direct to TASKO to the assigned route.

AGNIG TRANSITION: Do not exceed 220 kt until DASEP. At PELKA, climbing RIGHT turn direct to DASEP. Then climbing RIGHT turn track **142°** to AGNIG to the assigned route.

Communication Failure

On recognition of failure 10 minutes or less after take-off and in IFR weather conditions, proceed as follows:

- 1. Select transponder code 7600.
- 2. Maintain last assigned altitude until assigned transition waypoint.
- 3. Upon reaching assigned transition waypoint, proceed directly on course.
- 4. Climb to flight planned altitude.

NOTE: If communication failure occurs more than 10 minutes after take-off, comply with the appropriate procedure for communication failure enroute.