

Departure Route Description

Rwys 07, 19, 25: Contact Victoria Terminal passing **1500** unless instructed otherwise by ATC. Maintain **3000** or as assigned.

Rwy 07 – ½: Restricted to Cat A, B & C acft only (CAT D refer to CLEARBROOK SID). Requires a minimum climb gradient of **300 ft/NM** to **1200**. Do not exceed 200 kt until established on hdg **204°**. Climb hdg **069°** to **800**. Then climbing RIGHT turn hdg **204°** for vectors.

Note: Antenna to 217 ASL aprx 0.1 NM past departure end of rwy, 200' RIGHT of rwy centreline. Trees to 325 ASL aprx. 0.5 NM past departure end of rwy. Trees to 352 ASL aprx 0.8 NM past departure end of rwy.

Rwy 19 – ½: Climb hdg **189°** for vectors.

Note: Trees to 260 ASL aprx 0.3 NM past departure end of rwy.

Rwy 25 – ½: Requires a minimum climb gradient of **280 ft/NM** to **600**. Climb hdg **249°** for vectors.

Note: Trees to 262 ASL aprx 0.4 NM past departure end of rwy, 370' LEFT of rwy centreline. Trees to 325 ASL aprx 0.5 NM past departure end of rwy, 830' RIGHT of rwy centreline.

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
280 FT/NM	420	560	660	750	840	940	1170	1400
300 FT/NM	450	600	700	800	900	1000	1250	1500

Note: Refer to noise abatement procedures for additional requirements.

Communication Failure

If no radio contact with Departure Control by published/assigned altitude:

- 1. Select transponder code 7600;
- 2. Continue to "YVR" VOR/DME then via filed/assigned route;
- 3. Continue climb to flight planned/assigned altitude/flight level 5 minutes after departure.