

Departure Route Description

Rwy 05 - ½: Do not exceed 210 kt until RABIK. Requires a minimum climb gradient of **420 ft/NM to 2600**. Climb hdg **053° to 1400**. Then climbing RIGHT turn direct RABIK to **5000** or as assigned. As required shuttle climb and hold at RABIK as published. Expect further clearance 10 minutes after take-off.

Rwy 23 - ½: Do not exceed 210 kt until RABIK. Requires a minimum climb gradient of **370 ft/NM to 2600**. Climb hdg **233° to 1000**. Then climbing LEFT turn direct RABIK to **5000** or as assigned. As required shuttle climb and hold at RABIK as published. Expect further clearance 10 minutes after take-off.

Note: Trees to 378 ASL aprx 0.1 NM from departure end of rwy, 600' RIGHT of rwy centreline.

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
370 FT/NM	560	740	870	990	1110	1240	1550	1850
420 FT/NM	630	840	980	1120	1260	1400	1750	2100

Communication Failure

1. Select transponder code 7600;
2. Proceed for the published hold at the last assigned altitude;
3. 10 minutes after entering the hold, you are cleared for an approach at CZBM or to continue enroute.