

CZFA

VAR 19° E
2025
ANNUAL RATE
OF CHANGE 16' W

133 22.8 133 21.9

62 12.7 62 12.7

ELEV 2351

01

Down 0.40%

3996 x 100

gravel

CZFA
N62 12.42
W133 22.40

28

ELEV 2335

DEPARTURE CLIMB RATE VV (FPM)								
GROUND SPEED	90	120	140	160	180	200	250	300
480 FT/NM	720	960	1120	1280	1440	1600	2000	2400

*** DEPARTURE PROCEDURE**

Rwy 10 - ½ - Requires a minimum climb gradient of **480 ft/NM** to **7800**. Climb hdg **095°** to **6000**.
Note: Trees to 2395 ASL abeam departure end of rwy, 230' LEFT and RIGHT of rwy centreline.

or

SPEC VIS - Climb in visual conditions to cross apt at or above **6700 BPOC**.

Rwy 28 - ½ - Requires a minimum climb gradient of **480 ft/NM** to **7700**.
 Climb hdg **275°** to **5000**. Climb between hdg **254°** CCW to hdg **095°**.
Note: Trees to 2385 ASL abeam departure end of rwy, 230' LEFT of rwy centreline.
 COMM towers to 2382 ASL abeam departure end of rwy, 230' RIGHT of rwy centreline.

or

SPEC VIS - Climb in visual conditions to cross apt at or above **6700 BPOC**.

133 22.8 133 21.9

62 12.2 62 12.2

TAKE-OFF MINIMA

Rwys 10; 28: *

SCALE IN FEET

1000 500 0 1000

Source of Canadian Civil Aeronautical Data: © 2026 NAV CANADA All rights reserved