



- TRANSITION LEVEL BY ATC
TRANSITION ALTITUDE 3000 FT AMSL

OCA (OCH) ELEV THR 27: -12.1 FT

ACFT CAT	CAT III supported		LOC MAPT: THR	CIRCLING*/**	* Circling procedures to and landing on RWY 18L and 36L is not permitted, except in case of an emergency. ** Caution: during circling to RWY 22 or RWY 24 identify correct RWY.	MSA BASED ON SPL VOR/DME
	CAT I	CAT II				
A	126 (138)	(50)	440 (450)	630 (641)		
B	133 (145)	(59)		790 (801)	THR 27 521906.2N 0044748.9E AM260 522410.4N 0045111.9E	
C	146 (158)	(73)		890 (901)	AM261 522437.3N 0050458.5E AM262 522123.4N 0050514.9E	
D	159 (171)	(86)		900 (911)	AM639 521926.2N 0045750.4E AM640 521919.3N 0045419.3E	
DL	162 (174)	(86)				
CEILING AND VISIBILITY MINIMA				DIRECTIONS ARE MAGNETIC DISTANCES IN NM ALTITUDES AND ELEVATIONS IN FEET AMSL		
TAKE-OFF	DAY:	NA	NIGHT:			NA
LANDING	DAY:		NIGHT:			