

NOTES:

1. Navigation in the initial and intermediate approach segment is primarily based on radar vectors provided by ATC.
2. For ARTIP/RIVER/SUGOL 1G transitions, see night transition chart to RNP RWY 18C.
3. Execution of the complete procedure overhead SPL VOR in case of COM failure.
4. EGNOS CH 64251 E18A.
5. Uncompensated LNAV/VNAV MNM TEMP: -15° C.
6. LNAV APCH at ATC discretion only.
7. When established on final approach maintain 160 KIAS until 4 NM before threshold.
8. Approaches on RWY 06, 22, 27 or 36R may be executed simultaneously.
9. Contact Schiphol Ground after vacating RWY.
10. In case of COM failure, the Amsterdam ACC Supervisor may be reached on telephone number +3120 406 3999.

APP	119.055	Schiphol Approach / Departure
	121.205	
	118.405	Schiphol Arrival
	126.680	
TWR	118.105	Schiphol Tower Primary
	135.110	
	119.230	
	121.905	Schiphol Ground Ground Control
	121.500	General Emergency
	132.980	
ATIS	243.000	Arrival Information

TRANSITION LEVEL BY ATC
TRANSITION ALTITUDE 3000 FT AMSL

1. Missed approach
- Inform ATC immediately
- Track 181° MAG to AM123 and climb to 2000 FT AMSL.
2. Missed approach in case of communication failure:
- Track 181° MAG and climb to 3000 FT AMSL;
- At 2000 FT AMSL start a left turn to AM120 and cross AM120 at 3000 FT AMSL;
- After AM120, descend to 2000 FT AMSL and execute the instrument approach procedure again.

RDH 50 FT

2000 FT AMSL

MAPt
THR 18C

360 680 990 1310 1630

181° 181° 3.0° (5.2%)

OCA 1000

THR ELEV -12

DIST RELATED TO THR 18C

GS IN KT	60	80	100	120	140	160	180
VERTICAL SPEED	320 FT/MIN	425 FT/MIN	530 FT/MIN	635 FT/MIN	745 FT/MIN	850 FT/MIN	955 FT/MIN

OCA (OCH) ELEV THR 18C: -12.0 FT

ACFT CAT	LPV	LNAV/VNAV MNM TEMP -15°C	LNAV	CIRCLING*	* Circling procedures to and landing on RWY 18L and 36L is not permitted, except in case of an emergency.	THR 18C 521953.0N 0044424.1E AM120 522412.8N 0045252.3E AM121 523022.2N 0045328.6E AM122 523033.3N 0044811.9E AM123 520641.5N 0044312.4E AM630 522601.7N 0044458.0E
A	201 (213)	242 (254)		630 (641)		
B	213 (225)	248 (260)		790 (801)		
C	221 (233)	267 (279)	670 (681)	890 (901)		
D				900 (911)		
DL	232 (244)	293 (305)				

CEILING AND VISIBILITY MINIMA

TAKE-OFF	DAY:	NIGHT:	DIRECTIONS ARE MAGNETIC DISTANCES IN NM ALTITUDES AND ELEVATIONS IN FEET AMSL
LANDING	DAY: NA	NIGHT: NA	

MSA BASED ON SPL VOR/DME

