

GENEVA (LSGG)
RNAV RWY 22

COMMUNICATION FAILURE PROCEDURE:

- Set transponder on code 7600.
- If on final intercept or cleared for the approach, continue as instructed and follow the IAC.
- In any other case, proceed direct to GEVEA at last assigned and acknowledged FL.
- When in the GEVEA HLDG pattern descend or climb to FL100.
- If RWY 04 is in use, leave GEVEA HLDG at FL100 and proceed via PITOM, GG502 (MAX IAS 220kt) to INDIS and carry out an instrument approach according to IAC.
- Cross PITOM at or above FL080, GG502 at or above 7000.
- If RWY 22 is in use, leave GEVEA HLDG at FL100 and proceed via GG525, GG512 (MAX IAS 220kt) to SAPRE and carry out an instrument approach according to IAC.
- Cross GG525 at or above FL080, GG512 at or above 7000.
- For ACFT equipped with onboard telephone, dial +41 22 798 7600 and mention last RTF channel used.

SPEED LIMITATION, GENERAL:
Below FL100 MAX IAS 250kt or as requested by ATC.

RNAV 1
GNSS or DME/DME/IRU required.

MSA LSGG ARP
Outer Circle: 25 NM
Inner Circle: 10 NM

BEARINGS, TRACKS AND RADIALS ARE MAGNETIC DISTANCES IN NM ALTITUDES MFT

VAR 3° E 2024.5

Scale: 0 5 10 15 20 KM / 0 5 10 NM

Countries: FRANCE, SWITZERLAND, ITALY

Airports and Navigation Aids: SAPRE, GEVEA, GENEVA, VALBU, GOLEB, KINES, BANKO, INDIS, CBY, BELUS, ROCCA, GG519, ANNEXY-MEYTHET LFLP.

Holding Patterns: SAPRE HLDG, GEVEA HLDG, GOLEB HLDG, CBY HLDG.

Flight Paths: Various routes connecting airports and navigation aids, including holding patterns and descent/ascent profiles.

NOT TO SCALE

THIS PAGE INTENTIONALLY LEFT BLANK