

ZURICH (LSZH)
RNAV RWY 14

COMMUNICATION FAILURE PROCEDURE:
SET TRANSPONDER TO CODE 7600.

- After reception of a transition CLR: continue FLT according to the published profile of the PROC with subsequent final APCH of a published instrument approach PROC.
- After reception of a CLR direct to a WPT on a transition: continue FLT direct to the cleared WPT, rejoin transition according to the published profile of the PROC with subsequent final APCH of a published instrument approach PROC.
- When being radar vectored to a WPT on a transition: resume own navigation to rejoin transition in the most direct way and proceed according to the published profile of the PROC with subsequent final APCH of a published instrument approach PROC.

CLEARANCE PHRASEOLOGY:

- "CLEARED XXX TRANSITION":
Authorization to fly the lateral RNAV 1-Route.
Level assignments will be issued by ATC.
- "CLEARED DIRECT WAYPOINT XXX":
Authorization to fly from the present position direct to a waypoint and to join thereafter the appropriate RNAV 1-Route.
Level assignments will be issued by ATC.

MSA LSZH ARP
Outer Circle: 25 NM
Inner Circle: 17 NM

RNAV 1
GNSS or DME/DME required

BEARINGS, TRACKS AND RADIALS ARE MAGNETIC
DISTANCES IN NM
ALTITUDES IN FT

VAR 3° E 2020.5

SWITZERLAND

GERMANY

TMA ZÜRICH

ZH371 FL100

ZH373 FL080

RILAX HLDG
INBD 188° (191.3°T),
1min; 7000 - FL240

RILAX

ZH409

ZH410 6000

ZH408

ZH406

ZH404

ZH372 MAX IAS 240kt

GIPOL

GIPOL HLDG
INBD 077° (080.3°T),
1min; MAX IAS 230kt;
7000 - FL240

TRA
DME 114.3

OSNEM (FAF/FAP) 4000

ZH414 4300

ZH405 7000

ZH407

ZH403

ZH375

AMIKI 14

AMIKI HLDG
INBD 274° (277.1°T),
1min; MAX IAS 230kt;
7000 - FL240

DÜBENDORF LSMD

KLO DVOR 114.85

ZURICH LSZH

CTR ZÜRICH

HUNZIG WTL

Scale: 0 5 10 15 20 KM / 0 5 10 NM

COR: CTR & TMA LSZH, chart renaming, PBN box (WIEF 20/MAR2025)

THIS PAGE INTENTIONALLY LEFT BLANK