


Homework 6

Answers can be written in french or in english.

Reminder (conditions for ample sets):

- (C0) $red(s) = \emptyset$ iff $en(s) = \emptyset$.
- (C1) For every path $s \xrightarrow{a_1} s_1 \xrightarrow{a_2} \dots \xrightarrow{a_n} s_n \xrightarrow{a} t$ in \mathcal{K} (for any $n \geq 0$), if $a \notin red(s)$ and a depends on some action in $red(s)$ (i.e. there exists $b \in red(s)$ such that $(a, b) \notin I$), then there exists $1 \leq i \leq n$ such that $a_i \in red(s)$.
- (C2) If $red(s) \neq en(s)$, then all actions in $red(s)$ are invisible.
- (C3) For all cycles in the reduced system \mathcal{K}' , the following holds: if $a \in en(s)$ for some state s in the cycle, then $a \in red(s')$ for some (possibly other) state s' in the cycle.

Exercise 1. Let $\mathcal{K} = (S, A, \rightarrow, r, AP, \nu)$ be the Kripke structure below, with set of actions $A = \{a, b, c, d, e\}$ and atomic propositions $AP = \{p\}$.



1. Compute the maximal independence set I and the maximal set of invisible actions U . Justify your answers.
2. Give sets $red(s) \subseteq en(s)$ satisfying conditions C0 to C3, and such that for all state s , no action can be removed from $red(s)$ without breaking one of conditions C0 to C3. Justify your answer.
3. Draw the reduced system \mathcal{K}' associated with your assignment red , after removing unreachable states. Is there a smaller system \mathcal{K}'' , obtained by removing additional transitions, that is stuttering equivalent to \mathcal{K} ?