

ARUNAVA GHOSH

24BCG10121

—

MariaDB [(none)]> use crud;
Reading table information for completion of table and column names
You can turn off this feature to get a quicker startup with -A

Database changed
MariaDB [crud]> SHOW TABLES;
+-----+
| Tables_in_crud |
+-----+
| user |
+-----+
1 row in set (0.001 sec)

MariaDB [crud]> SHOW CREATE TABLE user\G;
***** 1. row *****
Table: user
Create Table: CREATE TABLE `user` (
 `sl\_no` int(5) DEFAULT NULL,
 `name` varchar(100) DEFAULT NULL,
 `email` varchar(100) DEFAULT NULL
) ENGINE=InnoDB DEFAULT CHARSET=latin1 COLLATE=latin1_swedish_ci
1 row in set (0.001 sec)

ERROR: No query specified

MariaDB [crud]> █

Figure 1: mysql-schema

java -cp "build:_deps/*" MongoDBTemplate
Jun 02, 2026 9:09:26 PM com.mongodb.internal.diagnostics.logging.Loggers shouldUseSLF4J
WARNING: SLF4J not found on the classpath. Logging is disabled for the 'org.mongodb.driver' component
Connected successfully to MongoDB!

Figure 2: Mongo Connection

```
javac -d build -cp "._:._deps/*" *.java
java -cp "build:_deps/*" MariaDBTemplate
Data Inserted Successfully
Sl No : 101
Name : Arun
Email : arun@gmail.com
-----
Data Updated Successfully
Sl No : 101
Name : Arun Kumar
Email : arunkumar@gmail.com
-----
Data Deleted Successfully
```

Figure 3: MySql CRUD

—

CODE

```
import java.sql.Connection;
import java.sql.DriverManager;

public class MariaDBConnection {
    public Connection getConnection() {
        Connection connection = null;
        try {
            Class.forName("org.mariadb.jdbc.Driver");
            connection = DriverManager.getConnection(
                "jdbc:mariadb://localhost:3306/crud",
                "root",
                "root"
            );
        } catch (Exception e) {
            System.out.println("Connection Failed: " + e.getMessage());
        }
        return connection;
    }
}

import java.sql.Connection;
import java.sql.PreparedStatement;
import java.sql.ResultSet;

public class MariaDBTemplate {
    public static void main(String[] args) {
        MariaDBTemplate app = new MariaDBTemplate();

        app.createData(101, "Arun", "arun@gmail.com");
        app.readData(101);
        app.updateData(101, "Arun Kumar", "arunkumar@gmail.com");
        app.readData(101);
        app.deleteData(101);
    }

    public void createData(int sl_no, String name, String email) {
        try (Connection con = new MariaDBConnection().getConnection();
            PreparedStatement ps = con.prepareStatement("INSERT INTO
user(sl_no,name,email) VALUES(?,?,?)")) {
            ps.setInt(1, sl_no);
            ps.setString(2, name);
            ps.setString(3, email);
            if(ps.executeUpdate() > 0) System.out.println("Data Inserted
Successfully");
        } catch (Exception e) { System.out.println(e); }
    }

    public void readData(int sl_no) {
        try (Connection con = new MariaDBConnection().getConnection();
            PreparedStatement ps = con.prepareStatement("SELECT * FROM user WHERE
sl_no=?")) {
            ps.setInt(1, sl_no);
            try (ResultSet rs = ps.executeQuery()) {
                while(rs.next()) {
                    System.out.println("Sl No : " + rs.getInt("sl_no"));
                    System.out.println("Name : " + rs.getString("name"));
                }
            }
        }
    }
}
```

```

        System.out.println("Email : " + rs.getString("email"));
        System.out.println("-----");
    }
}
} catch (Exception e) { System.out.println(e); }
}

public void updateData(int sl_no, String name, String email) {
    try (Connection con = new MariaDBConnection().getConnection();
        PreparedStatement ps = con.prepareStatement("UPDATE user SET
name=?,email=? WHERE sl_no=?")) {
        ps.setString(1, name);
        ps.setString(2, email);
        ps.setInt(3, sl_no);
        if(ps.executeUpdate() > 0) System.out.println("Data Updated
Successfully");
    } catch (Exception e) { System.out.println(e); }
}

public void deleteData(int sl_no) {
    try (Connection con = new MariaDBConnection().getConnection();
        PreparedStatement ps = con.prepareStatement("DELETE FROM user WHERE
sl_no=?")) {
        ps.setInt(1, sl_no);
        if(ps.executeUpdate() > 0) System.out.println("Data Deleted
Successfully");
    } catch (Exception e) { System.out.println(e); }
}
}

import com.mongodb.client.MongoClient;
import com.mongodb.client.MongoClients;
import com.mongodb.client.MongoDatabase;

public class MongoDBTemplate {
    public static void main(String[] args) {
        String connectionString = "mongodb://localhost:27017";

        try (MongoClient mongoClient = MongoClients.create(connectionString)) {
            MongoDatabase database = mongoClient.getDatabase("testdb");
            System.out.println("Connected successfully to MongoDB!");
        } catch (Exception e) {
            System.out.println("MongoDB Connection Failed: " + e.getMessage());
        }
    }
}

```