


## 6. AGGREGATION AND INHERITANCE



00:00

•1

### How to re-use source code?



00:00

•2

### Lesson Goals

- Explaining concepts of source code re-usability
- Showing the nature, description of concepts relating to aggregation and inheritance
- Comparison of aggregation and inheritance
- Representing aggregation and inheritance in UML
- Explaining principles of inheritance and initialization order, object destruction in inheritance
- Applying techniques, principles of aggregation and inheritance in Java programming language

00:00

•3

### Outline

1. Source code re-usability
2. Aggregation
3. Inheritance


00:00

•4

•5

## 1. Re-usability

- Source code re-usability: re-use already existing source code
  - Structure programming: Re-use function/sub-program
  - OOP: When modeling real world, there exist many object types that have similar or related attributes and behaviors
    - How to re-use already-written classes?



© 2011

•5

•6

## 1. Re-usability (2)

- How to use existing classes:
  - Copying existing classes → Redundant and difficult to manage changes
  - Creating new classes that re-use of **objects** of existing classes → **Aggregation**
  - Creating new classes based on the extension of existing **classes** → **Inheritance**

© 2011

•6

•7

## 1. Re-usability (2)

- Advantages
  - Reducing man-power, cost.
  - Improving software quality
  - Improving modeling capacity of the real world
  - Improving maintainability



© 2011

•7

•8

## Outline

1. Source code re-usability
- 2. Aggregation
3. Inheritance

© 2011

•8

## 2. Aggregation

- Example:


- Point

- A Quadrangle consists of 4 points

→ Aggregation

- Aggregation

- Has-a or **is-a-part-of** relations



UML

•9

## Terms

- Aggregation

- Members of a new class are objects of existing classes.
  - Aggregation reuses via objects

- New class: the Aggregate/Whole class

- Existing class: Member of the new class (the part)

UML


•10

## 2.1. What is aggregation?

- The whole class contains objects of member classes

- Is-a-part of the whole class

- Re-use data and behavior of member classes via member objects



UML



•11

## 2.2. Representing aggregation in UML

- Using “diamond” at the head of whole class


- Using multiplicity at two heads:

- A positive integer: 1, 2,...
  - A range (0..1, 2..4)
  - \*: Any number
  - None: By default is 1



UML

•12



•13

•14

## 2.3. Example in Java

```

class Point {
    private int x, y;
    public Point(){}
    public Point(int x, int y) {
        this.x = x; this.y = y;
    }
    public void setX(int x){ this.x = x; }
    public int getX() { return x; }
    public void print(){
        System.out.print("(" + x + ", "
                        + y + ")");
    }
}
  
```

UML

•14

•15

```

class Quadrangle{
    private Point[] corners = new Point[4];
    public Quadrangle(Point p1,Point p2,Point p3,Point p4){
        corners[0] = p1; corners[1] = p2;
        corners[2] = p3; corners[3] = p4;
    }
    public Quadrangle(){
        corners[0]=new Point(); corners[1]=new Point(0,1);
        corners[2]=new Point(1,1); corners[3]=new Point(1,0);
    }
    public void print(){
        corners[0].print(); corners[1].print();
        corners[2].print(); corners[3].print();
        System.out.println();
    }
}
  
```

```

classDiagram
    Quadrangle "1" *-- "4" Point
  
```

UML

•15

•16

```

public class Test {
    public static void main(String arg[])
    {
        Point p1 = new Point(2,3);
        Point p2 = new Point(4,1);
        Point p3 = new Point(5,1);
        Point p4 = new Point(8,4);

        Quadrangle q1 = new Quadrangle(p1,p2,p3,p4);
        Quadrangle q2 = new Quadrangle();
        q1.print();
        q2.print();
    }
}
  
```


UML

•16

## Another example of Aggregation

- A game consisting of two players, 3 dies and an arbitrator.
- Need 4 classes:
  - Player
  - Die
  - Arbitrator
  - Game
- Game class is the aggregation of the 3 remaining classes

•17



•18

## 2.4. Initialization order in aggregation

- When an object is created, the attributes of that object must be initialized and assigned corresponding values.
- Member objects must be initialized first
- Constructor methods of member classes must be called first

•19

## Outline


1. Source code re-usability
2. Aggregation
- 3. Inheritance

•20

•21

## 3.1. What is Inheritance?

- Example:
  - Point and Quadrangle: A quadrangle has 4 points  
→ Aggregation (is a part of)
  - Quadrangle and Square: A square is an Quadrangle  
→ Inheritance (is a kind of)



UML

•21

•22

## Terms

- Inherit, Derive
  - Creating a new class by extending existing classes.
  - New class inherits members of existing classes and implement its own new features.
- Existing class:
  - Parent class, superclass, base class
- New class:
  - Child class, subclass, derived class

UML

•22

•23

## What is Inheritance?

- On "modularization" view: If B inherits A, all services of A will be available in B
- On "type" view: If B inherits A, anywhere requires representation of A, B can replace A  
=> Polymorphism


UML

•23

•24

## Child classes?

- Child is a kind of parent
  - Inheritance is also called is-a-kind-of (or is-a) relationship
- Child reuse by inheriting data and behavior of parent
- Child can be customized in two ways (or both):
  - Extension: Add more new attributes/behaviors
  - Redefinition (Method Overriding): Modify the behavior inheriting from parent class




UML

•24

## More example

- Whale class inherits from mammal class.
- A whale *is-a* mammal
- Whale class is *subclass*, mammal class is *superclass*



UML

•25

## Similarity

- Both Whale and Horse have *is-a relation* with Mammal class
- Whale and Horse have some common behaviours of Mammal
- Inheritance is a key to reuse source code. Once a parent class is created, the child class can extend it and add more data and behaviours.

UML

•26

## 3.2. Aggregation and Inheritance

- Comparing aggregation and inheritance?
  - Similarity
    - Both are OOP techniques to re-use source code
  - Difference?

UML

•27

## Difference between Aggregation and Inheritance

- | Inheritance   | Aggregation  |
|---|--|
| <ul style="list-style-type: none"> <li>• Inheritance <b>re-uses</b> source code via <b>class</b>.               <ul style="list-style-type: none"> <li>• Creating new class by extending existing classes</li> </ul> </li> <li>• “is a kind of” relation</li> <li>• Example: Car is a kind of Transportation</li> </ul> | <ul style="list-style-type: none"> <li>• Aggregation <b>re-uses</b> source code via <b>objects</b>.               <ul style="list-style-type: none"> <li>• Create a reference to the objects of existing classes in the new class</li> </ul> </li> <li>• “is a part of” relation</li> <li>• Example: Car has 4 wheels</li> </ul> |


UML

•28

•29

### 3.3. Representing Inheritance in UML

- Using “empty triangle” at parent class




•29

•30

### 3.4. Inheritance hierarchy

- Is a hierarchy tree structure, representing inheritance relation between classes.
- Direct inheritance
  - B directly inherits from A
- Indirect inheritance
  - C indirectly inherits from A




•30

•31

### 3.4. Inheritance hierarchy (2)

- Child classes having the same parent class are called **siblings**
- A child class inherits **features from all of its ancestors**




•31

•32

### 3.4. Hierarchy tree (2)

All objects inherit from the most basic class: **Object**



•32



•33

## Class Object

- Class `Object` is defined in the standard package `java.lang`
- If a class is not defined as a child of another class, it is by default a direct child of class `Object`.  
→ Class `Object` is the root class in all hierarchy trees




•33

•34

## Class Object (2)

- Contains some useful methods that are inherited by all other classes, e.g., `toString`, `equals`, `finalize`



•34

•35

## 3.5. Inheritance rules

- Access modifier: **protected**
- Protected members in a parent class are accessed by:
  - Members of the parent class
  - Members of its children classes
  - **Members of classes that are in the same package of the parent class**
- What does a child class inherit?
  - Inherit all attributes/methods that are declared as public and protected in the parent class.
  - Inherit all members with the **default** access modifier, if child and parent classes are in the same package
  - Does not inherit private attributes/methods.



•35

•36

## 3.5. Inheritance rules (2)

Visibility of members in parent class	public	None (default)	protected	private
Classes in the same package				
Child classes – same package				
Child classes – different package				



•36

### 3.5. Inheritance rules (2)

	public	None	protected	private
Same package	Yes	Yes	Yes	No
Child classes – same package	Yes	Yes	Yes	No
Child classes – different package	Yes	No	Yes	No

•37

### 3.5. Inheritance rules (3)

- Construction and destruction methods can not be inherited
  - Those methods are responsible for initializing and deleting objects
  - These methods are defined to work in a specific class only
- Assignment operation =
  - Performs the same task as construction method

•38

### 3.6. Inheritance syntax in Java

- Inheritance syntax in Java:
  - <SubClass> **extends** <SuperClass>
- Example:
 

```
class Square extends Quadrangle {
    ...
}
class Bird extends Animal {
    ...
}
```

•39

#### Example 1

```
public class Quadrangle {
    protected Point corners = new Point[4];
    public Quadrangle() { ... }
    public void print() { ... }
    ...
}

public class Square extends Quadrangle {
    public Square() {
        corners[0]=new Point(0,0); corners[1]=new Point(0,1);
        corners[2]=new Point(1,0); corners[3]=new Point(1,1);
    }
}

public class Test{
    public static void main(String args[]){
        Square sq = new Square();
        sq.print();
    }
}
```

Using protected attributes of the parent class in the child class

Calling public method of parent class

•40

•41

## Example 2

protected

```

class Person {
    private String name;
    private Date birthday;
    public String getName() {return name;}
    ...
}
class Employee extends Person {
    private double salary;
    public boolean setSalary(double sal){
        salary = sal;
        return true;
    }
    public String getDetail(){
        String s = name+", "+birthday+", "+salary;//Error
    }
}

```

UML

•41

•42

## Example 2 (cont.)

```

public class Test{
    public static void main(String args[]){
        Employee e = new Employee();
        e.setName("John");
        e.setSalary(3.0);
    }
}

```

UML

•42

•43

## Example 3 – Same package

```

public class Person {
    Date birthday;
    String name;
    ...
}
public class Employee extends Person {
    ...
    public String getDetail() {
        String s;
        String s = name + "," + birthday;
        s += "," + salary;
        return s;
    }
}

```

UML

•43

•44

## Example 3 – Different package

```

package abc;
public class Person {
    protected Date birthday;
    protected String name;
    ...
}

import abc.Person;
public class Employee extends Person {
    ...
    public String getDetail() {
        String s;
        s = name + "," + birthday + "," + salary;
        return s;
    }
}

```

UML

•44

## Construction and destruction of objects in inheritance

- Object construction:
  - A parent class is initialized before its child classes.
  - Construction methods of a child class always call construction methods of its parent class at the very first command
    - Implicit call: when the parent class has a **default constructor**
    - Explicit call (explicit)
- Object destruction:
  - Contrary to object initialization

•45

### 3.4.1. Implicit call of constructor of parent class

```

public class Quadrangle {
    public Quadrangle() {
        System.out.println
            ("Parent Quadrangle()");
    }
    // . . .
}

public class Square
    extends Quadrangle {
    public Square() {
        //Implicit call "Quadrangle();"

        System.out.println
            ("Child Square()");
    }
}

public class Test {
    public static void
        main(String arg[])
    {
        HinhVuong hv =
            new HinhVuong();
    }
}

```

Parent Quadrangle()  
 Child Square()

•46

## Example

```

public class Quadrangle {
    protected Point[] corners=new Point[4];
    public Quadrangle(Point p1,Point p2,
        Point p3,Point p4){
        corners[0] = p1; corners[1] = p2;
        corners[2] = p3; corners[3] = p4;
    }
}

public class Square extends
    Quadrangle {
    public Square() {
        System.out.println
            ("Child Square()");
    }
}

public class Test {
    public static void
        main(String arg[])
    {
        Square sq = new
            Square();
    }
}

```

**Error**  
  
 Cannot find symbol ...

•47

### 3.4.2. Explicit constructor call of parent class

- The first command in constructor of a child class can explicitly call the constructor of its parent class
  - `super (Danh_sach_tham_so);`
  - This is obliged if the parent class does not have any default constructor (Parent class already has a constructor with arguments)

•48

•49

```

public class Quadrangle {
    protected Point corners = new Point[4];
    public Quadrangle() { ... }
    public Quadrangle(Point d1, Point d2, Point d3, Point d4) { ... }
    public void print() { ... }
}
public class Square extends Quadrangle {
    public Square() { super(); }
    public Square(Point p1, Point p2, Point p3, Point p4) {
        super(d1, d2, d3, d4);
    }
}
public class Test {
    public static void main(String args[]) {
        Square sq = new Square();
        sq.print();
    }
}

```

Example 1.1

•49

•50


Explicit constructor call of parent class  
Constructor of child class has no arguments

```


public class Quadrangle {
    protected Point[] corners = new Point[4];
    public Quadrangle(Point p1, Point p2,
        Point p3, Point p4) {
        System.out.println("Parent Quadrangle()");
        corners[0] = p1; corners[1] = p2;
        corners[2] = p3; corners[3] = p4;
    }
}
public class Square extends Quadrangle {
    public Square() {
        super(new Point(0,0), new Point(0,1), new Point(1,1),
            new Point(1,0));
        System.out.println("Child Square()");
    }
}

```

•50



•51



•52