

SOICT

Hanoi University of Science and Technology
School of Information and Communications Technology

Discrete Mathematics

Nguyễn Khánh Phương

Department of Computer Science
School of Information and Communication Technology
E-mail: phuongnk@soict.hust.edu.vn

PART 1

COMBINATORIAL THEORY

(Lý thuyết tổ hợp)

PART 2


GRAPH THEORY

(Lý thuyết đồ thị)

Content of Part 2

Chapter 1. Fundamental concepts
Chapter 2. Graph representation
Chapter 3. Graph Traversal
Chapter 4. Tree and Spanning tree
Chapter 5. Shortest path problem
Chapter 6. Maximum flow problem



NGUYỄN KHÁNH PHƯƠNG
CS-SOICT-HUST



SOICT

Hanoi University of Science and Technology
School of Information and Communications Technology

Chapter 2: Graph representation

NGUYỄN KHÁNH PHƯƠNG
CS-SOICT-HUST

Graph Representation

1. Incidence matrix
2. Adjacency matrix
3. Weight matrix
4. Adjacency list

Graph Representation

1. **Incidence matrix**
2. Adjacency matrix
3. Weight matrix
4. Adjacency list

1. Incidence Matrix

$G = (V, E)$ is an undirected graph:

- $V = \{v_1, v_2, v_3, \dots, v_n\}$
- $E = \{e_1, e_2, \dots, e_m\}$

Then the incidence matrix with respect to this ordering of V and E is the $n \times m$ matrix $M = [m_{ij}]$, where

$$m_{ij} = \begin{cases} 1 & \text{when edge } e_j \text{ is incident with } v_i \\ 0 & \text{otherwise} \end{cases}$$

Can also be used to represent :

- **Multiple edges:** by using columns with identical entries, since these edges are incident with the same pair of vertices
- **Loops:** by using a column with exactly one entry equal to 1, corresponding to the vertex that is incident with the loop

1. Incidence Matrix

Matrix $M_{|V| \times |E|} = [m_{ij}]$, where

$$m_{ij} = \begin{cases} 1 & \text{when edge } e_j \text{ is incident with } v_i \\ 0 & \text{otherwise} \end{cases}$$

Can also be used to represent :


- **Multiple edges:** by using columns with identical entries, since these edges are incident with the same pair of vertices
- **Loops:** by using a column with exactly one entry equal to 1, corresponding to the vertex that is incident with the loop

1.Incidence Matrix

Matrix $M_{|V| \times |E|} = [m_{ij}]$, where

$$m_{ij} = \begin{cases} 1 & \text{when edge } e_j \text{ is incident with } v_i \\ 0 & \text{otherwise} \end{cases}$$

Example: $G = (V, E)$



| | e_1 | e_2 | e_3 |
|---|-------|-------|-------|
| v | 1 | 0 | 1 |
| u | 1 | 1 | 0 |
| w | 0 | 1 | 1 |

NGUYỄN KHÁNH PHƯƠNG
CS-SOICT-HUST


9

1.Incidence Matrix

Matrix $M_{|V| \times |E|} = [m_{ij}]$, where

$$m_{ij} = \begin{cases} 1 & \text{when edge } e_j \text{ is incident with } v_i \\ 0 & \text{otherwise} \end{cases}$$

Example: What is the incidence matrix M for the following graph G based on the order of vertices a, b, c, d and edges $1, 2, 3, 4, 5, 6$?



Solution:

$$M = \begin{bmatrix} 1 & 1 & 0 & 0 & 1 & 0 \\ 1 & 0 & 1 & 0 & 0 & 0 \\ 0 & 0 & 0 & 1 & 1 & 1 \\ 0 & 1 & 1 & 1 & 0 & 0 \end{bmatrix}$$

Note: Incidence matrices of undirected graphs contain two 1s per column for edges connecting two vertices and one 1 per column for loops.

1.Incidence Matrix

$G = (V, E)$ is a directed graph:


- $V = \{v_1, v_2, v_3, \dots, v_n\}$
- $E = \{e_1, e_2, \dots, e_m\}$

Then the incidence matrix with respect to this ordering of V and E is the $n \times m$ matrix $M = [m_{ij}]$, where

$$m_{ij} = \begin{cases} 1 & \text{when } v_i \text{ is initial vertex of } e_j \\ -1 & \text{when } v_i \text{ is terminal vertex of } e_j \\ 0 & \text{otherwise} \end{cases}$$

11

1.Incidence Matrix



$$A = \begin{matrix} & (1,2) & (1,3) & (2,3) & (2,4) & (3,5) & (4,5) & (4,6) & (5,2) & (5,6) \\ \begin{matrix} 1 \\ 2 \\ 3 \\ 4 \\ 5 \\ 6 \end{matrix} & \begin{bmatrix} 1 & 1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ -1 & 0 & 1 & 1 & 0 & 0 & 0 & -1 & 0 & 0 \\ 0 & -1 & -1 & 0 & 1 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & -1 & 0 & 1 & 1 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & -1 & 0 & 0 & 1 & 1 & 1 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & -1 & 0 & -1 \end{bmatrix} \end{matrix}$$

NGUYỄN KHÁNH PHƯƠNG
CS-SOICT-HUST

Graph Representation

1. Incidence matrix
- 2. Adjacency matrix**
3. Weight matrix
4. Adjacency list


NGUYỄN KHÁNH PHƯƠNG 13
CS-SOICT-HUST

2. Adjacency Matrix

The Adjacency Matrix ($N \times N$) $A = [a_{ij}]$ where $|V| = N$

For undirected graph


$$a_{ij} = \begin{cases} 1 & \text{if } \{v_i, v_j\} \text{ is an edge of } G \\ 0 & \text{otherwise} \end{cases}$$



$$A = \begin{bmatrix} 0 & 1 & 1 \\ 1 & 0 & 1 \\ 1 & 1 & 0 \end{bmatrix}$$

diagonally symmetric matrix


For directed graph

$$a_{ij} = \begin{cases} 1 & \text{if } (v_i, v_j) \text{ is an edge of } G \\ 0 & \text{otherwise} \end{cases}$$


$$A = \begin{bmatrix} 0 & 1 & 0 \\ 0 & 0 & 0 \\ 1 & 1 & 0 \end{bmatrix}$$

This makes it easier to find subgraphs, and to reverse graphs if needed.

2. Adjacency Matrix




$$A[u,v] = \begin{cases} 1 & \text{if } \{u,v\} \in E \\ 0 & \text{otherwise} \end{cases}$$

$$A = \begin{matrix} & \begin{matrix} 1 & 2 & 3 & 4 & 5 & 6 \end{matrix} \\ \begin{matrix} 1 \\ 2 \\ 3 \\ 4 \\ 5 \\ 6 \end{matrix} & \begin{bmatrix} 0 & 1 & 0 & 1 & 0 & 0 \\ 1 & 0 & 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 1 & 1 & 0 \\ 1 & 0 & 1 & 0 & 1 & 0 \\ 0 & 0 & 1 & 1 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 \end{bmatrix} \end{matrix}$$

NGUYỄN KHÁNH PHƯƠNG
CS-SOICT-HUST

Representation- Adjacency Matrix




$$A[u,v] = \begin{cases} 1 & \text{if } (u,v) \in E \\ 0 & \text{otherwise} \end{cases}$$

$$A = \begin{matrix} & \begin{matrix} 1 & 2 & 3 & 4 & 5 & 6 \end{matrix} \\ \begin{matrix} 1 \\ 2 \\ 3 \\ 4 \\ 5 \\ 6 \end{matrix} & \begin{bmatrix} 0 & 1 & 0 & 1 & 0 & 0 \\ 0 & 0 & 1 & 0 & 0 & 0 \\ 0 & 0 & 0 & 1 & 1 & 0 \\ 0 & 0 & 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 \end{bmatrix} \end{matrix}$$

Representation- Adjacency Matrix

- The adjacency matrix of simple undirected graphs are symmetric ($a_{ij} = a_{ji}$) (why?)
- When there are relatively few edges in the graph the adjacency matrix is a **sparse matrix**
- Directed Multigraphs can be represented by using a_{ij} = number of edges from v_i to v_j




NGUYỄN KHÁNH PHƯƠNG
CS-SOICT-HUST 17

Representation- Adjacency List

```
int A[MAX][MAX];
int V, E;

void input() {
    cin >> V;
    for (int i = 0; i < V; i++)
        for (int j = 0; j < V; j++)
            cin >> A[i][j];
}
```


```
0 1 1 0
1 0 1 0
1 1 0 1
0 0 1 0
```



NGUYỄN KHÁNH PHƯƠNG
Bộ môn KHMT – ĐHBK HN

Analyze the cost

- Memory Space
 - $|V|^2$ bits
- Time to answer the query
 - Two vertices i and j are adjacent? $O(1)$
 - Add or delete one edge $O(1)$
 - Add one vertex increase the size of matrix
 - Enumerate the adjacent vertices of u $O(|V|)$ (even when u is an isolated vertex).



NGUYỄN KHÁNH PHƯƠNG
CS-SOICT-HUST 19

Graph Representation

- Incidence matrix
- Adjacency matrix
- Weight matrix**
- Adjacency list

NGUYỄN KHÁNH PHƯƠNG
CS-SOICT-HUST 20

3. Weight matrix

- **Weighted** graphs have values associated with edges.
- In the case weighted graphs, instead of adjacency matrix, we use weight matrix to represent the graph

$$C = c[i, j], \quad i, j = 1, 2, \dots, n,$$


where

$$c[i, j] = \begin{cases} c(i, j), & \text{if } (i, j) \in E \\ \theta, & \text{if } (i, j) \notin E, \end{cases}$$

- θ : special value to identify (i, j) is not an edge; depends on the case, the value of θ could be: $0, +\infty, -\infty$.

21


Weight matrix of undirected graph



| | 1 | 2 | 3 | 4 | 5 | 6 |
|---|---|---|---|---|---|---|
| 1 | 0 | 3 | 0 | 5 | 0 | 0 |
| 2 | 3 | 0 | 2 | 0 | 0 | 0 |
| 3 | 0 | 2 | 0 | 3 | 6 | 0 |
| 4 | 5 | 0 | 3 | 0 | 7 | 0 |
| 5 | 0 | 0 | 6 | 7 | 0 | 0 |
| 6 | 0 | 0 | 0 | 0 | 0 | 0 |

NGUYỄN KHÁNH PHƯƠNG
CS-SOICT-HUST

Weight matrix of directed graph



| | 1 | 2 | 3 | 4 | 5 | 6 |
|---|---|---|---|---|---|---|
| 1 | 0 | 3 | 0 | 7 | 0 | 0 |
| 2 | 0 | 0 | 1 | 0 | 0 | 0 |
| 3 | 0 | 0 | 0 | 2 | 3 | 0 |
| 4 | 0 | 0 | 0 | 0 | 9 | 0 |
| 5 | 0 | 0 | 0 | 0 | 0 | 0 |
| 6 | 0 | 0 | 0 | 0 | 0 | 0 |

NGUYỄN KHÁNH PHƯƠNG
CS-SOICT-HUST

Graph Representation

1. Incidence matrix
2. Adjacency matrix
3. Weight matrix
4. **Adjacency list**

NGUYỄN KHÁNH PHƯƠNG
CS-SOICT-HUST 24


3. Adjacency List

Adjacency list: each vertex has a list of which vertices it is adjacent


- Is an array **Adjacency** consisting of $|V|$ list
- Each vertex has 1 list
- Each vertex $u \in V$: Adjacency[u] consists of nodes that are adjacent to u .

Example:

Undirected graph




Directed graph



25

Representation- Adjacency List



```
int V, E;
list <int> Adj[MAX];
```

```
void input() {
    cin >> V >> E;
    for(int k = 1; k <= E; k++){
        int i, j;
        cin >> i >> j;
        Adj[i].push_back(j);
        Adj[j].push_back(i); //for undirected graph
    }
}
```

List of edges:

```
0 -> 1
0 -> 2
1 -> 0
1 -> 2
2 -> 0
2 -> 1
2 -> 3
3 -> 2
```

NGUYỄN KHÁNH PHƯƠNG
CS-SOICT-HUST

Analyze the cost

Memory Space

- $\Theta(|V|+|E|)$
- Is often much smaller compared to $|V|^2$, especially for sparse graph
- Sparse graph: $|E| \leq k|V|$ where $k < 10$.
- Note: Most of the graph in real-world application is sparse graph! → Adjacency list representation is usually preferred since it is more efficient in representing sparse graphs.
- Time to answer the query
 - Add an edge $O(1)$
 - Delete an edge go through the Adjacency lists of initial vertex and terminal vertex
 - Enumerate all adjacent vertex of v : $O(\text{#adjacent vertices})$ (better than adjacency matrix)
 - Two vertices i and j are adjacent?
 - Search on the Adjacency[i]: $\Theta(\text{degree}(i))$. In the worst case $O(|V|) \Rightarrow$ worse than adjacency matrix


27

Graph Representation


- **Incidence Matrix:** Most useful when information about edges is more desirable than information about vertices.
- **Adjacency (Matrix/List):** Most useful when information about the vertices is more desirable than information about the edges. This representation is also more popular since information about the vertices is often more desirable than edges in most applications

NGUYỄN KHÁNH PHƯƠNG
CS-SOICT-HUST 28

Graph representation





graph



Adjacency list

| | 1 | 2 | 3 | 4 | 5 |
|---|---|---|---|---|---|
| 1 | 0 | 1 | 0 | 0 | 1 |
| 2 | 1 | 0 | 1 | 1 | 1 |
| 3 | 0 | 1 | 0 | 1 | 0 |
| 4 | 0 | 1 | 1 | 0 | 1 |
| 5 | 1 | 1 | 0 | 1 | 0 |

Adjacency matrix



| | 1 | 2 | 3 | 4 | 5 | 6 |
|---|---|---|---|---|---|---|
| 1 | 0 | 1 | 0 | 1 | 0 | 0 |
| 2 | 0 | 0 | 0 | 0 | 1 | 0 |
| 3 | 0 | 0 | 0 | 0 | 1 | 1 |
| 4 | 0 | 1 | 0 | 0 | 0 | 0 |
| 5 | 0 | 0 | 0 | 1 | 0 | 0 |
| 6 | 0 | 0 | 0 | 0 | 0 | 1 |