



ĐẠI HỌC BÁCH KHOA HÀ NỘI  
VIỆN CÔNG NGHỆ THÔNG TIN VÀ TRUYỀN THÔNG

# BRANCH

## SOICT-HUST

# if statement

if ( *expression* )  
    *statement*

- Determines whether a statement or block is executed.
- Implements the selection instructions within an algorithm.
- Decides what to do by evaluating a Boolean expression.
- If the expression is **true (non-zero)**, the statement or block is executed.

# What is a statement?

- Statements are lines of instructions in our programs ending with a semicolon (;).
- A compound statement or block is a series of statements surrounded by braces.

## *Example*

```
{  
    number = number + 1;  
    printf("%d\n", number);  
}
```

- An empty statement is a single semicolon.

# Example


- Read in a number, and echo it if it is odd.

```
#include <stdio.h>
int main()
{
    int number;

    printf("Enter an integer: ");
    scanf("%d", &number);

    if (number % 2 != 0)
        printf("%d is an odd number", number);

    return 0;
}
```



there is no  
**then** here

# Common errors

Should be equal  
comparison ==

No ; here

```
if (number % 2 = 0) ;  
{  
    printf("%d\n", number);  
    printf("La so chan");  
}
```

; creates an empty statement after if

# else statement

```
if ( expression )  
    statement1  
else statement2
```

- *else* statement can only occur after an *if* statement
- *else* statement is only executed when the *if* block does not execute

# Example

- Check whether an integer is odd or even

```
#include <stdio.h>

int main()
{
    int number;

    printf("Enter an integer: ");
    scanf("%d", &number);

    if (number % 2 != 0)
        printf("%d is an odd number\n", number);
    else
        printf("%d is an even number\n", number);

    return 0
}
```

# Common errors

no ; here

```
if (number % 2 != 0)
{
    printf("%d\n", number);
    printf("is an odd number");
};
else
{
    printf("%d\n", number);
    printf("is an even number");
}
```



# Cascading if (**else-if**)

## Example

```
if (expr1)
    statement1
else if (expr2)
    statement2
else if (expr3)
    statement3
else
    statement4
```

```
if (ch >= 'a' && ch <= 'z')
{
    printf("%c is a lowercase", ch);
}
else if (ch >= 'A' && ch <= 'Z')
{
    printf("%c is a upper case". ch);
}
else if (ch >= '0' && ch <= '9')
{
    printf("%c is a number", ch);
}
```

- Cascading **if**: Multiple alternative blocks but at most only one block will be executed
- Cascading **if** is used when we need to choose one among several conditions

# Exercise

1. Write a program to compute the total days of a month
  - Algorithm
    - if (month in September, April, June, November) then  
output “30 days”
    - else if (month is February)  
output “28 or 29 days”
    - else output “31 days”

# Exercises

2. Write a program to get three numbers from input and print out the maximum of those
3. Write a program to solve  $ax^2 + bx + c = 0$
4. Write a program to get two numbers  $a, b$  from input and compute  $y = 15x^2 + x + 12$ , in which:

$$x = \begin{cases} \frac{a+b}{3} + b & \text{if } a < b \\ 15,172 & \text{if } a = b \\ \frac{a-b}{a^2 + b^2} & \text{if } a > b \end{cases}$$

# switch statement

switch (integer value)

```
{  
  case 1: statement1;  
    break; /* optional line */  
  case 2: statement2;  
    break; /* optional line */  
  ....  
  default: default statement;  
    break; /* optional line */  
}
```

- When a **switch** statement is encountered, the expression in the parentheses is evaluated and the program checks to see whether the result of that expression matches any of the constants labelled with case.
- If a match is made execution will start just after that case statement and will carry on until either the closing brace } is encountered or a *break* statement is found.
- Statements which follow the *default* case are executed for all cases which are not specifically listed.

# Example 1

```
printf("Yes/No (Y/N) ?");  
scanf("%c", &ch)  
switch (ch)  
{  
    case 'y' :  
    case 'Y' :  
        printf("say yes");  
        break;  
    default :  
        printf("say no");  
}
```

# Example 2

```
switch (digit){  
    case 0 : printf ("zero");  
        break;  
    case 1 : printf ("one");  
        break;  
    case 2 : printf ("two");  
        break;  
    ...  
    case 9 : printf ("nine");  
        break;  
    default:  
        printf ("others");  
}
```

# Exercises

- Display grade of a student based on marks
- diem = 9, 10: excellent
- diem = 7, 8: good
- diem = 5, 6: average
- other: weak

# using break

- When a **case** of the **switch** statement is found, statements are carried out from this point
- All following statements are carried out until a **break** statement
- **break** is a handy way of jumping straight out of the switch block

```
int a=1;
switch ( a ) {
    case 1:
        printf("a=1\n");
    case 2:
        printf("a=2\n");
        break;
    case 3:
        printf("a=3\n");
```

Output:

a=1

a=2



# Exercises

1. Write a program to get two numbers a,b from input and compute  $y = 15x^2 + x + 12$ , in which:

$$x = \begin{cases} \frac{a+b}{3} + b & \text{if } a < b \\ 15,172 & \text{if } a = b \\ \frac{a-b}{a^2 + b^2} & \text{if } a > b \end{cases}$$

2. Write a program to get an integer n ( $1 \leq n \leq 10$ ) and display the English name of that number. For example,  $n = 2$ , display  $2 \rightarrow$  two.



25 YEARS ANNIVERSARY  
**SOICT**

**VIỆN CÔNG NGHỆ THÔNG TIN VÀ TRUYỀN THÔNG**  
SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

**Thank you  
for your  
attentions!**



[soict.hust.edu.vn/](http://soict.hust.edu.vn/)



[fb.com/groups/soict](https://fb.com/groups/soict)

