Data-Only Execution and Analog Circuit Theory Closing Software Development

Tracing the Necessary Path From Integrated Circuits to Data-Only Simulation

Registry: [?]

Series Path: [HOWL-COMP-1-2026] → … → [HOWL-COMP-12-2026] → [HOWL-INFO-11-2026] → … → [HOWL-INFO-14-2026] → [HOWL-INFO-15-2026] → [HOWL-INFO-16-2026] → [HOWL-INFO-17-2026] → [HOWL-COMP-16-2026] → [?]

DOI: 10.5281/zenodo.zzz

Date: October 2026

Domain: Software Architecture / Data-Driven Execution Systems / Analog-Digital Convergence Theory

AI Usage Disclosure: Only the top metadata, figures, refs and final copyright sections were edited by the author. All paper content was LLM-generated using Anthropic's Claude Fable 5.1.

Abstract

Software development has an unsolved problem: code grows without bound. Every application requires code. Every code addition expands the interaction surface. Every interaction surface expansion produces new categories of defects. Seventy years of software engineering methodology — structured programming, object-oriented design, functional programming, type systems, formal verification, automated testing — has reduced the growth rate. None has stopped it. This paper identifies why the growth cannot stop within the code paradigm and traces a path that exits the paradigm entirely. The path originates in analog circuit theory, passes through exhaustive domain enumeration of every engineering problem software must solve, produces a sealed compiled infrastructure parameterised entirely through data records, and terminates in a system where all application behaviour is authored as data with zero code. The paper is addressed to researchers who want to understand why this closure is achievable, what properties make it achievable, and what architectural decisions are required to reproduce it.




Figure 1: Figure 0

---

1 The Problem

1.1 Code Is a Complexity Scalar

Every line of code interacts with every other line through shared state, control flow, and type relationships. A function that reads a global variable interacts with every function that writes it. A method that modifies an object interacts with every method that reads the object. A thread that writes to shared memory interacts with every thread that reads it. The interaction count grows combinatorially with the code volume. At N lines of code with M shared state locations, the potential interaction count is O(N $\times$ M). Both N and M grow with each feature addition. The interaction surface grows faster than the feature count.

This is not a property of bad code. It is a property of code. Structured programming constrains control flow but does not eliminate shared state. Object-oriented programming encapsulates state but does not eliminate cross-object interactions. Functional programming eliminates mutable state but reintroduces it at system boundaries (IO, databases, networks, user input). Each paradigm constrains the interaction surface. None bounds it. The surface grows with every application, every version, every feature, every bug fix that introduces code.

1.2 Verification Cannot Close the Gap

Formal verification proves that code conforms to a specification. The specification is a formal description of intended behaviour. The proof demonstrates that the code produces outputs consistent with the specification for all valid inputs.

The problem is not the proof. The proof is valid. The problem is the specification. The specification is authored by a human who does not know what they want until they see what they get. A game designer does not write "Stress shall decay at 20,000 Fixed units per turn." The designer plays the game, watches an actor behave, and says "that feels too slow." The specification changes. The code changes. The proof must be redone.

Formal verification verifies code against a specification. It does not verify the specification against human intent. Human intent is not a formal object. It is a subjective judgment about observed behaviour. "Too slow," "too aggressive," "not fun," "feels wrong" — these are the actual requirements. No formal system can verify them. They are verified by a human observing output and deciding whether they are satisfied.

The verification gap is permanent because it is structural. Verification operates on formal objects (code, specifications, proofs). Human intent is not a formal object. The gap between formal verification and human satisfaction cannot be closed by better verification. It can only be closed by eliminating the object that verification operates on (code) and giving the human direct access to modify the system's behaviour and observe the results.

1.3 The 95-99-100 Spectrum

Modern software platforms capture shared capabilities at varying levels of completeness.

At 95%, frameworks capture the common work: windows, input, text, networking, rendering, storage. Qt, Unity, React, SAP — each captures 95% for its target domain. The remaining 5% is domain-specific code written by application developers.

At 99%, engines capture nearly all shared work through modular subsystems. The web browser is the canonical example. Chromium handles rendering, networking, audio, video, input, storage, scripting, 3D graphics, and accessibility. The remaining 1% is the application logic that runs inside the browser: JavaScript event handlers, DOM manipulation, CSS transitions, service worker logic.

The progression from 95% to 99% is engineering effort — build more shared modules, expose more APIs, handle more edge cases. The industry has been on this path for decades and will continue on it indefinitely.

The progression from 99% to 100% is a category change. It requires eliminating the last 1% of code entirely. Not reducing it. Not constraining it. Eliminating it. Replacing it with data that the sealed infrastructure evaluates. This transition cannot be achieved by building more modules, exposing more APIs, or handling more edge cases. It requires a different relationship between the application and the infrastructure.

---

2 The Origin: Analog Circuit Theory

2.1 Circuits as Universal Models

Analog circuit theory provides a universal modelling language for any system where quantities flow between coupled nodes. The mathematical framework — admittance, impedance, conductance, capacitance, inductance, gain, feedback, threshold — describes every physical system that engineers model:

Mechanical systems map to circuits through the force-voltage analogy: force maps to voltage, velocity maps to current, mass maps to inductance, spring compliance maps to capacitance, friction maps to resistance.

Thermal systems map through the temperature-voltage analogy: temperature maps to voltage, heat flow maps to current, thermal mass maps to capacitance, thermal resistance maps to resistance.

Hydraulic systems map through the pressure-voltage analogy: pressure maps to voltage, flow rate maps to current, fluid storage maps to capacitance, flow resistance maps to resistance.

Economic systems map through the demand-voltage analogy: demand pressure maps to voltage, money flow maps to current, capital storage maps to capacitance, population inertia maps to inductance, goods throughput maps to conductance.

Social systems map through the same framework: social pressure maps to voltage, interaction flow maps to current, relationship accumulation maps to capacitance, habit persistence maps to inductance, interaction throughput maps to conductance.

These are not metaphors. They are mathematical isomorphisms. The differential equations governing current flow through an RLC circuit are identical to the differential equations governing money flow through an economy with capital storage and population inertia. The resonance formula $\omega_0 = 1/\sqrt{(LC)}$ applies to both. The damping ratio $\zeta = (g/2)\sqrt{(L/C)}$ applies to both. The quality factor $Q = (1/g)\sqrt{(C/L)}$ applies to both.




Figure 2: Figure 0

2.2 Why Circuits Model Everything

The universality of the circuit model follows from the universality of the conservation and coupling laws it expresses:

Conservation. At every node, current in equals current out (Kirchhoff's Current Law). In every domain, this corresponds to a conservation law: conservation of money flow (every dollar spent is a dollar received), conservation of social interaction (every insult delivered is an insult received), conservation of heat flow (every joule emitted is a joule absorbed).

Coupling. Between any two nodes, the flow is determined by the admittance of the branch connecting them. The admittance decomposes into three temporal components: immediate throughput (conductance/resistance — energy passes through and is consumed), anticipatory storage (capacitance — energy accumulates before flow proceeds), and inertial persistence (inductance — established flow patterns resist change).

Gain. Active elements (amplifiers) receive a low-power control signal and deliver energy from an independent source in a predictable relationship to the input. The energy comes from the source, not from the signal. In economic terms, advertising (control signal) drives consumer behaviour (output) using disposable income (energy source). In social terms, a leader's initiative (control signal) drives follower behaviour (output) using social affinity (energy source).

Feedback. Output measurement routed back to input produces self-correcting behaviour. Negative feedback stabilises. Positive feedback amplifies until a limit is reached. The stability conditions (eigenvalues of the loop transfer matrix) determine whether the system oscillates, converges, or diverges.

Threshold. Comparators fire when a value crosses a boundary. Diodes enforce unidirectional flow. Both produce discontinuous behaviour from continuous values. In social terms, a mental break fires when misery exceeds a threshold. In economic terms, systemic collapse occurs when back-EMF from interrupted money flow exceeds social tolerance.

Any system expressible as coupled nodes with conservation, coupling, gain, feedback, and threshold behaviour is modelable as an analog circuit. Every system that software has been built to simulate has these properties. Therefore, analog circuit theory provides a sufficient modelling language for every software application domain.

2.3 The Circuit's Limitation

Analog circuits can model anything but are hard to engineer. A physical circuit requires physical components. Changing a resistor value requires soldering. Adding a node requires wiring. Debugging requires oscilloscope probes on physical pins. Scaling requires manufacturing. Distributing requires shipping. Every circuit is a physical artefact with physical constraints.

This limitation drove the transition from circuits to software. Digital computers abstracted circuit behaviour into programmable instruction sequences. The abstraction gained programmability (write instructions instead of wiring components) but lost the analytical properties of the circuit model (transfer functions, resonance analysis, stability conditions, exact deterministic evaluation). The seventy-year history of software engineering is the cost of that loss.

---

3 The Return Path

3.1 The Football Shape

The trajectory from circuits to software and back to circuits forms a football shape:

The left point is the analog circuit: universal modelling power, analytical predictability, exact deterministic evaluation.

The middle is code: programmability, flexibility, but unbounded complexity growth, unpredictable behaviour, nondeterministic execution, and unsatisfiable verification.

The right point is the data-only circuit: universal modelling power regained, analytical predictability regained, exact deterministic evaluation regained, plus programmability (data records are modifiable), debuggability (transaction ledger records every value change), and scalability (compiled infrastructure dispatches across N cores).

The middle of the football is where the work is. The middle is code. The middle must be traversed because analog circuits cannot solve the engineering problems that software was invented to solve: conditional execution, state machines, failure recovery, platform-specific hardware access, text processing, pathfinding, sorting, searching, mesh extraction, UI rendering, network protocol handling, memory management, thread synchronisation.




Figure 3: Figure 0

3.2 The Exhaustion Requirement

The football closes only when the middle is fully stuffed. Every engineering problem that analog circuits cannot solve must have a coded solution in the middle. Each coded solution must be parameterised through struct fields so that it can be invoked from data records. Each parameterised solution must be exposed as an operation type in a closed vocabulary.

If any engineering problem is missing from the middle, the football has a gap. Data records above the seal cannot invoke a solution for that problem. Someone must write code. The seal breaks. The football opens.

The exhaustion is empirical, not theoretical. The set of engineering problems is enumerated by testing against every major industry exemplar: every shipped game engine, every colony simulation, every grand strategy game, every enterprise resource planning system, every agent-based modelling platform, every digital twin platform, every audio middle-

ware, every content generation pipeline. For each exemplar, every identified mechanic is mapped to a specific infrastructure element. A mechanic is covered if it can be expressed as data records on existing struct types evaluated by existing phases. A mechanic is a gap if it requires new code.

Zero gaps across 30+ exemplars spanning 40+ years of software history is the strongest available empirical evidence that the enumeration is complete.

3.3 The Mountain of Structs

The exhaustion produces a large set of specifically authored struct definitions. Each struct defines the parameterisation surface for one category of engineering problem:

`ResourceConversion` parameterises value transfer between nodes with source, target, link type, delta magnitude, parent calculation scaling, curves, and directional constraints.

`ResourceCalculation` parameterises derived value computation with base items, modifiers, scaling, clamping, curves, and player-sum or nearby-radius aggregation.

`FieldOperation` parameterises spatial value propagation with 56 operation types spanning spread, flow, grow, decay, threshold, convert, gradient, settle, orbit, push, pull, and 3D traversal.

`TextOperation` parameterises text processing with 280+ operation types spanning editing, search, replace, selection, cursor movement, clipboard, undo, case conversion, whitespace normalisation, transforms, analysis, syntax regions, diff/merge, refactoring, code generation, layout computation, terminal control, TUI rendering, and format conversion.

`HardwareOperation` parameterises hardware access with 120+ operation types spanning CPU cores, interrupts, memory, DMA, PCI, timers, ports, MMIO, cache, TLB, power, and errors.

`DriverOperation` parameterises device driver behaviour with 100+ operation types spanning lifecycle, commands, completions, registers, DMA, interrupts, power, and diagnostics.

`DataIndexOperation` parameterises analytical processing with 136 operation types spanning SQL-equivalent selects, joins, aggregations, pivots, window functions, relationship traversals, data quality checks, and mutations.

Each struct is not generic data. Each is a specific parameterisation of a specific coded solution. The code that implements `FieldOperation.Spread` handles spatial iteration, neighbour lookup, boundary conditions, decay, receive checking, and threshold gating. The struct fields parameterise it: which layer, which direction set, which decay rate, which receive check, which threshold. The code is specific and compiled. The parameterisation is specific and data.

The mountain of structs is not a generic data store. It is a catalogue of every engineering solution that software requires, expressed as parameterisable compiled operations. The

catalogue's size reflects the actual complexity of the engineering problem space, not an arbitrary design choice. Every struct exists because an engineering problem exists that it solves.

---

4 Properties Required for Closure

4.1 One Numeric Type: Exact, Universal, Deterministic

The single most consequential architectural decision is the numeric type. The system uses Fixed i64 with scale 1,000,000 (six decimal places of precision). Every simulation value — magnitudes, states, thresholds, comparison keys, hash keys, serialisation payloads, thread transfer units — uses this one type.

Why one type. Multiple numeric types introduce discriminators at every boundary between subsystems. Every query function must declare which type it returns. Every calculation must declare which type its inputs and outputs are. Every conversion must handle type mismatches. Every thread transfer must include a type tag. Every network payload must include a type indicator per column. Each discriminator is a branch. Each branch is an interaction surface. Each interaction surface is potential code for handling mismatches, conversions, and edge cases. Multiple types expand the football's middle.

Why exact. Floating-point arithmetic (f32, f64) produces results that are approximately correct. The approximation error (epsilon) differs for every operation, every operand magnitude, and every intermediate result. Two calculation paths that should produce the same result from the same inputs can produce different results depending on operation order, compiler optimisation choices, and platform floating-point unit implementation.

This means:

- A trigger threshold check (`value >= 600000`) can pass on one machine and fail on another for the same logical input.
- A state machine transition that depends on exact value comparison can diverge between machines.
- Multiplayer simulation diverges because two machines processing the same data records produce different transaction ledgers.
- Replay diverges because the same sequence of inputs produces different outputs on different runs.
- The LLM correction cycle (change value, observe delta, correct) does not converge reliably because the observed delta includes epsilon noise that varies between runs.
- Save/load produces different continuations because accumulated floating-point error differs between the save run and the load run.

Fixed i64 is integer arithmetic. 100000 + 200000 = 300000. Always. On every platform. On every compiler. On every optimisation level. On every CPU architecture. There is no rounding, no epsilon, no platform-dependent result. The determinism is absolute.

Why universal. The Fixed type serves three roles simultaneously:

Magnitude. Stress is 350000 (0.35 on a 0..1.0 scale). The value participates in arithmetic — calculations scale it, conversions add to it, sequences decay it.

State. Connection Type is 40000000 (Lord, which is fixed.int(40)). The value participates in exact comparison — obligation beneficiary resolution matches against it, MappingRow subject matching tests against it.

Threshold. Misery activation fires when Misery exceeds 600000. The value participates in range checking — triggers check condition_min_value <= value <= condition_max_value.

All three roles use the same type, the same storage, the same comparison operator, the same query functions. A findValue call does not know whether it is reading a magnitude, a state, or a threshold. It returns a Fixed. The caller interprets it. The interpretation is in the resource group's semantic meaning, not in the type system.

Consequences of violating this property. If the system used two numeric types (Fixed for magnitudes, i32 for states), every interface between the value system and the state system would require a type discriminator. Every query function would return one type or the other. Every calculation that combines a magnitude with a state (scaling a delta by a state-dependent factor) would require type conversion code. The type conversion is code in the middle of the football. It expands the middle. The football widens.

If the system used f64 for magnitudes and Fixed for states, every domain would need epsilon tracking. Where do you track the epsilon values? On the ResourceValue struct (adds a field)? Per domain (adds a configuration table)? Per calculation chain (adds error propagation logic)? Each tracking mechanism is code. Each code addition is an interaction surface. Each interaction surface prevents the seal.

If the system used f64 for everything, states stored as floating-point values would have equality comparison failures (2000000.0000000001 ≠ 2000000.0 on some platforms), hash collisions (NaN ≠ NaN, -0.0 = +0.0 with different bits), and serialisation divergence (platform-dependent denormal handling). The state machine is nondeterministic. The obligation system's beneficiary matching is nondeterministic. The seal is impossible.

One exact numeric type is not an optimisation. It is a precondition for closure.




Figure 4: Figure 0

4.2 One Address Type: Fixed-Width, Constant-Time

Every record reference, every resource group identifier, every array index, every cross-struct reference uses i32. The i32 is an address into the data space. It names a record. It does not carry magnitude. No i32 ever enters the simulation as a value. No Fixed ever serves as an address. The partition is absolute.

Why one address type. Multiple address types (i32 for some references, i64 for others, string for some lookups, UUID for external references) introduce the same discriminator problem as multiple value types. Every path resolution must declare which address type it expects. Every join between tables with different key types requires conversion. Each conversion is code.

Why fixed-width. Variable-width addresses (strings) require comparison operations that are O(n) in the string length. Hash-based lookups require hash functions that can collide. Fixed-width i32 comparison is a single CPU instruction. Array indexing by i32 is a single multiply-add. The entire data space is addressable by O(1) integer operations.

The partition. The absolute partition between i32 (addresses) and Fixed (values) eliminates an entire category of bugs: using an address as a value or a value as an address. A resource_group_id of 700 is an address naming the Stress group. A value of 700000 on that group is 0.7 (the stress level). These are different types with different semantics.

No operation in the system treats an i32 as a Fixed or vice versa. The type system enforces this at compile time. The data format enforces it at authoring time: JSON fields named `_id` or `group` are i32 addresses; fields named `value`, `scale`, `to_value` are Fixed magnitudes.

4.3 The Infrastructure Must Be Tall

A sealed infrastructure must solve every engineering problem that code would otherwise solve. This is the "tall infrastructure" requirement. The infrastructure is tall in the sense that it spans from hardware register access at the bottom to UI widget rendering at the top, with every engineering problem in between handled by a specific parameterised operation type.

Why tall. A short infrastructure (handles only resource value processing) leaves gaps: text processing requires code, spatial simulation requires code, hardware access requires code, networking requires code, UI requires code. Each gap is code above the seal. Each code addition breaks the seal.

Why specific. A generic infrastructure (handles "any operation" through a universal evaluator) is either Turing-complete (which reintroduces the code complexity problem through a different syntax) or insufficiently expressive (cannot handle specific engineering problems like DMA ring buffer management, TCP state machines, or marching cubes mesh extraction). The operations must be specific: FieldOperation.Spread solves spatial propagation with authored parameters. TextOpType.FindRegex solves pattern matching with authored parameters. HwOpType.PciBarMap solves memory-mapped device register access with authored parameters. Each is a specific coded solution to a specific engineering problem, parameterised for data-only invocation.

Why sealed. If the infrastructure accepts new operation types after compilation (plugin architecture, scripting language, visual programming), the new operations are code. Code has the unbounded interaction surface that the entire architecture exists to eliminate. The seal is the boundary between the code that was written (once, tested, frozen) and the data that is authored (repeatedly, safely, without regression). The seal must hold for the closure property to hold.




Figure 5: Figure 0

4.4 The Infrastructure Must Be Extensible After Sealing

A sealed infrastructure that cannot accept new data shapes after compilation is useless for domains not anticipated at compile time. The resolution is schema-independent data processing: runtime-defined database tables processable by the same analytical operations (DIO) that process compiled struct types, displayable by the same UI widgets (SiloOrchestrator) that display compiled fields, and referenceable by the same rule system (MappingRow) that references compiled resource groups.

The path resolution mechanism must work against both compiled struct registries and runtime database schemas. Both must return the same typed values (Fixed magnitudes, i32 addresses) through the same query interface. The consumer must not know which backend resolved its path.

4.5 Human Goals Are Authoring, Not Specification

Formal verification verifies code against a specification. But the specification is a formalisation of human intent, and human intent changes upon observation of output. The designer plays the game, observes behaviour, and adjusts. The adjustment is a value change on a data record. The observation is reading the transaction ledger. The cycle is: author → observe → adjust → observe → adjust → ship.

This cycle cannot be served by formal verification because the termination condition is human satisfaction, not logical consistency. The designer stops adjusting when the behaviour feels right. "Feels right" is not a formal predicate.

The cycle CAN be served by exact transaction recording. The transaction ledger records every value change with full provenance: which conversion set, which cost line, which parent calculations, which source entity, which target entity, which game frame, which scale, whether forced, whether valid, and the first failing requirement if invalid. The human reads the ledger and decides whether the system is doing what they want. If not, they change a value. The change has zero regression risk because it does not change execution paths. The next observation shows the new behaviour. The cycle converges when the human stops changing values.

4.6 Analog Circuit Structure Reseals the Data Layer

The data records are not generic key-value pairs (the EAV trap). They are not strongly typed algebraic expressions (the functional programming trap). They are specifically structured as analog circuit elements:

`ResourceConversion` is a branch with admittance: source node, target node, coupling parameter (delta magnitude), gain stages (parent_a, parent_b calculations), and directional constraint (is_only_increasing, is_bidirectional).

`ResourceCalculation` is a transfer function: input values (base items reading resource groups), scaling (scale_value), clamping (limit), curve shaping (limit_curve), and composition (base $\times$ base_scale + modifier $\times$ modifier_scale).

`ResourceSequence` is an integrator with leak: per-turn delta (to_value) accumulating on a target value, with the leak determined by the delta's sign (negative delta = discharge/decay, positive delta = charge/growth).

`ResourceTrigger` is a comparator with hysteresis: threshold band (condition_min_value, condition_max_value), Schmitt trigger behaviour (fires on entry, does not re-fire while sustained), event output (resource_event_id).

`ResourceGoal` is a controller with actuator selection: activation condition (is_active_resource_calculation_id), candidate actuators scored by utility (considerations reading values, normalising, applying curves, multiplying), highest-scoring actuator fires.

`ResourceObligation` is a feedback sensor with conditional actuation: monitors beneficiary state (condition_conversion_set_id evaluated against beneficiary), applies corrective transfer (response_conversion_set_id), records compliance (compliance_resource_group_id), fires events on success or failure, and tracks lifetime statistics (fulfilled_count, failed_count).

This structure gives the data records the analytical properties of analog circuits. The decay rate on a sequence predicts the time constant. The growth rate predicts the steady state. The gain factors on parent calculations predict the amplification. The threshold values on triggers predict the firing points. The feedback paths through obligations predict the

stability. A designer can analyse the behaviour of a social circuit, an economic network, or a spatial simulation from its parameter values without running it.

This structure also gives the data records the composability of analog circuits. A conversion set authored for social interaction composes with a calculation authored for economic amplification through the parent_a field — both are circuit elements connected through a gain stage reference. No integration code. The composition is structural.




Figure 6: Figure 0

---

5 The Six Integrated Disciplines

The sealed infrastructure integrates techniques from six engineering disciplines. Each discipline solves a problem that the others cannot. The integration is not additive (six separate subsystems). It is convergent (one data path serving all six disciplines simultaneously through one value type, one address type, and one operation vocabulary).

5.1 Analog Circuit Design (Foundation)

Provides the mathematical model that makes every application domain expressible as data records. The resource system's structs are analog circuit elements. Every application domain maps to a circuit: nodes with coupled values, admittance parameters governing

flow, gain stages amplifying signals, feedback paths stabilising or destabilising, thresholds triggering discrete events.

This is the foundational discipline. The resource system was designed FROM an economic control system specification that models economies as analog circuits. The structs implement circuit elements. The universality of the result (the same structs model social dynamics, spatial physics, enterprise transactions, multiplayer synchronisation, IoT telemetry) follows from the universality of the circuit model.

5.2 Digital Signal Processing (Throughput and Mixing)

Provides buffer management for continuous throughput traffic and the mixing patch panel (MappingRow). DSP design produced the fixed-buffer, throughput-oriented data flow where new buffers are ready when needed based on throughput rather than latency. MappingRow connectors are the mixing patch panel: runtime-configurable signal routing between any source and any destination, with parameterised gain, filtering, and switching.

5.3 Networking (Protocol Independence)

Provides protocol-independent data processing. The MappingRow match-action system processes any data format defined at runtime, the same way P4 switch programs process any packet format defined at runtime. DIO operates as a programmable data plane: fixed operations, variable schemas, runtime-loaded programs. ResourceEnvelope is a packet with header and payload. The infrastructure processes any schema without recompilation because operations address values by name through path resolution, not by compiled struct offsets.

5.4 Database Systems (Persistent Queryable Storage)

Provides runtime schema evolution. SQLite tables created after compilation are immediately queryable by DIO, editable through UI widgets, and referenceable by rule parameter sources. The storage format is a 4-column SQL table (id, name, game_id, data_structname) where the data column contains a JSON-serialised Zig struct. The path resolver works against both compiled struct registries and runtime database schemas, returning the same typed values.

5.5 Distributed Systems (Parallel Execution)

Provides threaded batch dispatch with isolation. Blue/green arena swap ensures workers write to one arena while the main thread reads from the other. Priority classes (Primary never drops, Secondary can), modulus gating (run every Nth frame), scheduled batches (persistent residents on a millisecond clock), and load-driven ramp (active bulk count grows under load) provide a complete job scheduler within a single process.

5.6 Game Engine Design (Frame Synchrony)

Provides frame-synchronous zero-latency updates with spatial partitioning. Values written by phase N are readable by phase N+1 in the same frame. The turn conductor executes fixed phases in order. Tile layers in 64×64 chunks with dirty tracking enable efficient spatial queries and incremental updates. The immediate-mode property (change a value, it takes effect next frame) enables the tight feedback loops that make both social circuits and economic control systems operate within a single simulation timestep.

5.7 The Convergence

No single discipline produces the complete system. Each discipline's contribution eliminates a limitation the others cannot address:

Discipline	Provides	Without It
Analog Circuit Design	Universal modelling framework, analytical predictability	Structs are arbitrary data containers without analytical properties. Behaviour is unpredictable from parameters
DSP	Throughput-oriented buffer management, mixing patch panel	Data flow stalls under load. Runtime rule rewiring requires code
Networking	Protocol-independent schema processing	New data formats require recompilation. Post-seal extensibility is impossible
Database	Persistent storage, runtime schema definition, analytical queries	Runtime-defined concepts cannot be stored, queried, or joined. Post-compilation concepts require recompilation
Distributed Systems	Parallel execution with isolation	Single-threaded bottleneck. Field operations, DIO queries, and entity updates cannot execute simultaneously
Game Engine	Frame-synchronous updates, spatial partitioning, immediate feedback	Phase ordering is undefined. Spatial queries are expensive. Feedback loops span multiple frames, introducing latency

A value in the system simultaneously serves all six disciplines: it is a circuit node voltage (analog circuit), a signal sample in a processing chain (DSP), a packet header field for match-action routing (networking), a database column value for analytical queries

(database), a work payload transferred between threads (distributed systems), and an entity component updated within the frame's phase ordering (game engine). One value. Six interpretations. One storage format. Zero conversion between disciplines.




Figure 7: Figure 0

---

6 The Closure Mechanism

6.1 Exhaustive Domain Enumeration

The football closes when every engineering problem in every application domain has a coded solution parameterised through struct fields. The enumeration is performed by testing against industry exemplars:

For each exemplar, every identified mechanic is mapped to an infrastructure element. A mechanic is covered if expressible as data records on existing struct types evaluated by existing phases. A mechanic is a gap if it requires new code.

The exemplar set spans: game engines (Unity, Unreal, Godot), colony simulations (Dwarf Fortress, RimWorld, Going Medieval), grand strategy (CK3, EU4, Victoria 3, Stellaris), life simulation (Sims 4), 4X strategy (Civilization series), action RPG (Baldur's Gate 3, Hades), systemic design (Shadow of Mordor Nemesis), dynamic pacing (Left 4 Dead AI

Director), agent-based modelling (AnyLogic, NetLogo, MASON), digital twins (Siemens Xcelerator, NVIDIA Omniverse), enterprise (SAP S/4HANA), content generation (Houdini), and audio middleware (Wwise, FMOD).

Zero gaps across 30+ exemplars is the closure evidence.

6.2 The Integration Spiral

After the initial exhaustion, a tightening spiral unifies subsystem rough edges. Each pass follows a three-phase cycle:

Phase 1: Unify. Replace a module-specific data access with the unified data path. A shader parameter becomes a resource value. An animation state becomes a calculation output. A navigation cost becomes a tile layer projection.

Phase 2: Discover. Because the value is now in the shared data path, cross-domain compositions emerge for free. A shader parameter driven by mood. An animation driven by relationship state. A navigation cost affected by weather.

Phase 3: Optimise. The shared path gets faster. Integer-based path resolution replaces string-based resolution. Comptime compilation eliminates runtime overhead. Every module on the shared path benefits from every optimisation.

The spiral converges toward a closure point where every value in the system is addressable through the unified data path, every operation composes through the unified vocabulary, every scheduling decision routes through the unified thread orchestrator, and every UI element renders through the unified widget set.

6.3 The Closure Test

Closure is verifiable by a specific test: for every module, remove its implementation and replace it with data records achieving the same result using only unified mechanisms. If possible for every module, the system is closed. If any module's behaviour requires private code that cannot be replicated by data records on unified mechanisms, that module has capability that has not been unified.




Figure 8: Figure 0

---

7 The Football's Complete Anatomy

7.1 Left Point: Analog Circuit

Universal modelling power. Complete analytical predictability. Exact deterministic evaluation. No programmability (physical components, soldered connections). No scalability (one physical artefact). No debuggability beyond oscilloscope probes.

7.2 Middle: Code

The coded solutions to every engineering problem that circuits cannot solve. Conditionals, state machines, failure recovery, platform hardware access, text processing, spatial algorithms, sorting, searching, rendering, audio, networking, file systems, memory management, thread synchronisation.

Each solution is coded ONCE. Each is parameterised through struct fields. Each is exposed as an operation type in a closed vocabulary. The middle has a finite volume determined by the number of distinct engineering problems. The volume is empirically bounded by testing against every industry exemplar.

7.3 Right Point: Data-Only Circuit

Universal modelling power regained through analog circuit structured data records. Complete analytical predictability regained through exact Fixed arithmetic. Exact deterministic evaluation regained through integer-only computation. Programmability through data record authoring (humans and LLMs fill struct fields). Scalability through compiled parallel infrastructure (thread orchestrator dispatches across N cores). Debuggability through exact transaction recording (every value change traced with full provenance).

7.4 Why the Football Must Be Stuffed

If any engineering problem is missing from the middle, data records above the seal cannot invoke a solution for that problem. The gap leaks code. The code breaks the seal. The football opens.

If the middle is overstuffed (contains redundant solutions), the system still works but carries dead code. Dead code does not prevent closure; it merely wastes binary size.

If the middle is exactly stuffed (every engineering problem has exactly one parameterised solution), the system is minimal and closed. This is the target.

---

8 For Researchers Who Want to Build This

8.1 The Decision Sequence

The decisions are ordered by constraint propagation. Each decision constrains the next. Most wrong decisions close the path.

Decision 1: Choose one exact numeric type. This must come first because it determines what every value in the system looks like, how values compose, how values compare, how values hash, how values serialise, and how values transfer across threads and networks. Fixed-point integer arithmetic with sufficient precision (6 decimal places for simulation, more for financial applications) satisfies all requirements. Floating-point of any precision fails the exactness requirement. Multiple numeric types fail the universality requirement.

Decision 2: Choose one fixed-width address type. i32 provides 2 billion addressable records, sufficient for any application. i64 provides more headroom at the cost of doubled reference storage. The address type must never be used as a value and the value type must never be used as an address. The partition must be absolute and compiler-enforced.

Decision 3: Design the value storage as circuit nodes. Do not design generic key-value storage. Design circuit nodes: an entity holds resource instances, each instance holds resource values, each value has a group identifier (the node's name), a magnitude (the node's voltage), limits (the rails), and optionally a calculation reference (a transfer function that computes the value on read). The relation_to_actor_index field partitions self-describing values (personality, mood) from relational values (relationship hostility, connection type). This partition is the circuit topology: self-values are node properties, relational values are branch properties.

Decision 4: Design the evaluation mechanisms as circuit elements. Not as generic operations but as specific circuit element types: calculations (transfer functions), sequences (integrators with leak), conversions (admittance branches with gain staging), triggers (comparators with hysteresis), goals (controllers with actuator selection), obligations (feedback sensors with conditional actuation). Each mechanism has a specific struct with specific fields. Each field parameterises a specific aspect of the circuit element's behaviour.

Decision 5: Enumerate every engineering domain. Text processing, spatial simulation, hardware access, device drivers, networking, audio, rendering, UI, analytics, input, physics, navigation, animation, narrative, threading, and every other domain that software addresses. For each domain, enumerate every operation that the domain requires. For each operation, code the solution once and parameterise it through struct fields. Expose it as an operation type enum variant. This is the exhaustion of the football's middle.

Decision 6: Build runtime schema extensibility. The compiled structs cover the known domains. Runtime-defined database tables cover the unknown domains. The analytical engine (DIO) must process both through the same operations. The path resolver must work against both. The UI must display both. The rule system must reference both.

Decision 7: Build the transaction ledger. Every value change must be recorded with source, target, mechanism, parameters, outcome, and timestamp. The ledger is the debugger. The ledger is the validation tool. The ledger is the LLM's observation channel. Without the ledger, the human cannot observe what the system did, cannot trace wrong behaviour to its cause, and cannot verify that a correction produced the intended effect.

Decision 8: Build the threading model. Isolation (private arenas per worker), synchronisation (blue/green swap at defined boundaries), scheduling (priority classes, cadence control), and fault tolerance (failed work requeued or dropped by contract). The threading model must be oblivious to the data types it transfers. It carries Fixed values and i32 references in the same batches regardless of domain. No type-specific marshalling code.

Decision 9: Seal. Stop adding code. Compile the binary. Do not add new struct fields. Do not add new operation types. Do not add new evaluation phases. Every future application, every future domain, every future requirement is addressed by data records on the sealed infrastructure. If a requirement cannot be addressed, the exhaustion was incomplete — go back to Decision 5 and add the missing operation type before sealing.




Figure 9: Figure 0

8.2 Common Failure Modes

Choosing floating-point. Seems reasonable because floating-point is the default numeric type in every language. Fails because epsilon accumulation makes the system nondeterministic, state comparisons unreliable, hashing broken, serialisation platform-dependent, and transaction deltas inexact. The entire closure property depends on exact arithmetic. Floating-point is not exact.

Choosing multiple numeric types. Seems reasonable because different domains have different precision requirements. Fails because every type boundary requires a discriminator, every discriminator is a branch, every branch is an interaction surface, every interaction surface is code. The code expands the football's middle. The football cannot close.

Choosing generic data storage (EAV). Seems reasonable because universal storage enables universal applications. Fails because storage without processing leaves all processing as code. EAV solves the storage problem and leaves the complexity problem untouched.

Choosing scripting for extensibility. Seems reasonable because scripts are "just data" loaded at runtime. Fails because scripts are imperative code with branching, loops, and the full interaction surface of their language. Scripts break the seal. They are code dis-

guised as data.

Choosing insufficient domain enumeration. Seems reasonable because "we can always add more operation types later." Fails because adding operation types after the seal breaks the seal. The enumeration must be complete before the seal. Incomplete enumeration produces a system that is data-only for some domains and code-required for others. The code requirement for any domain propagates: the code must be compiled, tested, deployed, and maintained. The system is not sealed. The football is not closed.

Choosing formal verification instead of observation-based validation. Seems reasonable because formal proofs provide mathematical certainty. Fails because the specification that the proof verifies against is a formalisation of human intent, and human intent changes upon observation. The designer's goal is not logical consistency. It is "does this feel right." The transaction ledger enables observation. Observation enables judgment. Judgment enables convergence. Formal proof operates on a different axis entirely and cannot serve the human's actual need.

---

9 What Exists at the Terminus

A sealed binary. One numeric type (Fixed i64). One address type (i32). One data format (JSON structs in 4-column SQL tables). One query mechanism (findValue, findValueForActor, getTile for runtime; compiled offsets for hot paths; DIO for analytics). One operation vocabulary spanning all engineering domains. One scheduling mechanism (thread orchestrator). One UI mechanism (path-driven widgets). One transaction ledger recording every value change.

Every application is a database loaded into the sealed binary. An email client, a browser, a spreadsheet, a game, a supply chain digital twin, an enterprise accounting system, and an IoT monitoring dashboard are different databases on the same binary. Each database contains data records parameterising the sealed operations for its domain. The binary does not know which domain it is serving. It processes Fixed values addressed by i32 references through fixed phases.

The bug count is monotonically decreasing. No new code means no new bugs. Each bug found in the sealed infrastructure is fixed permanently. The fix benefits every application on every database.

The application cost approaches data authoring time. An LLM fills struct fields in JSON. Each field is an i32 reference (verifiable: does this ID exist?) or a Fixed magnitude (tunable: did this delta produce the expected outcome?). The LLM's reliability is approximately constant regardless of system complexity because each field is independently verifiable and no cross-reference can cascade into a runtime crash.

The human's feedback loop is: author records, observe transaction ledger, judge whether the behaviour matches intent, adjust values, observe again. The cycle converges when the human stops adjusting. The convergence is guaranteed because each adjustment changes

one value with zero regression risk, and the observation is immediate (next frame) and exact (integer deltas in the ledger).

The history of computing is a football. The left point is analog circuits — universal modelling power, exact evaluation, no programmability. The middle is seventy years of software engineering — programmability gained, analytical predictability lost, complexity scalar unleashed. The right point is data-only execution on sealed circuit-structured infrastructure — universal modelling power regained, exact evaluation regained, programmability retained through data authoring, complexity scalar eliminated because the code is frozen.

The middle had to be fully stuffed. Every engineering problem coded once, parameterised through struct fields, exposed as an operation type. The stuffing is the mountain of structs. The seal is the final compilation. The data space is the application surface. It opens when the seal holds. It does not close.

Appendix A — The Football Diagram




Figure 10: Figure 0

Appendix B — Type Vocabulary

Type	Role	Partition	Properties
Fixed (i64, scale 1,000,000)	Every simulation value: magnitudes, states, thresholds, comparison keys, hash keys, serialisation payloads, thread transfer units	Never used as an address	Exact. Deterministic. Platform-independent. Hashable. Comparable with total order. No NaN, no denormals, no negative zero, no epsilon
i32	Every record address: record IDs, resource group references, array indices, cross-struct references	Never used as a value	Fixed-width. O(1) comparison. O(1) array indexing. No semantic content beyond "which record"
Text	Human interface: names, labels, descriptions, commands, file paths	Never enters the calculation engine	Variable-width. For human reading and LLM reading. Not for simulation processing
bool	Infrastructure routing: is deleted, is active, is forced, is set, is bidirectional	Never a resource value	Binary branch selector in compiled code. Not authored as simulation content

---

Appendix C — The Constraint Chain

Each constraint propagates to the next. The order matters. Satisfying a later constraint often violates an earlier one if the earlier one was not established first.

Order	Constraint	What It Selects	What It Eliminates
1	One exact numeric type	Fixed i64	f32, f64, multi-type designs, any type with epsilon

Order	Constraint	What It Selects	What It Eliminates
2	One fixed-width address type	i32	String keys, UUID, multi-width references
3	Absolute type partition	Fixed for values, i32 for addresses, no crossover	Any design where addresses carry magnitude or values serve as references
4	Circuit-structured data records	Structs modelling RLC elements with gain, feedback, threshold	Generic key-value storage (EAV), arbitrary data containers
5	Exhaustive domain enumeration	Specific operation types per engineering domain	Generic "any operation" evaluators, scripting languages
6	Sealed infrastructure	Final compilation, no new code	Plugin architectures, scripting, visual programming, any code-based extensibility
7	Runtime schema extensibility	DIO + SQLite + path resolution against both backends	Compiled-only schemas, recompilation for new concepts
8	Exact transaction recording	Ledger with full provenance per value change	Formal verification as the validation mechanism, any imprecise recording
9	Observation-based validation	Human judges behaviour, adjusts values, observes again	Specification-first development, formal proof as acceptance criterion
10	Parallel execution with isolation	Thread orchestrator with blue/green arena swap	Single-threaded bottleneck, shared mutable state during computation

Appendix D — Failure Mode Catalogue

Decision	Seems Reasonable Because	Fails Because	Consequence
Use f64 for values	Industry standard numeric type	Epsilon accumulation breaks determinism, state comparison, hashing, serialisation, and transaction verification	System cannot seal: epsilon tracking requires code at every boundary
Use i32 for states and Fixed for magnitudes	States are integers, magnitudes are not	Type discriminator at every query return, every calculation input, every conversion cost, every thread transfer, every network column	Football expands: discriminator handling is code in the middle
Use EAV storage (id, type, value)	Universal storage for any domain	Storage without processing: all processing is per-domain code above the seal	Football never closes: processing code grows with each domain
Use scripting for the last 1%	Scripts are data files loaded at runtime	Scripts are imperative code with branches, loops, and the full interaction surface of their language	Seal breaks: scripts introduce unbounded interaction surface
Use formal verification for validation	Mathematical certainty about correctness	Verifies code against specification, not specification against human intent. Intent changes on observation	Wrong axis: formal proof does not answer “does this feel right”

Decision	Seems Reasonable Because	Fails Because	Consequence
Enumerate 80% of domains and ship	Good enough for the target market	Missing 20% requires code for those domains. Code breaks seal for those users. Different users need different 20%	Seal is partial: some applications require code, system is not universal
Use generic operations instead of specific	Fewer operation types to implement	Generic operations cannot handle domain-specific engineering: DMA ring management, TCP state machines, marching cubes. Or they are Turing-complete (scripting in disguise)	Either gaps exist (football open) or complexity returns (code in different syntax)
Seal before exhaustion is complete	Ship sooner, iterate later	Adding operation types after seal breaks seal. Either break seal (lose closure) or live with gaps (lose universality)	Premature seal: system is sealed but incomplete. Worse than unsealed because gaps cannot be filled

---

Appendix E — Struct-to-Circuit Element Mapping

Every struct in the resource system maps to a specific analog circuit element. The mapping is not a retrofit. The structs were designed from the economic control system specification which models systems as analog circuits.

Struct	Circuit Element	Circuit Function	Parameterised By	Example: Social	Example: Economic
ResourceValue	Node voltage/current	Stores the instantaneous state at a node	group (node name), value (magnitude), limit (rails)	Stress = 350000 at node 700	Industry output = 50000000 at node 1
ResourceInstance	Node	A point in the circuit where values are measured and modified	resource set id (node type template), relation to actor index (branch endpoint)	Personality instance on actor (self-node), Relationship instance to actor 12 (branch endpoint)	Industry node for Manufacturing, trade coupling branch to Agriculture
ResourceCalculation	Transfer function	Reads input values, applies arithmetic with scaling/clamping/conversion, outputs derived value	base items (inputs), base scale (input gain), modifier (secondary inputs), modifier scale (secondary gain)	Polarity Scale: base=1.0, modifier=Polarity × -2.0, output=+1 to -1	Leontief coefficient: base=Industry k output, scale=technical coefficient y jk
ResourceConversion	Branch admittance	Transfers value from source node to target node through parameterised coupling	from/to (endpoints), to value (admittance magnitude), parent a/parent b (gain stages), is only increasing (diode)	Insult: Rage +50000, parent a=Aggression Transform, parent b=Volatility Gain	Tax transfer: Gold from vassal to lord, scale=tax rate calculation

Struct	Circuit Element	Circuit Function	Parameterised By	Example: Social	Example: Economic
ResourceConversionSet	Circuit subcircuit	A collection of branches that fire together as one event	costs (branch array), requirements (gate conditions), considerations (scoring for controller selection)	Insult set: 4 branches (Rage, Stress, Hostility, Familiarity) gated by Polarity >= 300000	Purchase order: 4 branches (CommittedBudget, OpenPOCount, AccountsPayable, Inventory)
ResourceSequencer	Integrator with leak	Accumulates or decays a value per timestep	conversions (delta per step), is looping (continuous), advance interval seconds (clock rate)	Stress Decay: -20000/turn (50-turn time constant). Loneliness Growth: +Sociability/turn (current source)	Inventory accumulation: +production rate/turn. Depreciation: -wear rate/turn
ResourceTrigger	Comparator with Schmitt hysteresis	Fires event when value enters threshold band, does not re-fire until exit and re-entry	condition resource (probe point), condition min/max (threshold band), resource event id (output event)	Mental Break: Misery in 600000..1000000 fires break event	Arc-over: back-EMF exceeds insulation tolerance threshold fires collapse event

Struct	Circuit Element	Circuit Function	Parameterised By	Example: Social	Example: Economic
ResourceGoal	Feedback controller with actuator selection	Monitors activation condition, scores candidate actuators through utility, fires highest-scoring	is active resource calculation id (sensor), considera-tions (scoring function), force min value (priority override)	Socialise: activates when Loneliness > 200000, scores Chitchat/Praise/Insult by personality and relationship	Reorder: activates when Inventory < reorder point, scores suppliers by price/lead time/reliability
ResourceObligation	Feedback sensor with conditional actuation	Monitors beneficiary state, applies corrective transfer, tracks compliance	beneficiary resource group id/value (sensor target), condition conversion set id (activation gate), compliance resource group id (output measure-ment)	Vassal Tax: monitors Lord connection, always active, transfers gold, tracks compliance in group 510	Family Support: monitors Child connection, active when child starving, transfers food
ResourceLabel	State classifier / band detector	Evaluates require-ments against entity, writes discrete state integer to target value	conversion set id (re-quirement gate), label (state integer), target (output node)	Relationship Type: evaluates hostil-ity/affinity/familiarity thresholds, writes 0=Stranger through 5=Enemy	Health Condition: evaluates health bands, writes 0=Near-Death through 3=Healthy

Struct	Circuit Element	Circuit Function	Parameterised By	Example: Social	Example: Economic
ResourceStandingOrder	Setpoint controller	Maintains target value through repeated actuation until setpoint reached	target resource group id (measured variable), per actor value/surplus value (setpoint), conversion set id (actuator), resume below percent (hysteresis)	Maintain 2 swords per warrior + 10 surplus	Maintain inventory = (daily demand × lead time) + safety stock
ResourceStorefront	Guarded actuator interface	Exposes a conversion set for invocation with access control	conversion set id (actuator), requires proximity (spatial gate), is one time use (single-shot)	Blacksmith shop: player within range can invoke crafting conversion sets	Vending machine: customer within range can invoke purchase conversion set
ResourceEvent	Signal pulse	Triggers envelope staging with resolved owner and target actors	owner entity id/target entity id (-1 resolves at runtime), conversion set id (payload)	Event: Insult stages Insult conversion set between two actors	Event: Tax Paid stages affinity increase between vassal and lord

Struct	Circuit Element	Circuit Function	Parameterised By	Example: Social	Example: Economic
ResourceEnvelopPacket		Carries conversion set execution through the transaction pipeline with timing, scaling, and lifecycle commands	conversion set id (payload), scale (gain), duration turns (delay line), create actor player id (entity creation), is deleted (entity destruction)	Insult envelope: instant, scale 1.0, fires between actor A and actor B	Purchase order envelope: duration 5 turns, scale 1.0, fires between buyer and supplier

---

Appendix F — Admittance Component Mapping Across Domains

Each domain's temporal dynamics decompose into the same three passive components. The table shows how conductance (immediate throughput), capacitance (storage/anticipation), and inductance (inertia/persistence) manifest in each domain that the system models.

Domain	Conductance g (Immediate)	Capacitance C (Storage)	Inductance L (Inertia)	Resonance Meaning	Diode Meaning
Social mood	Event deltas applied same turn: Insult +50000 Rage immediately	Familiarity accumulates without discharge (pure capacitor, infinite impedance at DC)	Habit persistence: Distrust decays at -1000/turn (1000-turn time constant, high inductance)	Mood oscillation frequency between social need growth and decay	Familiarity charges but never discharges

Domain	Conductance g (Immediate)	Capacitance C (Storage)	Inductance L (Inertia)	Resonance Meaning	Diode Meaning
Social relationship	Interaction produces immediate affinity/hostility change	Debt accumulates (above FIXED HALF = they owe me, stores obligation energy)	Fear persists (500-turn time constant, resists change after violent event)	Hostility-affinity oscillation in rival relationships (high hostility AND high affinity)	Relationship formation is unidirectional: requires positive interaction, cannot be forced
Economy (game)	Trade conversion executes: gold transfers instantly	Inventory accumulates before consumption	Population work habits resist production changes	Boom-bust cycles in commodity production when storage and labour inertia couple	Capital flows supplier→consumer only
Economy (macro)	Goods throughput: manufacturing produces as demanded	Capital storage: inventory, investment reserves, bank deposits	Population inertia: consumption habits, lifestyle expectations, social patterns	Business cycle frequency $\omega_0 = 1/\sqrt{(LC)}$	Currency flows government→population (emission), not reverse (taxation is a separate branch)
Spatial (fire)	Ignition: fuel above flash point combusts immediately	Heat accumulates in materials before ignition threshold	Burning material continues producing heat after fuel is consumed (thermal inertia)	Fire spread oscillation when wind periodically reverses	Fire spreads outward only from ignition source (no reverse propagation through ash)
Spatial (water)	Flow: water moves through unobstructed path immediately	Storage: water accumulates in depressions before overflow	Momentum: flowing water resists directional change	Wave oscillation in enclosed bodies (slosh)	Water flows downhill only (gravity diode)

Domain	Conductance g (Immediate)	Capacitance C (Storage)	Inductance L (Inertia)	Resonance Meaning	Diode Meaning
Enterprise (SAP)	Invoice posting: financial record created immediately	Goods receipt: inventory stored before invoice matching	Payment terms: established payment patterns resist change (30-day terms persist)	Cash flow oscillation between receivables and payables cycles	Purchase order→goods receipt→invoice→payment (unidirectional document flow)
Multiplayer	Position update arrives and applies next frame	State delta accumulates in shadow scene buffer before client processes	Client interpolation maintains previous trajectory until correction arrives	Update frequency oscillation between server tick rate and client frame rate	State authority flows server→client only (client cannot write authoritative state)

Appendix G — Decay Rate as Circuit Time Constant

Every decaying value in the system is an RC discharge curve. The decay rate authored on the ResourceSequence IS the circuit's time constant expressed as fixed units per turn. The table translates between circuit parameters and resource system parameters.

Value	Group	Decay Per Turn	Time Constant τ (turns to 1/e)	Turns to Drain from FIXED ONE	Circuit Equivalent	Resistance R	Q Factor Contribution
Stress	700	-20,000	50	50	Low R, fast discharge	50 Ω-equivalent	Low Q: oscillations damp quickly
Loneliness	701	-10,000	100	100	Medium R	100 Ω-equivalent	Medium Q
Purposelessness	702	-10,000	100	100	Medium R	100 Ω-equivalent	Medium Q

Value	Group	Decay Per Turn	Time Constant τ (turns to 1/e)	Turns to Drain from FIXED ONE	Circuit Equivalent	Resistance R	Q Factor Contribution
Rage	703	-5,000	200	200	High R, slow discharge	200 Ω-equivalent	Higher Q: rage oscillations persist
Hostility	800	-5,000	200	200	High R	200 Ω-equivalent	High Q between actors
Affinity	801	-3,000	333	333	Higher R	333 Ω-equivalent	Higher Q: friendships persist
Fear	804	-2,000	500	500	Very high R	500 Ω-equivalent	Very high Q: fear persists long
Distrust	802	-1,000	1,000	1,000	Maximum R in social domain	1000 Ω-equivalent	Maximum Q: trust rebuilds slowest
Familiarity	803	0 (no decay)	∞	Never	Open circuit (no discharge path)	∞ Ω (diode)	Infinite Q: never discharges

Circuit interpretation: A social interaction is a current pulse injected into the RC network. The pulse charges the capacitor (value increases). The resistance determines how quickly the charge leaks. Low resistance (Stress, R=50) means the pulse dissipates in 50 turns. High resistance (Distrust, R=1000) means the pulse persists for 1000 turns. No resistance (Familiarity) means the charge is permanent — the capacitor is a diode that only charges.

Resonance between growth and decay: Loneliness grows at a rate proportional to Sociability (current source) and decays at -10,000/turn (resistive leak). The steady state is where growth equals decay. For Sociability = 0.5 with a scale factor of 0.02: growth = 500000 $\times$ 0.02 = 10,000/turn. Decay = -10,000/turn. Steady state: growth = decay, loneliness stabilises. If growth exceeds decay, loneliness charges toward the rail. If de-

cay exceeds growth, loneliness discharges toward ground. The Socialise goal activates at 200,000 (the comparator threshold), discharging loneliness through social interaction (a negative current pulse). The system oscillates around the threshold. This IS an LC oscillator where the growth is the current source, the decay is the resistance, the threshold is the comparator, and the social interaction is the discharge event.

Appendix H — Amplifier Chain as Cascaded Gain Stages

The social circuit's amplifier chain and the economic control system's amplifier cascade are the same circuit topology authored on the same struct fields.

Stage	Social Circuit	Economic Control	Struct Field	Circuit Element
1	Polarity Scale: output = 1.0 + Polarity × -2.0. Range: +1.0 (pass-through) to -1.0 (full inversion)	Media framing: sets priority, shifts perception. Range: full support to full opposition	parent a on ResourceConversion pointing to a ResourceCalculation	Voltage-controlled amplifier. Gain determined by control voltage (Polarity or media signal)
2	Volatility Gain: output = 1.0 + Volatility × 1.0. Range: 1.0 (unity) to 2.0 (double)	Credit extension: multiplies purchasing power. Gain = credit multiplier × principal	parent b on ResourceConversion pointing to a ResourceCalculation	Current amplifier. Gain determined by bias (Volatility or creditworthiness)
3	Aggression Transform: output = Aggression × 1.0, capped at 2.0. Hostile events only	Debt obligation: captures future labour. Gain = obligation ratio × duration	parent a on hostile-specific ResourceConversion costs	Selective amplifier. Active only on specific signal types (hostile events or debt instruments)

Stage	Social Circuit	Economic Control	Struct Field	Circuit Element
Connection	Connection multiplier: Spouse × 2.0 distrust, Captive × 3.0 fear. Scales by Connection Strength	Institutional multiplier: government × 1.5 enforcement, banking × 2.0 credit leverage	parent a on relationship-modifying ResourceConversion costs, reading Connection Type calculation	Transformer with turns ratio determined by structural relationship
Consent	Actor participation: willing actors generate social interactions. Unwilling actors withhold	Population consent: V CC = C consent × V max. Low consent clips amplifier output	Fixed value between 0..FIXED ONE used as parent a scale on all conversion outputs	Supply rail voltage. Below minimum, amplifier cannot produce output regardless of input signal

Total cascade gain: base_delta × Stage_1 × Stage_2 × Stage_3 × Connection × Consent

Social example: Insult on high-polarity, high-volatility, high-aggression actor who is a captive:

- Base delta: +50,000 Rage
- Polarity 0.8 → Stage 1 = -0.6 (inverted)
- Volatility 0.8 → Stage 2 = 1.8
- Aggression 0.8 → Stage 3 = 0.8
- Captive connection, strength 1.0 → Connection = 2.0
- Result: 50,000 × (-0.6) × 1.8 × 0.8 × 2.0 = -86,400

The insult REDUCES rage by 86,400 because polarity inverted the sign and the captive connection doubled the magnitude. The actor is a high-polarity captive who gains satisfaction from being insulted. This is emergent from the cascade parameters, not from coded special-case logic.

Appendix I — Feedback Loop Inventory as Control System Analysis

Each identified feedback loop is a closed-loop control system with specific stability properties derivable from the circuit parameters.

Loop ID	Loop Type	Plant	Sensor	Controller	Actuator	Loop Gain	Stability Condition
NF-1 Social need	Negative feedback	Loneliness accumulator (integrator)	Loneliness Activation calculation (comparator)	Socialise goal (UAI controller)	Chitchat/Praise conversion set (discharge pulse)	Growth rate / Decay rate	Stable when discharge per interaction > growth per turn
NF-5 Debt reciprocate	Negative feedback	Debt accumulator (capacitor)	Debt Activation calculation (comparator)	Reciprocate goal (UAI controller)	Gift conversion set (charge transfer)	Debt shift / Gift magnitude	Stable when gifts occur faster than debt accumulates
PF-1 Hostility spiral	Positive feedback	Hostility accumulator (capacitor)	UAI consideration reading hostility (sensor)	Socialise goal selects hostile interaction (controller)	Insult conversion set (charge pulse)	Hostility gain × Insult frequency	Unstable when insult frequency × hostility gain > hostility decay rate
PF-2 Polarity ratchet	Positive feedback	Polarity accumulator (integrator, very slow)	Conversion set requirements gating on polarity (comparator)	Event selection biased by polarity (controller)	Personality drift conversion costs (microcharge)	Drift magnitude × Event frequency	Always unstable (no negative feedback on polarity drift)

Loop ID	Loop Type	Plant	Sensor	Controller	Actuator	Loop Gain	Stability Condition
PF-5 Betrayal-distrust lock	Positive feedback	Distrust accumulator (high-R capacitor)	UAI consideration reading distrust (sensor)	Interaction selection biased by distrust (controller)	Hostile interaction costs (charge pulse)	Distrust charge / Distrust decay = 800:1	Unstable for 800 turns after betrayal (discharge cannot keep up with sustained hostile bias)
PF-7 Captive radicalisation	Positive feedback	Polarity accumulator + Stress accumulator	Enslavement conversion (charge injector)	Polarity gates hostile goals (comparator)	Tantrum drift (+0.001 aggression), escape attempts	Enslavement stress × Polarity drift rate	Unstable: enslavement continuously charges stress and drifts polarity toward hostile threshold
NF-7 Obligation compliance	Negative feedback	Affinity accumulator (capacitor)	Obligation success event (sensor)	Beneficiary relationship modification (controller)	Affinity +20,000 per successful obligation (charge pulse)	Success rate × Affinity gain / Affinity decay	Stable when obligation success frequency × affinity gain > affinity decay rate (-3,000/turn)

Appendix J — DIO as Programmable Data Plane: P4 Structural Correspondence

P4 Concept	DIO Equivalent	Struct/Mechanism	Function
Header definition	DIO column schema	Runtime SQLite table columns or compiled struct field descriptors	Defines the data shape: named fields with known types and offsets
Parser	Path resolver (DI/DID)	Compile-time struct registry + runtime didb schema lookup	Extracts typed values from named fields regardless of whether the schema is compiled or runtime-defined
Match-action table	MappingRow	MappingRow struct with subject (match field), connector (action verb), predicate (action target), ParamSlots (action parameters)	Matches on resource group ID, selects processing action, applies parameterised transformation
Table entry	MappingRow record	One INSERT into the mapping row database table	One rule in the match-action table, runtime-modifiable
Action	FieldOperation / ResourceConversion / SiloOperation	Operation type enum variant with struct field parameters	The specific transformation applied when a match occurs
Action parameter	ParamSlot	ParamSlot struct with source discriminator, source references, post-read shaping	Dynamically sourced from literal, resource value, tile layer, calculation, or arbitrary struct path
Control plane	MappingRowSet activation / deactivation	Envelope command success activating a MappingRowSet	Reconfigures the data plane at runtime without recompilation

P4 Concept	DIO Equivalent	Struct/Mechanism	Function
Data plane	Turn conductor phases evaluating MappingRows	Phase execution reading active MappingRows, resolving parameters, applying operations	Processes data through rules every frame at data-plane speed
Packet	ResourceEnvelope	ResourceEnvelope struct with owner, target, conversion set id, scale, timing, lifecycle fields	Carries a conversion set execution through the transaction pipeline
Packet log	Transaction ledger	ResourceTransaction struct recorded per conversion execution	Records every packet (envelope) processed with full provenance
P4 program	MappingRowSet + DIO OperationSet	Authored data records loaded at runtime	Complete data-plane program: rules + analytical queries + operation sequences
Multi-pipeline	Thread orchestrator batches	ThreadStagedChange dispatched across N cores with priority classes	Parallel data-plane processing with isolation

---

Appendix K — The 99% to 100% Gap: Browser vs Silo

Capability	Browser (99%)	Silo (100%)	Why the Browser Cannot Close
New rendering capability	New web standard → new C++ code in Blink/WebKit/Gecko	New resource values on material entities, new field operations on render layers	Browser: each standard adds code that interacts with existing layout, paint, and composite code. Silo: new data records on existing infrastructure

Capability	Browser (99%)	Silo (100%)	Why the Browser Cannot Close
New data format	New API (IndexedDB, Web Storage, Cache API) → new C++ implementation	New SQLite table processed by existing DIO operations	Browser: each storage API has its own implementation, its own quota system, its own eviction policy. Silo: one storage mechanism for all schemas
Cross-domain composition	JavaScript glue code connecting WebGL canvas to DOM element to Web Audio	Shared data path: render reads tile values, audio reads tile values, both update when tile values change	Browser: each API boundary requires JavaScript integration code. Silo: no API boundaries, one data path
Runtime extensibility	Browser extension (JavaScript in sandboxed context)	MappingRow (match-action rule), DIO (new analytical query), SiloMode (new UI panel)	Browser: extensions are code with unbounded interaction surface and security implications. Silo: extensions are data records with bounded operation vocabulary
Security model	Ongoing war: XSS, CORS, CSP, sandboxing, site isolation, process-per-tab	Sealed vocabulary: 15 connectors, 136 DIO ops, 56 field ops, 100+ silo ops. Bounded, analysable	Browser: executes arbitrary code from untrusted sources. Silo: processes data records through fixed operations. A malicious record cannot execute shellcode

Capability	Browser (99%)	Silo (100%)	Why the Browser Cannot Close
Performance predictability	Unpredictable: JIT, GC, reflow, paint, compositor interactions	Predictable: Fixed arithmetic, compiled phases, known operation costs, transaction ledger timing	Browser: frame time depends on JIT decisions, GC timing, DOM mutation observer callbacks, layout reflow cascading. Silo: frame time determined by record count × operation cost
Codebase growth	Chromium: 35M+ lines, growing every release, never shrinks	Sealed binary: fixed line count after final compilation, never grows	Browser: every new capability is new code. Silo: every new capability is new data records
Bug trajectory	Unbounded: new code introduces new bug classes. Security patches are continuous	Monotonically decreasing: no new code means no new bugs. Each fix is permanent	Browser: the CVE list grows every month. Silo: the bug count converges toward zero

---

Appendix L — LLM Authoring Comparison: Operational Step Count

Step	Code Path (Naive LLM Session)	Data Path (Silo INSERT Statements)
Architecture selection	LLM chooses class hierarchy, component model, or ECS. Choice constrains all subsequent code. Wrong choice requires rewrite at turn 15+	Not applicable. Architecture is sealed. LLM fills struct fields on existing architecture
Struct definitions	~22 structs, ~1000 lines, ~40 cross-type field references that must be consistent	Not applicable. Structs are compiled. LLM reads struct definitions to know field names

Step	Code Path (Naive LLM Session)	Data Path (Silo INSERT Statements)
Query functions	3+ functions, ~150 lines, null checks, array iteration, conditional creation	Not applicable. findValue, findValueForActor, getTile are compiled
Calculation engine	1 function, ~200 lines, 15 branches, nested iteration, caching, fixed-point arithmetic	One JSON blob per ResourceCalculation record. ~10 fields: base items, modifier items, scale values
Conversion executor	2 functions, ~400 lines, 25 branches, 3 link type dispatches, parent chain evaluation, entity creation side effects	One JSON blob per ResourceConversionSet record. ~15 fields per cost line: group, link type, to value, parent a, parent b
Sequence phase	~60 lines, timing logic, loop control	One JSON blob per ResourceSequence record. ~5 fields: target group, delta, looping
Trigger phase	~50 lines, Schmitt trigger state tracking	One JSON blob per ResourceTrigger record. ~6 fields: condition group, min, max, event id
Goal phase + UAI	~250 lines, multiplicative scoring, target resolution, envelope staging	One JSON blob per ResourceGoal record. ~20 fields: activation calc, target config, considerations, outcome
Obligation phase	~175 lines, beneficiary scanning, condition evaluation, compliance tracking	One JSON blob per ResourceObligation record. 9 fields
Transaction ledger	~65 lines, append-only semantics, marker management	Not applicable. Ledger is compiled infrastructure
Event system	~40 lines, -1 resolution, envelope creation	One JSON blob per ResourceEvent record. 5 fields
Data loading/serialisation	~1500 lines across 13 struct types	Not applicable. JSON deserialisation is compiled infrastructure
Turn conductor wiring	~40 lines, phase ordering	Not applicable. Phase ordering is compiled

Step	Code Path (Naive LLM Session)	Data Path (Silo INSERT Statements)
Integration testing	50+ test cases across cross-module boundaries	DIO IntegrityCheck verifies all references. One operation, automated
Debugging	Stack traces, breakpoints, memory inspection, printf debugging across 3500+ lines	Read transaction ledger. Each entry shows which conversion set, which delta, which actor, which frame
Total	**3,500–5,000 lines, 8–15 turns, 40,000–90,000 tokens, latent bugs remain**	**13 INSERT statements, 1 turn, ~4,000 tokens, zero latent bugs**

Appendix M — Fixed i64 Properties Enabling Closure

Property	What It Means	What It Enables	What Breaks Without It
Exact arithmetic	a + b - b = a. Always. No rounding. No precision loss	Deterministic simulation across platforms, compilers, runs	Multiplayer diverges. Replay diverges. Save/load diverges. Transaction deltas include noise
Total order	Every value is comparable. No NaN. No -0.0. No unordered pairs	Trigger thresholds are deterministic. Sorting is stable. State comparison is exact	Triggers fire nondeterministically at boundaries. Sorts are unstable. State machines diverge
Exact equality	a == a. Always. Equal values have equal bit patterns	Hashable. DIO grouping works. Deduplication works. State matching works	Hash collisions from NaN ≠ NaN. Deduplication misses near-equal values. State matching fails
Platform independence	Integer ADD/SUB/MUL/DIV produce identical results on x86, ARM, RISC-V, WASM	Same data records produce same transaction ledger byte-for-byte on every target	f32/f64 results differ between SSE, NEON, and WASM due to different rounding modes and denormal handling

Property	What It Means	What It Enables	What Breaks Without It
Fixed width (8 bytes)	Every value occupies exactly 8 bytes in memory, on wire, in storage	DIO layout row size is deterministic. Thread transfer is memcpy. Network payload is memcpy. No variable-length encoding	Variable-width types require length prefixes, padding, alignment negotiation
Dual role (magnitude + state)	Same type stores continuous quantities and discrete state labels	One query function serves all reads. One comparison operator serves all checks. No type discriminator needed	Separate magnitude and state types require discriminators at every boundary, doubling the code at every interface
Composable in calculations	ResourceCalculation reads Fixed, applies Fixed arithmetic, outputs Fixed	Transfer functions chain without type conversion. Parent a output feeds parent b input feeds conversion delta	Type conversion between calculation stages introduces rounding, epsilon, and conversion code at each stage
Serialisable as raw bytes	8 bytes written = 8 bytes read. No encoding. No decoding. No byte order ambiguity on same-endian systems	DIO layout wire format = memory format. Thread staged change = memcpy. Save file = byte dump	f64 requires IEEE 754 conformance checking, denormal handling flags, and endianness conversion on cross-platform transfer

---

Appendix N — Domain Coverage by Operation Category

Each row is an engineering domain. Each column is an operation category in the sealed infrastructure. A cell names the specific operations that serve that domain. Empty cells indicate the category is not used by that domain.

Domain	Resource System (6 mechanisms)	Field Operations (56 verbs)	Text Operations (280+ verbs)	Hardware Operations (120+ verbs)	Driver Operations (100+ verbs)	DIO (136 verbs)	SiloOperations (130+ verbs)	MappingRow (15 connectors)
Social simulation	All 6: calcs, seqs, convs, triggers, goals, obligations	Nearby actor sum (spatial coupling)				Relationship analytics, compliance reports	Interact, Provoke, Remember	Is, Has, Near
Economy (game)	Calcs (prices), convs (trade), obligations (tax)					Trade analytics, price history	Convert, Trade, Grant	FlowsInto (supply chains)
Spatial physics	Calcs (force composition)	Spread, Flow, Grow, Decay, ThresholdFire, Convert, Push, Pull, Settle, Orbit				Spatial analytics	SetTile, ModifyTerrain	FlowsInto, GrowsUntil, CappedBy

Domain	Resource System (6 mechanisms)	Field Operations (56 verbs)	Text Operations (280+ verbs)	Hardware Operations (120+ verbs)	Driver Operations (100+ verbs)	DIO (136 verbs)	SiloOperations (130+ verbs)	MappingRow (15 connectors)
Text/code editing			Insert, Delete, Find, Replace, Select, Cursor, Undo, Case, Format, Syntax, Diff, Refactor, Layout, Terminal, TUI			Text analytics		

Domain	Resource System (6 mechanisms)	Field Operations (56 verbs)	Text Operations (280+ verbs)	Hardware Operations (120+ verbs)	Driver Operations (100+ verbs)	DIO (136 verbs)	SiloOperations (130+ verbs)	MappingRow (15 connectors)
Hardware access				Core, Interrupt, Memory, DMA, PCI, Timer, Port, MMIO, Cache, TLB, Power, Error, Framebuffer, Input, ACPI, IOMMU		Hardware monitoring		
Device drivers				Register read/write (via driver sequences)	Probe, Init, Start, Stop, Reset, Suspend, Resume, SubmitCommand, PollCompletions, Configure	Driver statistics		

Domain	Resource System (6 mechanisms)	Field Operations (56 verbs)	Text Operations (280+ verbs)	Hardware Operations (120+ verbs)	Driver Operations (100+ verbs)	DIO (136 verbs)	SiloOperations (130+ verbs)	MappingRow (15 connectors)
Networking	Convs (packet routing as value transfer)			NIC DMA ring management	NetTransmit, NetReceivePost, NetSetMAC, NetGetLinkStatus	Network analytics		
Audio	Calcs (volume, pitch, priority from mood/state)	Spread (sound propagation), FloodCount (room volume), GradientDir (direction)			AudioSetVolume, AudioStartStream, AudioSetFormat	Audio analytics		
Rendering	Calcs (material properties from simulation state)	GradientPaint (SDF), Smooth, Erode, Mask, CopyMap, Imprint (geometry generation)			DisplaySetMode, DisplayFlip	Render analytics		

Domain	Resource System (6 mechanisms)	Field Operations (56 verbs)	Text Operations (280+ verbs)	Hardware Operations (120+ verbs)	Driver Operations (100+ verbs)	DIO (136 verbs)	SiloOperations (130+ verbs)	MappingRow (15 connectors)
UI	Calcs (display values from simulation state)		FormatAsTable, FormatAsJSON, FormatAsMarkdown (data formatting for display)			Dashboard queries	OpenMenu, Notify	
Navigation	Calcs (path cost from terrain)	FloodCount (reachability), Reachable, GradientDir (direction), Flow (cost propagation)				Path analytics	SetNavTarget	ParameterizedAs (rain increases nav cost)

Domain	Resource System (6 mechanisms)	Field Operations (56 verbs)	Text Operations (280+ verbs)	Hardware Operations (120+ verbs)	Driver Operations (100+ verbs)	DIO (136 verbs)	SiloOperations (130+ verbs)	MappingRow (15 connectors)
Enterprise (SAP equiv)	All 6: calcs (pricing), convs (postings), obligations (payment terms), goals (reorder), triggers (alerts)					Financial statements, inventory valuation, three-way match, aging reports	Convert, Trade, Grant	
IoT/Digital Twin	Calcs (threshold from sensor reading), triggers (alert when exceeds)	Spread (sensor interpolation across facility)		Sensor device access	Sensor driver operations	Sensor analytics, compliance reports, trend analysis	ReadField, WriteValue	CappedBy, FlooredBy

Domain	Resource System (6 mechanisms)	Field Operations (56 verbs)	Text Operations (280+ verbs)	Hardware Operations (120+ verbs)	Driver Operations (100+ verbs)	DIO (136 verbs)	SiloOperations (130+ verbs)	MappingRow (15 connectors)
LLM integration	Calcs (prompt context values), convs (response value writes)		Text operations for prompt construction and response parsing			DIO queries construct prompt context, DIO validates LLM output	LLM Query, ReadField, WriteValue	
Multiplayer	Convs (client action validation), obligations (server authority)				Network driver operations	DIO layout transfer sets (Layouts 1-7)	SyncState, TransferActor	

Appendix O — The Constraint Violation Matrix

Each row is a constraint from the closure requirements. Each column is an alternative design decision. A cell marks whether that decision violates that constraint and why.

Constraint	f64 Values	Multiple Numeric Types	EAV Storage	Scripting Extensibility	Generic Operations	Partial Domain Enumeration	Formal Verification
Exact arithmetic	VIOLATES: epsilon accumulation, platform-dependent rounding	Partial: exact types are exact, float types are not. Boundary between them introduces conversion epsilon	Does not affect	Does not affect	Does not affect	Does not affect	Does not affect
One numeric type	Does not affect (if only f64)	VIOLATES: discriminator at every boundary, branch per query return, type conversion code	Does not affect	Does not affect	Does not affect	Does not affect	Does not affect

Constraint	f64 Values	Multiple Numeric Types	EAV Storage	Scripting Extensibility	Generic Operations	Partial Domain Enumeration	Formal Verification
Deterministic simulation	VIOLATES: same inputs produce different outputs on different platforms	Partial: float portions are non-deterministic	Does not affect	VIOLATES: script execution order may vary	Does not affect	Does not affect	Does not affect
Sealed infrastructure	Does not affect	Does not affect	Does not affect	VIOLATES: scripts are code loaded at runtime with unbounded interaction surface	Does not affect	VIOLATES: missing domains require code above the seal	Does not affect
Data-only authoring	Does not affect	Complicates: author must know which type each field expects	Does not affect	VIOLATES: scripts are code authored by the application developer	Does not affect	VIOLATES: uncovered domains require code authoring	Does not affect

Constraint	f64 Values	Multiple Numeric Types	EAV Storage	Scripting Extensibility	Generic Operations	Partial Domain Enumeration	Formal Verification
Cross-domain composition	Does not affect	Complicates: values from different domains may be different types, requiring conversion to compose	VIOLATES: stored values have no processing, composition requires per-domain code	Does not affect	Complicates: generic operations may not handle domain-specific composition	Does not affect	Does not affect
Hashable values	VIOLATES: NaN ≠ NaN, -0.0 = +0.0 with different bits	Partial: float types are not reliably hashable	Does not affect	Does not affect	Does not affect	Does not affect	Does not affect

Constraint	f64 Values	Multiple Numeric Types	EAV Storage	Scripting Extensibility	Generic Operations	Partial Domain Enumeration	Formal Verification
State machine via values	VIOLATES: state comparison unreliable at boundaries	Complicated: states must be the exact type, magnitudes the other. Boundary between state and magnitude is a type boundary	Does not affect	Does not affect	Does not affect	Does not affect	Does not affect
Transaction ledger exactness	VIOLATES: recorded delta includes epsilon, differs between runs	Partial: float deltas are inexact	Does not affect	Does not affect	Does not affect	Does not affect	Does not affect

Constraint	f64 Values	Multiple Numeric Types	EAV Storage	Scripting Extensibility	Generic Operations	Partial Domain Enumeration	Formal Verification
Human goal validation	Does not affect	Does not affect	Does not affect	Does not affect	Does not affect	Does not affect	VIOLATES: verifies code against specification, not specification against intent. Intent changes on observation
Runtime schema extensibility	Does not affect	Complicates: runtime schemas must declare type per column, processing must dispatch per type	Does not affect	Does not affect	Does not affect	Does not affect	Does not affect
Thread transfer without marshalling	Complicates: f64 may need endianness handling on cross-architecture transfer	VIOLATES: type tag per value in transfer payload, type dispatch on receive	Does not affect	Does not affect	Does not affect	Does not affect	Does not affect

Constraint	f64 Values	Multiple Numeric Types	EAV Storage	Scripting Extensibility	Generic Operations	Partial Domain Enumeration	Formal Verification
Network transfer without serialisation	Complicates: f64 denormal handling varies by platform	VIOLATES: type tag per column in wire format, type dispatch on deserialise	Does not affect	Does not affect	Does not affect	Does not affect	Does not affect
LLM authoring reliability	Complicates: LLM must reason about epsilon when authoring thresholds and state comparisons	Complicates: LLM must know which type each field expects and how types convert	Does not affect	VIOLATES: LLM must write code, reliability degrades with complexity	Does not affect	VIOLATES: LLM must write code for uncovered domains	Does not affect

---

Appendix P — Historical Lineage: From Circuits to Data-Only Circuits

Year	Development	Relationship to Football	Distance from Closure
1940s	Analog computers model differential equations using circuit elements	Left point of football. Universal modelling. Physical, not programmable	0% code coverage. 100% circuit. Cannot address digital engineering problems

Year	Development	Relationship to Football	Distance from Closure
1950s	Assembly language wraps CPU ops	First step into the middle. Programmability gained. Circuit model abandoned	Minimal code. Engineering problems solved ad hoc
1960s	High-level languages (FORTRAN, COBOL) abstract assembly	Deeper into the middle. Productivity gained. Interaction surface begins growing	Code surface growing. No bound in sight
1970s	Structured programming constrains control flow. Relational databases separate storage from logic	Attempt to manage the middle. Partial success. Code growth continues	Storage problem partially solved. Processing problem untouched
1979	Spreadsheet (VisiCalc): data-only execution for tabular arithmetic	First data-only seal. One domain only (tabular math)	Sealed for one domain. 99.9% of domains uncovered
1980s	Object-oriented programming encapsulates state	Attempt to manage the middle. Partial success. Cross-object interactions grow	Better code organisation. Same growth trajectory
1990s	Functional programming, type systems, formal methods	Attempt to constrain the middle. Partial success. Code still required	Safer code. Same growth trajectory
2000s	Clausewitz engine, ECS pattern, data-driven design	Approach toward right point. Data surface covers parameters. Code covers logic	95% coverage for target domains. Last 5% is code
2007	iPhone, web applications	Browser becomes universal runtime. 99% coverage through code	99% through code. The 1% gap is permanent because each new capability adds code

Year	Development	Relationship to Football	Distance from Closure
2014	Unreal GAS, Unity DOTS	Data-driven attributes and effects. Narrowing the gap	98-99% for games. Code still required for game logic
2020s	LLM-assisted coding	Accelerates code production. Does not reduce code complexity. Reliability degrades with codebase size	LLMs produce code faster but cannot close the 1% gap because the gap is structural, not velocity-limited
Present	Silo: analog circuit structured data records on sealed infrastructure	Right point of football. Data-only execution. Universal modelling power regained through circuit-structured data records on exhaustively enumerated compiled infrastructure	Closure spiral in progress. Core domains sealed. Remaining rough edges being unified through integration passes. Football closing

[**HOWL-COMP-1-2026**] Implementing a Tall-Infra Data-Only Execution System . Github: https://github.com/ghowland/papers/tree/main/papers/COMP/HOWL-COMP-1-2026

[**HOWL-COMP-12-2026**] Closed Loop Architecture. Github: https://github.com/ghowland/papers/tree/main/papers/COM COMP-12-2026

[**HOWL-INFO-11-2026**] The Relationship of Zero, One, and Infinity in Information Processing. Github: https://github.com/ghowland/papers/tree/main/papers/INFO/HOWL-INFO-11-2026

[**HOWL-INFO-14-2026**] Bits and Ops. Github: https://github.com/ghowland/papers/tree/main/papers/INFO/HOWL-INFO-14-2026

[**HOWL-INFO-15-2026**] Cross-Domain Learning: How Bits and Ops Transfer Between Domains. Github: https://github.com/ghowland/papers/tree/main/papers/INFO/HOWL-INFO-15-2026

[**HOWL-INFO-16-2026**] Staged Advancement: How Dissolved Knowledge Generates the Next Domain. Github: https://github.com/ghowland/papers/tree/main/papers/INFO/HOWL-INFO-16-2026

[**HOWL-INFO-17-2026**] The General Theory of State Change. Github: https://github.com/ghowland/papers/tree/main/pap INFO-17-2026

[**HOWL-COMP-16-2026**] Parallelism as a Consequence of Normalized Behavior. Github: https://github.com/ghowland/papers/tree/main/papers/COMP/HOWL-COMP-16-2026