



















Comment	Description	Designator	Footprint	LibRef	Quantity
0.1uF	0603 (1608 Metric) Chip Capacitor	C1, C2, C19, C20, C21	CAPC0603(1608)100_L	CMP-1590-00005-1	5
18pF	0603 (1608 Metric) Chip Capacitor	C3, C4, C22, C23	CAPC0603(1608)100_L	CMP-1590-00005-1	4
Торі	Tantalum Capacitor, 10	03, 04, 022, 023	CAI C0003(1000)100_E	CIVII -1370-00003-1	7
	uF, +/- 10%, 35 V, -55 to 125 degC, 2-Pin				
T491D106K035AT	SMD, RoHS, Tape and Reel	C5	KEMT-T491-D_L	CMP-2000-07580-1	1
	CAP 1uF 16V ±5% 0603 (1608 Metric) Thickness				
CAP 1uF 16V 0603(1608)	1mm SMD CAP 100nF 25V ±20%	C6, C7, C8	CAPC0603(1608)100_N	CMP-1035-02736-1	3
CAP 100nF 25V 0603(1608)	0603 (1608 Metric) Thickness 1mm SMD	C9, C10, C11, C12, C13, C14, C15	CAPC0603(1608)100_N	CMP-1035-02589-1	7
0.1uF	0805 (2012 Metric) Chip Capacitor	C15	CAPC0805(2012)145_L	CMP-1590-00003-1	1
CAP 4.7uF 10V	CAP 4.7uF 10V ±20% 0603 (1608 Metric)				
0603(1608)	Thickness 1mm SMD	C16	CAPC0603(1608)100_M	CMP-1035-02787-1	1
	CAP 2.2uF 16V ±20%				
CAP 2.2uF 16V 0603(1608)	0603 (1608 Metric) Thickness 0.55mm SMD	C17, C18	CAPC0603(1608)55_L	CMP-1035-02764-1	2
100nF	0805 (2012 Metric) Chip Capacitor	C24	CAPC0805(2012)145_L	CMP-1590-00003-1	1
10uF	0805 (2012 Metric) Chip Capacitor	C25	CAPC0805(2012)145_L	CMP-1590-00003-1	1
LTST-C171AKT	LED AMBER CLR THIN 0805 SMD	D1, D3	LTST-C171AKT_V	CMP-1674-00004-3	2
LTST-C170GKT	LED GREEN CLEAR 0805 SMD	D2	LTST-C170GKT_V	CMP-1674-00002-2	1
Stack Headers	JD	J1, J2	SSW-105	Stack Headers	2
Stack Headers		J3, J4	TSW-105	Stack Headers	2
Program-Debug	High Performance	J5	SSW_Double_Header	Program-Debug	1
IM69D120	MEMS microphone utilizing PDM	MK1	M69D120	IM69D120	1
	, ,	R1, R2, R6, R13, R14, R15, R16, R17, R18,			
	0603 (1608 Metric) Chip	R19, R20, R21, R22,			
49.9R	Resistor	R23, R24, R25, R26, R27, R28	RESC0603(1608)_L	CMP-1591-00001-1	19
	Chip Resistor, 2.2 KOhm, +/- 5%, 0.1 W, -				
	55 to 155 degC, 0603 (1608 Metric), RoHS,		RESC1608X55X25LL10T1		
RC0603JR-072K2L	Tape and Reel 4K87 0.1W 1% 0603	R3, R4, R5, R7, R9, R10	5	CMP-2000-06957-1	6
4K87 1% 0603(1608)	(1608 Metric) SMD 510R 0.1W 5% 0603	R8	RESC0603(1608)_N	CMP-1012-00588-1	1
510R 5% 0603(1608)	(1608 Metric) SMD 100K 0.1W 5% 0603	R11	RESC0603(1608)_L	CMP-1012-00067-1	1
100K 5% 0603(1608)	(1608 Metric) SMD	R12	RESC0603(1608)_N	CMP-1012-00122-1	1
7K5	0805 (2012 Metric) Chip Resistor	R29	RESC0805(2012)_L	CMP-1591-00002-1	1
5k	0805 (2012 Metric) Chip Resistor	R30, R33	RESC0805(2012)_L	CMP-1591-00002-1	2
20k	0805 (2012 Metric) Chip Resistor	R31	RESC0805(2012)_L	CMP-1591-00002-1	1
100R	0805 (2012 Metric) Chip Resistor	R31	RESC0805(2012)_L	CMP-1591-00002-1	1
10K	0805 (2012 Metric) Chip Resistor	R32, R34	RESC0805(2012)_L	CMP-1591-00002-1	2
	100K 0.1W 5% 0603				2
300R 5% 0603(1608)	(1608 Metric) SMD	R35, R36, R39	RESC0603(1608)_N	CMP-1012-00122-1	3
	Ultra-Small Tactile Switch, 0.05 A, 12 V, -25				
B3U-1000P	to 70 degC, 2-Pin SMD, RoHS, Tape and Reel	SW1	OMRON-B3U-1000_V	CMP-2100-03586-1	1
	PHYTER® Industrial Temperature Single				
	Port 10/100 Mb/s Ethernet Physical Layer				
	Transceiver, 48-pin LQFP, Pb-Free, 1000				
DP83848IVVX/NOPB	Reel ARM Cortex-M4 32-bit	U1	PT0048A_L	CMP-0058-01357-3	1
	MCU+FPU, 210 DMIPS, 1024 kB Flash, 192 kB				
	Internal RAM, 82 I/Os,				
STM32F407VGT6U	100-pin LQFP, -40 to 85 degC, Tray	U2	STM-LQFP100_V	CMP-0243-00032-2	1
	1A, Low Drop Positive Voltage Regulator,				
LD1117AS33TR	3.3V, 4-Pin SOT-223, Tape and Reel	U3	SOT-223_M	CMP-0244-00316-1	1
	Low Voltage, Rail-to- Rail Operational				
	Amplifier, 1.8 to 12 V, - 40 to 105 degC, 8-Pin				
MC33201D	SOIC, Tube	U4	ONSC-SOIC-8-751-07_V	CMP-1310-00330-1	1
	Low Profile Surface Mount Microprocessor				
	Crystal, 25 MHz +/-30 ppm, 180 Ohm, -40 to				
ABLS-25.000MHZ-B4-F-	85 degC, 2-Pin 11.4 x 4.7 x 3.3 mm SMD,				
T	RoHS, Tape and Reel	X1, X2	ABRA-ABLS2-2_V	CMP-0277-00002-1	2