



Cyber Incident Response

The following is a sample cyber incident report. The report is a detailed example of the information that will be used to track and report incidents.

Contact information			
First Name:	Ghusun	Email:	ghsw5594@gmail.com
Last Name:	Hussam aldubayk	Phone Number:	0505212706
Job title:	Incident Response Analyst (Trainee)	Report Date:	15\7\2026
General information about the incident			
Title:	Outbound connection to a malware Command & Control (C2) server (crypto wallet stealer)	Category:	Malware / Information-Stealer (C2 Communication) Date - Time of incident: Captured within sample network traffic file Example.pcap
Date - Time of incident:	15\7\2026	Type	Data Exfiltration / Malware Beacon (Crypto Stealer)
Date/Time of Incident Discovery:	Discovered during traffic analysis using Wireshark	Source of the incident:	• Internal
Incident Summary			

Include analyst observations here...

Analysis of Example.pcap using Wireshark identified an HTTP POST request from internal host 10.41.30.54 to external IP 37.220.87.68 on port 80. The request used an unusual User-Agent string ([unusual-agent-string]) and sent a machineld and configld, consistent with a malware check-in beacon to a Command & Control (C2) server. The server responded with a large configuration file listing dozens of cryptocurrency wallet browser extensions (MetaMask, TronLink, Coinbase, Trust Wallet, etc.), wallet application folders (Exodus, Electrum, Ledger Live, Atomic, etc.), Telegram/Discord data paths, and rules for grabbing files from the Desktop and Documents folders. The configuration also contained loader URLs instructing the infected host to download additional executables (Clip1.exe and bebra.exe)



from external servers. A follow-up request to download a file named nss3.dll from the same C2 server was blocked by network security policy (HTTP 503 - File Transfer Blocked).

Results and associated risks

Include analyst observations here...

This traffic pattern matches known behavior of an information-stealer/clipper malware family that specifically targets cryptocurrency wallets, browser extension credentials, and messaging app data. If not blocked, this malware could have exfiltrated sensitive financial data, private keys, and personal files, and could have downloaded additional malicious payloads onto the host. The successful block of the .dll download suggests network security controls partially mitigated the incident, but the initial C2 beacon (POST request) was not blocked, meaning the infected host was actively communicating with the attacker's server.

Recommendations/Comments

Include analyst observations here...

- 1) Isolate host 10.41.30.54 from the network immediately and perform a full malware scan.
- 2) Block the C2 IP addresses (37.220.87.68, 37.220.87.61, 77.73.134.35) at the firewall/proxy level.
- 3) Investigate how the initial infection occurred (e.g., phishing email, malicious download) and check other hosts for similar indicators of compromise (IOCs).
- 4) Advise the affected user to consider any cryptocurrency wallets, browser-saved passwords, or Telegram/Discord accounts on that machine as potentially compromised, and rotate credentials.
- 5) Add detection rules for the unusual User-Agent string [unusual-agent-string] the observed C2 domains/IPs to network monitoring tools.