

Java Stream

Object–Oriented Programming



SoftEng
<http://softeng.polito.it>

Version 2.2.2

© Marco Torchiano, 2025



Licensing Note



This work is licensed under the Creative Commons Attribution–NonCommercial–NoDerivatives 4.0 International License.

To view a copy of this license, visit

<http://creativecommons.org/licenses/by-nc-nd/4.0/>.

You are free: to copy, distribute, display, and perform the work

Under the following conditions:



- **Attribution.** You must attribute the work in the manner specified by the author or licensor.



- **Non-commercial.** You may not use this work for commercial purposes.



- **No Derivative Works.** You may not alter, transform, or build upon this work.
 - For any reuse or distribution, you must make clear to others the license terms of this work.
 - Any of these conditions can be waived if you get permission from the copyright holder.

— Your fair use and other rights are in no way affected by the above.

Stream

A **sequence** of elements from a **source** that supports data processing **operations**.

- ◆ Operations are defined by means of behavioral parameterization
 - Basic features:
 - ◆ Pipelining
 - ◆ Internal iteration:
 - no explicit loops statements
 - ◆ Lazy evaluation (*pull*):
 - no work until a terminal operation is invoked
-

Pipelining


```
Stream.of("All", "along", ...)
```

Source

Intermediate

Intermediate

Terminal



```
.map(String::toLowerCase)
```

```
.limit(4)
```

```
.forEach(System.out::println);
```

External vs. Internal iteration

```
for( word : lyrics) {  
    out.println(word) ;  
}
```

■ External

- ◆ Mixes **how** and **what**
- ◆ Fine grained control
- ◆ Multiple iterations

```
Lyrics.forEach(  
    out::println  
) ;
```

■ Internal

- ◆ Focuses on **what**
 - ◆ More concise code
 - ◆ Less error prone
 - ◆ Transparent optimization
-

Reminder: functional interfaces

- An interface with exactly one method
 - The semantics is purely **functional**
 - ♦ The result of the method depends solely on the arguments
 - ♦ There are no side-effects on attributes
 - Can be implemented as lambda expressions
 - Predefined interfaces are defined in
 - ♦ `java.util.function`
-

Lazy evaluation

- Stream pipelines are built first
 - ♦ without performing any processing
 - Then executed
 - ♦ In response to a terminal operation
 - **Supplier<T>** is used to delay creation of objects until when required, e.g.:
 - ♦ Supplier argument in `collect` is a factory object as opposed to passing an already created accumulating object
-

Common Functional Interfaces

Interface	Method
<code>Function <T,R></code>	<code>R apply(T t)</code>
<code>BiFunction <T,U,R></code>	<code>R apply(T t, U u)</code>
<code>BinaryOperator <T></code>	<code>T apply(T t, T u)</code>
<code>UnaryOperator <T></code>	<code>T apply(T t)</code>
<code>Predicate <T></code>	<code>boolean test(T t)</code>
<code>Consumer <T></code>	<code>void accept(T t)</code>
<code>BiConsumer <T,U></code>	<code>void accept(T t, U u)</code>
<code>Supplier <T></code>	<code>T get()</code>

Primitive specializations

- Functional interfaces handle references
 - Specialized versions are defined for primitive types (`int`, `long`, `double`, `boolean`)
 - Functions: `ToTypeFunction`
`Type1ToType2Function`
 - Suppliers: `TypeSupplier`
 - Predicate: `TypePredicate`
 - Consumer: `TypeConsumer`
-

Source operations

Operation	Args	Purpose
static <code>Arrays.stream</code>	<code>T[]</code>	Returns a stream from an array
default <code>Collection.stream</code>	-	Returns a stream from a collection
static <code>Stream.of</code>	<code>T...</code>	Creates a stream from the list of arguments or array

Stream source

- Arrays

- ◆ `Stream<T> stream()`

```
String[] s={"One", "Two", "Three"};  
Arrays.stream(s)  
        .forEach(System.out::println);
```

- Stream `of`

- ◆ `static Stream<T> of(T... values)`

```
Stream.of("One", "Two", "Three").  
        forEach(System.out::println);
```

Stream source

- Collection

- ◆ `Stream<T> stream()`

```
Collection<String> coll =  
    Arrays.asList("One", "Two", "Three");  
coll.stream().  
    forEach(System.out::println);
```

Source generation in Stream

Operation	Args	Purpose
<code>generate()</code>	<code>Supplier<T> s</code>	Elements are generated by calling <code>get()</code> method of the supplier
<code>iterate()</code>	<code>T seed,</code> <code>UnaryOperator<T> f</code>	Starts with the seed and computes next element by applying operator to previous element
<code>empty()</code>		Returns an empty stream

Stream source generation

- Generate elements using a **Supplier**

```
Stream.generate(  
    () -> Math.random() * 10 )
```

- Generate elements from a seed

```
Stream.iterate( 0,  
    (prev) -> prev + 2 )
```

- ◆ Warning: they generate **infinite** streams
-

Numeric streams

- Provided for basic numeric types
 - ◆ `DoubleStream`
 - ◆ `IntStream`
 - ◆ `LongStream`
 - Conversion methods from `Stream<T>`
 - ◆ `mapToX()`
 - Generator method: `range(start, end)`
 - New terminal operations e.g. `average()`
 - More efficient: no boxing and unboxing
-

Numeric streams

24 ns per element

```
IntStream seq = IntStream.generate(  
    () -> (int) (Math.random() * 100)) ;  
int max = seq.limit(10).max().getAsInt() ;
```

30 ns per element

```
Stream<Integer> seq = Stream.generate(  
    () -> (int) (Math.random() * 100)) ;  
int max = seq.limit(10)  
    .max(naturalOrder()) .get() ;
```

~ 6ns for boxing + unboxing

Sample Classes

```
class Student {  
    Student(int id, String n, String s) { }  
    String getFirst() { }  
    boolean isFemale() { }  
    Collection<Course> enrolledIn() { }  
}
```

```
class Course {  
    String getTitle() {}  
}
```

Intermediate operations

Return type	Operation	Arg. type	Ex. argument
Stream<T>	filter	Predicate<T>	T -> boolean
Stream<T>	limit	int	
Stream<T>	skip	int	
Stream<T>	sorted	<i>optional</i> Comparator<T>	(T, T) -> int
Stream<T>	distinct	-	
Stream<R>	map	Function<T, R>	T -> R

Basic filtering

- `default Stream<T> distinct()`
 - ♦ Discards duplicates
 - `default Stream<T> limit(int n)`
 - ♦ Retains only first n elements
 - `default Stream<T> skip(int n)`
 - ♦ Discards the first n elements
-

Advanced Filtering

- default `Stream<T> filter(Predicate<T>)`
 - ◆ Accepts as predicate
 - boolean method reference

```
oopClass.stream().  
    filter(Student::isFemale).  
    forEach(System.out::println);
```

- lambda

```
oopClass.stream().  
    filter(s->s.getFirst().equals("John")).  
    forEach(System.out::println);
```

Sorting

- `default Stream<T> sorted()`
 - ♦ Sorts the elements of the stream
 - ♦ Either in natural order

```
oopClass.stream().  
    sorted().  
    forEach(System.out::println);
```

- ♦ or with comparator

```
oopClass.stream().  
    sorted(comparingInt(Student::getId)).  
    forEach(System.out::println);
```

Mapping

- `default Stream<R>`

- `map (Function<T, R> mapper)`

- ◆ Transforms each element of the stream using the mapper function

```
oopClass.stream().
```

```
    map (Student::getFirst).
```

```
    forEach (System.out::println);
```

Mapping to primitive streams

- Defined for the main primitive types:

`IntStream mapToInt(ToIntFunction<T> mapper)`

`LongStream mapToLong(ToLongFunction<T> m)`

`DoubleStream mapToDouble(ToDoubleFunction<T>m)`

- ♦ Improve efficiency

```
oopClass.stream() .  
    map(Student::getFirst) .  
    mapToInt(String::length) .  
    forEach(System.out::println) ;
```

Flat mapping

- Context:
 - ◆ Stream elements are containers (e.g. List)
 - Or elements are mapped to containers
 - Problem:
 - ◆ Processing should be applied to all elements inside those containers
 - Solution:
 - ◆ Use the `flatMap()` method
-

Flat mapping

`<R> Stream<R>`

`flatMap(Function<T, Stream<R>> mapper)`

- ◆ Extracts a stream from each incoming stream element
 - ◆ Concatenate together the resulting streams
 - Typically
 - ◆ `T` is a `Collection<R>` (or a derived type)
 - ◆ `mapper` can be `Collection::stream`
-

Flat mapping

- `<R> Stream<R> flatMap (`
`Function<T, Stream<R>> mapper)`

```
oopClass.stream().
```

Stream<Student>

```
map(Student::enrolledIn).
```

Stream<Collection<Course>>

```
flatMap(Collection::stream).
```

```
distinct().
```

Stream<Course>

```
map(Course::getTitle).
```

Stream<String>

```
foreach(System.out::println);
```

Terminal Operations

Operation	Return	Purpose
<code>findAny()</code>	<code>Optional<T></code>	Returns the first element (order does not count)
<code>findFirst()</code>	<code>Optional<T></code>	Returns the first element (order counts)
<code>min()</code> / <code>max()</code>	<code>Optional<T></code>	Finds the min/max element based on the comparator argument
<code>count()</code>	<code>long</code>	Returns the number of elements in the stream
<code>forEach()</code>	<code>void</code>	Applies the Consumer function to all elements in the stream

Terminal Operation – Predicate

Operation	Return	Purpose
<code>anyMatch()</code>	<code>boolean</code>	Checks if any element in the stream matches the predicate
<code>allMatch()</code>	<code>boolean</code>	Checks if all the elements in the stream match the predicate
<code>noneMatch()</code>	<code>boolean</code>	Checks if none element in the stream match the predicate

Kinds of Operations

- **Stateless** operations
 - ◆ No internal storage is required
 - E.g. map, filter
 - **Stateful** operations
 - ◆ Require internal storage, can be
 - **Bounded**: require a fixed amount of memory
 - E.g. reduce, limit
 - **Unbounded**: require unlimited memory
 - E.g. sorted, collect
-

Terminal operations


Operation	Arguments	Purpose
<code>reduce()</code>	<code>T,</code> <code>BinaryOperator<T></code>	Reduces the elements using an identity value and an associative merge operator
<code>collect()</code>	<code>Collector<T,A,R></code>	Reduces the stream to create a collection such as a List, a Map, or even an Integer.

Reducing

- `T reduce(T identity, BinaryOperator<T> merge)`
 - ♦ Reduces the elements of this stream, using the provided identity value and an associative merge function

```
int m=oopClass.stream().  
    map(Student::getFirst).  
    map(String::length).  
    reduce(0,Math::max);
```

Reducing



reduce (0 , Math :: max)

Ought to be the
identity operand w.r.t.
the merge operator


Parallel streams

```
IntStream.of(numbers)  
    .reduce(0, Math::max) ;
```

```
IntStream.of(numbers)  
    .parallel()  
    .reduce(0, Math::max) ;
```

Up to n times faster
(n = number of CPU cores)

Parallelized reduce




Collecting


- `Stream.collect()` takes as argument a recipe for accumulating the elements of a stream into a summary result.
 - ♦ It is a stateful operation

```
class Acc { int n; }  
int s = Stream.of(numbers) .  
    collect(Acc::new,           // supplier  
            (a,i) -> a.n+=i,    // accumulator  
            (a1,a2) -> a1.n+=a2.n // combiner  
    ) .n;
```


Collecting




Collecting



Collecting




Collecting



Collecting example

```
List<Integer> n = Stream.of(numbers) .  
collect(LinkedList::new, // supplier  
        List::add,        // accumulator  
        List::addAll);    // combiner
```


Collecting



Collect vs. Reduce

- Reduce
 - ◆ Is bounded
 - ◆ The merge operation can be used to combine results from parallel computation threads
 - Collect
 - ◆ Is unbounded
 - ◆ Combining results from parallel computation threads can be performed with the combiner
-

Java Stream API

PREDEFINED COLLECTORS

Predefined collectors

- Predefined recipes are returned by static methods in **Collectors** class

- ◆ Method are easier to access through:

```
import static java.util.stream.Collectors.*;
```

```
double averageWord = Stream.of(txta)  
    .collect(averagingInt(String::length));
```

Summarizing Collectors

Collector	Return	Purpose
<code>counting()</code>	<code>long</code>	Count number of elements in stream
<code>maxBy()</code> / <code>minBy()</code>	<code>T</code> (elements type)	Find the min/max according to given Comparator
<code>summingType()</code>	<i>Type</i>	Sum the elements
<code>averagingType()</code>	<i>Type</i>	Compute arithmetic mean
<code>summarizingType()</code>	<i>Type</i> Summary-Statistics	Compute several summary statistics from elements

Type can be `Int`, `Long`, or `Double`

Accumulating Collectors

Collector	Return	Purpose
<code>toList()</code>	<code>List<T></code>	Accumulates into a new <code>List</code>
<code>toSet()</code>	<code>Set<T></code>	Accumulates into a new <code>Set</code> (i.e. discarding duplicates)
<code>toCollection (Supplier<> cs)</code>	<code>Collection<T></code>	Accumulate into the collection provided by given <code>Supplier</code>
<code>joining()</code>	<code>String</code>	Concatenates into a <code>String</code> Optional arguments: separator, prefix, and postfix

Group container collectors

- ◆ Returns the three longest words in text:

```
List<String> longestWords = Stream.of(txta)
    .filter( w -> w.length()>10)
    .distinct()
    .sorted(comparing(String::length).reversed())
    .limit(3)
    .collect(toList());
```



What if two words share the 3rd position?

Grouping Collectors


Collector	Return	Purpose
groupingBy (Function<T,K> classifier)	Map<K, List<T>>	Map according to the key extracted (by classifier) and add to list. Optional arguments: <ul style="list-style-type: none">- Downstream Collector (nested)- Map factory supplier
partitioningBy (Predicate<T> p)	Map<Boolean, List<T>>	Split according to partition function (p) and add to list. Optional arguments: <ul style="list-style-type: none">- Downstream Collector (nested)- Map supplier

Example: grouping collectors


- Grouping by feature

```
Map<Integer,List<String>> byLength =  
    Stream.of(txta).distinct()  
        .collect(groupingBy(String::length));
```


Grouping Collector




Grouping Collector



Grouping Collector



Grouping Collector



Example: grouping collectors

- Sorted grouping by feature

```
Map<Integer,List<String>> byLength =  
Stream.of(txta).distinct()  
.collect(groupingBy(String::length,  
    () -> new TreeMap<>(reverseOrder()),  
    toList()))
```



Map sorted by descending length

Example: grouping collectors

- Grouping and counting

```
Map<String,Long> frequency =  
Stream.of(txta)  
.collect(groupingBy(  
    w->w,  
    counting()));
```

Grouped by word

Downstream is counting

Example: grouping collectors

- Stream of map entries:

```
List<String> freqSorted =  
Stream.of(txta)  
  .collect(groupingBy(w->w, counting()))  
  .entrySet().stream()  
  .sorted(  
    comparing(Map.Entry<String, Long>::getValue)  
    .reversed()  
    .thenComparing(Map.Entry::getKey)  
  )  
  .map(e -> e.getValue() + ":" + e.getKey())  
  .collect(toList());
```

Collector Composition

Collector	Purpose
collectingAndThen <code>(Collector<T,?,R> cltr, Function<R,RR> mapper)</code>	Apply a transformation (mapper) after performing collection (cltr)
mapping <code>(Function<T,U> mapper, Collector<U,?,R> cltr)</code>	Performs a transformation (mapper) before applying the collector (cltr)

Example: grouping collectors

- Re-open the map entry set:

```
List<String> longestWords =  
Stream.of(txta).distinct()  
.collect(collectingAndThen(  
    groupingBy(String::length,  
        () -> new TreeMap<>(reverseOrder()),  
        toList())  
    ,  
    m -> m.entrySet().stream()  
        .limit(3)  
        .flatMap(e -> e.getValue().stream())  
        .collect(toList()) );
```

collecting

and then

Example: collecting and then

- Stream of map entries:

```
Stream.of(txta)
```

```
.collect(collectingAndThen(
```

```
    groupingBy(w->w, counting())
```

collecting

```
,
```

```
    m->m.entrySet().stream()
```

and then

```
        .sorted(comparing(Map.Entry::getValue)
```

```
        .map(e->e.getValue() + ":" + e.getKey())
```

```
        .collect(toList())))
```

Example: mapping

- Stream of map entries:

```
Stream.of(txta)
  .collect(collectingAndThen(
    groupingBy( w->w, counting())
    ,
    m->m.entrySet().stream()
      .collect(groupingBy(
        Map.Entry::getValue,
        mapping(Map.Entry::getKey,
          toList())))) );
```

CUSTOM COLLECTORS

Collector

T : element

A : accumulator

```
interface Collector<T,A,R>{
```

```
    Supplier<A> supplier()
```

- Creates the accumulator container

```
    BiConsumer<A,T> accumulator();
```

- Adds a new element into the container

```
    BinaryOperator<A> combiner();
```

- Combines two containers (used for parallelizing)

Operator, not
consumer!

```
    Function<A,R> finisher();
```


- Performs a final transformation step

```
    Set<Characteristics> characteristics();
```


- Capabilities of this collector

```
}
```

Collecting



Collector.of

```
static Collector<T,A,R> of(  
    Supplier<A> supplier,  
    BiConsumer<A,T> accumulator,  
    BinaryOperator<A> combiner,  
    Function<A,R> finisher,  optional  
    Characteristic... characts)
```

- ◆ More compact than extending the interface `Collector`
-


Collector.of

```
Collector<String,List<String>,List<String>>  
toList = Collector.of( supplier  
    ArrayList::new,  
    List::add, accumulator  
    (a,b)->{a.addAll(b);return a;}  
);
```

combiner

Implicit finisher => identity transformation
No characteristics

Collector



```
collect (Collector.of (
  ArrayList::new,
  List::add,
  (a,b) -> {a.addAll (b) ;
              return a ;}))
```

Collector example

- More compact form:

```
String listOfWords = Stream.of(txta)
    .map(String::toLowerCase)
    .distinct()
    .sorted(comparing(String::length).reversed())
    .collect(Collector.of(
        ArrayList::new,
        List::add,
        (a,b) -> { a.addAll(b); return a; },
        List::toString));
```

supplier

accumulator

combiner

finisher

Characteristics

- **IDENTITY_FINISH**

- ◆ Finisher function is the identity function therefore it can be elided

- **CONCURRENT**

- ◆ Accumulator function can be called concurrently on the same container

- **UNORDERED**

- ◆ The operation does require stream elements order to be preserved
-

Characteristics

- Characteristics can be used to optimize execution
 - If both **CONCURRENT** and **UNORDERED**, then, when operating in parallel,
 - ◆ Accumulator method is invoked concurrently by several threads
 - ◆ Combiner is not used
-

Collector and accumulator

- Collector used to compute the average length of a stream of String
 - ♦ Uses the **AverageAcc** accumulator object

```
Collector<Integer, AverageAcc, Double>
avgCollector = Collector.of(
    AverageAcc::new,          // supplier
    AverageAcc::addWord,     // accumulator
    AverageAcc::merge,       // combiner
    AverageAcc::average      // finisher
);
```

Average Accumulator

```
class AverageAcc {  
    private long length;  
    private long count;  
    public void addWord(String w) {  
        this.length+=w.length(); // accumulator  
        count++; }  
    public double average() { // finisher  
        return length*1.0/count; }  
    public AverageAcc merge(AverageAcc o) {  
        this.length+=other.length;  
        this.count+=other.count; // combiner  
        return this;  
    }  
}
```


EXCEPTIONS AND FUNCTIONAL INTERFACES

Exceptions and Functional If.

- Functional interfaces largely used in Stream API do not include exceptions
 - Lambdas and method reference are not allowed to throw (checked) exceptions
 - ◆ This is mainly due to the intermediate code that does not handle exceptions
 - ◆ Unchecked exceptions works as usual and interrupt the stream processing
-

Exceptions in streams

```
Stream.of("1", "2", "B", "6", "30")  
  .mapToInt( s -> convert(s) )  
  .sum();
```



Unhandled exception

```
static int convert(String s)  
    throws NotANumber {  
    try { return Integer.parseInt(s);  
    } catch (NumberFormatException e) {  
        throw new NotANumber(e);  
    }  
}
```

Exception & streams: remedies

- Bury the exception:
 - ◆ catch the exception and ignore it
 - Wrap the exception
 - ◆ use `RuntimeException` pointing to the original one
 - Sneaky exceptions
 - ◆ throw as unchecked (using a trick)
 - Annotate the results
-

Bury the exception

```
Stream.of("1", "2", "B", "6", "30")
    .mapToInt( s -> {
        try{ return convert(s); }
        catch (NotANumber e)
        { return 0; }
    })
    .sum();
```

No exception is thrown. Just uses 0 when a parsing error occurs

Wrap the exception

```
Stream.of("1", "2", "B", "6", "30")  
    .mapToInt( s -> {  
        try{ return convert(s); }  
        catch(NotANumber e)  
        {throw new RuntimeException(e); }  
    })  
    .sum();
```



A RuntimeException is thrown
whose cause is the NotANumber

Sneakily throw the exception

```
Stream.of("1", "2", "B", "6", "30")  
    .mapToInt( s -> {  
        try{ return convert(s); }  
        catch (NotANumber e)  
        { sneakyThrow(e);  
          return -1; } })  
    .sum();
```

Never executed but
required for syntax
reasons

A `NotANumber` is thrown but the
compiler does not complain

Sneaky throw method

- Using generics type erasure it is possible to “unchecked” an exception

Replaced by RuntimeException

```
static <E extends Throwable>  
void sneakyThrow(  
    Exception exception) throws E {  
    throw (E)exception;  
}
```

Due to type erasure the cast is never applied in practice

Summary

- Streams provide a powerful mechanism to express computations of sequences of elements
 - The operations are optimized and can be parallelized
 - Operations are expressed using a functional notation
 - ◆ More compact and readable w.r.t. imperative notation
-