

# Quant II

## Lab 9: RDD

Giacomo Lemoli

April 6, 2023

# Today's plan

- RDD implementation: local regression approach
- Material from [Cattaneo, Idrobo, and Titiunik \(2020\)](#)
- packages: `rdrobust`, `rddensity`, `rdlocrand` (available in both Stata and R format)
- Next week
  - Extensions: fuzzy RDD, local randomization approach
  - Topics in RDD: GRDD, Diff-in-disc etc

# Working example: Meyersson (2014)

*Econometrica*, Vol. 82, No. 1 (January, 2014), 229–269

## ISLAMIC RULE AND THE EMPOWERMENT OF THE POOR AND PIOUS

BY ERIK MEYERSSON<sup>1</sup>

Does Islamic political control affect women's empowerment? Several countries have recently experienced Islamic parties coming to power through democratic elections. Due to strong support among religious conservatives, constituencies with Islamic rule often tend to exhibit poor women's rights. Whether this reflects a causal relationship or a spurious one has so far gone unexplored. I provide the first piece of evidence using a new and unique data set of Turkish municipalities. In 1994, an Islamic party won multiple municipal mayor seats across the country. Using a regression discontinuity (RD) design, I compare municipalities where this Islamic party barely won or lost elections. Despite negative raw correlations, the RD results reveal that, over a period of six years, Islamic rule increased female secular high school education. Corresponding effects for men are systematically smaller and less precise. In the longer run, the effect on female education remained persistent up to 17 years after, and also reduced adolescent marriages. An analysis of long-run political effects of Islamic rule shows increased female political participation and an overall decrease in Islamic political preferences. The results are consistent with an explanation that emphasizes the Islamic party's effectiveness in overcoming barriers to female entry for the poor and pious.

KEYWORDS: Political Islam, regression discontinuity, education.

Causal effects of interest:

- Victory of Islamic candidate on educational attainment of women

Elements:

- **Outcome (Y)**: percentage of women aged 15-20 in 2000 who had completed high school by 2000

Causal effects of interest:

- Victory of Islamic candidate on educational attainment of women

Elements:

- **Outcome (Y)**: percentage of women aged 15-20 in 2000 who had completed high school by 2000
- **Running variable (X)**: vote percentage of the Islamic party minus vote percentage of the strongest secular opponent

Causal effects of interest:

- Victory of Islamic candidate on educational attainment of women

Elements:

- **Outcome (Y)**: percentage of women aged 15-20 in 2000 who had completed high school by 2000
- **Running variable (X)**: vote percentage of the Islamic party minus vote percentage of the strongest secular opponent
- **Treatment (T)**: 1 if Islamic party won in 1994, 0 otherwise

# Set-up

```
library(rdrobust); library(rddensity); library(haven)

# Import data and define variables
data <- read_dta("CIT_2019_Cambridge_polecon.dta")

Y <- data$Y
X <- data$X
T <- data$T
T_X <- T*X
```






# Visualization

```
# Before we begin:
```

```
# ?rdplot
```

```
# Raw means comparison
```


```
rdplot(Y, X, nbins = c(2500, 500), p = 0, col.lines = "red", col.dots = "black", title = "",  
       x.label = "Islamic Margin of Victory", y.label = "Female High School Percentage", y.lim = c(0,70))
```



# Visualization

```
# Local means comparison
```

```
rdplot(Y[abs(X) <= 50], X[abs(X) <= 50], nbins = c(2500, 500), p = 4, col.lines = "red", col.dots = "black",  
       title = "", x.label = "Islamic Margin of Victory", y.label = "Female High School Percentage",  
       y.lim = c(0,70))
```



- It may be hard to spot visually discontinuities in raw data

# Binning

- It may be hard to spot visually discontinuities in raw data
- Common approach: binning to “smooth” the data

# Binning

- It may be hard to spot visually discontinuities in raw data
- Common approach: binning to “smooth” the data
- Split the raw data into segments (bins) of the running variable, compute the mean outcome in each bin

# Binning

- It may be hard to spot visually discontinuities in raw data
- Common approach: binning to “smooth” the data
- Split the raw data into segments (bins) of the running variable, compute the mean outcome in each bin
- Plot the mean outcome against the mid point of the bin

# Binning

- It may be hard to spot visually discontinuities in raw data
- Common approach: binning to “smooth” the data
- Split the raw data into segments (bins) of the running variable, compute the mean outcome in each bin
- Plot the mean outcome against the mid point of the bin
- Overlay global polynomial fit of the outcome on the running variable, estimated **separately** on each side of the cutoff and using the **raw data**

- It may be hard to spot visually discontinuities in raw data
- Common approach: binning to “smooth” the data
- Split the raw data into segments (bins) of the running variable, compute the mean outcome in each bin
- Plot the mean outcome against the mid point of the bin
- Overlay global polynomial fit of the outcome on the running variable, estimated **separately** on each side of the cutoff and using the **raw data**
- `rdrobust::rdplot` does it automatically




# Binning

Set bin size manually: evenly-spaced.

*# Default is 4th polynomial degree on each side*


```
rdplot(Y, X, nbins = c(20,20), binselect = "es", y.lim = c(0,25))
```



# Principled binning

Quantile-spaced bins: retain information about actual data distribution, reduce discretion


```
rdplot(Y, X, nbins = c(20,20), binselect = 'qs', x.label = 'Score',  
       y.label = 'Outcome', title = '', x.lim = c(-100,100), y.lim = c(0,25))
```



# Principled binning

Data-driven approach: minimize IMSE of local means estimator (optimize along bias-variance)


```
rdplot(Y, X, binselect = 'qs', x.label = 'Score',  
       y.label = 'Outcome', title = '', x.lim = c(-100,100), y.lim = c(0,25))
```



# Principled binning

Mimicking variance: choose number of bins so that the variability of means “mimicks” that of the raw data.

```
rdplot(Y, X, binselect = 'qsmv', x.label = 'Score',  
       y.label = 'Outcome', title = '', x.lim = c(-100,100), y.lim = c(0,25))
```



“Which method of implementation is most appropriate depends on the researcher’s particular goal, for example, illustrating/testing for the overall functional form versus showing the variability of the data. We recommend to start with MV bins to better illustrate the variability of the outcome as a function of the score, ideally comparing ES and QS bins to highlight the distributional features of the score. Then, if needed, the researcher can select the number of bins to be IMSE-optimal in order to explore the global features of the regression function.” (Cattaneo, Idrobo, and Titiunik 2020)

## Continuity-based framework

- If CEF functions are continuous at cutoff, RDD identifies a causal effect at cutoff

## Continuity-based framework

- If CEF functions are continuous at cutoff, RDD identifies a causal effect at cutoff
- In practice, observations never have the cutoff value

## Continuity-based framework

- If CEF functions are continuous at cutoff, RDD identifies a causal effect at cutoff
- In practice, observations never have the cutoff value
- Approximate CEF on both sides of cutoff



## Continuity-based framework

- If CEF functions are continuous at cutoff, RDD identifies a causal effect at cutoff
- In practice, observations never have the cutoff value
- Approximate CEF on both sides of cutoff
- Global approximations: good for plots (descriptions), not suitable for causal effect estimation: [Gelman and Imbens \(2019\)](#)

## Continuity-based framework

- If CEF functions are continuous at cutoff, RDD identifies a causal effect at cutoff
- In practice, observations never have the cutoff value
- Approximate CEF on both sides of cutoff
- Global approximations: good for plots (descriptions), not suitable for causal effect estimation: [Gelman and Imbens \(2019\)](#)
- Best current practice: local polynomial functions with low order near cutoff

Sharp RDD:

- Choose polynomial of order  $p$  and a kernel function  $K(\cdot)$

Sharp RDD:

- Choose polynomial of order  $p$  and a kernel function  $K(\cdot)$
- Choose a bandwidth  $h$  around the cutoff  $c$

# Estimation of causal effects

Sharp RDD:

- Choose polynomial of order  $p$  and a kernel function  $K(\cdot)$
- Choose a bandwidth  $h$  around the cutoff  $c$
- Estimate on each side of the cutoff a WLS regression with weights  $K(\frac{X_i - c}{h})$ :

# Estimation of causal effects

Sharp RDD:

- Choose polynomial of order  $p$  and a kernel function  $K(\cdot)$
- Choose a bandwidth  $h$  around the cutoff  $c$
- Estimate on each side of the cutoff a WLS regression with weights  $K(\frac{X_i - c}{h})$ :

# Estimation of causal effects

Sharp RDD:


- Choose polynomial of order  $p$  and a kernel function  $K(\cdot)$
- Choose a bandwidth  $h$  around the cutoff  $c$
- Estimate on each side of the cutoff a WLS regression with weights  $K(\frac{X_i - c}{h})$ :

$$\hat{Y}_i = \hat{\mu}_+ + \hat{\mu}_{+,1}(X_i - c) + \hat{\mu}_{+,2}(X_i - c)^2 + \dots + \hat{\mu}_{+,p}(X_i - c)^p$$

$$\hat{Y}_i = \hat{\mu}_- + \hat{\mu}_{-,1}(X_i - c) + \hat{\mu}_{-,2}(X_i - c)^2 + \dots + \hat{\mu}_{-,p}(X_i - c)^p$$

- Calculate the sharp RD estimate:  $\hat{\tau}_{SRD} = \hat{\mu}_+ - \hat{\mu}_-$ , the difference of the two functions when  $X_i = c$

# Estimation of causal effects





## Relevant parameters

- **Kernel:** triangular one is recommended (weight = 0 outside  $h$  and  $\uparrow$  as we get closer to  $c$ ) and default in `rdrobust`. Alternatives: Uniform and Epanechnikov

## Relevant parameters

- **Kernel:** triangular one is recommended (weight = 0 outside  $h$  and  $\uparrow$  as we get closer to  $c$ ) and default in `rdrobust`. Alternatives: Uniform and Epanechnikov
- **Bandwidth:** the most important thing. Usually chosen by a data-driven approach to minimize the MSE of the local polynomial point estimator

## Relevant parameters

- **Kernel:** triangular one is recommended (weight = 0 outside  $h$  and  $\uparrow$  as we get closer to  $c$ ) and default in `rdrobust`. Alternatives: Uniform and Epanechnikov
- **Bandwidth:** the most important thing. Usually chosen by a data-driven approach to minimize the MSE of the local polynomial point estimator
- `rdrobust:rdbwselect` selects a variety of optimal bandwidths. Either stand-alone or called from inside `rdrobust` using the option `bwselect`

## Relevant parameters

- **Kernel:** triangular one is recommended (weight = 0 outside  $h$  and  $\uparrow$  as we get closer to  $c$ ) and default in `rdrobust`. Alternatives: Uniform and Epanechnikov
- **Bandwidth:** the most important thing. Usually chosen by a data-driven approach to minimize the MSE of the local polynomial point estimator
- `rdrobust:rdbwselect` selects a variety of optimal bandwidths. Either stand-alone or called from inside `rdrobust` using the option `bwselect`
- **Polynomial order:** low to avoid overfitting, generally local linear is the default choice

# Estimation

```
# By default c = 0
out <- rdrobust(Y, X, kernel = "uniform", p = 1, h = 20)
summary(out)
```

```
## Call: rdrobust
##
## Number of Obs.      2629
## BW type           Manual
## Kernel             Uniform
## VCE method         NN
##
## Number of Obs.      2314      315
## Eff. Number of Obs.    608      280
## Order est. (p)         1         1
## Order bias (q)         2         2
## BW est. (h)          20.000     20.000
## BW bias (b)          20.000     20.000
## rho (h/b)            1.000     1.000
## Unique Obs.          2311      315
##
## =====
##      Method      Coef. Std. Err.      z    P>|z|      [ 95% C.I. ]
## =====
## Conventional    2.927    1.235    2.371    0.018    [0.507 , 5.347]
## Robust          -        -    1.636    0.102    [-0.582 , 6.471]
## =====
```


# Estimation

```
# Choose h to minimize MSE
out <- rdrobust(Y, X, kernel = "triangular", p = 1, bwselect = "mserd")
summary(out)
```

```
## Call: rdrobust
##
## Number of Obs.          2629
## BW type            mserd
## Kernel              Triangular
## VCE method          NN
##
## Number of Obs.          2314          315
## Eff. Number of Obs.      529          266
## Order est. (p)              1              1
## Order bias (q)              2              2
## BW est. (h)          17.240          17.240
## BW bias (b)          28.576          28.576
## rho (h/b)            0.603          0.603
## Unique Obs.          2311          315
##
## =====
##      Method      Coef. Std. Err.      z    P>|z|      [ 95% C.I. ]
## =====
## Conventional      3.020      1.427      2.116    0.034    [0.223 , 5.816]
## Robust             -        -      1.776    0.076    [-0.309 , 6.276]
## =====
```

# Illustrate the main effect

```
bw <- out$bws[1,1]
rdplot(Y[abs(X)<=bw], X[abs(X)<=bw], p = 1, kernel = 'triangular',
       x.label = 'Score', y.label = 'Outcome', title = '', y.lim = c(10,22))
```



- Local polynomial function may be biased



- Local polynomial function may be biased
- Take into account the bias when making inference

- Local polynomial function may be biased
- Take into account the bias when making inference
- One can:

- Local polynomial function may be biased
- Take into account the bias when making inference
- One can:
- Estimate the bias and remove it from the derivation of confidence interval

- Local polynomial function may be biased
- Take into account the bias when making inference
- One can:
- Estimate the bias and remove it from the derivation of confidence interval
- Incorporate extra variability from bias removal in the SE estimate

Table 3: Local Polynomial Confidence Intervals

	Centered at	Standard Error
Conventional: $\text{CI}_{\text{us}}$	$\hat{\tau}_{\text{SRD}}$	$\sqrt{\hat{\mathcal{V}}}$
Bias-Corrected: $\text{CI}_{\text{bc}}$	$\hat{\tau}_{\text{SRD}} - \hat{\mathcal{B}}$	$\sqrt{\hat{\mathcal{V}}}$
Robust bias-corrected: $\text{CI}_{\text{rbc}}$	$\hat{\tau}_{\text{SRD}} - \hat{\mathcal{B}}$	$\sqrt{\hat{\mathcal{V}}_{\text{bc}}}$

- Robust bias correction enables to do valid inference using the same bandwidth used for the point estimate

- Robust bias correction enables to do valid inference using the same bandwidth used for the point estimate
- Another approach: use a different bandwidth for SE calculation

# Inference

```
out <- rdrobust(Y, X, kernel = 'triangular', p = 1, bwselect = 'mserd', all = TRUE)
summary(out)
```

```
## Call: rdrobust
##
## Number of Obs.          2629
## BW type              mserd
## Kernel              Triangular
## VCE method              NN
##
## Number of Obs.          2314          315
## Eff. Number of Obs.      529          266
## Order est. (p)           1           1
## Order bias (q)           2           2
## BW est. (h)             17.240       17.240
## BW bias (b)             28.576       28.576
## rho (h/b)               0.603       0.603
## Unique Obs.             2311       315
##
## =====
##           Method      Coef. Std. Err.      z    P>|z|      [ 95% C.I. ]
## =====
##   Conventional      3.020    1.427    2.116   0.034   [0.223 , 5.816]
## Bias-Corrected     2.983    1.427    2.090   0.037   [0.186 , 5.780]
## Robust              2.983    1.680    1.776   0.076  [-0.309 , 6.276]
## =====
```



- Key ID assumption: potential outcomes continuous at the cutoff

$$\lim_{x \rightarrow c^+} E[Y_i(j)|X = x] = \lim_{x \rightarrow c^-} E[Y_i(j)|X = x] = E[Y_i(j)|X = c], j \in (0, 1)$$

- Key ID assumption: potential outcomes continuous at the cutoff

$$\lim_{x \rightarrow c^+} E[Y_i(j)|X = x] = \lim_{x \rightarrow c^-} E[Y_i(j)|X = x] = E[Y_i(j)|X = c], j \in (0, 1)$$

- There are instances where this assumption can be plausibly violated.

# RDD assumption violations

**Sorting:** units try to get just above/below the cutoff

# RDD assumption violations

**Sorting:** units try to get just above/below the cutoff

- In our example: Islamic parties may invest more in winning election in some important municipalities

**Sorting:** units try to get just above/below the cutoff

- In our example: Islamic parties may invest more in winning election in some important municipalities
- If they are successful, just-won towns would be different from just-lost ones, i.e. a discontinuity at the cutoff


**Sorting:** units try to get just above/below the cutoff

- In our example: Islamic parties may invest more in winning election in some important municipalities
- If they are successful, just-won towns would be different from just-lost ones, i.e. a discontinuity at the cutoff
- Check for discontinuities in observable variables that we would expect to be continuous: typically pre-treatment covariates


**Sorting:** units try to get just above/below the cutoff

- In our example: Islamic parties may invest more in winning election in some important municipalities
- If they are successful, just-won towns would be different from just-lost ones, i.e. a discontinuity at the cutoff
- Check for discontinuities in observable variables that we would expect to be continuous: typically pre-treatment covariates
- Placebos


# RDD with placebo outcomes




(a) Log Population in 1994




(b) Number of Parties Receiving Votes in 1994




(c) Islamic Vote Percentage in 1994



(d) Islamic Mayor in 1989



(e) Province Center Indicator




(f) District Center Indicator



# RDD with placebo outcomes

```
bw <- rdrobust(data$partycount, X)$bws[1, 1]
xlim <- ceiling(bw)
rdplot(data$partycount[abs(X) <= bw], X[abs(X) <= bw],
       p = 1, kernel = "triangular", x.lim = c(-xlim, xlim), x.label = "Islamic vote margin", y.label = "", tit
```



# Density tests

- Check for evidence of sorting by looking at the distribution of the running variable

# Density tests

- Check for evidence of sorting by looking at the distribution of the running variable
- Formal tests: estimate density of RV on the two sides with local polynomial density estimator

# Density tests

- Check for evidence of sorting by looking at the distribution of the running variable
- Formal tests: estimate density of RV on the two sides with local polynomial density estimator
- Test the null that the density is the same on the two sides

# Density tests

- Check for evidence of sorting by looking at the distribution of the running variable
- Formal tests: estimate density of RV on the two sides with local polynomial density estimator
- Test the null that the density is the same on the two sides
- Classic test: [McCrary \(2008\)](#)

# Density tests

- Check for evidence of sorting by looking at the distribution of the running variable
- Formal tests: estimate density of RV on the two sides with local polynomial density estimator
- Test the null that the density is the same on the two sides
- Classic test: [McCrary \(2008\)](#)
  - Stata: user-written `DCdensity` ([here](#))

# Density tests

- Check for evidence of sorting by looking at the distribution of the running variable
- Formal tests: estimate density of RV on the two sides with local polynomial density estimator
- Test the null that the density is the same on the two sides
- Classic test: [McCrary \(2008\)](#)
  - Stata: user-written DCdensity ([here](#))
  - R: DCdensity in the package rdd

# Density tests

- Check for evidence of sorting by looking at the distribution of the running variable
- Formal tests: estimate density of RV on the two sides with local polynomial density estimator
- Test the null that the density is the same on the two sides
- Classic test: [McCrary \(2008\)](#)
  - Stata: user-written DCdensity ([here](#))
  - R: DCdensity in the package rdd
- Another test: [Cattaneo, Jansson and Ma \(2020\)](#)



# Density tests

- Check for evidence of sorting by looking at the distribution of the running variable
- Formal tests: estimate density of RV on the two sides with local polynomial density estimator
- Test the null that the density is the same on the two sides
- Classic test: [McCrary \(2008\)](#)
  - Stata: user-written DCdensity ([here](#))
  - R: DCdensity in the package rdd
- Another test: [Cattaneo, Jansson and Ma \(2020\)](#)
  - Stata and R:rddensity

# Density tests

```
library(rddensity)
```

```
out <- rddensity(X)
summary(out)
```

```
##
## Manipulation testing using local polynomial density estimation.
##
## Number of obs =      2629
## Model =          unrestricted
## Kernel =         triangular
## BW method =      estimated
## VCE method =     jackknife
##
## c = 0            Left of c      Right of c
## Number of obs    2314          315
## Eff. Number of obs 965          301
## Order est. (p)    2             2
## Order bias (q)     3             3
## BW est. (h)       30.539        28.287
##
## Method           T             P > |T|
## Robust           -1.3937        0.1634
##
##
## P-values of binomial tests (H0: p=0.5).
##
## Window Length / 2    <c      >=c    P>|T|
## 0.426                11       9      0.8238
## 0.852                18       26     0.2912
## 1.278                32       34     0.9022
## 1.704                42       48     0.5984
## 2.130                52       57     0.7018
## 2.556                62       68     0.6618
```

# Density tests

```
library(lpdensity)


bw_left <- as.numeric(rddensity(X)$h[1])
bw_right <- as.numeric(rddensity(X)$h[2])

est1 <- lpdensity(data = X[X < 0 & X >= -bw_left], grid = seq(-bw_left, 0,
                                                             0.1),
                  bwselect = "IMSE", scale = sum(X < 0 & X >= -bw_left) / length(X))

est2 <- lpdensity(data = X[X >= 0 & X <= bw_right], grid = seq(0, bw_right,
                                                             0.1),
                  bwselect = "IMSE", scale = sum(X >= 0 & X <= bw_right) / length(X))
```

# Density tests

```
library(ggplot2)
plot1 <- lpdensity.plot(est1, est2, CIshade = 0.2, lcol = c(4, 2), CIcol = c(4, 2), legendGroups = c("Control",
  labs(x = "Score", y = "Density") + geom_vline(xintercept = 0, color = "black") +
  theme_bw(base_size = 17)+theme(legend.position = c(0.8, 0.85))
plot1
```



# RDD with placebo cutoffs

- So far, placebo outcomes: replace the outcome with one that should not be affected by treatment

# RDD with placebo cutoffs

- So far, placebo outcomes: replace the outcome with one that should not be affected by treatment
  - If it is affected, evidence of confounding

# RDD with placebo cutoffs

- So far, placebo outcomes: replace the outcome with one that should not be affected by treatment
  - If it is affected, evidence of confounding
  - Other examples: Balance tests in experiments

# RDD with placebo cutoffs

- So far, placebo outcomes: replace the outcome with one that should not be affected by treatment
  - If it is affected, evidence of confounding
  - Other examples: Balance tests in experiments
- Now placebo treatments: replace the treatment with one that by construction has no effect but the same confounding source



# RDD with placebo cutoffs

- So far, placebo outcomes: replace the outcome with one that should not be affected by treatment
  - If it is affected, evidence of confounding
  - Other examples: Balance tests in experiments
- Now placebo treatments: replace the treatment with one that by construction has no effect but the same confounding source
  - If there is effect, evidence of confounding also in the original treatment

# RDD with placebo cutoffs

- So far, placebo outcomes: replace the outcome with one that should not be affected by treatment
  - If it is affected, evidence of confounding
  - Other examples: Balance tests in experiments
- Now placebo treatments: replace the treatment with one that by construction has no effect but the same confounding source
  - If there is effect, evidence of confounding also in the original treatment
  - Other examples: “Pre-trend” coefficients in DiD are an example

# RDD with placebo cutoffs

- So far, placebo outcomes: replace the outcome with one that should not be affected by treatment
  - If it is affected, evidence of confounding
  - Other examples: Balance tests in experiments
- Now placebo treatments: replace the treatment with one that by construction has no effect but the same confounding source
  - If there is effect, evidence of confounding also in the original treatment
  - Other examples: “Pre-trend” coefficients in DiD are an example
- In RDD: vary the cutoff where there should be no discontinuities


# RDD with placebo cutoffs

```
placebo <- function(Y, X, new_cutoff){  
  if (new_cutoff > 0){  
    Y <- Y[X>=0]; X <- X[X>=0]  
  }  
  if (new_cutoff < 0){  
    Y <- Y[X<0]; X <- X[X<0]  
  }  
  else{  
    Y <- Y; X <- X  
  }  
  
  out <- rdrobust(Y, X, c = new_cutoff)  
  coef <- out$coef["Conventional",]  
  ll <- out$ci["Robust",1]  
  ul <- out$ci["Robust",2]  
  
  cbind(coef, ll, ul)  
}  
  
cutoffs <- as.list(c(-3:3))  
(placebos <- do.call("rbind", lapply(cutoffs, function(i) placebo(Y, X, i))))
```

```
##           coef           ll           ul  
## [1,]  1.687817  -3.5083421  8.397096  
## [2,] -2.300012  -9.4137423  9.517862  
## [3,] -3.004159 -11.2961682 11.407925  
## [4,]  3.019526  -0.3092892  6.275769  
## [5,] -1.130650  -9.9671538 13.146914  
## [6,] -1.972790 -15.3333665  7.313371  
## [7,]  3.766433  -8.6998298 13.569346
```

# RDD with placebo cutoffs

```
library(dplyr)
placebos %>% as.data.frame() %>% mutate(cutoff = -3:3) %>%
  ggplot(aes(x=cutoff, y=coef)) + geom_point(col="red") +
  geom_errorbar(aes(ymin=ll, ymax=ul), col="blue",width=0.1) +
  labs(y = "RD Treatment Effect", x = "Cutoff (x=0 true cutoff)") +
  geom_hline(yintercept=0, col="black", linetype = "dashed") + theme_bw()
```



# Sensitivity checks

Other possible sensitivity analyses to check for stability of results:

- Exclude points closer to the cutoff

Other possible sensitivity analyses to check for stability of results:

- Exclude points closer to the cutoff
- Vary the bandwidth in a neighborhood of the optimal bandwidth

# Summing up

The standard practice includes:

- Graphical and formal placebo tests with covariates and other outcomes
- Density tests for sorting around the cutoff
- Perturbate the cutoff values
- Exclude observations near the cutoff
- Vary the bandwidth choice



- Can we add covariates to RDD estimation?

# Covariates

- Can we add covariates to RDD estimation?
- [Calonico, Cattaneo, Farrell, and Titiunik \(2019\)](#) study properties of RDD estimators with covariate adjustment

- Can we add covariates to RDD estimation?
- [Calonico, Cattaneo, Farrell, and Titiunik \(2019\)](#) study properties of RDD estimators with covariate adjustment
- There can be an efficiency argument in favor of covariate adjustment ( $\sim$  randomized experiments)

- Can we add covariates to RDD estimation?
- [Calonico, Cattaneo, Farrell, and Titiunik \(2019\)](#) study properties of RDD estimators with covariate adjustment
- There can be an efficiency argument in favor of covariate adjustment ( $\sim$  randomized experiments)
- In applications, often people include group fixed effects or unbalanced covariates

- Can we add covariates to RDD estimation?
- [Calonico, Cattaneo, Farrell, and Titiunik \(2019\)](#) study properties of RDD estimators with covariate adjustment
- There can be an efficiency argument in favor of covariate adjustment ( $\sim$  randomized experiments)
- In applications, often people include group fixed effects or unbalanced covariates
- CCFT recommend not to interact covariates with treatment indicator (allowing for different effects on the two sides requires stronger assumptions)

- Can we add covariates to RDD estimation?
- [Calonico, Cattaneo, Farrell, and Titiunik \(2019\)](#) study properties of RDD estimators with covariate adjustment
- There can be an efficiency argument in favor of covariate adjustment ( $\sim$  randomized experiments)
- In applications, often people include group fixed effects or unbalanced covariates
- CCFT recommend not to interact covariates with treatment indicator (allowing for different effects on the two sides requires stronger assumptions)
- In `rdrobust`: use the `covs` argument