



cicala

REV B.04 / ESP32-S3 / 16MB
4 LAYERS / 1.2mm / PROTOTYPE

POWER: USB 5V -> U2 -> VSYS
LiPo <-> U2 / VSYS -> U3 -> 3V3
U2 BQ25185: 100mA CHARGE
U7 + Q2: NTC CHARGE GUARD

22 CELL+
○

20 RESET ○

TOP TEST POINTS

1 BOOT 2 EN 3 GND

7 3V3 8 BAT 9 SYS

10 5V 14 STAT1

16 CLK 17 MOSI

18 CS 19 DC 21 BUSY

J2 UC8253 / CONTACTS DOWN

J3 1:+ 2:NTC 3:GND

PROTECTED 1S LiPo ONLY

NTC 10k B3435 ON CELL

11 PGOOD
○

5 RX
○

J4 RECOVERY / 3V3 LOGIC

1 3V3 2 GND 3 EN

4 BOOT 5 TX 6 RX

BOOT LOW + PULSE EN

3V3 REF ONLY / NO POWER

4 TX
○

6 FACTORY OD
○

U1 ESP32-S3 / 16MB

TX / RX FROM MCU

CERN-OHL-S-2.0

15 STAT2
○

ANTENNA / KEEP CLEAR