



cicala

REV B.03 / ESP32-S3 / 16MB
4 LAYERS / 1.2mm / PROTOTYPE

POWER: USB 5V -> U2 -> VSYS
LiPo <-> U2 / VSYS -> U3 -> 3V3
U2 BQ25185: 100mA CHARGE
U7 + Q2: NTC CHARGE GUARD

20 RESET 
22 CELL+ 

TOP TEST POINTS

1 BOOT 2 EN 3 GND
7 3V3 8 BAT 9 SYS
10 5V 14 STAT1
16 CLK 17 MOSI
18 CS 19 DC 21 BUSY 11 PG00D 
J2 UC8253 / CONTACTS DOWN
J3 1:+ 2:NTC 3:GND
PROTECTED 1S LiPo ONLY
NTC 10k B3435 ON CELL  



5 RX 



J4 RECOVERY / 3V3 LOGIC
1 3V3 2 GND 3 EN
4 BOOT 5 TX 6 RX
BOOT LOW + PULSE EN
3V3 REF ONLY / NO POWER



6 FACTORY OD 

U1 ESP32-S3 / 16MB
TX / RX FROM MCU
CERN-OHL-S-2.0

15 STAT2 

4 TX 

ANTENNA / KEEP CLEAR