Big Data Computing

The Data Growth Problem

Data volumes grow far faster than the capacity of any individual machine

Doubling disk capacity every few years is not enough when data doubles every few months. Some workloads (web indices, sensor networks) generate data faster than a single disk can even write it. Even a "big" machine is still bounded it just moves the ceiling, not eliminates it.

Vertical Scaling

Vertical scaling ("scale up") means making a single machine bigger. Add more CPU cores, more RAM, faster/larger disks, etc... However, although it works, we demand how far it can go? and at what cost?

Configuration	Relative Capacity	Relative Cost
Commodity server	1×	1×
High-end server	4×	~10×+
Top-of-line mainframe-class	16×	~100×+

Usually, the vertical scaling requires lots of money, and not always it does worth it. In fact, even with infinite money, vertical scaling hits physical limits that we cannot exceed: Motherboards have a fixed maximum number of CPU sockets, memory slots can only hold a finite amount of RAM, maximum bandwidth limits for data transfer, dissipation and power supply limits, and so on…

So, vertical scaling buys time, but it is not a long-term strategy for web-scale or exabyte-scale data.

Horizontal Scaling

Horizontal scaling ("scale out") means adding more machines, not bigger ones. A workload is spread across many modest and independent nodes. In this way the capacity grows by adding nodes to a cluster, not by upgrading any single node. Furthermore, thousands of inexpensive nodes can be cheaper in aggregate than a handful of premium ones, also reducing the failure's problems (that, in Big Data Scenarios, are considered expected, not exceptional).

For all of these reasons: The Horizontal Scaling is the foundational strategy behind the big data systems.

Aspect	Vertical (Scale Up)	Horizontal (Scale Out)
Approach	Bigger single machine	More machines
Ceiling	Hard physical limit	Effectively unbounded
Cost growth	Superlinear at high end	Roughly linear (commodity HW)
Failure handling	Hardware reliability	Software-level fault tolerance
Complexity	Low (same software model)	High (distributed coordination)

Cost-per-Byte vs. Cost-per-FLOP at Scale

Two different cost dimensions matter differently when scaling out (horizontally):

- **Cost-per-byte (storage):** disks make raw storage cheap; the dominant cost becomes replication and durability overhead.
- **Cost-per-FLOP (compute):** CPUs make raw compute cheap; the dominant cost becomes coordination and data movement.

Because of this, in the horizontal scaling, the bottleneck shifts from raw hardware cost to how well the system coordinates many cheap parts.

Distributed Storage

A Distributed File System (DFS) presents a single, unified file system interface backed by storage spread across many machines. Files appear to clients as if stored on one logical file system but, in reality, file contents are split, replicated, and distributed across a cluster of machines. The DFS hides this complexity behind familiar file operations (open, read, write, close).

In particular, Big Data DFSs are optimized for a specific trade-off:

- **Throughput-Oriented**: maximize total data moved per second across the whole cluster.
- **Latency-Tolerant**: individual operations may take longer than on a local disk.

And designed considering:

- **Huge File Size**: gigabytes to terabytes
- **Sequential Access**: read the whole file, or large chunks, start to finish
- **Avoidance of Random Access**: small reads/writes in specific positions are explicitly not the primary target workload and, usually, they are not even allowed.

For example, most big data DFSs assume a specific lifecycle for files: A file is written once (e.g., appended, then closed) and then read many times by different analytics jobs. In-place modification of existing file content is rare or disallowed.

Block/Chunk Abstraction

To work efficiently, a DFS splits files into fixed-size blocks, or chunks, rather than storing a file as one contiguous unit. Each block is then stored, replicated, and managed independently. Different blocks of the same file can live on different machines.

Obviously, a fixed block size (rather than a variable-size) simplifies the whole system: the system knows exactly where to find the metadata (e.g., block locations) and can easily interchange blocks (without leaving any empty space). However, it's fundamental to choose the right block size:

Block Size	Pros	Cons
Small (e.g., 4 KB)	Fine-grained, low waste for small files	Huge metadata overhead at scale
Large (e.g., 64–128 MB)	Low metadata overhead, efficient sequential I/O	Wasteful for small files, coarser load balancing


Usually, Big Data DFSs choose large blocks assuming that there will not be many "small files".

Metadata and Data Separation

Big Data DFSs usually separate the system that tracks "**where things are**" from the "**actual bytes**". In this way we can identify two different services:

- **Metadata Service**: service maintains the namespace: the hierarchical structure of directories and files. Tracks file-to-block mappings (which blocks make up which file). Tracks block-to-location mappings (which servers hold each block's replicas). Clients never read or write data through the metadata server — only its location information.
- **Data Servers**: the actual block contents, stored on local disks.

This separation allows each subsystem to be optimized independently (e.g., metadata MUST be held the memory for fast lookups, while data servers can optimize raw I/O throughput).



In addition, DFS designs usually use a **single coordinating node for metadata**: As we could imagine, this is simple, globally consistent and does not risk any race condition / consensus on every metadata change. However, it also introduces some problems, first of all: **single point of failure** and potential scalability bottleneck if metadata operations grow too large.

Replication

For many reasons, in Distributed Systems the replication is fundamental.


Usually in a single machine, RAID can protect against disk failure… but at cluster scale, this is insufficient because RAID protects against disk failure, not machine, rack, or network failure. Furthermore, with thousands of machines, the expected number of failures at any moment is non-zero. The DFS itself must replicate data across machines and racks to survive these failures

Racks and Network Topology Awareness

Distributed storage systems are aware of physical network topology. In these situations, machines are grouped into racks, connected by top-of-rack switches, where **intra-rack bandwidth** is typically much higher than **inter-rack bandwidth**.

Google File System (GFS)

The Google File System (GFS), published in 2003, was designed for Google's internal workloads, optimized for huge files, sequential reads, and append-heavy writes.



GFS Master

GFS simplifies the design using a **single Master**. It is the single metadata-managing node in the cluster. It:

- **Maintains the file system namespace**: composed of directory structure and "file → chunks" mapping
- **Maintains the chunk location map**: which chunkservers hold which chunks.
- **Manages chunk lease assignment for writes**.
- **Coordinates chunk creation, replication, and garbage collection**.

The Master's Metadata is kept in memory for speed, allowing the Master to handle metadata operations extremely fast, while chunk location information is not persisted it is rebuilt by polling chunkservers at startup. However, even if the Master keeps metadata in memory, it must survive crashes. For this reason:

- All namespace mutations are appended to a persistent operation log, replicated to multiple machines.
- Periodically, the Master writes a checkpoint (a compact snapshot of its full state) to avoid replaying an ever-growing log from scratch.
- On restart: load latest checkpoint, then replay the log entries since that checkpoint.


GFS also runs **Shadow Masters**, which are secondary, read-only replica of the primary Master node. Its main purpose is to alleviate the workload on the primary Master by handling requests that do not require modifying the system's state. When a client needs to find the location of a specific chunk of data (a read-only metadata query), it can ask a shadow master instead of the primary one. This effectively distributes the read traffic and prevents the primary Master from being overwhelmed by location queries.

Because the primary Master keeps its metadata in its main memory, the shadow masters must maintain an identical, up-to-date copy of this memory state. They achieve this by continuously reading and applying the exact same operation log that the primary Master creates. Whenever the primary Master records a change to the file system namespace (such as creating a file or assigning a chunk), the shadow master reads that log entry and applies the same change to its own memory. This ensures that the shadow master mirrors the primary Master's state as closely as possible, although there might be a slight delay.

GFS Chunkservers

Chunkservers are responsible to actually store the chunk data.

Each chunkserver stores chunks as regular files on its local file system (usually Linux) and serve read/write requests directly to clients.



In addition, Chunkservers periodically report their chunk inventory to the Master via heartbeats, which therefore serve not only for simple liveness detection. The Master uses this to detect under-replicated chunks (after a failure) or over-replicated chunks (after recovery). The Master issues replication/deletion commands piggybacked on heartbeat responses.

Each chunk is replicated, by default, 3 times across different chunkservers to ensure durability against individual chunkserver/disk failure. The replication factor is configurable per file, allowing more critical data to be replicated further. (We will see later where the replicas are placed).


GFS Chunk Size

GFS uses a notably large 64 MB chunk size (much larger than typical local file system blocks) **to reduce the number of chunks** per file and, consequently, the Master metadata size.

It also reduces the frequency of client-Master interactions (fewer chunk lookups per large read) encouraging large, sustained, sequential data transfers per chunk.


Downside: small files waste a disproportionate fraction of a chunk, but it is an accepted trade-off since GFS doesn't use small file 99% of the time.

GFS Read a File



0. Client computes the chunk index for the requested file offset.
1. Client asks the Master for the chunk handle and the list of chunkserver locations.
2. Master replies with chunk handle + locations (cached briefly by the client).
3. Client contacts the nearest replica chunkserver directly (bypassing the Master).
4. Chunkserver streams the requested data directly to the client.

GFS Write a File



1. Client asks the Master for the chunkservers holding the chunk's replicas, including which one holds the current lease (the primary).
2. Client pushes data to all replicas (in any order), which buffer it temporarily.
3. Client sends a write request to the primary replica.
4. The primary assigns a serial order to the write and forwards it to secondary replicas in that order.
5. Secondaries acknowledge; the primary replies to the client once all replicas confirm

This avoids needing a separate consensus protocol for every single write, since ordering is delegated to one replica at a time.

GFS Delete a File

In the GFSystem a "deleted" file does not immediately reclaim space. It is simply renamed to a hidden name and kept for a few days. This technique is simpler, more robust, allows to undo accidental deletes and deletion does not require immediate synchronous cluster-wide operations.

GFS Limitations

The single-Master design, while simple, introduces known limitations such as:

- **Metadata Scalability**: the entire namespace must fit in one machine's memory.
- **Bottlenecks on the Master**: very high rates of metadata operations (e.g., huge numbers of small files) can overwhelm a single Master.
- **Slow recovery**: recovering from a Master crash it’s not instantaneous… it takes some time, even with checkpoints and logs

Data Locality & Replication Strategy

"Move Computation to Data, Not Data to Computation"


At big data scale, moving computation is far cheaper than moving data. Since network bandwidth is orders of magnitude slower than local disk/memory bandwidth, moving terabytes of data across a network for every job is prohibitively slow and expensive.

So, the idea is to minimize the amount of data to exchange across the network and, consequently, the bottleneck across the racks. To do that we use Rack-Replicas.

NOTE: The replica placement is not random, it deliberately balances two competing goals:

- **Durability**: replicas should be spread across failure domains (different machines and different racks, even if it is much slower).
- **Write/Read Efficiency**: since the write must be propagated to every replica before being acknowledged, too much spreading increases cross-rack network traffic and slows down the process.

The common compromise place some replicas within the same rack (fast intra-rack replication for the write path), and at least one replica in a different rack (survives an entire rack failure).



Replication strategy must account for correlated failures across different scopes:

- **Disk failure**: affects one chunk's local copy.
- **Node failure**: affects all chunks on that machine.
- **Rack failure**: affects all nodes sharing a switch/power source.
- **Datacenter failure**: affects an entire facility (power outage, network outage, disaster).

Spreading replicas across these domains protects against progressively larger-scale failures.

Re-Replication after Node Failure


When a node fails, the system does not simply leave affected chunks under-replicated:

1. The Master detects the failure (missed heartbeats).
2. It identifies all chunks that were stored on the failed node, now under-replicated.
3. It schedules new replication of those chunks from surviving replicas to other healthy nodes.
4. Once complete, the system returns to full replication factor

Beyond simple replication, the system also tries to balance the storage usage across nodes to avoid that some nodes get overloaded while others are underused. New chunk placement and re-replication both consider current disk utilization across the cluster. A well-balanced cluster avoids hotspots that could become bottlenecks or premature failure points.

Hadoop Distributed File System (HDFS)

HDFS was built primarily to support large-scale, fault-tolerant batch processing (originally for MapReduce, that we'll see later) and it was designed as an open-source storage system directly inspired by GFS. For this reason, it adopts the same fundamental architecture with a slightly different terminology.



Structurally:

- **NameNode -> GFS Master**: it is HDFS's metadata-managing node, directly analogous to the GFS Master. It maintains the file system namespace (directories, files, permissions), the file-to-block mapping and the block-to-DataNode location mapping. Coordinates block replication, deletion, and rebalancing decisions. Keeps all of this metadata in memory for fast access.
- **DataNodes -> ChunkServers**: they are HDFS's data-storing nodes, directly analogous to GFS Chunkservers. They store HDFS blocks as files on their local file system and serve read and write requests for blocks to clients. DataNodes communicate with the NameNode through two periodic mechanisms: Heartbeats (frequent, e.g., every few seconds, as simple liveness signal) and Block reports (less frequent, it's the full list of blocks currently stored on that DataNode). Together, these let the NameNode maintain an accurate, near-real-time view of the cluster's block distribution and node health

HDFS uses 128MB block size (instead of 64MB chunk size of GFS) but the rationale idea the same: large blocks minimize metadata overhead and favor large sequential transfers.

NameNode Tolerance

HDFS persists NameNode metadata using two complementary structures:

- **FsImage -> GFS Checkpoint**: a complete, point-in-time snapshot of the entire file system namespace.
- **EditLog -> GFS Operation Log**: an append-only log of every namespace mutation (create, delete, rename, etc.) since the last FsImage.

This is the HDFS equivalent of GFS's checkpoint + operation log mechanism. On restart, the NameNode reconstructs its full in-memory state as follows:

1. Load the most recent FsImage into memory.
2. Replay every entry in the EditLog recorded since that FsImage was taken.
3. The resulting in-memory state reflects the namespace exactly as it was before the restart.
4. A new FsImage checkpoint is typically taken soon after, to bound future EditLog replay time.


NOTE: **The name Secondary NameNode is often misunderstood**. It is not a hot standby or failover replica for the primary NameNode. It periodically merges the FsImage and EditLog into a new checkpoint, then send it back to the primary NameNode. This offloads the (potentially expensive) checkpointing work from the primary NameNode's critical path. For real failover capability, HDFS requires a separate High Availability configuration (covered next).

HDFS High Availability

To address the single-point-of-failure risk, production HDFS deployments run **HA (High Availability) NameNode pairs**:


- One Active NameNode handles all client requests.
- One or more Standby NameNodes stay synchronized, ready to take over.
- A shared, consistent edit log (often via a separate consensus-based logging service) keeps Standby nodes up to date.
- Automatic failover mechanisms detect Active NameNode failure and promote a Standby

HDFS Read a File



1. Client asks the NameNode for the block locations comprising the target file.
2. NameNode returns block IDs and an ordered list of DataNodes holding each block (ordered by proximity to the client when possible).
3. Client connects directly to the nearest available DataNode for each block.
4. DataNode streams the block data directly to the client; the NameNode is not involved in this transfer

HDFS Write a File



1. Client asks the NameNode to create a new file
2. NameNode checks permissions and allocates the first block
3. NameNode returns a list of DataNodes to form a replication pipeline for that block.
4. Client streams data to the first DataNode in the pipeline.
5. Each DataNode forwards data to the next DataNode in the pipeline, in sequence.
6. Acknowledgments flow back up the pipeline once all DataNodes have persisted the data

As we can see, it differs from GFS in how it manages the data flow and client network load. In GFS, the data delivery and the control instructions are decoupled the client is responsible for pushing the data to *every* replica independently. The HDFS client, instead, only needs to communicate with the first DataNode, completely offloading the downstream replication work to the cluster's internal network.

Generally, the **HDFS Write** process is considered more efficient than GFS Write in terms of network utilization and client-side load. Because HDFS utilizes a linear streaming pipeline, the client only needs to establish a single network connection to the first DataNode preventing the network from bottlenecks.

At the same time, consistent with the write-once-read-many assumption, HDFS traditionally supports append operations to existing files, but not arbitrary in-place modification or random writes into the middle of an existing file are not supported. This restriction simplifies consistency and replication — exactly the same trade-off GFS makes.

HDFS Replica replacement Policy

HDFS's default placement policy (for replication factor 3) follows a rack-aware pattern:

1. 1st replica: on the DataNode where the client is writing (or a nearby node).
2. 2nd replica: on a different node, in a different rack from the first.
3. 3rd replica: on a different node, in the same rack as the second replica.

This balances cross-rack durability (replicas 1 and 2/3 are on different racks) against limiting cross-rack write traffic (replicas 2 and 3 share one rack-to-rack hop).

NOTE: HDFS does not automatically infer network topology — administrators must configure it explicitly: A configurable script or mapping tells HDFS which rack each DataNode belongs to. Without this configuration, HDFS treats all nodes as if they were in a single rack, losing the durability benefits of cross-rack placement.

HDFS Federation

To address the single-NameNode metadata bottleneck (the same limitation discussed for GFS), HDFS supports "**Federation**". It consists of multiple independent NameNodes, each managing a distinct portion of the namespace. DataNodes register with, and serve blocks for, all NameNodes in the federation. Each NameNode still has its own in-memory metadata limit, but the aggregate namespace capacity scales with the number of NameNodes.

GFS vs. HDFS

While structurally similar, GFS and HDFS have few architectural differences are worth noting:

- **HDFS's write path uses an explicit replica pipeline** (data flows node-to-node in sequence); GFS's write path has the client push to all replicas directly, then coordinate via a primary/lease mechanism.
- **HDFS persists metadata via FsImage + EditLog**; GFS uses an analogous **checkpoint + operation log**.
- **HDFS Federation and HA NameNode pairs are explicit**, separately-configured extensions; GFS's original paper describes shadow masters but a comparable, fully productized HA/federation story evolved later in industry practice

Failure Handling

As we already said before: “at scale, failures are expected, not exceptional”. The quality of a distributed storage system is measured by how gracefully it degrades and recovers, not by how rarely it fails… and all the mechanisms studied so far — replication, heartbeats, leases, checkpoints — exists specifically to make failure survivable. Not all failures look the same, and systems must handle several categories:

- **Transient failures**: temporary network blips, brief process pauses, garbage collection stalls, etc… in these cases the node is fine but briefly unresponsive.
- **Permanent failures**: disk death, hardware failure, node decommissioning, etc… the node or data is gone for good.
- **Correlated failures**: failures that strike multiple machines simultaneously (e.g., rack power loss, top-of-rack switch failure)

Both GFS and HDFS rely on the same basic detection mechanism: Each data-storing node sends periodic heartbeats to the metadata node. If no heartbeat is received within a configured timeout window, the node is presumed dead. This is inherently a trade-off: too short timeouts risk false positives (a healthy-but-slow node marked dead); too long delays real failure detection

Chunkserver/DataNode Failures

When a data-storing node is presumed dead, recovery follows a consistent pattern:

1. Metadata node marks all chunks/blocks on that node as under-replicated.
2. It schedules re-replication of each under-replicated chunk/block from a surviving replica to a healthy node.
3. Re-replication proceeds in the background, prioritized to restore full redundancy as quickly as network/disk capacity allows.

This is the same re-replication mechanism introduced in Section 4, now framed explicitly as a recovery process.

Master/NameNode Failure

Recovering the metadata node itself is more delicate, since it holds the single authoritative namespace view:

- **Without HA (High Availability) configured**: the cluster becomes unavailable for new operations until the Master/NameNode is manually restarted (replaying checkpoint + log, as covered earlier).
- **With HA (High Availability) configured**: a Standby node is promoted to Active, using the shared, continuously-synchronized edit log to resume with minimal interruption.

This is precisely why production deployments almost always run HA configurations despite the added complexity.

Checksums and Silent Data Corruption

Not all failures are obvious crashes — some are silent: a disk returns subtly corrupted bits without reporting an error. Both GFS and HDFS store checksums alongside each block/chunk. On every read, the checksum is verified against the data; mismatches indicate corruption. A detected corruption triggers the same re-replication mechanism — read from a different (presumably valid) replica, and recreate the corrupted one.

GFS and HDFS Recovery System

The combination of heartbeats, block reports, and checksums creates a continuously self-healing system: Under-replicated blocks (from node failure) are automatically restored to full replication. Corrupted blocks (detected via checksum mismatch) are automatically replaced from valid replicas. No human operator needs to manually intervene for routine, individual failures (only for large-scale or unusual events).

Example: Chunkserver Dies Mid-Read

1. A client is reading a chunk from Chunkserver A; Chunkserver A crashes mid-transfer.
2. The client's read request times out or errors.
3. The client re-queries the Master for alternate replica locations for the same chunk.
4. The client retries the read against a different chunkserver (B or C) — the application-level read succeeds, transparently to the end user.
5. Separately, the Master detects Chunkserver A's missed heartbeats and schedules re-replication of all its chunks elsewhere

MapReduce

Before MapReduce, every large-scale data processing job required re-solving the same hard problems:

- How do I split work across machines?
- How do I handle a machine crashing mid-job?
- How do I collect and combine partial results?

these problems are the same for almost every batch job… so MapReduce solve them once, in a reusable framework, and let programmers focus only on their specific logic. The idea is that:

"The biggest difficulty in distributed computing is not the algorithm; it's making the algorithm survive the cluster."

So, MapReduce does not invent new algorithms. It invents a way to run old and simple algorithms safely across thousands of unreliable machines.

Map and Reduce Functions

MapReduce borrows two primitives directly from functional programming:

- **map(f, list):** apply function f independently to every element of a list, producing a new list. Takes a single (key, value) pair from the input. Emits zero, one, or many intermediate (key, value) pairs.
- **reduce(g, list):** combine elements of a list pairwise using function g, producing a single aggregated result. Takes an intermediate key and the full list of values emitted for that key by all Map calls. Emits the final output value(s) for that key.

To guarantee MapReduce's fault-tolerance Map and Reduce functions must be **pure**: given the same input, they always produce the same output. They must have **no side effects**: no writing to external state, no relying on external mutable state)

Programmers POV

From the programmer's point of view, writing a MapReduce job means implementing just two functions:

- **map(key, value) → list(intermediate_key, intermediate_value)**
- **reduce(intermediate_key, list(intermediate_value)) → list(output_value)**

Then, the framework (not the programmer) is responsible for distributing map and reduce calls across the cluster. In this way, the programmer never writes scheduling, networking, or failure-handling code.

Example: The canonical MapReduce example. We want to count occurrences of every word across a massive collection of documents.

- **Map**: Each Map call processes one document. For every word encountered, it emits the pair (word, 1) to say: "I saw this word once."

```
map(document_id, document_text):
    for each word w in document_text:
        emit(w, 1)
```

- **Reduce**: Each Reduce call receives one word and the full list of 1s emitted for it across all documents. It simply sums them, producing the final total count for that word.

```
reduce(word, list_of_counts):
    total = sum(list_of_counts)
    emit(word, total)
```

Example 2: To see the abstraction generalize, consider building a search engine's inverted index (word → list of documents containing it).

```
map(document_id, document_text):
    for each word w in document_text:
        emit(w, document_id)

reduce(word, list_of_document_ids):
    emit(word, unique_sorted(list_of_document_ids))
```

NOTE: It both examples the programmer never had to specify which machine runs the functions, how data moves between different machine or what happens if a machine crashes mid-computation… All of this is handled directly by MapReduce at run-time.


MapReduce Master (or JobTracker)

Turning the user's map / reduce functions into a running cluster job involves several coordinated steps. A central coordinator (often called the **Master** or **JobTracker**) manages the overall job execution (conceptually plays a role analogous to the GFS Master/HDFS NameNode but for computation, not storage):

1. Splits the input into chunks suitable for Map tasks.
2. Assigns Map and Reduce tasks to available worker machines.
3. Tracks task progress and re-assigns tasks on failure (Section 4).

According to the “Move Computation to Dat, not Data to Computation” principle, the Master schedules each Map task on the machine that already holds the corresponding input block (or near). This minimizes network traffic during the Map. When a perfectly local machine is unavailable, the Master falls back to the same rack, then to any available machine.

MapReduce Execution



In addition, **MapReduce input** usually comes already split into blocks (HDFS) or chunks (GFS), directly from the DFS. By default, one Map task is created per input block — the natural unit of parallel work is inherited directly from the storage layer… This is not a coincidence: **MapReduce was designed hand-in-hand with GFS.**

Each **Map task's output** does not go directly to the final destination. Map output is written to local disk on the machine that ran the Map task, not to the distributed file system. This intermediate data is only ever needed temporarily, by the Reduce phase, and then trashed away.

About **Reduce functions instead**, before any tasks can run, intermediate (key, value) pairs must be grouped by key and routed to the correct Reduce task. For this reason a partitioning function maps each intermediate key to one of the Reduce tasks. All pairs with the same key must be routed to the same Reduce task, regardless of which Map task produced them. The most common partitioning strategy uses a hash function due to determinism (the same key always maps to the same Reduce task, from any Map task). Custom partitioning functions can be supplied for specialized load-balancing needs.

Just as MapReduce input arrives as multiple blocks, its output is also written as multiple sharded files, not one monolithic file. So, each Reduce task writes its own output file, conventionally named something like 00001 , …

Unlike the number of Map tasks (driven by input block count), the number of Reduce tasks is typically chosen by the user:

- **More Reduce tasks** → finer-grained parallelism, but more output files and shuffle overhead.
- **Fewer Reduce tasks** → simpler output, but less parallelism and potentially larger per-task workloads.

A common rule of thumb: choose a number of Reduce tasks on the order of the number of available worker machines, sometimes a small multiple of it.

Choice	Consequence
Too few Reduce tasks	Each handles a huge share of keys; poor parallelism; risk of a single overloaded "hot" reducer
Too many Reduce tasks	More output files to manage; higher shuffle coordination overhead; diminishing returns past available machines

MapReduce Combiners

A combiner is an optional optimization that aggregates each Map task's output locally. In this way, each machine, instead of sending n pairs (word, 1) sends directly (word, n) reducing the network traffic. Then, the Reduce function, combines al the (words, n) pair summing them to produce the final count.

The Shuffle Phase

Shuffle is the process of moving intermediate Map output to the correct Reduce task across the network. Every Reduce task must receive all intermediate pairs matching its assigned keys — regardless of which machine produced them. This requires data to potentially travel from every Map task to every Reduce task creating an all-to-all communication pattern (Cartesian Product). And, obviously, this is a lot of information on the network… making the Shuffle Phase the most expensive part of MapReduce.

With M Map tasks and R Reduce tasks, the shuffle pattern can involve up to M × R distinct data transfers. Unlike the Map phase (which benefits from data locality), shuffle data must generally cross the network there is no way to make every Reduce task "local" to every Map task simultaneously. Disk I/O is also significant, since data is written to local disk by Map tasks and then read again to be transferred.

Two practical techniques reduce the impact of the shuffle bottleneck:

- **Combiners**: As we've seen before, they reduce intermediate data volume locally, on the machine that runs the Map task, before it ever needs to be shuffled.
- **Compression**: intermediate data is frequently compressed before network transfer, trading CPU time for reduced network and disk I/O — usually a favourable trade at cluster scale.

The Sorting Phase

After receiving its assigned partitions from all Map tasks, each Reduce task sorts its received data by intermediate key to ensure that all values for the same key will be adjacent to one another. The framework typically performs this sort as part of merging data received from multiple Map tasks.

NOTE: The programmer does not need to implement their own grouping/hashing logic inside reduce — the framework guarantees grouping via sorting. This is the same "do the hard distributed-systems work once, in the framework" philosophy seen before.

The Reduce Phase

With data sorted and grouped by key, the Reduce task processes one group at a time. Each call to the user's reduces function handles exactly one key and its full value list.

```
for each (key, sorted_list_of_values) in sorted_input:
    call reduce(key, sorted_list_of_values)
    emit result to output file
```

Once a Reduce task finishes processing its assigned keys, it writes its output directly on the distributed file system (HDFS/GFS) — unlike intermediate Map output, which stayed on local disk.

Failure During Computation

Previously we covered failures of storage (disks, chunkservers, the Master) but now, MapReduce introduces failures during active computation. A worker machine can crash while running a MapReduce task or it can run abnormally slowly without technically "failing", but slowing down all the system. In addition, the MapReduce Master can itself fail. To resolve these problems the MapReduce Master detects worker failures using the same fundamental mechanism as the storage layer:

- Workers send periodic **heartbeats** to the Master, reporting task progress.
- If a worker misses heartbeats beyond a timeout threshold, the Master marks it as failed.

Map Task Fails

When a worker running a **Map** task fails **the Master simply re-schedules** that Map task on a different, healthy worker. This is safe even if the original Map task had already partially or fully completed, since its output lived on the failed machine's local disk, which is now unreachable. Because Map functions are deterministic re-running produces identical output.

Reduce Task Fails

Recovering a failed **Reduce** task is similar, but **only requires retracing the shuffle step**, not the original Map computation. The new worker re-fetches its assigned intermediate data from the (still-available) Map task outputs.

NOTE: If Map/Reduce functions were not deterministic, re-execution could silently produce different results than the original (now-lost) run. Because they are pure functions of their input, re-execution after failure is functionally indistinguishable from the task having succeeded on the first attempt.

MapReduce Master Fails

The Master coordinating the MapReduce job is itself a potential point of failure. In the original MapReduce design, Master failure is rare (a single job-tracking process) and is typically handled by restarting the entire job from scratch.

This is a deliberate simplicity trade-off: unlike the GFS/HDFS metadata node (which must survive for the cluster's entire lifetime), a MapReduce Master only needs to survive for the duration of one job.

The Straggler Problem

A straggler is a task that is still running, has not crashed, but is taking far longer than other equivalent tasks, slowing down the entire system (the entire job's completion time is bound by the slowest single task, even if 999 out of 1000 tasks finished quickly.). The main problem is that stragglers do not trigger the heartbeat-timeout failure-detection mechanism, since the worker is alive and responsive, but slow...

Several real-world conditions can cause a healthy-but-slow task:

- **Hardware Degradation**: a disk or CPU performing below its rated specification without outright failing.
- **Resource Contention**: other jobs or processes competing for CPU, disk, or network bandwidth on the same machine.
- **Data Skew**: a Reduce task assigned an unusually large number of values for one key, taking disproportionately long to process.

Speculative Execution

MapReduce's solution to the straggler problem is speculative execution. Near the end of a job, the Master identifies tasks that are running much slower than the average for similar tasks. It launches a backup copy of that task on a different, idle worker. Whichever copy (original or backup) finishes first is taken as the result; the other is discarded.

However, **speculative execution is not free**, it involves a direct trade-off:

- **Benefit**: can dramatically reduce overall job completion time when a small number of tasks are anomalously slow.
- **Cost**: wastes cluster resources on backup copies that are ultimately discarded if the original finishes first (or vice versa).

Spark

Existing dataflow systems (like MapReduce) lacked an efficient way to reuse data across multiple operations.

Spark is a new framework, built up to resolve the MapReduce imitations:

- **Disk-Heavy:** intermediate data between Map and Reduce always touches local disk.
- **Rigid Structure**: every job is exactly Map → Shuffle → Reduce, no more, no less.
- **High Latency**: favors large batch throughput, not fast iterative or interactive workloads

To solve these problems Spark propose a new abstraction, the **Resilient Distributed Dataset (RDD),** that is both memory-resident and fault-tolerant, without relying on replication. This is fundamental for many types of situations, such as:

- algorithms that repeatedly scan the same dataset across many iterations
- Iterative graph algorithms
- Iterative machine learning training loops
- …

In which, using MapReduce to iterate, would mean: re-read input from disk, re-run a full Map-Reduce job, write output and repeat (also considering the cost of Map, Shuffle, Reduce phases).

A second key motivation is that Spark enables fast, interactive querying of a dataset already loaded into a cluster's memory. A data analyst exploring a dataset wants successive queries to run in seconds, not minutes. If the dataset is cached in memory once, repeated queries against it avoid repeated disk I/O entirely.

Spark vs MapReduce


Aspect	MapReduce	Spark
Pipeline shape	Fixed two-stage (Map → Reduce)	Arbitrary DAG of operations
Intermediate data	Written to disk between stages	Held in memory when possible
Reuse across iterations	Re-read from disk each time	Cached in memory across iterations
Fault tolerance	Re-execution of failed tasks	Lineage-based recomputation (Section 6)
Best fit	Large one-pass batch jobs	Iterative, interactive, multi-step pipelines

Direct Acyclic Graphs (DAGs)

A Directed Acyclic Graph (DAG) is a natural way to represent a computation:

- **Nodes:** represent operations (or the datasets they produce).
- **Directed Edges:** represent data dependencies ("this operation's output feeds that operation's input")
- **Acyclic**: means no cycles since computation always flows forward, never back on itself.

A MapReduce job is, in this view, simply a DAG with exactly two stages. Spark generalizes this to DAGs of arbitrary shape and depth.



NOTE: In MapReduce each operations needs to write the output in its local disk. Spark's second major shift, instead, allows us to **keep data in the RAM** memory across operations. Data is only written to durable storage when the programmer explicitly requests it, or when memory is insufficient. **This directly attacks the "disk-heavy" limitation of MapReduce.**

Resilient Distributed Dataset (RDD)

A Resilient Distributed Dataset (RDD) is a collection of elements, partitioned across the machines in a cluster. It is:

- **Immutable**: once created RDD's contents never change (any change generates a new RDD). It is not an arbitrary restriction; it is foundational to Spark's design. Since an RDD never changes, how it was created is a complete and permanent description of its contents, enabling lineage-based fault tolerance and avoiding concurrency bugs that arise from shared mutable state across machines.
- **Resilient**: it can be automatically recovered after a partition is lost. this resilience does not come from replicating data across machines (unlike GFS/HDFS blocks). Instead, Spark records how each RDD was derived from its parent. Eventually, if a partition is lost Spark can recompute just the last partition using the recorded lineage, rather than reading a replica (we'll see the specific mechanism later).

Every dataset a Spark program manipulates, whether loaded from storage or derived from another dataset, is represented as an RDD.

RDDs Partitions

Like we've seen in the last lectures, also **RDDs are split into partitions**. Each partition is a subset of the RDD's data, residing on (or processed by) one machine at a time. Operations on an RDD are applied **independently, in parallel**, to each partition. The number of partitions determines the maximum degree of parallelism for operations on that RDD.

RDDs Creation

```
# From distributed storage (e.g., HDFS)
rdd = sc.textFile("hdfs://path/to/data")

# From an existing in-memory collection
rdd = sc.parallelize([1, 2, 3, 4, 5])
```

Two primary ways an RDD comes into existence:

- **textFile**: partitions are derived from the underlying file's blocks.
- **parallelize**: the driver's local collection is split into partitions and distributed to the cluster.

RDD Interface (Programmer's POV)

Conceptually, the RDD interface exposes:

- **Transformations:** operations that derive a new RDD from an existing one.
- **Actions:** operations that trigger actual computation and return a result or write output.
- **Persistence Controls:** explicit instructions to cache an RDD in memory (or disk) for reuse.

```
rdd = sc.textFile("hdfs://path/to/data")
rdd.cache()  # mark this RDD for in-memory persistence
```

NOTE: an RDD can be explicitly cached (persisted) in memory across multiple uses. Without caching, Spark may need to recompute an RDD from scratch (via lineage) every time it is reused.

RDDs Operations

Every operation a Spark program performs on an RDD falls into exactly one of two categories:

- **Transformations:** derive a new RDD from an existing one.
- **Actions:** trigger computation and produce a result outside the RDD abstraction (returned to the driver, or written to storage).

Transformations

A transformation takes one (or more) RDDs and produces a new RDD, describing a derived dataset. Transformations are deterministic functions over data, much like the Map function.

- **map(f):** apply f to every element *(identical to MapReduce)*
- **filter(f):** keep only elements where f returns true
- **flatMap(f):** apply f, flattening the resulting lists
- **distinct():** remove duplicate elements
- **union(other):** combine with another RDD

However, **transformations are not free**, their cost does not vanish, it is only deferred. Every transformation still needs to eventually run, as part of whatever action ultimately triggers the chain. What changes is when the work happens and how much visibility Spark has into the full pipeline before deciding how to run it.

Example:

```
rdd1 = sc.textFile("data.txt")
rdd2 = rdd1.filter(lambda line: "error" in line)
# rdd1 is unchanged; rdd2 is a new RDD describing the filtered result
```

Actions

An action triggers Spark to actually compute results, either returning them to the driver program or writing them to storage. Until an action is called, no actual data processing has necessarily happened yet.

- **count()**: return the number of elements
- **collect():** return all element to the memory (RAM)
- **reduce(f):** agraggate elements using f *(identical to MapReduce)*
- **saveAsTextFile(path):** write the RDD's contents to storage (disk)

Example: Word Counting

```
lines = sc.textFile("hdfs://documents/")
words = lines.flatMap(lambda line: line.split())
pairs = words.map(lambda word: (word, 1))
counts = pairs.reduceByKey(lambda a, b: a + b)
```

Until now we have all transformations — none of them have triggered computation yet. Only when an action is called does Spark actually execute the chain.

```
result = counts.collect()
```

This single line causes Spark to: read input from HDFS, run flatMap , run map, run reduceByKey (including any necessary shuffle), and finally collect results to the driver. All of the previously-defined transformations execute together, as part of this one triggered computation.

Lazy Evaluation

Lazy evaluation is the principle in which transformations are recorded as a plan and not executed until an action is called.

Thanks to this principle Spark can see the entire pipeline of transformations before committing to a specific execution strategy. This visibility enables optimizations across operations that would be impossible if each transformation was executed immidiatly, in isolation. It also avoids wasted work: if an action only needs part of the data, Spark can sometimes avoid computing more than necessary.

Optimizations

Having full visibility into the DAG before execution lets Spark apply several optimizations:

- **Operator Fusion (or Pipelining)**: chain compatible operations together to avoid unnecessary intermediate materialization.
- **Avoiding Unneeded Computation**: skip parts of the DAG not required to produce the requested action's result.
- **Choosing Physical Execution Strategy**: decide how to group operations into stages based on the dependency structure

Operation Fusion (or Pipelining)

When a sequence of transformations can be applied to the same data element without needing to wait for siblings or other partitions, Spark can pipeline them together:

```
words.map(f).filter(g).map(h)
```

Rather than materializing the full intermediate result after *map(f),* then again after *filter(g),* Spark can apply *f*, then *g* and then *h* to each element in a single pass, per partition. This avoids unnecessary memory overhead and extra passes over the data.

Pipelining directly reduces the cost of multi-step pipelines compared to MapReduce's job-chaining approach since, in chained MapReduce jobs, each job's complete output had to be materialized (written to HDFS) before the next job could start.

- Operations like ***map*** or ***filter*** can be **pipelined freely** since they need no data from other partitions.
- Operations like ***reduceByKey*** or ***join*** require data to be regrouped across partitions (exactly like the shuffle phase from MapReduce)

Stages

A stage is a group of operations that can be executed together, without requiring data to be shuffled across the network in between. Thanks to these properties operations within a single stage are pipelined together.

A new stage begins whenever the DAG requires a shuffle (data must be redistributed across partitions before the next operation can proceed). **[why we need to introduce narrow and wide to complete the definition?]**

From Logical DAG to Physical Jobs

When an action is finally called, Spark converts the logical DAG into something it can actually run on the cluster:

1. The DAG scheduler examines the full chain of dependencies leading to the requested action.
2. It divides the DAG into a set of stages.
3. Each stage is further divided into tasks, one per partition, scheduled across the cluster — conceptually similar to MapReduce's task scheduling

Example: Building and Triggering a Multi-Step DAG

Extending the word count example with an additional step — filtering out rare words after counting:

```
lines = sc.textFile("hdfs://documents/")
words = lines.flatMap(lambda line: line.split())
pairs = words.map(lambda word: (word, 1))
counts = pairs.reduceByKey(lambda a, b: a + b)
frequent = counts.filter(lambda kv: kv[1] > 100)
result = frequent.collect()  # ACTION triggers the entire chain
```

Five chained transformations, executed as a single coordinated DAG when collect() is finally called

Dependencies

This is the precise, formal version of the "Resilient" point introduced informally in the first RDDs paragrapher.

A dependency describes the relationship between a child RDD's partitions and the partition(s) of its parent RDD(s) that it depends on

Narrow Dependences

A dependency is narrow when each partition of the child RDD depends on a small, fixed number of partitions (typically exactly one) of the parent RDD.

map, ***filter***, and ***flatMap*** are all narrow: each output partition is computed purely from the corresponding single input partition. No data needs to move between partitions on different machines. It's entirely local, no network transfer required, allowing safe pipeling (a chain of narrow transformations can be computed entirely within one partition, on one machine, in one pass).

Wide Dependences

A dependency is wide when a child RDD's partition may depend on data from multiple, potentially all, partitions of the parent RDD

groupByKey, reduceByKey, and ***join*** are all wide: producing any single output partition may require data originally scattered across every input partition. This is structurally identical to the all-to-all data movement problem in MapReduce's shuffle. In fact, wide dependencies carry the same cost characteristics identified for MapReduce's shuffle:

- High Network bandwidth consumption
- Disk I/O for writing and reading shuffle data.
- All partitions (of the wide dependency) must complete before the next stage can fully proceed.

For these reasons, Spark programs are often written to minimize the number of wide dependencies:

- **Prefer reduceByKey over groupByKey** followed by a separate aggregation, since reduceByKey can partially aggregate locally before shuffling.
- **Push narrow operations before wide operations**, reducing the volume of data that must be shuffled

Stage Boundaries

We can now state precisely what determines a stage boundary:

- **A stage is a maximal run of narrow-dependency** transformations that can be pipelined together.
- **A new stage begins exactly at each wide dependency**, because computing it requires the shuffle's output to be available before proceeding.

Example: Identifying Stages in a DAG

```
lines ──flatMap──► words ──map──► pairs ──reduceByKey──► counts ──filter──► frequent
        (narrow)          (narrow)           (wide)                (narrow)
```

- flatMap, map, and filter filter are narrow — this form pipelined segments within stages.
- reduceByKey is wide — this is exactly where a stage boundary (and a shuffle) occurs.

Result: this five-step chain compiles down to just two physical stages.

Lineage – RDD(s) Fault Tollerance

Lineage is the recorded chain of transformations that describes exactly how an RDD's partitions were derived from their parent RDD(s).

This is precisely the DAG structure of before, now viewed in its role as a fault tolerance mechanism rather than an execution-planning mechanism.

This is the central distinction between Spark's fault tolerance and GFS/HDFS's:

- **GFS/HDFS**: keep multiple physical copies of the actual data.
- **Spark**: if a partition of some RDD is lost (e.g., the machine holding it crashes), Spark can rebuild exactly that partition identifying the lost partition's parent(s) and asking them to recompute the lost operation. If a parent partition is also missing, we can of course recurse further back along the lineage chain until reaching available data.

However, **lineage-based recovery is not free.** If a lineage chain is very long, recomputing a lost partition near the end of the chain may require recomputing a large portion of everything before it. This recomputation cost grows with the depth of the DAG, particularly problematic for iterative algorithms where the same RDD is transformed repeatedly across many iterations.

To address **long-lineage** recomputation cost, Spark allows explicit **checkpointing.** A checkpoint writes an RDD's current data to durable, replicated storage (e.g., HDFS) and it is clearly a trade-off: pay an upfront storage/replication cost now, in exchange for bounded recomputation cost later.

You can find a full Spark Summary at the end of "Lecture 1.3 Spark" Slides

High Dimensional Data Representation

"In high dimensions, almost all of the volume of a convex body lies near its surface, and almost all pairs of points are almost orthogonal."

This part of the course will answer to the question: "**once data lives on these platforms, how is it mathematically represented?**"

- **Text**: documents are often represented as vectors over a vocabulary of tens of thousands of words.
- **Images**: raw pixel representations, or learned embeddings, frequently have hundreds to thousands of dimensions.
- **Graphs**: node embeddings often live in spaces of dimension 64–512 or more.
- **Algorithms**: many classic algorithms implicitly assume low dimensional geometric intuition holds.

Before building or trusting such algorithms at scale, we must understand precisely how geometry itself changes as dimensionality grows.

Low-Dimensional Intuition

Most of our geometric reasoning is built from direct experience with 2 or 3 dimensions. However, most of these intuitions fails dramatically once the dimension becomes large... and this is not a coincidence…

It is a direct consequence of biology and physics. Human visual and spatial reasoning evolved to navigate a three-dimensional physical world. We have no direct sensory experience of a 100-dimensional or 1000-dimensional space.

So, rather than treating this divergence as an abstract anomaly, the study of high-dimensional geometry aims to rigorously formalize and quantify how volume, distance, and angular relationships behave as the dimension $\boldsymbol{d} \to \infty$.

Vectors and Points

We work throughout with the **d-dimensional real vector space** $\mathbb{R}^d$. In this situation a point and a vector are used interchangeably (a point's coordinates are simply the vector from the origin to that point).

$$\boldsymbol{x} = (\boldsymbol{x_1}, \boldsymbol{x_2}, \dots, \boldsymbol{x_d})$$

The Euclidean norm (length) of a generic point *x* is:

$$||\boldsymbol{x}||_2 = \sqrt{\boldsymbol{x_1^2} + \boldsymbol{x_2^2} + \cdots + \boldsymbol{x_d^2}}$$

Volume and Distance

This lecture's entire argument is built around two geometric quantities, tracked as grows:

- **Volume**: how is the "mass" of a high-dimensional region (cube, sphere) distributed across that region?
- **Distance**: how spread out are the pairwise distances between random points in such a region?

We will show these two questions are deeply connected — volume concentration is, in fact, the root cause of distance concentration.

Unit HyperCube

Unit HyperCube (C_d): The Cartesian product of d unit intervals, defining the region where each coordinate satisfies $0 \leq x_i \leq 1$:

$$C_d = [0,1]^d = \left\{ x \in \mathbb{R}^d : 0 \leq x_i \leq 1 \text{ for all } i \in \{1, \ldots, d\} \right\}$$

Volume of the Hypercube

To analyze how geometric mass behaves in high-dimensional spaces, we first establish a reference baseline using the **unit hypercube** $C_d = [0,1]^d$.


The total volume of the hypercube is calculated as the product of its side lengths. However, by definition, each edge along all d dimensions has a side length equal to 1. So:

$$\text{Vol}(C_d) = 1 * 1 * \ldots * 1 = 1^d = 1$$

This means that the volume of the hypercube remains constant to 1 across all dimensions. It only serves as a normalized benchmark that allows us to determine the proportion of volume that occupies specific regions **inside the cube** as the dimension d grows. Not the cube itself.

Boundary Shell and Inner Cube

To understand the distribution of volume inside C_d, consider decomposing the cube into two complementary regions: an **inner cube** and an outer **boundary shell**.



Let ϵ be a fixed parameter such that $\epsilon \in (0, 1/2)$.

We define the inner cube C_d^{inner} **as the set of all points that are located at a distance of at least ϵ from every face** of the unit cube:

$$C_d^{\text{inner}} = [\epsilon, 1-\epsilon]^d$$

The remaining region is the shell, defined as the set difference. The shell consists of all points that lie within a distance ϵ of at least one boundary face.

$$C_d^{\text{shell}} = C_d \setminus C_d^{\text{inner}}$$

Derivation of Volume Concentration

We said that the cube volume is computer as l^d, where l is the side length of the cube. So, in the inner cube, since it has **side lengths =** $(1-2\epsilon)$ across all d dimensions, its volume is given by:

$$\text{Vol}\left(C_d^{\text{inner}}\right) = (1-2\epsilon)^d$$

Since $\epsilon \in (0, 1/2)$, the base of this exponential expression satisfies $0 < (1 - 2\epsilon) < 1$.

The volume of the shell, instead, is calculated by complementary subtracting the inner volume from the total volume and dividing by the total volume:

$$\mathbf{Vol}\left(C_d^{\text{shell}}\right) = \frac{\mathbf{Vol}(C_d) - \mathbf{Vol}\left(C_d^{\text{inner}}\right)}{\mathbf{Vol}(C_d)} = \frac{1 - (1 - 2\epsilon)^d}{1} = 1 - (1 - 2\epsilon)^d$$

Cube Volume Concentration Theorem

Now, let's see what happens at the volume as the dimension $d \to \infty$:

$$\lim_{d\to\infty} \left(\mathbf{Vol}\left(C_d^{\text{inner}}\right)\right)^d = \lim_{d\to\infty} (1 - 2\epsilon)^d = 0$$

And do the same on the shell:

$$\lim_{d\to\infty} \left(\mathbf{Vol}\left(C_d^{\text{shell}}\right)\right)^d = \lim_{d\to\infty} \left[1 - (1 - 2\epsilon)^d\right] = 1 - 0 = 1$$

From that we can derive our first theorem:

Theorem (Cube Volume Concentration): For any fixed $\epsilon > 0$, as the dimension $d \to \infty$, the fraction of the unit cube's volume residing within a distance ϵ of its boundary approaches 1 (or 100%).

In lower terms: as $d \to \infty$ the hypercube becomes essentially all shell and the inner cube effectively vanishes in terms of volume.

What happens to Random Points?

This concentration of volume directly influences the behavior of randomly sampled points. When a point $x = (x_1, x_2, \ldots, x_d)$ is sampled uniformly at random from C_d, each coordinate x_i is chosen independently from the uniform distribution $[0, 1]$.

However, because the volume of the inner region vanishes with high dimensions, the probability of sampling a point from the interior approaches zero. A randomly chosen point will almost certainly lie within ϵ of a boundary face, placing it far from the center and close to "**corner-like**" outer regions.

The Diagonal of the Hypercube

While each side of the cube has fixed length 1, **the diagonal grows without bound as d increases**. This means the cube becomes increasingly "spiky". Most of its volume is far from the center relative to its side length.

$$\mathbf{diag}(C_d) = \sqrt{1^2 + 1^2 + \ldots + 1^2} = \sqrt{d}$$

Distance Behaviour

The growing diagonal, combined with boundary-volume concentration, defines the first result of this lecture:

If most random points sit near the cube's boundary, and the boundary itself spans a diagonal of length $\sqrt{d}$ then pairwise distances between random points should scale with $\sqrt{d}$ as well.

Unit HyperSphere (or Ball)

Unit HyperSphere/Ball (B_d): The set containing the interior and boundary of a hypersphere of radius 1 centered at the origin. It is formally characterized by points whose Euclidean norm is at most 1:

$$\boldsymbol{B_d = \{x \in \mathbb{R}^d : \|x\| \leq 1\} = \left\{x \in \mathbb{R}^d : \sqrt{x_1^2 + x_2^2 + \cdots + x_d^2} \leq 1\right\} = \{x \in \mathbb{R}^d : x_1^2 + x_2^2 + \cdots + x_d^2 \leq 1\}}$$

Volume of the Ball

The volume of a d-dimensional ball of radius r is given by the closed-form expression:

$$\boldsymbol{V_d(r) = \frac{\pi^{d/2}}{\Gamma\left(\frac{d}{2} + 1\right)} r^d}$$

Where $\Gamma(\cdot)$ represents the **Gamma function**, which provides a continuous generalization of the factorial function to real and complex numbers. Specifically, for any non-negative integer n, it satisfies the property:

$$\Gamma(n + 1) = n!$$

This generalized expression unifies and reproduces the classic geometric formulas known in lower dimensions:

- For $d = 2$, evaluating the formula yields $V_2(r) = \frac{\pi^1}{\Gamma(2)} r^2 = \frac{\pi}{1!} r^2 = \pi r^2$, which corresponds to the standard area of a circle.
- For $d = 3$, substituting $d = 3$ gives $V_3(r) = \frac{\pi^{3/2}}{\Gamma(5/2)} r^3 = \frac{\pi\sqrt{\pi}}{\frac{3}{2}\frac{1}{2}\sqrt{\pi}} r^3 = \frac{4}{3}\pi r^3$, matching the familiar volume of a 3D sphere.

Vanishing Ball Volume Theorem

When setting the radius to $r = 1$, the volume of the **unit ball** simplifies to:

$$V_d(1) = \frac{\pi^{d/2}}{\Gamma\left(\frac{d}{2} + 1\right)}$$

Examining the behaviour of this expression as $d \to \infty$ reveals an apparent paradox:

Even though the radius remains constantly equal to 1, the total volume vanishes asymptotically.

The mathematical explanation lies in the competing growth rates of the numerator and denominator:

- The numerator grows exponentially in d
- The denominator grows faster than exponentially by Starling's approximation

So the denominator dominates, leading to:

$$\lim_{d \to \infty} V_d(1) = 0$$

Theorem (Vanishing Ball Volume): As the dimension $d \to \infty$, the volume of the d-dimensional unit ball B_d approaches zero, despite its radius remaining strictly equal to 1 for all d.

Let's consider inscribing a unit ball B_d inside a hypercube of side length 2, formally represented by $[-1, 1]^d$. Since the cube's side length is 2 the ball of radius 1 fits exactly inside. In this configuration, the ball touches every face of the cube tangentially.

The volume of this circumscribing cube is $\mathbf{Vol}\left([-1, 1]^d\right) = 2^d$. Calculating the ratio of the inscribed ball's volume to the cube's volume gives:

- In two dimensions ($d = 2$), an inscribed circle covers $\frac{\pi}{4} \approx 78.5\%$ of the square's area.
- In three dimensions ($d = 3$), an inscribed sphere occupies $\frac{\pi}{6} \approx 52.4\%$ of the cube's volume.
- In four dimensions ($d = 4$), an inscribed sphere occupies $\frac{\pi}{32} \approx 30.84\%$ of the cube's volume.
- …
- As d grows large, the volume fraction occupied by the inscribed sphere becomes practically zero.

Geometrically, this demonstrates that virtually all the mass of a high-dimensional cube is concentrated away from the center, pushed into the "corners" that lie entirely outside the inscribed ball.

Spherical Shell

As we already did with the hypercube let's consider a thin **shell** near the surface of the ball itself: **the region between radius $(1 - \epsilon)$ and radius 1.**

According to the general formula $V_d(r) = V_d(1) \cdot r^d$, an inner ball of radius $(1 - \epsilon)$, has a volume of:

$$\mathbf{Vol}\left(B_d^{\text{inner}}\right) = V_d(1 - \epsilon) = V_d(1) \cdot (1 - \epsilon)^d$$

Then, by complementary (as before) we can calculate the volume contained within this outer shell:

$$\mathbf{Vol}\left(B_d^{\text{shell}}\right) = \frac{V_d(1) - V_d(1 - \epsilon)}{V_d(1)} = \frac{V_d(1) - V_d(1)(1 - \epsilon)^d}{V_d(1)} = 1 - (1 - \epsilon)^d$$

Ball Surface Concentration

Taking the limit as the dimension $d \to \infty$, and noting that $0 < 1 - \epsilon < 1$:

$$\lim_{d \to \infty} (1 - \epsilon)^d = 0 \Longrightarrow \lim_{d \to \infty} \left[1 - (1 - \epsilon)^d\right] = 1$$

Theorem (Sphere Surface Concentration): For any fixed shell thickness $\epsilon > 0$, as $d \to \infty$, the fraction of the unit ball's volume located within a distance ϵ of its surface approaches 1 (or 100%).

Even though the total volume of the unit sphere decays toward zero, whatever minuscule volume remains does not sit in the interior; it concentrates entirely in an infinitesimally thin skin near the boundary surface.

Cube vs Ball

Both the hypercube and the hypersphere exhibit the exact same boundary concentration phenomenon:

Object	Fraction in boundary shell	Limit as $d \to \infty$
Hypercube	$1-(1-2\epsilon)^d$	$\to 1$
Hypersphere	$1-(1-\epsilon)^d$	$\to 1$

Both derivations stem from the same fundamental mathematical rule: any fixed base strictly between $\mathbf{0}$ and $\mathbf{1}$, when raised to an increasing power $\boldsymbol{d}$, decays to zero. This single principle governs the geometric distribution of mass in high dimensions, leaving both cubes and spheres with completely hollow interiors and concentrating all volume at their outer edges


Equator Band

New Question: Where on the Sphere's Surface Do Points Concentrate?

To formalize this question, we fix an arbitrary unit vector $\boldsymbol{e} \in \mathbb{R}^{\boldsymbol{d}}$ to serve as a reference pole (e.g., the "North Pole"). For any point $\boldsymbol{x}$ lying on the surface of the unit sphere, its coordinate along this chosen directional axis is obtained through the standard inner product:

$$\boldsymbol{x_1 = x \cdot e}$$

Def. The equatorial band of width ϵ is the set of points with $|x_1| \leq \epsilon$



The regions outside of this equator band (where $\boldsymbol{x_1 > \epsilon}$ or $\boldsymbol{x_1 < -\epsilon}$) constitute the corresponding Northern and Southern **polar caps**.

Slicing the Sphere

To understand why the surface area concentrates around the equator, we examine the intrinsic geometry of hyperspherical cross-sections. The unit sphere in $\boldsymbol{d}$ dimensions is formally defined as the set of unit vectors:

$$\boldsymbol{S_{d-1} = \{x \in \mathbb{R}^d : x_1^2 + x_2^2 + \cdots + x_d^2 = 1\}}$$

Because of the single norm equality constraint, the surface S_{d-1} possesses an intrinsic dimensionality of $(d-1)$. If we slice this sphere perpendicular to the polar axis at a fixed coordinate height $x_1 = t$, the remaining coordinates must satisfy:

$$x_2^2 + x_3^2 + \cdots + x_d^2 = 1 - t^2$$

This cross-sectional slice is itself an embedded sphere of intrinsic dimension $(d-2)$, denoted S_{d-2}, with an effective radius given by:

$$r = \sqrt{1 - t^2}$$

The Decline of Surface Area Away from the Equator

The surface area of a $(d-2)$-dimensional hypersphere of radius r scales proportionally to r^{d-2}. Substituting the slice radius $r = \sqrt{1-t^2}$, the differential surface area of a slice located at height $x_1 = t$ scales as:

$$\text{Area(slice at } t) \propto \left(\sqrt{1-t^2}\right)^{d-2} = (1-t^2)^{(d-2)/2}$$

Evaluating this expression across different latitudes illustrates an extreme geometric imbalance:

- At the equator ($t = 0$), the radius is maximized ($r = 1$), yielding $(1-0^2)^{(d-2)/2} = 1$.
- Moving away from the equator toward the poles ($|t| > 0$), the base term strictly satisfies $0 < 1 - t^2 < 1$.

As $d \to \infty$, raising a number strictly smaller than 1 to the growing power $(d-2)/2$ causes the slice's surface area to vanish exponentially:

$$\lim_{d\to\infty} (1-t^2)^{(d-2)/2} = 0 \quad \text{for all } |t| > 0$$

The Equatorial Concentration Theorem

This geometric scaling yields a formal probability bound describing the location of points on the hypersphere:

Theorem (Equatorial Concentration): For a point x chosen uniformly at random on the unit sphere S_{d-1} and any fixed coordinate direction $x_1 = x \cdot e$, the probability that x lies in the polar caps declines exponentially with the dimension d:

$$\Pr[|x_1| > \epsilon] \leq e^{-d\epsilon^2/2}$$

For any fixed band width $\epsilon > 0$, as the dimension grows without bound, this tail probability rapidly decays to zero:

$$\lim_{d\to\infty} e^{-d\epsilon^2/2} = 0 \Rightarrow \lim_{d\to\infty} \Pr[|x_1| \leq \epsilon] = 1$$

So, the equatorial band does not expand as d increases. Its width ϵ remains fixed and can be chosen arbitrarily small. Instead, the surface area of the hypersphere progressively collapses into the equatorial strip.

Because the hypersphere is perfectly rotationally symmetric, no single directional axis is mathematically privileged. The reference pole e can be chosen in any direction whatsoever. Therefore, for **any** fixed direction picked in advance, almost all points on the hypersphere reside within an ϵ-thin band orthogonal to that direction.

Near-Orthogonality of Random Vectors

This generalization leads directly to one of the most counterintuitive results in this lecture: **randomly chosen vectors are almost always perpendicular to one another.**

Consider two vectors $\boldsymbol{x}$ and $\boldsymbol{y}$ sampled independently and uniformly at random from the unit sphere in $\mathbb{R}^{\boldsymbol{d}}$. Because the orientation of $\boldsymbol{y}$ is arbitrary, we can fix $\boldsymbol{y}$ and treat it as the reference pole vector $\boldsymbol{e}$. The dot product between $\boldsymbol{x}$ and $\boldsymbol{y}$ corresponds to the coordinate projection of $\boldsymbol{x}$ along $\boldsymbol{y}$:

$$\boldsymbol{x} \cdot \boldsymbol{y} = \|\boldsymbol{x}\|_2 \|\boldsymbol{y}\|_2 \cos(\boldsymbol{\theta})$$

Since $\boldsymbol{x}$ and $\boldsymbol{y}$ are unit vectors ($\|\boldsymbol{x}\|_2 = \|\boldsymbol{y}\|_2 = \mathbf{1}$), this reduces directly to the cosine of the angle $\boldsymbol{\theta}$ between them:

$$\boldsymbol{x} \cdot \boldsymbol{y} = \cos(\boldsymbol{\theta})$$

Applying the equatorial concentration bound directly to this inner product produces the following formal result:

Theorem (Near-Orthogonality): For two independent, uniformly distributed unit vectors $\boldsymbol{x}, \boldsymbol{y} \in \mathbb{R}^{\boldsymbol{d}}$ and any fixed tolerance $\boldsymbol{\epsilon} > \mathbf{0}$:

$$\Pr[|\boldsymbol{x} \cdot \boldsymbol{y}| > \boldsymbol{\epsilon}] \leq \boldsymbol{e}^{-\boldsymbol{d}\boldsymbol{\epsilon}^2/2}$$

As $\boldsymbol{d} \to \infty$, this probability vanishes. Consequently:

- The inner product satisfies $\boldsymbol{x} \cdot \boldsymbol{y} \approx \mathbf{0}$ with high probability.
- Because $\cos(\boldsymbol{\theta}) \approx \mathbf{0}$, the angle between the two vectors satisfies $\boldsymbol{\theta} \approx \mathbf{90}^\circ$ ($\boldsymbol{\pi}/\mathbf{2}$ radians).

While two random vectors in low dimensions ($\boldsymbol{d} = \mathbf{2}$ or $\boldsymbol{d} = \mathbf{3}$) have a broad spread of potential angles, high-dimensional geometry forces two independent random directions to be almost perfectly orthogonal.

Near-Orthogonality Motivation

The near-orthogonality of random vectors is fundamentally governed by the same exponential concentration behaviour seen in earlier sections:

- In the **hypercube and hypersphere volume derivations** (Sections 2 and 3), the geometric mass concentrates near boundaries because polynomial scaling $(\mathbf{1} - \boldsymbol{\epsilon})^{\boldsymbol{d}} \to \mathbf{0}$ suppresses the interior.
- In the **equatorial surface analysis** (Section 4), the exponential factor $\boldsymbol{e}^{-\boldsymbol{d}\boldsymbol{\epsilon}^2/2} \to \mathbf{0}$ suppresses the polar caps and concentrates the surface area along the equator.

In all cases, high dimensionality acts as a powerful exponential sieve, collapsing probability mass into low-dimensional submanifolds and thin boundary shells.

Distance Concentration

In low-dimensional environments, distances between objects feel natural and intuitive: some objects are clearly close, others are clearly far away, and identifying the nearest neighbour is easy. When working in high-dimensional spaces, instead, this intuition completely breaks down.

To see why, imagine choosing two points completely at random inside a $\boldsymbol{d}$-dimensional unit cube, where each coordinate is selected uniformly and independently. Because the total Euclidean distance between two points is computed across all coordinates, every additional dimension adds another independent difference into the sum. As the number of dimensions $\boldsymbol{d}$ increases, the average squared distance does not stay constant—it grows steadily and linearly with $\boldsymbol{d}$, matching the scaling of the cube's longest diagonal.

The Relative Spread of Distances

Points in high dimensions are, on average, physically far apart from one another. The key problem in high dimensions is not just that points are far apart, but how distances compare to one another. While the average squared distance grows proportionally to $\boldsymbol{d}$, the standard deviation (which measures how much distances vary around that average) grows much more slowly, scaling only with $\sqrt{\boldsymbol{d}}$.

When we look at the **relative spread** (the ratio of the standard deviation to the average), this ratio approaches zero as the number of dimensions increases:

$$\lim_{\boldsymbol{d}\to\infty} \frac{\text{Standard Deviation}}{\text{Mean}} \approx \boldsymbol{O}\left(\frac{\mathbf{1}}{\sqrt{\boldsymbol{d}}}\right) \underset{\boldsymbol{d}\to\infty}{\to}$$

In practice, this means that:

- **The Average Distance grows much faster than the Variation:** Even if the absolute variation between distances grows slightly, it is tiny compared to the massive increase in the average distance itself.
- **Distances Converge Together:** Distances between pairs of points do not spread out. Instead, they end up very close to a single expected value.
- **Distances look almost Identical:** If you plot a chart of distances between random pairs of points, it changes from a wide, informative shape into a sharp, narrow spike. In this spike, almost every pair of points seems to be the exact same distance apart.

Using standard statistical rules like Chebyshev's inequality, we can prove mathematically that random distances are almost guaranteed to be trapped within this very narrow range around their average.

Nearest Neighbor

This clustering of distances creates serious practical problems for computer science algorithms. Classic algorithms rely on a basic assumption: a shorter distance means two points are truly similar.

In high-dimensional spaces, this assumption breaks down:

- **The Closest and Farthest points become Nearly Equal:** For any group of random points, the ratio between the distance to the farthest neighbor and the distance to the nearest neighbor gets closer and closer to 1 as *d* grows:

$$\lim_{\boldsymbol{d}\to\infty} \frac{\text{Distance to Farthest Neighbor}}{\text{Distance to Nearest Neighbor}} = \mathbf{1}$$

- **There is not a “Nearest Neighbour”:** since the closest and farthest points are nearly equal, any the "nearest" neighbor is barely closer to the target point than a randomly chosen point.
- **Distance stops being useful for comparison:** Distance measurements lose their power to tell points apart, making it impossible to reliably know which data points are truly similar and which are not.

The Curse of Dimensionality

This loss of contrast is the exact mathematical reason behind a well-known concept in big data and machine learning:

Def. The **Curse of Dimensionality** describes how distance measurements steadily lose their meaning as the number of features or dimensions ($\boldsymbol{d}$) increases.

Because space concentrates near the outer edges and distances between points converge around their average, our ability to tell "near" and "far" completely disappears. This is not just an empirical rule, it is a geometric fact that actually changes how algorithms must handle data with many features.

Algorithmic Consequences

We say a distance metric **breaks down** in high dimensions when it loses its **discriminative power** — its ability to meaningfully separate "similar" from "dissimilar" points.

It is essential to clarify that the metric itself remains mathematically well-defined (it still satisfies the triangle inequality, non-negativity, etc.). What breaks down is its **usefulness.** The distance metric can no longer distinguish between genuine similarity and simple random noise.

Why the Euclidean Metric Degrades in High Dimensions

The standard **Euclidean Distance** ($\boldsymbol{L_2}$) is especially vulnerable to this degradation because of the way it calculates separation across dimensions. It computes a sum **across all $\boldsymbol{d}$ coordinates**.

In real-world data, instead, useful information is usually contained in only a small subset of meaningful features. As the dimension $\boldsymbol{d}$ grows large, irrelevant coordinates continuously add independent noise.

Q: Alternative Distance Metrics degrades too?

Other common distance metrics show similar issues in high dimensions, although their behaviour differs depending on their definition:

- **Manhattan Distance ($\boldsymbol{L_1}$):** Defined as the sum of absolute coordinate differences, $\sum_{i=1}^{d} |\boldsymbol{x_i} - \boldsymbol{y_i}|$. It displays the same qualitative concentration behaviour as the Euclidean Distance, although empirical studies suggest that its relative discriminative power might degrade slightly more slowly.
- **Chebyshev Distance ($\boldsymbol{L_\infty}$):** Defined by taking only the single maximum coordinate difference, $\max_{i} |\boldsymbol{x_i} - \boldsymbol{y_i}|$. Because it focuses exclusively on the largest single difference rather than summing over all coordinates, it concentrates differently from summation-based metrics.

While the exact rate of decline depends on the metric used, the overall conclusion remains general: high dimensionality degrades distance contrast across all standard geometric measures.

Impact on Machine Learning and Data Mining Algorithms

Because basic machine learning methods rely heavily on geometric distance, this loss of contrast directly damages standard algorithms:

- **Nearest-Neighbor Search:** In tasks like similarity search, the goal is to locate the data items closest to a specific query. When the closest neighbor and the most distant neighbor have nearly identical distances, choosing the top result becomes arbitrary and loses its practical value.

- **Clustering Algorithms (k-means):** Algorithms such as k-means partition a dataset by assigning each data point to its closest centroid. However, if the distance to the assigned centroid is barely smaller than the distance to other centroids or to an average point, these assignments become unstable and produce arbitrary clusters that fail to reflect the real structure of the data.
- **Classification (k-NN Classifiers):** In a k-nearest-neighbor classifier, a test sample is labeled according to the majority class among its closest training neighbors. In very high dimensions, the k chosen neighbors are often only marginally closer than many other points in the training set. Paradoxically, adding more features can reduce classification accuracy because the extra dimensions introduce more noise than useful signal—a direct consequence of the curse of dimensionality.

Algorithmic Solutions

This breakdown does not mean that high-dimensional data cannot be used. Instead, it shows that applying low-dimensional algorithms directly to raw high-dimensional feature spaces will systematically fail. Because modern big data architectures routinely generate high-dimensional embeddings for text, images, and graphs, addressing this challenge is a central requirement in systems design.

To solve this problem, algorithms must avoid computing raw pairwise distances in the original space. This reality motivates two core techniques in big data computing:

1. **Dimensionality Reduction:** Techniques like the **Johnson-Lindenstrauss Lemma** prove that high-dimensional vectors can be mapped into a much lower-dimensional space using random projections while approximately preserving their original pairwise distances.
2. **Locality-Sensitive Hashing (LSH):** Advanced indexing methods that allow systems to perform rapid, approximate similarity searches without calculating every full-dimensional distance explicitly.

Dimensionality Reduction

"You don't need to measure everything precisely — you just need to measure enough, in the right way, to preserve what matters."

As we saw in the last lectures, the Curse of Dimensionality causes that pairwise Euclidean Distances in $\mathbb{R}^d$ converge around the average as d grows. So, the relative gap between near and far distances vanishes invalidating most of the distance-based algorithms (nearest-neighbor search, clustering, classification, etc…).

The Projections solves this problem.

Rather than working in the original $\mathbb{R}^d$ space, suppose we have a function f that maps all n data points into a much lower-dimensional space $\mathbb{R}^k$ with $k \ll d$. We want this function to preserve the geometric structure of the original dataset (specifically, the pairwise distances between points).:

- If x and y are close in $\mathbb{R}^d$ they should remain close in $\mathbb{R}^k$
- If x and y are far in $\mathbb{R}^d$ they should remain far in $\mathbb{R}^k$
- Distance-Based algorithms (nearest-neighbor, clustering, …) operating on $f(x)$ should produce approximately the same result as operating on x directly

Exact Isometry vs Approximate Isometry

Def **A function $f: \mathbb{R}^d \to \mathbb{R}^k$ is an isometry** if it preserves all pairwise distances exactly (e.g., rotations, reflections, translations, …)

$$\|f(x) - f(y)\|_2 = \|x - y\|_2 \quad \text{for all } x, y \in \mathbb{R}^d$$

However, obtaining an exact isometry while strictly compressing the space ($k < d$) is mathematically impossible. So, we relax our requirements to an **approximate isometry**. Instead of requiring exact equality, we allow a small, controlled distortion factor parameterized by $\epsilon \in (0, 1)$:

$$(1 - \epsilon)\|x - y\|_2 \;\leq\; \|f(x) - f(y)\|_2 \;\leq\; (1 + \epsilon)\|x - y\|_2$$

This two-sided inequality ensures that the geometry remains stable:

- The **lower bound** prevents points from collapsing onto each other; points that were originally close cannot become arbitrarily closer.
- The **upper bound** prevents points from expanding too far apart.

For practical tasks, choosing a small tolerance such as $\epsilon = 0.1$ (allowing a 10% relative distortion) is sufficient for downstream algorithms to remain stable and accurate.

Setup for the JL Lemma

The formal framework of the **Johnson-Lindenstrauss (JL) Lemma** considers:

- A finite dataset $S = \{x_1, x_2, \dots, x_n\} \subset \mathbb{R}^d$ of n points.
- We seek a map $f: \mathbb{R}^d \to \mathbb{R}^k$ for some target dimension $k \ll d$
- We want f to satisfy the $(1 \pm \epsilon)$-distortion guarantee holds for **all** $\binom{n}{2}$ possible pairs of points simultaneously.

The central challenge: satisfying this for all pairs simultaneously makes the problem significantly harder than satisfying it for just one pair.

Two Families of Solutions

To understand how the Johnson-Lindenstrauss approach operates, it is helpful to contrast it with classical methods across two main paradigms:

Data-Dependent Methods: Compute the reduction map from the dataset itself. The traditional benchmark for dimensionality reduction is **Principal Component Analysis (PCA)**, typically computed via the **Singular Value Decomposition (SVD)**.

- **Mechanism:** Given a data matrix $X \in \mathbb{R}^{n \times d}$, SVD decomposes the data into singular vectors to find the k orthogonal directions of maximum variance. This provides the optimal rank-k approximation in terms of reconstruction error (measured by the Frobenius norm).
- **Computational Bottlenecks at Scale:** Computing an exact SVD requires a global pass over the entire dataset, with an overall computational cost of approximately $O(nd \cdot \min(n, d))$. Because the projection directions depend on the relationships between all points, the transformation cannot be planned in advance. In distributed computing environments (such as Apache Spark or MapReduce), running distributed SVD requires significant network communication and synchronization to aggregate covariance matrices, making it difficult to scale out efficiently to massive datasets.

Data-Oblivious Methods: Choose the reduction map independently of the data, before ever looking at it. Differently from PCA/SVD, the Johnson-Lindenstrauss Lemma introduces a data-oblivious strategy based on random linear projections:

- **Mechanism:** The projection matrix $\boldsymbol{A}$ is generated completely at random. With high probability, the exact same random matrix works for any arbitrary dataset of size $\boldsymbol{n}$.
- **Efficiency and Parallelism:** Because the matrix is independent of the data, there is no need for global passes, covariance calculations, or eigen decompositions. Projecting a point requires only a standard matrix-vector multiplication costing $\boldsymbol{O(kd)}$ operations. Furthermore, each point can be projected entirely independently, making the method parallel and a natural fit for distributed big data pipelines.

Data Dependent vs Data Oblivious

	PCA / SVD	Random Projection (JL)
Depends on data?	Yes (data-dependent)	No (data-oblivious)
Optimizes for	Reconstruction error	Pairwise distance preservation
Cost	$O(nd \cdot \min(n, d))$, global	$O(kd)$ per point, embarrassingly parallel
Target dimension	Chosen by variance explained	$k = O(\log n/\epsilon^2)$, independent of d
Best suited for	Interpretability, compression, denoising	Fast preprocessing before distance-based algorithms at scale

Random Projections (JL Lemma)

The construction at the heart of JL is elegantly simple: pick a random linear map from $\mathbb{R}^{\boldsymbol{d}} \rightarrow \mathbb{R}^{\boldsymbol{k}}$.

Rather than carefully designing a projection tailored to a specific dataset, simply draw the projection matrix at random. The remarkable fact is that a random projection works well for any dataset, with high probability

This mechanism works because of the geometric properties established in earlier lectures:

- On a high-dimensional unit sphere, surface area concentrates near any chosen equator.
- A randomly selected direction in $\mathbb{R}^{\boldsymbol{d}}$ is nearly orthogonal to any fixed reference vector.
- Because random directions treat all spatial orientations uniformly without bias, a random projection does not distort any single direction more than another.

This equal treatment across all directions is known as **isotropy**. Because the projection is isotropic, it does not favor or distort any single direction more than another, allowing it to preserve distance relationships without examining the data in advance.

Gaussian Projection Matrix

To project data points into a lower-dimensional space, we define a projection matrix $\boldsymbol{A} \in \mathbb{R}^{\boldsymbol{k}\times\boldsymbol{d}}$ whose dimensions match our target dimension $\boldsymbol{k}$ and original dimension $\boldsymbol{d}$. Rather than learning weights, every entry in this matrix is drawn independently from a standard normal distribution:

$$\boldsymbol{A_{ij}} \sim \boldsymbol{\mathcal{N}(0, 1)}$$

Given an input point $\boldsymbol{x} \in \mathbb{R}^{\boldsymbol{d}}$, its projected representation in $\mathbb{R}^{\boldsymbol{k}}$ is obtained by applying the linear transformation scaled by a normalization factor:

$$f(x) = \frac{1}{\sqrt{k}} Ax$$

The choice of standard Gaussian values is deliberate because Gaussian distributions possess **rotational invariance**: any orthogonal transformation of a Gaussian random vector produces another Gaussian random vector with the same distribution.

This means that the distribution of Ax depends only on the original length $\|x\|_2$, not on the direction of x. Consequently, all directions in $\mathbb{R}^d$ are treated identically by the projection (thanks to the isotropy property mentioned before).

Why the Projection Preserves Lengths in Expectation

When projecting vectors into a lower-dimensional space, the mapping must be **unbiased** so that lengths do not systematically shrink or expand. In expectation, the squared length of the projected vector should match the squared length of the original vector:

$$\mathbb{E}\left[\|f(x)\|_2^2\right] = \|x\|_2^2$$

The reason this equality holds is intuitive:

1. **A Single Coordinate Measurement:** Each entry of the projected vector is formed by taking the dot product between a row of the matrix and the vector x. Because the row consists of standard Gaussian values, this operation produces an unbiased measurement whose expected squared value is exactly equal to the original squared length $\|x\|_2^2$.
2. **Summing Across Dimensions:** The projected vector has k dimensions, meaning it combines k such independent measurements. When we sum their squared values to compute the total squared Euclidean norm, the expected result is naturally magnified by a factor of k:

$$\mathbb{E}\left[\|Ax\|_2^2\right] = k \cdot \|x\|_2^2$$

3. **Correcting the Scale:** Because projecting into k dimensions inflates the sum by k, we normalize the projection by dividing the vector by $\sqrt{k}$ (or equivalently, dividing the squared length by k). This normalization cancels out the factor of k, ensuring that the expected length of the projected point matches the original length.

An equivalent way to view this scaling is to notice that projecting from d dimensions down to k dimensions naturally compresses vector lengths by a factor of roughly $\sqrt{k/d}$.

Formulating Pairwise Distance Preservation

In data mining applications, our primary interest is not just preserving single vector lengths, but ensuring that the distances between pairs of points remain stable. Because the projection map f is linear, computing the difference between two projected points $f(x)$ and $f(y)$ is identical to projecting their difference vector directly:

$$f(x) - f(y) = \frac{1}{\sqrt{k}} A(x - y)$$

If we define the difference vector between two points as $u = x - y$, the squared distance between their projected coordinates simplifies to the squared length of the projected difference vector:

$$\|f(x) - f(y)\|_2^2 = \frac{1}{k} \|Au\|_2^2$$

This simplifies the overall analysis: verifying that random projections preserve distances between all pairs of points reduces to proving that the single random variable $\frac{1}{k}\|Au\|_2^2$ stays tightly concentrated around its true squared length $\|u\|_2^2$.

JL Lemma Statement (informally)

The **Johnson-Lindenstrauss (JL) Lemma** provides a powerful mathematical foundation for dimensionality reduction. In simple terms it states:

> For any collection of $\boldsymbol{n}$ points in a high-dimensional Euclidean space there exists a map into $\boldsymbol{O\left(\frac{\log n}{\epsilon^2}\right)}$ dimensions that approximately preserves all pairwise distances up to a $(\mathbf{1} \pm \boldsymbol{\epsilon})$ factor.

NOTE: The target dimension $\boldsymbol{k}$ does not depend at all on the original dimensions $\boldsymbol{d}$. It depends mainly on $\boldsymbol{n}$ (the number of points) and $\boldsymbol{\epsilon}$ (the desired accuracy)

JL Lemma Statement (formally)

The formal theorem establishes the quantitative conditions required for this transformation:

> **Theorem (Johnson & Lindenstrauss, 1984; Dasgupta & Gupta, 2003):** Let $\boldsymbol{\epsilon} \in (\mathbf{0}, \mathbf{1/2})$ represent the allowed distortion tolerance, and let $\boldsymbol{S} = \{\boldsymbol{x_1}, \dots, \boldsymbol{x_n}\} \subset \mathbb{R}^{\boldsymbol{d}}$ be a set of $\boldsymbol{n}$ data points. If we set the target dimension to:
>
> $$\boldsymbol{k} = \left\lceil \frac{\mathbf{24} \ln \boldsymbol{n}}{\boldsymbol{\epsilon}^{\mathbf{2}}} \right\rceil$$
>
> then for a random projection matrix $\boldsymbol{A} \in \mathbb{R}^{\boldsymbol{k} \times \boldsymbol{d}}$ whose entries are drawn independently from a standard normal distribution $\boldsymbol{\mathcal{N}}(\mathbf{0}, \mathbf{1})$, the normalized linear map $\boldsymbol{f}(\boldsymbol{x}) = \frac{\mathbf{1}}{\sqrt{\boldsymbol{k}}}\boldsymbol{Ax}$ satisfies the two-sided distance bound:
>
> $$(\mathbf{1} - \boldsymbol{\epsilon})\|\boldsymbol{x_i} - \boldsymbol{x_j}\|_2 \leq \|\boldsymbol{f}(\boldsymbol{x_i}) - \boldsymbol{f}(\boldsymbol{y_i})\|_2 \leq (\mathbf{1} + \boldsymbol{\epsilon})\|\boldsymbol{x_i} - \boldsymbol{x_j}\|_2$$
>
> for all $\binom{\boldsymbol{n}}{\mathbf{2}}$ pairs of points simultaneously, with a probability of success of at least $\mathbf{1} - \frac{\mathbf{1}}{\boldsymbol{n}}$.

To understand the practical power of the theorem, three aspects of its formal statement are essential:

- **Simultaneous Preservation:** The guarantee does not merely state that a single, typical pair of points will have its distance preserved with high probability. Instead, it guarantees that **every single pair** among all $\binom{\boldsymbol{n}}{\mathbf{2}} \approx \frac{\boldsymbol{n}^{\mathbf{2}}}{\mathbf{2}}$ possible pairs in the dataset satisfies the distortion bound at the same time.
- **High Success Probability $(\mathbf{1} - \mathbf{1}/\boldsymbol{n})$:** The randomness exists purely in the generation of the projection matrix $\boldsymbol{A}$. The theorem ensures that drawing one random Gaussian matrix gives a success probability exceeding $\mathbf{1} - \frac{\mathbf{1}}{\boldsymbol{n}}$. As the dataset size $\boldsymbol{n}$ grows, the probability of failure becomes vanishingly small.
- **Distortion Constraint $(\boldsymbol{\epsilon} < \mathbf{1/2})$:** The error parameter $\boldsymbol{\epsilon}$ is restricted to values strictly below $\mathbf{1/2}$. Allowing excessively large errors would render the preservation bound trivial and useless for downstream algorithms.

The required target dimension $\boldsymbol{k}$ is governed by three primary factors:

1. **The Number of Points $(\boldsymbol{n})$:** As the dataset size grows, more pairwise relationships must be preserved simultaneously, requiring a larger target dimension $\boldsymbol{k}$.
2. **The Accuracy Requirement $(\boldsymbol{\epsilon})$:** Demanding a tighter approximation (a smaller $\boldsymbol{\epsilon}$) requires a higher dimension $\boldsymbol{k}$ to keep distances from distorting.
3. **The Target Dimension $(\boldsymbol{k})$:** The output dimension is calculated directly from $\boldsymbol{n}$ and $\boldsymbol{\epsilon}$.

Most importantly, **the original dimension d does not appear anywhere in the formula for k**. The target dimension depends strictly on the logarithm of the number of points and the inverse square of the distortion parameter:

$$k = O\left(\frac{\log n}{\epsilon^2}\right)$$

[I'm brutally skipping the Proof of the JL Lemma. But you can find it in the Lecture 2.2 Section 4]

Algorithmic Applications

In practical big data pipelines, the JL)Lemma is most commonly used as a lightweight **preprocessing step** before executing more computationally demanding downstream tasks. Rather than feeding high-dimensional vectors directly into algorithms, the workflow follows a sequential structure:

1. **Input Representation:** The dataset begins in a very high-dimensional Euclidean space $\mathbb{R}^d$.
2. **Matrix Generation:** A random projection matrix $A \in \mathbb{R}^{k \times d}$ is generated with independent, identically distributed standard normal entries, $A_{ij} \sim \mathcal{N}(0, 1)$.
3. **Linear Embedding:** Each data vector $x \in \mathbb{R}^d$ is mapped to a low-dimensional representation using the normalized projection $f(x) = \frac{1}{\sqrt{k}} Ax$, landing in $\mathbb{R}^k$ where $k = O(\log n / \epsilon^2)$.
4. **Downstream Execution:** Any standard distance-based method—such as k-nearest neighbors, hierarchical clustering, or k-means—is executed entirely within the target space $\mathbb{R}^k$.

By substituting the original dimension d with a much smaller dimension k, the downstream algorithm operates on a compressed dataset whose dimensionality is often several orders of magnitude lower.

Mitigating the Curse of Dimensionality

Because the JL embedding guarantees that every pairwise distance is preserved within a multiplicative factor of $(1 \pm \epsilon)$, the relative contrast between distinct points is retained. Consequently, the reduced space $\mathbb{R}^k$ acts as a reliable, computationally efficient substitute for the original space $\mathbb{R}^d$, allowing distance-based algorithms to recover their discriminative power at a fraction of the computational cost.

Sparse Rhabdom Projections

Gaussian random matrices require $O(kd)$ random numbers and $O(kd)$ multiplications per point. It is really expensive when d is very large

Sparse Random Projections replace Gaussian entries with sparse alternatives:

$$A_{ij} = \begin{cases} +1 & \text{with probability } \frac{1}{6} \\ 0 & \text{with probability } \frac{2}{3} \\ -1 & \text{with probability } \frac{1}{6} \end{cases}$$

With two-thirds of the matrix entries equal to zero, matrix-vector multiplication speeds up considerably, especially when the input vectors x are already sparse. Despite this simplification, the core JL distance preservation guarantees continue to hold with appropriate scaling.

Fast JL Transform (FJLT)

To accelerate projections on dense inputs, the FJLT replaces the unstructured Gaussian matrix with a structured matrix decomposition $\boldsymbol{A = PHD}$. Where:

- $\boldsymbol{D}$ **is a random diagonal sign matrix** with diagonal entries chosen uniformly from $\{-\mathbf{1}, +\mathbf{1}\}$.
- $\boldsymbol{H}$ **is a normalized Hadamard matrix** that can be applied in $\boldsymbol{O(d \log d)}$ time using a Fast Fourier-like algorithm.
- $\boldsymbol{P}$ **is a sparse random subsampling matrix.**

This reduces projection time from $\boldsymbol{O(kd)}$ to $\boldsymbol{O(d \log d)}$ per point.

Limitations of JL

Although the JL Lemma provides strong mathematical bounds for pairwise Euclidean distances, it is essential to recognize the geometric properties it does **not** preserve exactly:

- **Exact Inner Products:** The dot product between projected points, $\langle \boldsymbol{f(x)}, \boldsymbol{f(y)} \rangle$, approximates the original inner product $\langle \boldsymbol{x}, \boldsymbol{y} \rangle$ via the polarization identity, but it is not preserved exactly.
- **Strict Distance Ordering:** Because every distance is allowed to fluctuate within a $(\mathbf{1} \pm \boldsymbol{\epsilon})$ margin, the relative order of distances can invert for pairs that have very similar original lengths. If two candidate points are nearly tied in distance to a query, their relative ranking can swap in the projected space.
- **Angles Between Vectors:** Angular relationships between vectors are preserved only approximately, subject to small geometric distortions introduced by the projection.

When JL Fails or Is Insufficient

JL is not universal solution. Several settings limit its applicability:

- **Demanding Extreme Precision (Very Small ϵ):** Because the target dimension scales quadratically with the inverse of the error tolerance ($\boldsymbol{k} \propto \boldsymbol{\epsilon^{-2}}$), requiring extremely tight precision (such as $\boldsymbol{\epsilon = 0.001}$) causes $\boldsymbol{k}$ to explode into millions of dimensions. If the calculated target dimension $\boldsymbol{k}$ exceeds the original dimension $\boldsymbol{d}$, applying the lemma is counterproductive.
- **Astronomical Dataset Sizes (Very Large n):** Although the dependence on dataset size is logarithmic ($\boldsymbol{\log n}$), an extraordinarily large number of points (such as $\boldsymbol{n = 10^{100}}$) can push $\boldsymbol{k}$ beyond practical limits.
- **Non-Euclidean Metrics:** The JL Lemma relies strictly on the properties of Euclidean ($\boldsymbol{\ell_2}$) space. It does not provide guarantees for alternative distance functions, such as edit distance or Earth Mover's Distance, which require specialized non-Euclidean embedding techniques.

Choosing the right ϵ

Selecting the distortion parameter $\boldsymbol{\epsilon}$ involves an engineering balance between computational compression and metric accuracy.

ϵ	$k \approx 24 \ln n / \epsilon^2$ (for $n = 10^6$)	Downstream algorithm impact
0.5	~1,327	Very compact; some algorithms sensitive to 50% distortion
0.1	~33,158	Good balance for most distance-based algorithms
0.01	~3,315,800	Tight but k may exceed d — JL becomes unhelpful

In production environments and large-scale data engineering systems, selecting an error tolerance within the range of $\boldsymbol{\epsilon} \in [\mathbf{0.1}, \mathbf{0.3}]$ provides the best practical compromise between memory footprint, runtime efficiency, and model accuracy.

Vector Representation of Text

Machine learning models, similarity search, and clustering algorithms all operate on numerical vectors, not raw symbolic strings. To apply any tool from this course to text, we need a systematic, well-defined map from documents or words into $\mathbb{R}^{\boldsymbol{d}}$

Curse of Dimensionality

In real-world applications, text corpora are massive. Only the English version of Wikipedia contains several million unique tokens. Consequently, since the dimension $\boldsymbol{d}$ is defined as the vocabulary size, text representations operate in spaces with hundreds of thousands or millions of dimensions. This massive dimensionality connects directly to the principles of high-dimensional geometry studied before:

As the dimension d approaches infinity, pairwise Euclidean distances concentrate, causing the relative discriminative power of distance metrics to vanish.

The Vocabulary as a Coordinate System

To construct a vector space for text, we first define a **vocabulary**

$$\boldsymbol{V = \{w_1, w_2, \dots, w_{|V|}\}}$$

which represents the set of all distinct terms appearing across a text corpus. In this coordinate system, each individual dimension corresponds to exactly one unique term from the vocabulary. Consequently, any document or word can be represented as a point or vector in $\mathbb{R}^{|\boldsymbol{V}|}$, meaning that the size of the vocabulary directly defines the ambient dimensionality $\boldsymbol{d = |V|}$.

Bag of Words (BoW)

The simplest and most fundamental approach for representing text is the **Bag-of-Words (BoW)** model in which a document is represented purely by counting the occurrences of each word it contains, while word order is discarded entirely.

$$\mathbf{x}_d \in \mathbb{R}^{|V|}, \qquad x_{d,i} = \text{count of } w_i \text{ in document } d$$

Despite its widespread use, the Bag-of-Words model suffers from several fundamental limitations:

- **Word Order and Syntactic Structure are ignored:** meaning phrases with different word order can yield identical vector profiles. *For example, the phrases "The dog bit the man" and "The man bit the dog" produce identical BoW vectors because word order carries no information in this representation.*

```
Vocabulary:  [the, dog, bit, man, cat, ran, ...]

Document: "the dog bit the man"


Vector:      [ 2 ,  1 ,  1 ,  1 ,  0 ,  0 , ... ]
              the  dog  bit  man  cat  ran
```

- **Polysemy**: words with multiple meanings (e.g., "bank" referring to a riverbank versus a financial institution) cannot be disambiguated because each word form is assigned a single static vector.

One Hot Encoding

At the individual word level, the simplest representation is **one-hot encoding**, where a single word $\boldsymbol{w_i}$ is represented as a standard basis vector $\boldsymbol{e_i} \in \{\mathbf{0}, \mathbf{1}\}^{|V|}$ with a $\mathbf{1}$ at position $\boldsymbol{i}$ and zeros elsewhere.

Every pair of distinct one-hot vectors is orthogonal ($\boldsymbol{e_i} \cdot \boldsymbol{e_j} = \mathbf{0}$ for $\boldsymbol{i} \neq \boldsymbol{j}$) with a unit length ($\|\boldsymbol{e_i}\|_2 = \mathbf{1}$). As a result, this encoding contains no inherent notion of similarity between different words.



Term Frequency - Inverse Document Frequency (TF-IDF)

While the Bag-of-Words (BoW) model provides a straightforward way to map text into numerical vectors, relying solely on raw word counts introduces significant distortions. In natural language, high-frequency function words such as "the," "is," and "of" appear repeatedly across almost every document, even if they carry virtually no additional information about a document's actual topic.

So, if raw counts are used directly, these generic terms dominate the vector values, masking the contribution of meaningful topic-specific words

To solve this problem and to construct a more informative feature space, we require a weighting mechanism that **penalizes terms that appear commonly across the entire corpus** while rewarding terms that appear frequently within a specific document.

Term Frequency–Inverse Document Frequency (TF-IDF) is the classical solution to exactly this problem.

Term Frequency (TF)

The first component of the framework is **Term Frequency (TF)**, which measures how frequently a specific term $\boldsymbol{w}$ occurs inside a given document $\boldsymbol{d}$. To prevent longer documents from producing artificially inflated values simply because they contain more total words, the raw count is normalized by the total number of words in that document:

$$\mathrm{TF}(w, d) = \frac{\mathrm{count}(w, d)}{\sum_{w' \in d} \mathrm{count}(w', d)}$$

Inverse Document Frequency (IDF)

While Term Frequency measures local relevance within a single document, **Inverse Document Frequency (IDF)** evaluates global rarity across the entire collection of documents.

Let $\boldsymbol{N}$ denote the total number of documents in the corpus, and let $\mathrm{df}(\boldsymbol{w})$ represent the number of documents containing w at least once (also named document frequency). The Inverse Document Frequency of term $\boldsymbol{w}$ is calculated as:

$$\mathrm{IDF}(w) = \log\left(\frac{N}{\mathrm{df}(w)}\right)$$

So, IDF(w) is **large** for rare terms (since we have a small df(w)) and approcches zero for terms appearing in nearly every document.

- If df($\boldsymbol{w}$) = $\boldsymbol{N}$: the word w appears in every single document, so $\boldsymbol{IDF(w) = log(\frac{N}{N}) = \log(1) = 0}$. Such terms receive a weight of zero and are completely neutralized.
- If df($\boldsymbol{w}$) = $\mathbf{1}$**:** the word w appears in only one document, we have IDF($\boldsymbol{w}$) = $\boldsymbol{log(\frac{N}{1}) = \log(N)}$ that's the highest possible discriminative weight.

TF-IDF

The final weight assigned to a word $\boldsymbol{w}$ within a document $\boldsymbol{d}$ is obtained by multiplying its local Term Frequency (TF) by its global Inverse Document Frequency (IDF):

$$\textbf{TF-IDF(w, d)} = \textbf{TF(w, d)} \times \textbf{IDF(w)}$$

Using this formula, a document $\boldsymbol{d}$ is mapped to a vector $\boldsymbol{x_d} \in \mathbb{R}^{|V|}$, where each coordinate $\boldsymbol{x_{d,i}}$ = TF-IDF($\boldsymbol{w_i}, \boldsymbol{d}$) provides a refined, topic-sensitive feature representation over the full vocabulary $\boldsymbol{V}$.

TF-IDF Variants

In production retrieval systems, practical variants are frequently used to improve numerical stability:

- **Smoothed IDF:** IDF($\boldsymbol{w}$) = $\boldsymbol{\log\left(\frac{N}{1+\text{df}(w)}\right) + 1}$, which prevents division-by-zero errors when encountering previously unseen words.
- **Sublinear TF Scaling:** TF($\boldsymbol{w}, \boldsymbol{d}$) = $\boldsymbol{1 + \log}$(count($\boldsymbol{w}, \boldsymbol{d}$))), which dampens the impact of repetitive word occurrences within a single document.

TF-IDF Vector Space and Cosine Similarity

Because documents naturally differ in length, their corresponding TF-IDF vectors vary significantly in magnitude. Using raw Euclidean distance to compare two documents can be misleading, as long documents might appear distant from short documents even when discussing identical topics.

To overcome length discrepancies, document similarity is measured using **Cosine Similarity**, which evaluates the angle $\boldsymbol{\theta}$ between two vectors rather than their spatial distance:

$$\boldsymbol{\cos(\theta) = \frac{x_d \cdot x_{d'}}{\|x_d\|_2 \|x_{d'}\|_2}}$$

Cosine similarity normalizes for document length, focusing entirely on the directional orientation of the vectors:

- **A value of $\boldsymbol{\cos(\theta) \approx 1}$ indicates that the vectors point in nearly the same direction**, reflecting high topic similarity.
- **A value of $\boldsymbol{\cos(\theta) \approx 0}$ indicates that the documents share no relevant terms** (the vectors are nearly orthogonal)

Sparse Storage Formats

While the **vocabulary dimension** can expand into millions of coordinates, a typical **document dimension** only contains a few hundred or thousand distinct words.

As a result almost every entry in a document vector x_d is zero

Consequently, storing such high-dimensional sparse vectors as dense arrays would waste immense amounts of computational memory.

Real systems resolve this issue by adopting **sparse storage formats**, which store only (index, value) pairs for non-zero coordinates. This structure ensures that memory usage scales directly with the number of actual words present in a document, rather than the enormeous dimension of the total vocabulary.

Sparsity Induced Near Orthogonality

In high-dimensional sparse representations, metric degradation presents a distinct, sparsity-driven issue known as **sparsity-induced near-orthogonality**.

Because documents contain only a tiny fraction of the total vocabulary, two randomly selected document vectors $\boldsymbol{x_d}$ and $\boldsymbol{x_{d'}}$ usually share very few overlapping non-zero coordinates. The expected coordinate overlap between two sparse documents scales inversely with the vocabulary size:

$$\mathbb{E}[\text{overlap}] \propto \frac{\text{nnz}(\boldsymbol{x_d}) \cdot \text{nnz}(\boldsymbol{x_{d'}})}{|\boldsymbol{V}|}$$

As the vocabulary dimension $|\boldsymbol{V}|$ grows, the expected overlap between vectors decays toward zero. Consequently:

- Two topically related documents that use slightly different words or synonyms will share no common dimensions.
- Under raw term-matching metrics like **Cosine Similarity**, their vectors will evaluate as orthogonal ($\boldsymbol{\cos(\theta) = 0}$), making them appear completely unrelated.
- Sparsity does not eliminate the curse of dimensionality; instead, it relocates the issue by causing topically similar documents to appear dissimilar.

Computational Bottlenecks at Scale

Representing document collections through high-dimensional sparse vectors creates major system-level bottlenecks:

- **Scalability of Storage:** A single sparse vector may be cheap to store, but a massive corpus of $\boldsymbol{10^9}$ documents, each with few hundred non zero entries, still requires between $\boldsymbol{10^{11}}$ and $\boldsymbol{10^{12}}$ distinct (index, value) pairs, introducing significant synchronization challenges across distributed clusters.
- **Computational Cost of Retrieval:** Evaluating all pairwise cosine similarities across a collection of $\boldsymbol{n}$ documents requires $\boldsymbol{O(n^2)}$ vector comparisons, which is computationally intractable for large values of $\boldsymbol{n}$.

The expansion of vocabulary size $\boldsymbol{d = |V|}$ is governed by two empirical laws of natural language processing: Zipf's and Heap's Law.


Zipf's Law

Word frequencies across natural language corpora follow an inverse power-law distribution, where the frequency of any word is inversely proportional to its frequency rank:

$$\text{frequency}(\boldsymbol{w}) \propto \frac{\mathbf{1}}{\text{rank}(\boldsymbol{w})}$$

This distribution creates an extreme structural imbalance:

- A small set of extremely common words (such as "the," "of," and "and") accounts for the vast majority of all word occurrences across a text collection.
- A long set of rare words, that occur only once or twice in an entire corpus, makes up the bulk of the vocabulary.



Heaps' Law

Heaps' Law: vocabulary size grows roughly as $|\boldsymbol{V}| \approx \boldsymbol{K}\boldsymbol{n}^{\boldsymbol{\beta}}$ for corpus of $\boldsymbol{n}$ tokens, with $\boldsymbol{\beta} \in (\mathbf{0}, \mathbf{1})$ typically around $\mathbf{0.4}$ - $\mathbf{0.6}$.

- Differently from many statistical quantities that stabilize with more data, vocabulary size keeps growing as more text is observed (e.g., new rare words, names, typos, … are continually introduced).

This means that the dimension $\boldsymbol{d} = |\boldsymbol{V}|$ is unbounded and continues to expand as datasets grow.

The Distributional Hypothesis

In natural language processing, defining what a word "means" is a complex challenge. Rather than treating meaning as an unobservable mental concept, modern computational linguistics adopts an operational approach known as the **distributional hypothesis**.

"words appearing in similar linguistic contexts tend to have similar meanings"

This principle serves as the conceptual foundation for almost every modern word-embedding technique, including the Word2Vec framework. Under this view, semantic meaning is reframed as a measurable, corpus-derived statistical property.

For example, words like "dog" and "cat" are often surrounded by similar terms (such as "pet," "leash," "litter," or "bark/meow"), leading the model to deduce that they are semantically related based purely on their shared environments.

Context Window

To capture these linguistic surroundings programmatically, we use the concept of a **context window**.

Given a text sequence and a target word $\boldsymbol{w_t}$ located at position $\boldsymbol{t}$, we fix a window size $\boldsymbol{c}$ (for instance, $\boldsymbol{c} = \mathbf{2}$). The **context** of the target word is defined as the set of words falling within $\boldsymbol{c}$ positions on either side of $\boldsymbol{w_t}$:

$$\text{context}(\boldsymbol{w_t}) = \{\boldsymbol{w_{t-c}}, \dots, \boldsymbol{w_{t-1}}, \boldsymbol{w_{t+1}}, \dots, \boldsymbol{w_{t+c}}\}$$

Example: Consider the sentence:

"the quick brown fox jumps over the lazy dog"

with a window size of $\boldsymbol{c} = \mathbf{2}$ and the target word **"fox"**:

context(fox) = {quick, brown, jumps, over}

Then, the pairs: (fox, quick), (fox, brown), (fox, jumps), and (fox, over) form the training data used by predictive models like the Skip-gram architecture.

Semantic and Syntactic Similarity

Co-occurrence patterns capture two distinct dimensions of language structure:

- **Semantic Similarity:** Words with related meanings (such as synonyms or conceptual relatives) appear in overlapping contexts because they describe similar real-world situations and objects.
- **Syntactic Similarity:** Words belonging to the same grammatical categories (such as different verb forms or plural nouns) share distributional patterns because strict grammatical rules govern which words can legally appear near one another.

From Sparse to Dense: Word Embeddings

Instead of one dimension per word in the vocabulary, each word is mapped to a compact, continuous vector $\boldsymbol{v_w} \in \mathbb{R}^{\boldsymbol{d}}$, where the target dimension $\boldsymbol{d}$ typically ranges between $\mathbf{50}$ and $\mathbf{300}$.

```
One-hot ("cat"), |V| = 1,000,000:
[0,0,...,0,1,0,...,0]          ← exactly one nonzero, dimension = 10^6

Dense embedding ("cat"), d = 100:
[0.12,-0.87,0.33,...,0.05,-0.61] ← all 100 dimensions populated
```

Unlike sparse vectors, where nearly all entries are zero, this mechanism reduces the ambient dimensionality by orders of magnitude while capturing rich semantic relationships.

Distributed Representations

In a dense embedding space, individual dimensions do not possess human-interpretable meanings (such as representing a specific word or categorical trait). Instead, the meaning of a word is encoded jointly across the entire pattern of coordinates (a concept known as a **distributed representation**).

Because words with similar meanings are mapped to nearby coordinates within this continuous space, semantic proximity can be measured efficiently using cosine similarity:

$$\cos(\boldsymbol{v_{w_1}}, \boldsymbol{v_{w_2}}) = \frac{\boldsymbol{v_{w_1}} \cdot \boldsymbol{v_{w_2}}}{\|\boldsymbol{v_{w_1}}\|_2 \|\boldsymbol{v_{w_2}}\|_2}$$

Unlike sparse spaces where similarity collapses if two documents or words fail to share exact term matches, dense cosine similarity evaluates semantic closeness even when surface forms differ.

Analogy Arithmetic

One of the most remarkable and unexpected empirical properties of learned word embeddings is their ability to perform **analogy arithmetic**.

Linear vector operations in the embedding space successfully capture complex semantic and syntactic relationships as emergent properties of the training process, without being explicitly programmed into the model. For example:

$$\boldsymbol{v_{king}} - \boldsymbol{v_{man}} + \boldsymbol{v_{woman}} \approx \boldsymbol{v_{queen}}$$

Subtracting the vector *"man"* from *"king"* and adding the vector for *"woman"* yields a vector whose nearest neighbor in the embedding space is *"queen"*. This linear regularity extends across various linguistic dimensions:

- **Gender Relationships:** $\boldsymbol{v_{king}} - \boldsymbol{v_{man}} + \boldsymbol{v_{woman}} \approx \boldsymbol{v_{queen}}$
- **Capital Cities:** $\boldsymbol{v_{Paris}} - \boldsymbol{v_{France}} + \boldsymbol{v_{Italy}} \approx \boldsymbol{v_{Rome}}$
- **Verb Tenses:** $\boldsymbol{v_{walking}} - \boldsymbol{v_{walk}} + \boldsymbol{v_{swim}} \approx \boldsymbol{v_{swimming}}$


These consistent translation vectors illustrate that semantic relationships naturally project onto parallel geometric offsets within a well-trained dense embedding space.

Word2Vec

Def. **The Word2Vec framework constructs dense word vectors** by training a neural model on a self-supervised prediction task.

Rather than computing and materializing an explicit global co-occurrence matrix, Word2Vec learns continuous vector representations as a direct byproduct of predicting surrounding text. The framework proposes two distinct model architectures:

- **Continuous Bag-of-Words (CBOW):** The model receives the embeddings of context words, averages them together, and attempts to predict the word at "the center of the window".



- **Skip-gram:** The model takes a single central target word to predict each context word independently



While both architectures rely on the same underlying vector-learning mechanisms, empirical evaluations show that the **Skip-gram** architecture performs significantly better when handling rare words and training over large datasets.

Skip-gram Optimization Objective

Consider a text corpus represented as a sequence of T words, $w_1, w_2, \dots, w_T$. For a target word w_t at index t, the context consists of all words within a symmetric window of radius c:

$$\text{context}(w_t) = \{w_{t+j} \mid -c \le j \le c,\ j \neq 0\}$$

The objective of the Skip-gram model is to learn vector parameters θ that maximize the average log probability of observing context words given target words across the entire sequence:

$$J(\theta) = \frac{1}{T}\sum_{t=1}^{T}\sum_{\substack{-c\le j\le c \\ j\neq 0}} \log p\left(w_{t+j} \mid w_t; \theta\right)$$

To model the conditional probability $p(w_O \mid w_I)$ of an output context word w_O given an input target word w_I, Word2Vec maintains two distinct vector representations for every vocabulary item $w \in V$:

1. An **input vector** v_w, used when w serves as the target word.
2. An **output vector** v'_w, used when w serves as a context word.
3. The dense embeddings derived from this process are the learned input vectors v_w. Once model training concludes, the auxiliary context vectors v'_w are discarded, and the input matrix containing v_w serves as the final word embedding lookup table for downstream machine learning applications.

Softmax Function

The conditional probability is formally defined using the **Softmax function**, which transforms raw dot-product similarity scores into a valid probability distribution over the full vocabulary:

$$p(w_O \mid w_I) = \frac{\exp\left({v'_{w_O}}^{\top} v_{w_I}\right)}{\sum_{w=1}^{|V|} \exp\left({v'_w}^{\top} v_{w_I}\right)}$$

However, evaluating the standard Softmax function creates an immense computational bottleneck at scale due to the denominator of the Softmax expression: $\exp\left({v'_w}^{\top} v_{w_I}\right)$

To normalize a single probability prediction, the model must compute the dot product and exponentiation for **every single word** in the vocabulary V…. When processing $|V|$ reaches millions of distinct tokens, the computational complexity per parameter update scales as $O(|V| \cdot d)$ making raw softmax computationally intractable.

Negative Sampling (SGNS)

To eliminate the $O(|V|)$ computational bottleneck it was introduced Skip-gram with Negative Sampling.

Instead of framing word prediction as a massive multiclass classification problem over $|V|$ choices, Negative Sampling reformulates the task into a series of independent binary logistic regressions. The model is trained to answer a simple decision question:

Is a given word pair a real observed context pair, or is it random noise?

Let $\sigma(x) = \frac{1}{1+e^{-x}}$ denote the standard logistic sigmoid function. For a true observed pair (w_I, w_O), the single-instance negative sampling loss function is defined as:

$$\log \sigma\left({v'_{w_O}}^{\top} v_{w_I}\right) + \sum_{i=1}^{k} \mathbb{E}_{w_i \sim P_n(w)} \left[\log \sigma\left(-{v'_{w_i}}^{\top} v_{w_I}\right)\right]$$

where k represents the number of randomly sampled "negative" noise words drawn from a noise distribution $P_n(w)$:

- **Positive Alignment:** Maximizing $\log \sigma\left({v'_{w_O}}^{\top} v_{w_I}\right)$ drives the dot product ${v'_{w_O}}^{\top} v_{w_I} \to +\infty$. Geometrically, this rotates the target vector v_{w_I} and the true context vector v'_{w_O} toward alignment, maximizing their cosine similarity.
- **Negative Separation:** Maximizing $\log \sigma\left(-{v'_{w_{neg}}}^{\top} v_{w_I}\right)$ relies on the sigmoid identity

  $$\sigma(-s) = 1 - \sigma(s)$$

  Driving $\sigma(-s) \to 1$ forces the raw dot product $s = {v'_{w_{neg}}}^{\top} v_{w_I} \to -\infty$. Geometrically, forcing the dot product into negative values expands the angle between vectors beyond $90°$, actively pushing random noise vectors away from the target vector.

Without the negative sampling term, all word vectors would trivially collapse onto a single point to maximize positive dot products.

Complete SGNS Objective and Training Algorithm

The final global objective function for **Skip-gram with Negative Sampling** combines these local binary objectives over the entire sequence $\boldsymbol{T}$:

$$J_{\text{SGNS}}(\boldsymbol{\theta}) = \frac{1}{T}\sum_{t=1}^{T}\sum_{\substack{-c\le j\le c\\ j\neq 0}}\left[\log\sigma\left({v'_{w_{t+j}}}^{\top} v_{w_t}\right) + \sum_{i=1}^{k}\mathbb{E}_{w_i\sim P_n(w)}\left[\log\sigma\left(-{v'_{w_i}}^{\top} v_{w_t}\right)\right]\right]$$

In practice, the noise distribution $\boldsymbol{P_n(w)}$ is defined as the corpus unigram distribution raised to the $\boldsymbol{3/4}$ power ($\boldsymbol{P_n(w) \propto U(w)^{3/4}}$). This scaling dampens the dominance of extremely frequent words while slightly inflating the sampling probability of rare words.

Stochastic Gradient Descent (SGD) Implementation

SGNS is trained end-to-end using **Stochastic Gradient Descent (SGD)**:

1. **Window Processing:** The model slides a context window of radius $\boldsymbol{c}$ across the stream of corpus tokens $\boldsymbol{w_1, w_2, \dots, w_T}$.
2. **Noise Sampling:** For each valid target-context pair $\boldsymbol{(w_t, w_{t+j})}$, the algorithm samples $\boldsymbol{k}$ negative noise words $\boldsymbol{w_{1,\text{neg}}, \dots, w_{k,\text{neg}} \sim P_n(w)}$.
3. **Gradient Calculation:** The gradient of the loss with respect to the active target vector $\boldsymbol{v_{w_t}}$ is computed as:

$$\nabla_{v_{w_t}} = \left(1 - \sigma\left({v'_{w_{t+j}}}^{\top} v_{w_t}\right)\right) v'_{w_{t+j}} - \sum_{i=1}^{k}\left(1 - \sigma\left(-{v'}^{\top}_{w_{i,\text{neg}}} v_{w_t}\right)\right) v'_{w_{i,\text{neg}}}$$

4. **Sparse Parameter Updates:** The algorithm executes an in-place gradient step $\boldsymbol{\theta \leftarrow \theta + \eta\nabla_\theta}$ restricted exclusively to the active vectors:

$$\left\{v_{w_t}, v'_{w_{t+j}}, v'_{w_{1,\text{neg}}}, \dots, v'_{w_{k,\text{neg}}}\right\}$$


All other $\boldsymbol{|V| - k - 2}$ vectors in the vocabulary memory matrix remain untouched during the update step.

This sparse update mechanism reduces the per-step training cost to $\boldsymbol{O(k \cdot d)}$, completely decoupling training complexity from total vocabulary size $\boldsymbol{|V|}$ and enabling linear scaling across massive datasets.

Training Word2Vec at Scale

Training word-embedding models on web-scale datasets involves processing billions of tokens. Even though Skip-gram with Negative Sampling (SGNS) reduces the cost of a single update to $\boldsymbol{O(k)}$, multiplying this cost across billions of training pairs requires massive computational infrastructure.

To handle this volume of data, the training corpus is split into disjoint chunks and distributed across multiple machines (directly analogous to MapReduce input splits). Then, each worker computes gradient updates for its local chunk using the SGNS objective.



In addition, to optimize training speed and improve vector quality, frequent function words (such as "the", "a", or "is") are probabilistically discarded during text processing. The probability of dropping a word $\boldsymbol{w}$ is defined as:

$$\boldsymbol{P}(\textbf{discard } \boldsymbol{w}) = \mathbf{1} - \sqrt{\frac{\boldsymbol{t}}{\boldsymbol{f}(\boldsymbol{w})}}$$

where $\boldsymbol{f}(\boldsymbol{w})$ represents the frequency of word $\boldsymbol{w}$ in the corpus and $\boldsymbol{t}$ is a pre-selected threshold. This subsampling mechanism offers two major benefits:

- **It reduces the total number of uninformative pairs** formed by generic words, accelerating overall training throughput.
- **It allows the model to learn more informative vector representations** for less frequent words by focusing computational capacity on meaningful contexts.

Asynchronous Parameter Updates

In a distributed training setup, all worker nodes update a shared set of global words $\{\boldsymbol{v_w}, \boldsymbol{v'_w}\}_{\boldsymbol{w \in V}}$, which is maintained in a shared memory across a Parameter Server cluster.

Rather than coordinating updates through expensive synchronization locks, workers apply asynchronous Stochastic Gradient Descent (SGD) steps directly to the central parameter store:

$$\boldsymbol{v_w} \leftarrow \boldsymbol{v_w} - \boldsymbol{\eta \nabla \mathcal{L}}$$

This asynchronous execution avoids cross-worker blocking delays and relies on two main factors:

1. **Low Memory Contention via Sparsity:** Because negative sampling modifies only $\boldsymbol{k + 2}$ vectors per step (the target word, the true context word, and $\boldsymbol{k}$ negative noise words), workers rarely write to the same parameter locations simultaneously.
2. **Scalable Parameter Synchronization:** By combining cheap local updates with sparse parameter adjustments, the dominant system bottleneck shifts from gradient calculation to memory communication—a problem addressed by asynchronous frameworks such as Hogwild! and Parameter Server architectures.

Tokenization at Scale

Before any text representation model can be constructed, raw text must be split into discrete, manageable units known as **tokens**.

Tokenization choices directly determine the vocabulary size $|\boldsymbol{V}|$ and determines what constitutes an atomic "word" during embedding training.

Word-Level Tokenization

The simpliest approach to tokenization is word-level segmentation, where text is split strictly along whitespace and punctuation boundaries, treating each resulting string as an independent token. However, this approach suffers from a major structural limitation known as the **Out-of-Vocabulary (OOV) Problem**:

- Given a fixed vocabulary $\boldsymbol{V}$ built from a specific training corpus, any new word, typo, or rare noun cannot be mapped to an existing token or embedding.
- Because human language is constantly evolving through the creation of new words, names, and technical terms, no finite or static vocabulary can ever be completely comprehensive.

Subword Tokenization

To overcome the limitations of rigid word-level segmentation, modern text pipelines rely on **subword tokenization**. Instead of treating entire words as atomic units, subword algorithms decompose words into smaller, reusable components. For example, a complex word like:

*"**unbelievable**"*

can be broken down into subword units such as:

"un" + "believ" + "able".

By breaking words into subparts, novel or unseen words can be represented as a sequence of known subword units, which drastically reduces the frequency of out-of-vocabulary errors.

Byte-Pair Encoding (BPE)

Byte-Pair Encoding (BPE) is an iterative compression algorithm adapted for subword tokenization in modern large language models. The construction process follows a systematic workflow:

1. **Initialization:** The vocabulary $\boldsymbol{V}$ is initialized with the characters present in the training corpus + a special end-of-word marker "_"
2. **Select a target budget $\boldsymbol{K}$**: desired number merge operations to perform.
3. **Iterative Merging:** For $\boldsymbol{k = 1}$ to $\boldsymbol{K}$
    1. Count the frequencies of all adjacent symbol pairs across the corpus
    2. Identify the most frequent pair $(\boldsymbol{A}, \boldsymbol{B})$
    3. Create a new merged symbol $\boldsymbol{AB}$ and add it to the vocabulary ($\boldsymbol{V} \leftarrow \boldsymbol{V} \cup \{\boldsymbol{AB}\}$)
    4. In all corpus words, replace occurrences of adjacent *A B* with *AB*
4. **Final Output:** Fixed vocabulary $|\boldsymbol{V}| = |\boldsymbol{V}_{\text{initial}}| + \boldsymbol{K}$ and an ordered list of $\boldsymbol{K}$ merge rules.

Example:

Mini-corpus: `"low_": 5`, `"lower_": 2`, `"newest_": 6`, `"widest_": 3`
Initial tokens: `l o w _`, `l o w e r _`, `n e w e s t _`, `w i d e s t _` ($|V_0| = 11$)

Step	Pair (A, B)	Corpus Count	Action & Vocabulary Update
$k = 1$	`('e', 's')`	$6 + 3 = 9$	Add `es` → words have `... n e w es t _`, `... w i d es t _`
$k = 2$	`('es', 't')`	$6 + 3 = 9$	Add `est` → words have `... n e w est _`, `... w i d est _`
$k = 3$	`('est', '_')`	$6 + 3 = 9$	Add `est_` → words have `... n e w est_`, `... w i d est_`
$k = 4$	`('l', 'o')`	$5 + 2 = 7$	Add `lo` → words have `lo w _`, `lo w e r _`

Inference on unseen text: Replay the K merge rules in exact order:

- Unseen word `"lowest_"` → `l o w e s t _` $\xrightarrow{\text{rule 1,2,3}}$ `l o w est_` $\xrightarrow{\text{rule 4}}$ `['lo', 'w', 'est_']`
- No Out-of-Vocabulary (OOV) error: unmerged letters fall back to atomic characters!

WordPiece Tokenization

Standard BPE can inadvertently merge ubiquitous characters (such as 'e' and 's') simply because they appear together frequently by chance. WordPiece addresses this by selecting candidate pairs using a likelihood-based criterion derived from **Pointwise Mutual Information (PMI)**:

- **WordPiece merge criterion:** Maximizes the language model likelihood of the corpus:

$$\text{Score}(A, B) = \frac{\text{count}(AB)}{\text{count}(A) \times \text{count}(B)} \propto \frac{P(AB)}{P(A) \cdot P(B)}$$

- **Sub-word Continuation Syntax**: Suffix pieces receive ## (e.g. ['un', '##believ', '##able']).
- **Inference without Merge Rules**: Rather than replaying history, WordPiece uses greedy longest-match-first from left to right directly against the final vocabulary

Tokenization Comparison

Granularity	Handles OOV?	Vocabulary size	Sequence length
Word-level	No	Very large, unbounded	Short
Subword (BPE/WordPiece)	Mostly	Fixed, moderate	Medium
Character-level	Yes (fully)	Small, fixed	Very long

Graph Representations

While previous lectures examined vector spaces and text corpora, many real-world complex systems exhibit works with graphs to capture intricate connections, rather than flat vectors.

Def. Formally, a **graph** $\boldsymbol{G = (V, E)}$ is defined by two primary components:

- $\boldsymbol{V}$**:** A set of vertices (nodes), where the total number of nodes is denoted by $\boldsymbol{|V| = n}$.
- $\boldsymbol{E \subseteq V \times V}$**:** A set of edges (links), where the total number of edges is denoted by $\boldsymbol{|E| = m}$, representing pairwise relationships between nodes.

Graphs exhibit structural variations depending on the nature of their interactions:

- **Undirected vs. Directed:** Undirected graphs represent symmetric interactions such as co-authorships or friendships, whereas directed graphs represent asymmetric ties such as hyperlinks, Twitter follows, or financial transfers.
- **Unweighted vs. Weighted:** Graphs can feature binary connectivity or include scalar values $\boldsymbol{w(u, v)}$ indicating bandwidth, interaction frequency, or similarity.

In modern big data systems, graph scales are massive, with $\boldsymbol{|V|}$ over $\boldsymbol{10^9}$ and $\boldsymbol{|E|}$ over $\boldsymbol{10^{11}}$.

Why Graphs?

Standard machine learning models and dimensionality reduction techniques treat data points as fixed-dimensional vectors $\boldsymbol{x} \in \mathbb{R}^{\boldsymbol{d}}$. Graphs, instead, surpass this assumpion for three main reasons:

- **No Uniform Dimensionality:** Vertex neighborhoods vary by orders of magnitude; there is no fixed, universal set of coordinates.
- **Permutation Invariance:** Reordering vertex labels leaves the underlying graph topology completely unchanged, whereas permuting dimensions in a standard vector alters its meaning.
- **Non-Independent Samples:** Traditional machine learning assumes data instances are independent and identically distributed (i.i.d.). In graphs, vertices are explicitly connected, and those structural dependencies form the core analytical signal.

Before applying vector-space machine learning or graph embedding algorithms, we must establish how to efficiently represent and store $\boldsymbol{G}$.

Adjacent Matrix Representations

The canonical mathematical representation of a graph is the **adjacency matrix** $\boldsymbol{A} \in \{\boldsymbol{0}, \boldsymbol{1}\}^{\boldsymbol{n \times n}}$, defined as:

$$\boldsymbol{A_{ij}} = \begin{cases} \boldsymbol{1} & \text{if } (\boldsymbol{i}, \boldsymbol{j}) \in \boldsymbol{E} \\ \boldsymbol{0} & \text{otherwise} \end{cases}$$

The adjacency matrix provides powerful linear algebra tools for theoreticians:

- **Degree Calculation:** Out-degrees and in-degrees can be computed directly as row and column sums ($\boldsymbol{\deg_{\text{out}}(i) = \sum_j A_{ij}}$, $\boldsymbol{\deg_{\text{in}}(j) = \sum_i A_{ij}}$).
- **Path Counting:** The entry $\boldsymbol{\left(A^k\right)_{ij}}$ gives the exact number of distinct walks of length $\boldsymbol{k}$ from node $\boldsymbol{i}$ to node $\boldsymbol{j}$.
- **Spectral Graph Theory:** The eigenvalues and eigenvectors of $\boldsymbol{A}$ (along with graph Laplacians $\boldsymbol{L = D - A}$) uncover connected components, clusters, and random-walk behaviors such as PageRank.

However, beyond its mathematical elegance, storing an adjacency matrix explicitly as a dense two-dimensional array requires $\boldsymbol{O(n^2)}$ space, independently from the number of edges $|\boldsymbol{E}|$.

BUT, even considering just $\mathbf{1}$ bit per entry:

Network Scale	$n = \|V\|$	n^2 Entries	Storage (1 bit/entry)	Feasibility
Campus Network	10^4	10^8	12.5 MB	Trivial (RAM)
Citation Graph	10^7	10^{14}	12.5 TB	Cluster Memory
Web / Social Graph	10^9	10^{18}	**125 PB**	**Catastrophic!**

Even if distributed across $\mathbf{1,000}$ machines, each node would require $\mathbf{125}$ TB of storage purely to hold a matrix where over $\mathbf{99.9999\%}$ of the values are zero… we can do better than this.

Adjacency Lists

To bypass the memory wall of dense matrices, real-world systems use **adjacency lists**, which store only the actual existing neighbors for each vertex: $\text{Adj}[\boldsymbol{i}] = \{\boldsymbol{j} \mid (\boldsymbol{i},\boldsymbol{j}) \in \boldsymbol{E}\}$. This reduces the storage complexity from quadratic to edge-proportional:

$$\text{Space(Adj)} = \boldsymbol{O(n+m)}$$

For a massive social network with $\boldsymbol{n = 10^9}$ nodes, an average degree of $\mathbf{200}$, and $\boldsymbol{m = 10^{11}}$ edges, the comparison is striking:

- **Dense Adjacency Matrix ($\boldsymbol{O(n^2)}$):** Requires $\mathbf{125}$ PB of storage.
- **Adjacency List ($\boldsymbol{O(n+m)}$):** Requires approximately $\mathbf{800}$ GB, which easily fits into the RAM of a single high-end server.

However, different graph representations involve distinct operational trade-offs between memory and query efficiency:


Operation	Dense Matrix (A)	Adjacency List (Adj)
Space	$O(n^2)$	$O(n+m)$
Edge check $(u,v) \in E$?	$O(1)$	$O(\deg(u))$
Enumerate neighbors of u	$O(n)$ (must scan row)	$O(\deg(u))$ (optimal)
Matrix-Vector Mult (Ax)	$O(n^2)$ flops	$O(m)$ flops (only nonzeros)

Compressed Sparse Row (CSR)

To bridge the gap between memory and operations efficiency, production big data frameworks utilize the **Compressed Sparse Row** format, which represents graphs using three contiguous arrays:

- **values**: An array of $\boldsymbol{m}$ elements, containing edge weights of length $\boldsymbol{m}$.
- **col_idx**: An array of $\boldsymbol{m}$ elements, containing target column indices.
- **row_ptr**: An array of $\boldsymbol{n+1}$ pointers marking the start of each vertex's row within the column index array.

This architecture enables efficient $\boldsymbol{O(m)}$ matrix-vector multiplications while eliminating storage overhead for absent edges.



Degree Distributions

To understand the structural properties of large-scale networks, we analyze their **degree distribution** $P(k)$, which represents the fraction of vertices in a graph that have a specific degree k:

$$P(k) = \frac{|\{v \in V : \deg(v) = k\}|}{n}$$

Historically, network science relied on the **Erdős-Rényi** $G(n, p)$ **model** as a naive baseline. In this random model, every pair of nodes is connected with an independent probability p. Consequently, the degree distribution follows a **Poisson distribution**:

$$P(k) \approx \frac{e^{-\lambda}\lambda^{k}}{k!}$$

where $\lambda = (n-1)p$ represents the expected mean degree. A defining characteristic of the Erdős-Rényi model is:

- **concentration**: all nodes are around the mean degree $\overline{k} = \lambda$, and the probability of encountering a node whose degree is substantially larger than the average drops off exponentially fast

However, real-world networks (e.g., the World Wide Web, social media networks, …) never conform to this Poisson behavior.

Power-Law Degree Distributions

Empirical observations reveal that real-world networks follow a **Power Law**. Their degree distribution decays polynomially rather than exponentially:

$$P(k) \sim k^{-\gamma}$$

where the scaling parameter γ typically falls between 2 and 3. When plotted on a log-log scale, a power-law distribution appears linear, satisfying the equation $\log P(k) = -\gamma \log k + \text{const}$. The primary structural features of power-law networks include:

- **Heavy Tails:** The polynomial decay $k^{-\gamma}$ decreases vastly slower than an exponential decay like e^{-k}, allowing for the existence of highly connected nodes.
- **Preferential Attachment:** The underlying generative mechanism is often described by the "rich get richer" phenomenon, where new nodes preferentially connect to existing popular hubs rather than linking uniformly at random.

Non-Uniform Sparsity

The structural density of an undirected graph measures the fraction of possible edges that are actually present relative to the theoretical maximum:

$$r(G) = \frac{m}{\binom{n}{2}} \approx \frac{2m}{n^2}$$


In real-world networks, density is astonishingly low, as illustrated by empirical datasets:

- **Web Graph (Pages):** Features roughly 5×10^{10} vertices and 10^{12} edges, yielding a density of approximately 8×10^{-10}.
- **Twitter / X (Users):** Contains around 5×10^{8} vertices and 5×10^{10} edges, with a density of roughly 4×10^{-7}.
- **Citation Network:** Comprises 10^{8} vertices and 2×10^{9} edges, resulting in a density of approximately 4×10^{-7}.

Rather than having densities of 1% or 5%, real graphs exhibit densities between 10^{-7} and 10^{-10}. They are essentially vast voids punctuated by sparse links and dense superstar hubs. So, structural sparsity is non-uniform due to power-law scaling. Consequently, storing graphs in adjacency lists creates severe operational skews:

- The vast majority of nodes (99%) have very low degrees (deg $= 1$ or 2), requiring minimal memory.
- Conversely, rare hub vertices can possess adjacency lists containing millions of entries, requiring megabytes of memory for a single node.

This imbalance creates major challenges in distributed and multi-threaded processing environments, leading to **straggler effects**. While workers processing average, low-degree nodes finish tasks in milliseconds, a worker assigned to handle a major hub can take hours, causing severe bottlenecks across the entire distributed system.



Graph Partitioning

When analyzing massive networks where vertex counts reach $n = 10^{10}$ and edge counts surpass $m = 10^{12}$, storing an entire graph in a single machine's memory becomes impossible. Even compact representations like adjacency lists or Compressed Sparse Row (CSR) formats expand to hundreds of gigabytes or terabytes, forcing iterative algorithms to run across distributed computing clusters.


Because graphs cannot fit onto a single node, they must be divided across k worker machines. An effective partitioning strategy must achieve two primary objectives:

1. **Load Balancing:** Distribute data storage and computational workload across all available workers
2. **Minimize Communication:** Minimize edges or vertices that cross machine boundaries, preventing network shuffle bottlenecks

However, finding an optimal graph partitioning is a computationally intractable NP-hard problem. Consequently, real-world systems rely on structural heuristics.

Strategy 1: Edge-Cut Partitioning (Vertex Assignment)

The traditional approach is **edge-cut partitioning**, where the set of vertices is divided into k disjoint subsets assigned to different machines. Then, an edge is considered a **cut edge** if its two endpoints reside on separate machines, and the main optimization objective is to minimize the total number of cut edges across the cluster:



This approach performs well on uniform, planar, or grid-like graphs, where node degrees are strictly bounded. But it catastrophically fails when applied to power-law networks containing massive hubs.


If a hub vertex h has a degree of 10^6, assigning it to Machine 1 means that nearly all of its incident edges connect to nodes residing on other machines. This creates two irreconcilable problems:

1. **Massive Communication Bottleneck:** Every cut edge requires remote procedure calls (RPCs) across the network, saturating Machine 1's network interface.
2. **Incompatible Trade-offs:** If the partitioner attempts to balance the number of vertices per machine, Machine 1 is forced to process 10^6 edges while other machines handle only a few hundred, causing extreme computational imbalance. Conversely, if it attempts to balance edge counts by isolating the hub on its own machine, that machine becomes a severe network bottleneck.

Strategy 2: Vertex-Cut Partitioning (Edge Assignment)

To overcome the limitations of edge-cut partitioning, modern big data frameworks invert the approach using **vertex-cut partitioning**. Instead of dividing vertices, we divide the edges.

When an edge is assigned to a machine, its endpoints must also be present on that machine. Consequently, vertices that possess many incident edges (e.g., high-degree hubs) are **replicated** across multiple machines.



At this point, we have to maintain a consistent state across the cluster. To do it, we use a **Master-Mirror synchronization mechanism**:

1. **Designated Master Replica:** Out of all the machine replicas for a given vertex, one is designated as the master replica, while the others act as read/compute mirrors.
2. **Local Computation:** During an iterative algorithm (like PageRank or a graph neural network), each machine processes local edge data independently using its local mirror of the vertex.
3. **Aggregated Syncing:** Instead of sending separate network messages for every single edge or individual update, each machine aggregates its local changes or computations for the mirror.
4. **Final Reduction:** At the end of the computational step, a single aggregated value is sent across the network from each mirror back to the master replica to update the global state.

This approach replaces $O(\deg(h))$ individual edge communication messages with an efficient $O(k)$ synchronization step (where k is the number of machine replicas)

Edge-Cut vs Vertex-Cut

The structural differences between the two partitioning paradigms are summarized below:

Property	Edge-Cut (Vertex Partitioning)	Vertex-Cut (Edge Partitioning)
What is divided?	Vertices are partitioned ($V_i \cap V_j = \emptyset$)	Edges are partitioned ($E_i \cap E_j = \emptyset$)
What crosses nodes?	Cut edges	Vertex replicas / mirrors
Communication cost	Proportional to number of cut edges	Proportional to replica factor $\times \lvert V \rvert$
Behavior on Hubs	**Terrible:** hub machine overwhelmed	**Excellent:** hub edges divided evenly
Target Workload	Road networks, finite-element meshes	**Social networks, Web graphs (Power-Law)**


Advanced big data graph processing systems—such as **PowerGraph (GraphLab)** and **Spark GraphX**—specifically adopt vertex-cut partitioning to handle web-scale analytics efficiently.

Node Embeddings

While text representations transition from sparse Term Frequency-Inverse Document Frequency (TF-IDF) vectors to dense Word2Vec embeddings, graph structures present a unique challenge due to their irregular, non-Euclidean nature.

Consequently, node embedding techniques aim to map each vertex of a graph into a compact, continuous vector space in which topological similarity is directly mirrored by geometric proximity.

Formally, node embedding is defined as a mapping function $\boldsymbol{z}: \boldsymbol{V} \rightarrow \mathbb{R}^{\boldsymbol{d}}$ that takes the vertex set $\boldsymbol{V}$ as input and embeds it into a $\boldsymbol{d}$-dimensional vector space (where the target dimension $\boldsymbol{d} \ll |\boldsymbol{V}|$, typically around $\mathbf{128}$)



An effective graph embedding must capture multiple layers of structural information:


- **First-Order Proximity (Direct Proximity):** If an edge $(\boldsymbol{u}, \boldsymbol{v}) \in \boldsymbol{E}$ exists, their corresponding embedding vectors should be close, resulting in a large dot product $\boldsymbol{z_u^\top z_v}$
- **Second-Order Proximity (Neighborhood Overlap):** If two nodes $\boldsymbol{u}$ and $\boldsymbol{v}$ share many common neighbors (even if no direct edge connects them) their embeddings should remain close.
- **Community Structure (Homophily):** Nodes belonging to the same dense cluster or local subgraph should map to tightly knit geometric clusters in $\mathbb{R}^{\boldsymbol{d}}$.
- **Structural Equivalence (Roles):** Nodes that occupy identical topological positions in distant parts of the graph (such as central hubs or network bridges) should receive similar representations.

DeepWalk

The **DeepWalk framework** introduced a foundational insight: graph topologies can be translated into linear sequences analogous to sentences in natural language. By executing **random walks** across the graph, a sequence of visited node IDs is generated:

$$v_1 \rightarrow v_2 \rightarrow v_4 \rightarrow v_5 \rightarrow v_2 \rightarrow v_3$$

Once these graph "sentences" are generated, DeepWalk applies the **Skip-gram with Negative Sampling** algorithm (even if it was originally developed for text embeddings).



Consequently, if two nodes are topologically close, random walks visit them in proximity, causing them to appear within the same context window and pulling their embedding vectors together via gradient descent.

Node2Vec

While DeepWalk relies on uniform random walks, real-world networks require balancing two distinct notions of similarity:

- **Homophily**: Nodes belonging to the same dense cluster or local subgraph should map to tightly knit geometric clusters in $\mathbb{R}^d$.
- **Structural Equivalence**: Nodes that occupy identical topological positions in distant parts of the graph (such as central hubs or network bridges) should receive similar representations.

node2vec addresses this by introducing a second-order random walk controlled by two parameters, p and q. Suppose a random walk has just traversed an edge $(t \rightarrow v)$ and currently resides at node v. The unnormalized transition probability π_{vx} to the next candidate node x is defined as:

$$\pi_{vx} = \alpha_{pq}(t,x) \cdot w_{vx}$$

where w_{vx} represents the edge weight, and the search bias $\alpha_{pq}(t,x)$ is determined by the shortest path distance $dist(t,x)$ between the previous node t and candidate x:

$$\alpha_{pq}(t,x) = \begin{cases} \frac{1}{p} & \text{if } dist(t,x) = 0 \\ 1 & \text{if } dist(t,x) = 1 \\ \frac{1}{q} & \text{if } dist(t,x) = 2 \end{cases}$$

- **Value p:** Controls the likelihood of immediately revisiting the previous node t.
  - **Low p ($p < 1$):** Walk tends to return to the node it just left. Keeps the walk local (BFS-like) encouraging micro-neighborhood homophily.
  - **High p ($p > 1$):** Encourages discovering new nodes.

- **Value q:** Controls the likelihood of moving outward to unvisited nodes.

- **Low q ($q < 1$):** Walk aggressively goes away from t towards unvisited nodes (DFS-like). Useful to discover global structure roles (bridges, hubs, etc…)
- **High q ($q > 1$):** Walk stays confined to nodes connected to t. Encourages local cluster membership

By tuning (p, q) node2vec seamlessly interpolates between community detection and role discovery!

Matrix Factorization

Alternative approaches derive graph embeddings by factorizing graph proximity matrices directly, thanks to matrix factorization techniques such as Singular Value Decomposition (SVD). In this way, proximity matrices $S \in \mathbb{R}^{n \times n}$ are decomposed into lower-dimensional factors.

Theoretical frameworks like NetMF demonstrate that DeepWalk is implicitly factorizing a shifted Pointwise Mutual Information (PMI) matrix derived from graph transition probabilities:

$$S_{ij} = \log\left(\frac{\sum_{r=1}^{c}(P^r)_{ij}}{\sum_k \sum_{r=1}^{c}(P^r)_{kj}}\right) - \log(k_{\text{neg}})$$

Applications and Challenges


Once node embeddings $z_v \in \mathbb{R}^d$ are learned, they serve as continuous feature vectors for standard machine learning pipelines:

1. **Link Prediction:** Estimating the likelihood of an edge existing between two nodes
2. **Node Classification:** Feeding node vectors into classifiers to predict labels like fraud or user churn.
3. **Graph Clustering:** Applying k-means clustering directly on the embedding vectors to identify communities without expensive combinatorial graph cuts.

Despite these computational advantages, embeddings do not eliminate underlying distributed systems challenges. Generating massive random walks requires distributed graph traversal over vertex-cut clusters, updating vector parameters requires asynchronous frameworks, and storing one billion node vectors in 32-bit floating-point precision demands substantial memory resources.

Web-Scale Search

While earlier modules taught us how to represent data, we now face a much harder question: once billions of documents are represented, how do we actually find anything, in milliseconds, at planetary scale?




The architecture of a web-scale retrieval pipeline is divided into offline processing and online execution. Raw documents are first crawled, processed through sorting and MapReduce jobs, structured into an inverted index, and compressed before being deployed to serve incoming queries in under two hundred milliseconds.

Web-Scale Retrieval Problem

Formally, given a massive text corpus $\mathcal{D}$ consisting of N documents and an incoming query q composed of terms $(t_1, \ldots, t_{|q|})$, a search engine must execute the retrieval function:

$$\text{Retrieval}(q, \mathcal{D}) \rightarrow \mathcal{R}_k$$

to return a compact subset of the k most relevant documents, ranked from best to worst, where $k \ll N$ (typically representing the top 10 or 20 results).



All of this without examining all the documents. The query time must be strictly sub-linear in N and planetary-scale search imposes strict Service Level Objectives (SLOs):

- **Corpus Size:** Managing tens of billions of documents ($N \approx 10^{10}$).
- **Throughput:** Handling tens of thousands of incoming queries every second (10^4 queries/s).
- **Latency Budget:** Maintaining an ultra-strict P99 latency budget of no more than 200 ms per query.

If a search engine were to evaluate a query using a naive linear scan, the computational cost would scale as $O(N \cdot L)$, where $L \approx 10^3$ tokens per document. For a corpus of 10^{10} documents, this requires scanning approximately 10^{13} tokens per query—translating to hundreds of terabytes per second of memory bandwidth.

Because such linear scans are physically infeasible within a 200 ms window, the system must rely on precomputed index structures that avoid examining every document in the corpus. Instead, query processing must operate in sub-linear time relative to N.


Sub-Problems of Retrieval

To achieve sub-linear query times, web-scale retrieval decomposes it into two distinct operational phases:

1. **Candidate Selection:** The system rapidly determines which documents contain any of the query terms at all, filtering the massive corpus of documents down to a manageable pool of candidates $\mathcal{C}_q$. This phase is solved using an inverted index combined with sorted posting list merges.
2. **Relevance Scoring:** Among the filtered candidate pool, the system evaluates which documents are most relevant to the user's intent. This involves computing statistical and geometric relevance scores (such as TF-IDF, BM25, and cosine similarity).

Crucially, the inverted index provides a unified data structure that supports both rapid candidate filtering and precise relevance scoring.

Content vs Structure




Modern search engines do not rely solely on raw text matching; instead, they combine:

- **Structural Authority (Offline):** Using the web graph, systems can compute query-independent authority parameters before the actual search happens, also allowing to store and re-use these metrics in future queries.
- **Textual Relevance (Online):** Using the text content of web pages, systems compute specific query-dependent relevance scores in milliseconds.

By combining these offline structural priors with online text relevance, search engines achieve both semantic accuracy and global web-scale authority.


Inverted Index



To retrieve relevant documents from a massive corpus without executing computationally prohibitive scans, search engines rely on an inverted architecture.

- **Forward Index**: The traditional document-centric view, which maps individual documents to the terms they contain. Even if it seems natural for document storage, in this scenario answering a query like *"Which documents contain data?"* requires scanning every single document.
- **Inverted Index**: To bypass the forward index inefficiency, the inverted index maps each term to its corresponding list of documents.

Dictionary and Posting List




An inverted index consists of two tightly coupled components that separate term metadata from document references:

1. **The Dictionary:** Maintained entirely in RAM for rapid access, the dictionary stores each distinct vocabulary term, its document frequency $\boldsymbol{df}$, and a pointer to its posting list.
2. **The Posting Lists:** For each unique term, the corresponding posting list contains a sequence of postings represented as tuples $(\boldsymbol{docID},\ \boldsymbol{tf}_{\boldsymbol{t,d}})$ where:
    1. $\boldsymbol{docID}$: is the document identifier
    2. $\boldsymbol{tf}_{\boldsymbol{t,d}}$: is the local frequency of term $\boldsymbol{t}$ in document $\boldsymbol{d}$

    These tuples are strictly sorted by $\boldsymbol{docID}$. This is essential because it enables rapid linear merges during multi-term query processing.


Sparse Matrix Perspective and CSR Analogy

The inverted index can be represented mathematically as a **term-document incidence matrix A**, where rows are terms and columns are documents. An entry is set to $\mathbf{1}$ if term t appears in document d, and $\mathbf{0}$ otherwise.




But, at web scale, this incidence matrix contains approximately $\mathbf{10^{17}}$ cells, of which over $\mathbf{99.995\%}$ are zeros.

So, as we already seen with graphs, storing such a matrix is a waste of memory and the real systems use a format equivalent to **Compressed Sparse Row (CSR)**: each posting list explicitly stores only the non-zero coordinate entries for a given term row.



Index Construction Pipeline

Transforming raw web crawls into a structured inverted index requires a clear rigorous pipeline:



And raw text must be converted into standardized search terms:


- **Tokenization:** divides the raw text streams into discrete units along whitespace and punctuation boundaries (carefully handling edge cases such as email addresses, URLs, etc…)
- **Normalization and Stemming:** Implements case folding (converting uppercase characters to lowercase) and stemming algorithms to strip suffixes and conflate morphological variants (e.g., mapping *"computing"* and *"computed"* to the common stem *"comput"*). This prevents vocabulary fragmentation and explosive dimensional growth.
- **Stopword Handling:** Highly frequent function words (such as *"the"* or *"in"*) are either filtered out entirely or specially compressed to optimize storage and retrieval performance.

Once normalized, text streams are converted into flat key-value pairs of $(\boldsymbol{term}, \boldsymbol{docID})$ tuples.

MapReduce for Index Construction

Once tokens are paired into $(\boldsymbol{t}, \boldsymbol{d})$ tuples, index creation is fundamentally a sorting problem. However, since $\boldsymbol{K}$ far exceeds the RAM capacity of any single machine, index creation must rely on distributed sorting infrastructure. The standard solution maps index construction directly onto the **MapReduce** framework:

- **Map:** Each mapper parses its local blocks and emit (term, docID) pairs.
- **Shuffle and Sort:** The framework routes all pairs of a term to a designated reducer, automatically sorting them by $\boldsymbol{docID}$.
- **Reduce:** Each reducer writes the posting list of its terms.



Posting List Compression


At planetary scale, managing an inverted index containing billions of documents and trillions of postings introduces severe hardware constraints. With a corpus size of $N \approx 10^{10}$ documents and approximately 10^{12} total postings, storing raw 64-bit document IDs alone requires 8 TB of memory. When incorporating term frequencies and positional data, the uncompressed index expands to tens of terabytes.

To meet the strict 200 ms per query requirement, the active index must reside entirely in RAM. Compression is therefore not merely a storage optimization; it is an economic and architectural necessity that makes keeping the active index in cluster RAM feasible.

Gap Encoding

To reduce the memory footprint of posting lists, search engines exploit the fact that posting lists are strictly sorted by docID. So, instead of storing raw, absolute docID values, systems only store the gaps between them.


The first document ID is stored directly ($\Delta_1 = d_1$), while all subsequent entries are stored as the integer difference between consecutive document IDs ($\Delta_i = d_i - d_{i-1}$).



However, since frequent terms appear across a vast number of documents, their average gap size is extremely small, scaling inversely with document frequency. For example, a term appearing in 10^8 out of 10^{10} documents yield an average gap of approximately 100, which can be represented using only 7 bits instead of 64 bits. While rare terms exhibit larger gaps, their posting lists are inherently short, keeping their total memory impact minimal.

Variable-Byte Encoding (VB)


To serialize these gaps efficiently, systems utilize **Variable-Byte (VB) Encoding** which represents each integer using a sequence of bytes where the most significant bit serves as a continuation flag (1 indicating that more bytes follow, and 0 marking the final byte), leaving the remaining 7 bits as the numerical payload.



This byte-aligned structure permits rapid CPU decoding without complex bit-shifting operations. More advanced compression schemes, such as **Rice and Golomb coding**, achieve even higher compression ratios, allowing raw indexes to fit comfortably within cluster RAM.


Boolean Retrieval and Skip Pointers

Once the index is built and compressed, query processing begins with **Boolean Retrieval**, which evaluates logical conditions such as intersections (AND) and unions (OR).



However, when query terms differ wildly in frequency (e.g., intersecting a rare term with a highly frequent term) scanning the entire long posting list becomes wasteful.

To optimize this, search engines embed **skip pointers** at regular intervals along long posting lists. When merging lists, if the skip target value is less than or equal to the desired search value, the algorithm jumps ahead across the block; otherwise, it performs a local scan.



Ranked Scoring

While Boolean retrieval successfully filters the corpus, a web query may match millions of documents while users only review the top results. Consequently, retrieval engines must transition from unranked filtering to **Ranked Retrieval**.

By representing queries and documents as **TF-IDF vectors**, relevance is quantified using **cosine similarity**., that, for a fixed query, can be simplified to computing a normalized dot product across matching terms:


$$\text{score}(\boldsymbol{q}, \boldsymbol{d}) \propto \sum_{t \in q \cap d} \boldsymbol{w}_{t,q} \cdot \boldsymbol{w}_{t,d}$$

NOTE: The inverted index already contains everything a cosine score needs: local term frequencies are stored in the posting lists and global document frequencies reside in the dictionary.

TAAT vs DAAT


To accumulate partial relevance scores across candidate documents, search engines adopt one of two primary architectural paradigms:

- **Term-at-a-Time (TAAT):** The outer loop iterates over each query term. The system maintains an array of accumulators $A[d]$ for candidate documents, reads the entire posting list for a given term, updates the partial scores for matching documents, and repeats the process until all query terms are processed before normalizing and extracting the top-k results.



While TAAT benefits from perfectly sequential reads, its primary drawback is memory exhaustion caused by maintaining an accumulator for every document touched by any query term.

- **Document-at-a-Time (DAAT):** The outer loop iterates over documents in lockstep across all query term posting lists using individual pointers. The system identifies the smallest $docID$, computes its final composite score immediately, and maintains a min-heap of size k to track top results.




DAAT requires minimal memory and enables advanced **early termination** algorithms to bypass unpromising posting list segments, making it the dominant architecture in modern web-scale engines.

Distributed Index Partitioning

Even with 8× compression, an inverted index for 10^{10} documents requires multiple terabytes of memory. Furthermore, production web search engines must process tens of thousands of concurrent queries every second under strict Service Level Objectives (SLOs).


Consequently, maintaining an index on a single machine is computationally and economically impossible; the index must be partitioned and sharded across multiple worker nodes. The main techniques are:

- **Document Partitioning:** Each machine contains the entire inverted index for its assigned documents.
- **Term Partitioning:** The vocabulary V is partitioned across machines, meaning each worker node holds the entire posting list for a specific subset of terms across all N documents in the corpus.



Document Partitioning

Because document assignment across shards is performed without prior knowledge of term content or document relevance, the query router cannot predict which shard holds the highest-scoring pages for an incoming query q.



As a result, query processing proceeds through a two-stage broadcast and merge pipeline:

1. **Query Broadcast:** The query router broadcasts the query q simultaneously to all K worker shards.
2. **Local Execution:** Each shard independently evaluates the query over its local index using TAAT or DAAT and extracts only its local top-k documents.
3. **Global Aggregation:** Each shard returns its local top-k list of ($docID$, *score*) tuples to a centralized aggregator. The aggregator uses a min-heap data structure of size k to merge the incoming $K \times k$ candidate tuples and determine the final global top-k results.

This setup keeps network overhead minimal during the aggregation phase because, rather than transferring full document texts or posting lists, the system only transmits $K \times k$ numerical tuples.


Advantages: Document partitioning is the industry-standard architecture for high-throughput, web-scale search engines due to several key advantages:

- **Zero Inter-Node Communication During Scoring:** Shards execute candidate selection and relevance scoring entirely in parallel without exchanging intermediate state or posting lists across worker nodes.
- **Scalability:** As the corpus expands, new documents can be indexed by adding new worker shards to the cluster without re-indexing existing shards.
- **High Fault Tolerance:** If a single worker shard fails, the system loses access to only a fraction ($\mathbf{1}/\boldsymbol{K}$) of the total document collection, allowing the engine to return partial results gracefully.

Disadvantages:


- **Computational Overhead:** Every incoming query must be broadcast to all shards, which multiplies the total cluster effort.
- **The Straggler Problem:** End-to-end query latency is governed by the slowest-responding shard in the cluster.
- **Increased Latency Spikes:** As the cluster grows, the probability that at least one worker experiences a transient latency spike (due to hardware jitter, garbage collection, or memory contention) increases significantly.
- **Long-Tail Latency Challenge:** Managing long-tail latency across thousands of shards remains a key system design hurdle in real-world deployments.

NOTE: Visualization of the Straggler Problem



Term Partitioning

In a term-partitioned architecture, each worker machine is assigned a specific subset of terms (for example, alphabetically or via a hash function over the term string). Crucially, a machine holding a specific term stores its **complete, global posting list** covering all N documents in the corpus.



The primary apparent advantage of term partitioning is avoiding cluster-wide query broadcasting. When a multi-term query such as "search" AND "engine" enters the system, the query router contacts only the specific nodes responsible for those terms (e.g., Machine 1 for "engine" and Machine 3 for "search"), leaving unrelated nodes idle and available for other tasks.

However, term partitioning suffers from a **critical performance flaw** when executing multi-term queries. To compute an intersection (AND) or union (OR) across multiple terms, their respective posting lists must be evaluated on the same machine. Consequently, one node must transmit its entire posting list (millions of docIDs) across the network, completely destroying the 200ms latency budget.




NOTE: In document partitioning, instead, scoring is executed locally on each shard, and workers transmit only a tiny payload of k numerical ($docID$, score) tuples to the aggregator.

Workload Imbalance

Term partitioning also introduces severe load-balancing issues caused by natural language term distributions.

Following the **Zipf's Law**, a few terms (e.g., "web" or "news") dominate postings and queries causing their nodes to become bottlenecks, while rare words nodes remain idle (e.g., the nodes containing “xylophone”)



Conversely, document partitioning distributes documents uniformly across shards (via hashing or random assignment), ensuring near-perfect load balance across all machines ($1/K$ load per shard).

Doc vs Term Partitioning


The trade-offs between document partitioning and term partitioning are summarized below:

	Document partitioning	Term partitioning
Partitioning key	doc ID range / hash	term range / hash
Query routing	broadcast to all K shards	only the |q| term shards
Inter-node traffic	small top-k lists	full posting lists
Load balancing	uniform	Zipf-skewed
Fault isolation	lose 1/K of the docs	lose queries with that term
In practice	standard in web search	specialized systems

Because network bandwidth is the primary bottleneck in web-scale clusters, modern distributed search engines almost universally adopt **Document Partitioning** over Term Partitioning.

End-to-End Distributed Search Infrastructure

To build a fully functional, web-scale search engine that operates within strict latency budgets, the distributed components of the system must be assembled into a cohesive pipeline.




When a user submits a query:

1. **Front-End Cache Check:** The query first encounters a front-end result cache designed to serve popular searches almost instantaneously. If the query has been processed recently, the system immediately returns the saved response without touching the main servers, ensuring near-zero latency.
2. **Query Routing:** If a cache miss occurs, the query is forwarded to a query router, which distributes the workload across a cluster of replicated shards.
3. **Local Shard Evaluation:** Each shard evaluates the query locally in its local index to produce a list of k best candidates.
4. **Aggregation and Scoring:** An aggregator collects the local top results and merges them with global authority scores to re-rank the overall best matches accurately.
5. **Result Delivery:** The final ranked results are returned to the user.

Caching Strategies

Web search traffic closely follows a **Zipf-like distribution**, where a small set of queries most of the user requests, while the vast majority of queries form a sparse long tail.




Search engines exploit this behaviour using:

- **Query Result Cache:** Maps normalized queries directly to their precomputed top-k results, successfully serving 30% to 50% of total traffic in under 5 ms.
- **Posting-List Cache:** Stored locally on each shard, this tier maintains decompressed versions of frequently accessed hot posting lists to avoid repetitive decompression overhead.
- **Compressed Index:** The underlying storage layer holding the full set of compressed posting lists for the long tail of queries.

Replication, Throughput, and Fault Tolerance

To ensure high system availability and handle massive concurrent query volumes, every document shard is copied R times across different physical racks in the data center. This **replication strategy** provides two major operational benefits:

- **Throughput Scaling:** System query throughput scales linearly with the replication factor R, multiplying shard capacity (e.g., $R = 3$ yields three times the processing throughput).
- **Fault Tolerance:** If a server hosting a specific shard replica crashes, incoming traffic automatically fails over to alternative replicas in other racks, ensuring zero downtime. This mechanism mirrors the block replication principles found in distributed file systems like GFS and HDFS.



PageRank


In previous lectures we answered the question: "which pages match this query?". However, thousands of pages may match equally well. Today we ask a different question about the same crawl:

"Which pages deserve to be on top?"


Def. PageRank (PR) is an algorithm used by Google Search to rank web pages in their search engine results

PageRank evaluates the importance of a web page using two primary intuitions:

1. **Links as Votes:** Every hyperlink pointing from a web page w to a page v is treated as a vote of confidence for v. The more incoming links (in-links) a page accumulates, the higher its importance.




2. **Unequal Vote Weight:** Not all votes carry equal value. An incoming link originating from an authoritative or "famous" page contributes significantly more than numerous links originating from obscure pages.



Because determining which pages are important requires knowing the importance of the pages pointing to them, PageRank establishes a **recursive definition** of authority.

Example: Let's assume a small web, with only 11 pages.



In this scenario, B has 10 in-links, E has 6, and C only 1… However, C is still second over E, because it has ony one vote, but it comes from the important page B.

From Votes to Equations

To translate the intuitive concept of "links as votes" into a rigorous mathematical framework, we have to model the World Wide Web as a directed graph $\boldsymbol{G} = (\boldsymbol{V}, \boldsymbol{E})$, where $\boldsymbol{V}$ represents the set of all web pages, and $\boldsymbol{E}$ denotes the set of directed hyperlinks connecting them. For any individual page $\boldsymbol{v} \in \boldsymbol{V}$, we define key structural attributes:

- **Out-Link Set ($\boldsymbol{O_v}$):** The set of pages that page $\boldsymbol{v}$ links to.
- **Out-Degree ($\boldsymbol{o_v}$):** The total number of outgoing links from page $\boldsymbol{v}$, denoted as $\boldsymbol{o_v} = |\boldsymbol{O_v}|$.
- **In-Link Set ($\boldsymbol{I_v}$):** The set of pages that point via hyperlinks to page $\boldsymbol{v}$.
- **Page Rank ($\boldsymbol{r_v}$):** A numerical value quantifying the global importance or authority of page $\boldsymbol{v}$.

Flow Model


The foundational mechanics of PageRank operate on a conservation principle often referred to as the **flow model**. Authority flows through the graph according to two fundamental rules:

1. **Rank Splitting:** Each web page divides its total importance score equally among all of its outgoing links. Consequently, if a page $\boldsymbol{w}$ points to $\boldsymbol{o_w}$ pages, each page receives a fractional vote equal to $\frac{\boldsymbol{r_w}}{\boldsymbol{o_w}}$
2. **Rank Aggregation:** The total importance score (or rank) of any given page $\boldsymbol{v}$ is equal to the sum of all fractional votes it receives from the pages linking to it.

This relationship can be expressed mathematically as a system of linear equations, where each page $\boldsymbol{v}$ is governed by the summation over its in-link set $\boldsymbol{I_v}$. For a web graph containing $\boldsymbol{N}$ pages, this formulation generates a system of $\boldsymbol{N}$ linear equations with $\boldsymbol{N}$ unknowns.

$$\boldsymbol{r_v} = \sum_{\boldsymbol{w} \in \boldsymbol{I_v}} \frac{\boldsymbol{r_w}}{\boldsymbol{o_w}}$$

Example: To illustrate how these equations operate in practice, consider only three pages: $\boldsymbol{v}$, $\boldsymbol{w}$, and $\boldsymbol{x}$. Their structural out-degrees are defined as $\boldsymbol{o_v} = \mathbf{2}$, $\boldsymbol{o_w} = \mathbf{2}$ (including a self-loop where page $\boldsymbol{w}$ links to itself), and $\boldsymbol{o_x} = \mathbf{1}$.




Applying the flow model to each node yields the following coupled system of linear equations:

$$\begin{cases} r_v = r_w/2 + r_x \\ r_w = r_v/2 + r_w/2 \\ r_x = r_v/2 \end{cases}$$

However, these equations are **not independent**: they only fix the proportions between ranks. So, we add the constraint $\boldsymbol{r_v} + \boldsymbol{r_w} + \boldsymbol{r_x} = \mathbf{1}$ to impose a unique solution.

Solving this constrained system yields the precise importance distribution for the three-page network:


$$r_v = \frac{2}{5} \qquad r_w = \frac{2}{5} \qquad r_x = \frac{1}{5}$$



However, the real World Wide Web comprises hundreds of billions of interconnected pages and equations, rendering exact analytical solutions computationally impossible. Consequently, we need a new formulation.

Transition Probability Matrix

To formalize the flow model globally, we construct a **column-stochastic transition matrix** $\boldsymbol{M} \in \mathbb{R}^{N \times N}$, where each column corresponds to a web page and encodes how that page distributes its importance rank across its outgoing links.



For any pair of pages $\boldsymbol{v}$ and $\boldsymbol{w}$, the matrix entry $\boldsymbol{M}_{v,w}$ is defined as:

$$\boldsymbol{M}_{v,w} = \begin{cases} \dfrac{1}{o_w} & \text{if } w \text{ links to } v \\ 0 & \text{otherwise} \end{cases}$$

By incorporating this matrix representation, the individual flow equations for all pages simplify into a single, elegant matrix-vector product:

$$\boldsymbol{Mr} = \boldsymbol{r}$$

where $\boldsymbol{r} = (r_v, r_w, r_x, \dots)^T$ represents the global rank vector of all pages in the network.


The Eigenvector Formulation

The matrix equation $\boldsymbol{Mr} = \boldsymbol{r}$ reveals that the global rank vector $\boldsymbol{r}$ is an **eigenvector** of the transition matrix $\boldsymbol{M}$ associated with an eigenvalue of $\lambda = 1$. Furthermore, because $\boldsymbol{M}$ is a column-stochastic matrix, 1 is guaranteed to be the largest eigenvalue in magnitude, making $\boldsymbol{r}$ the **principal eigenvector** of the system.

Consequently, rather than attempting to solve a massive system of $\boldsymbol{N}$ linear equations directly, numerical methods exploit this eigenvector property to compute importance scores iteratively.

Power Iteration

To calculate the principal eigenvector at scale without explicit matrix inversion, search engines employ **power iteration**, an iterative algorithm that simulates the continuous "voting" process across the web graph.



The computational procedure follows a structured sequence of steps:


1. **Initialization:** The algorithm initializes the rank vector with uniform probability distribution across all N pages, setting $\boldsymbol{r(0)} = \left[\frac{1}{N}, \frac{1}{N}, \ldots, \frac{1}{N}\right]^T$
2. **Iterative Voting:** At each iteration step t, every page passes its current rank along its outgoing links by multiplying the current rank vector by the transition matrix:
$$\boldsymbol{r(t+1) = M \cdot r(t)}$$
3. **Convergence Testing:** The algorithm monitors the difference between successive rank vectors using a vector norm metric, evaluating whether $\|\boldsymbol{r(t+1) - r(t)}\| < \boldsymbol{\epsilon}$ for a predefined tolerance threshold $\boldsymbol{\epsilon}$. If the condition is met, the iteration terminates; otherwise, the process repeats.

Power iteration is highly efficient for big data architectures because each iteration requires touching every link exactly once, resulting in low computational cost per step even across massive web graphs. However, ensuring that this iterative process always converges reliably to a unique and meaningful vector requires resolving structural anomalies such as dead ends and spider traps.

The Random Surfer Model

While the flow model evaluates PageRank through structural voting, the process can be equivalently reinterpreted through a probabilistic lens known as the **Random Surfer Model**.

Imagine an idealized user browsing the World Wide Web indefinitely. Starting at an initial page, the surfer selects one of the available outgoing links uniformly at random, navigates to the destination page, and repeats this process infinitely. Under this formulation, hyperlink navigation is mapped to a **random walk** over the graph.



The directed edges connecting pages represent transition paths, while the weights associated with each edge denote the transition probabilities. This situation can be easily represented as a **Markov Chain**, where the probability of moving to a future page depends strictly on the current page.

The system uses the same column-stochastic transition matrix $\boldsymbol{M} \in \mathbb{R}^{N \times N}$ introduced before. Each entry $\boldsymbol{M}_{v,w}$ represents the conditional probability that a random surfer currently located at page $\boldsymbol{w}$ will step to page $\boldsymbol{v}$ in the next time step:

Assuming that $\boldsymbol{p}(\boldsymbol{t})$ represents the probability distribution over all $\boldsymbol{N}$ pages at time step $\boldsymbol{t}$, the state distribution at step $\boldsymbol{t}+\mathbf{1}$ is derived via matrix-vector multiplication:

$$\boldsymbol{p}(\boldsymbol{t}+\mathbf{1}) = \boldsymbol{M} \cdot \boldsymbol{p}(\boldsymbol{t})$$

As before, assuming an initial uniform distribution $\boldsymbol{p}(\mathbf{0}) = \left[\frac{\mathbf{1}}{\boldsymbol{N}}, \ldots, \frac{\mathbf{1}}{\boldsymbol{N}}\right]^{\boldsymbol{T}}$, updating the probability vector step-by-step produces the exact numerical sequence generated by power iteration.

Consequently, the PageRank score $\boldsymbol{r}^* = \boldsymbol{p}^*$ of a web page represents the **long-run fraction of time** that a random surfer will spend on that page after browsing indefinitely. A page visited frequently by the surfer is an authoritative page that holds high structural importance.

Existence, Uniqueness and Theoretical Limitations

But, does power iteration always converge? Is $\boldsymbol{r}^*$unique? Does the walk reach a steady state?

Theorem Perron–Frobenius (informal):

If M is column stochastic and strictly positive (no zero entries), then $\boldsymbol{r}^*$ exists, is unique, and power iteration converges to it from any starting vector.

However, real-world web graphs violate this condition:

- **Real transition matrices are extremely sparse**, containing mostly zero entries because the vast majority of page pairs do not share direct hyperlinks.
- **Raw web topologies contain structural anomalies**, such as dead ends (pages without outgoing links) and spider traps (closed loops of pages), which disrupt probability conservation and prevent standard power iteration from converging.

Resolving these topological limitations required Sergey Brin and Larry Page to introduce structural modifications to the transition matrix, which forms the core of Google's robust PageRank algorithm.

Robust PageRank

While the basic Random Surfer model translates hyperlink structures into a Markov chain, real-world web graphs violate the ideal conditions required for power iteration to converge due to two major anomalies:

- **Dead Ends:** Pages that contain no outgoing hyperlinks ($\boldsymbol{o}_{\boldsymbol{v}} = \mathbf{0}$). From a matrix perspective, the column corresponding to a dead end consists entirely of zeros, rendering the transition matrix $\boldsymbol{M}$ non-stochastic. During power iteration, rank continuously flows into a dead end but cannot escape, causing the total rank in the system to leak out until the rank vector vanishes to zero ($\lim_{\boldsymbol{t}\to\infty} \boldsymbol{r}(\boldsymbol{t}) = \mathbf{0}$).
- **Spider Traps:** Strongly connected subgraphs or loops of pages that contain internal outgoing links but no links pointing to the rest of the web. When a random surfer enters a spider trap, it can never leave. Consequently, nodes outside the trap lose all rank, and the rank vector rotates indefinitely within the loop without reaching a meaningful stationary distribution.

Google's Fix: Teleportation


To guarantee convergence and mathematical stability, there were introduced two structural modifications based on the concept of **random teleportation**.

1. **Teleporting from Dead Ends:** any node without out-links is modeled as if it connected to every page in the web graph with equal probability $\frac{1}{N}$. This adjustment restores the column-stochastic property of $\boldsymbol{M}$, ensuring that total rank is conserved during power iteration.
2. **Teleporting from Everywhere:** To prevent spider traps from absorbing all system rank, the Random Surfer model is extended to allow teleportation from any page at any step. At each step, a surfer on page $\boldsymbol{w}$ makes a probabilistic decision governed by a **damping factor** $\boldsymbol{d}$ (typically set to $\boldsymbol{d = 0.85}$):
    - With probability $\boldsymbol{d = 0.85}$, the surfer follows a randomly chosen outgoing link from the current page with probability $\frac{1}{o_w}$.
    - With probability $\boldsymbol{1 - d = 0.15}$, the surfer stops following links and **teleports** to a completely random page chosen uniformly from the entire web with probability $\frac{1}{N}$.

The Google Matrix Formulation

Combining the structured link transitions with uniform random teleportation brings us to a single, dense matrix called "**Google Matrix**":

$$\mathbf{G} = d\mathbf{M} + \frac{1-d}{N}\mathbf{1}\mathbf{1}^T$$



where $\boldsymbol{M}$ is the column-stochastic transition matrix (with dead-end columns fixed), $\mathbf{1}$ represents an all-ones column vector of dimension $\boldsymbol{N}$, and $\mathbf{1}\mathbf{1}^{\boldsymbol{T}}$ forms an $\boldsymbol{N \times N}$ matrix of ones.

Properties:

1. **Column Stochastic:** Every column in $\boldsymbol{G}$ sums to $\mathbf{1}$, preserving total rank across iterations.
2. **Strictly Positive:** Because $\frac{1-d}{N} > \mathbf{0}$, every entry $\boldsymbol{G_{i,j}}$ is strictly greater than zero ($\boldsymbol{G_{i,j} > 0}$).
3. **Perron-Frobenius Applicability:** Because $\boldsymbol{G}$ is column-stochastic and strictly positive, the **Perron-Frobenius Theorem** applies directly. A unique principal eigenvector $\boldsymbol{r^*}$ with eigenvalue $\boldsymbol{\lambda = 1}$ is guaranteed to exist, and power iteration is guaranteed to converge to $\boldsymbol{r^*}$ from any initial probability vector.

PageRank at Scale

When scaling PageRank to web-sized corpora containing billions of documents, direct storage and manipulation of the dense Google matrix $\boldsymbol{G}$ becomes physically impossible. Consequently, the dense Google matrix $\boldsymbol{G}$ and the $\boldsymbol{1/N}$ dead-end columns are never built or stored explicitly. Instead, systems store only the sparse link structure and account for teleportation and dead ends analytically.

To avoid materializing the dense matrix $\boldsymbol{G}$, practical implementations does not execute the real formula, but uses an optimized update formula:

$$\boldsymbol{r(t+1) = dM_{links} r(t) + \frac{1-S}{N} 1}$$

where $\boldsymbol{S = \sum_v r'_v}$ represents the total rank sum retained on the valid graph links prior to normalization. This formulation operates through two distinct mechanisms:

- The term $\boldsymbol{dM_{links} r(t)}$ ensures that rank distribution is performed strictly along existing hyperlinks using sparse matrix-vector multiplication, keeping the underlying matrix representation sparse.
- The constant correction term $\frac{\boldsymbol{1-S}}{\boldsymbol{N}}$ efficiently re-inserts both the uniform random teleportation probability and any rank lost due to dead-end nodes, producing mathematically identical results to multiplying by the full Google matrix $\boldsymbol{G}$.

Pseudocode

Algorithm 1 PageRank by sparse power iteration


Input: out-links O_w for every page w; damping d; tolerance ε **Output:** rank vector $\mathbf{r}$

$\mathbf{r} \leftarrow (1/N, \ldots, 1/N)$
repeat
  $\mathbf{r}' \leftarrow \mathbf{0}$
  for each page w **do**
    for each $v \in O_w$ **do** $r'_v \leftarrow r'_v + d\, r_w / o_w$
  $S \leftarrow \sum_v r'_v$
  for each page v **do** $r'_v \leftarrow r'_v + (1 - S)/N$
  $\delta \leftarrow \|\mathbf{r}' - \mathbf{r}\|_1$; $\mathbf{r} \leftarrow \mathbf{r}'$
until $\delta < \varepsilon$
return $\mathbf{r}$

Distributed Execution: MapReduce vs Spark

The choice of distributed computing framework drastically impacts overall performance:

- **MapReduce Implementation:** Traditional MapReduce architectures write both link structures and rank vectors to distributed file systems (such as HDFS) at the end of every iteration. This forces the cluster to re-read the massive web graph from disk repeatedly across all 90 iterations, creating heavy I/O bottlenecks.
- **Spark Implementation:** cache the invariant link topology directly in distributed cluster memory. Because the graph structure remains constant, it is read from disk only once at the beginning, allowing subsequent iterations to stream and process lightweight rank vectors entirely in memory.



Near-Duplicate Detection

Def. Near-duplicate detection is a computational technique used to identify files, documents, or content that are almost identical to one another.

Near-duplicates (such as website mirrors, syndicated news articles, or pages differing only by an advertisement banner) are widespread across the web. They waste crawl budget, clutter search results, and split link votes across duplicate URLs.

An inverted index cannot solve this problem because a full page shares common words with almost every other document in the corpus. In addition, comparing every possible pair of pages directly is computationally impossible. To make the problem solvable, we define:

- **A similarity function** $\boldsymbol{s(A, B)} \in [\mathbf{0}, \mathbf{1}]$, where 1 indicates identical documents
- **A similarity threshold** $\boldsymbol{t}$ (such as $t = 0.8$)

Goal: identify pairs where $s(A, B) \geq t$ without looking at all pairs

This is achieved through a multi-stage data-reduction pipeline:

1. **Shingling:** Converts raw page text into a set of overlapping pieces.
2. **MinHashing:** Compresses large shingle sets into short, fixed-size signatures.
3. **Banding (Locality-Sensitive Hashing / LSH):** Filters signatures so that only similar items collide into the same buckets, generating a small pool of candidate pairs.
4. **Verification:** Performs an exact similarity check exclusively on the surviving candidate pairs.


Shingling

To compare documents structurally rather than as bags of isolated words, we apply **shingling**, which transforms a document into a set of overlapping substrings. Specifically, a ***k*-shingle** is defined as any sequence of k consecutive tokens (words or characters) found within the text. Nearly identical documents share most of their shingles.

Example: Let's assume a file containing: *"the cat sat on the mat"*, and a window size of $k = 2$



If a second document contains *"the cat sat on the sofa"*, their shingle comparison will be:



Choosing k

Choosing the appropriate shingle length k involves balancing sensitivity against specificity:

- **If k is too small** (e.g., $k = 1$ or 2 characters), almost every possible shingle appears in almost every document, causing unrelated pages to appear artificially similar.
- **If k is too large**, even minor edits (such as changing a single word) destroy many overlapping shingles, making near-duplicate pages look completely different.

Rule of Thumb: For character-level shingles, $k \approx 5$ works well for short texts, while $k \approx 9$--10 is standard for long documents. The goal is to ensure that rare shingles remain genuinely rare so that two unrelated pages have a negligible probability of sharing them.

Jaccard Similarity

Once documents are represented as sets of shingles, their similarity is quantified using **Jaccard Similarity**. For two sets A and B, the Jaccard similarity $J(A, B)$ is defined as the size of their intersection divided by the size of their union:

$$J(A, B) = \frac{|A \cap B|}{|A \cup B|}$$


A value of $J(A, B) = 1$ indicates identical sets, whereas $J(A, B) = 0$ indicates disjoint sets with nothing in common.

Example: Using our two example sentences: *"the cat sat on the mat"* and *"the cat sat on the sofa",* the sets share 4 shingles in their intersection and contain 6 unique shingles in their union. So:

$$J(A,B) = \frac{4}{6} = \frac{2}{3}.$$

Characteristic Matrix

Set collections are formally visualized using a **Characteristic Matrix**, where each column represents a document and each row represents a unique shingle from the universal vocabulary. An entry is set to 1 if the document contains that shingle, and 0 otherwise.



When comparing two columns A and B, rows fall into three categories:

- $(\mathbf{1},\mathbf{1})$ **rows:** The shingle is present in both documents; these rows contribute to both the intersection $|A \cap B|$ and the union $|A \cup B|$.
- $(\mathbf{1},\mathbf{0})$ **or** $(\mathbf{0},\mathbf{1})$ **rows:** The shingle appears in only one document; these rows contribute exclusively to the union $|A \cup B|$.
- $(\mathbf{0},\mathbf{0})$ **rows:** The shingle is absent from both documents and is completely ignored in the similarity calculation.

Obstacles at Web Scale


While shingling and Jaccard similarity accurately formalize near-duplicate detection, applying them directly across the web faces two severe scalability bottlenecks:

1. **Huge Set Sizes (Storage Bottleneck):** A typical web page generates roughly $5{,}000$ shingles. Across 10^{10} web pages, storing raw shingle sets requires approximately 200 TB of data, making direct storage and set intersection slow and expensive. This obstacle is resolved using MinHashing.
2. **Too Many Pairs (Computational Bottleneck):** Evaluating all $\frac{n(n-1)}{2} \approx 5 \times 10^{19}$ document pairs remain intractable even if individual set comparisons are fast. This obstacle is resolved using Banding (Locality-Sensitive Hashing).

Replacing Shingle Sets with MinHashing

While shingling successfully converts raw web pages into comparable sets of substrings, storing shingle sets for billions of documents introduces a severe storage bottleneck. To overcome this limitation, search engines employ MinHash.

Def. **MinHash is a probabilistic data compression technique** that reduces large shingle sets into short, fixed-size numerical fingerprints called **signatures**.



The fundamental objective of MinHashing is to map two sets, A and B, into fingerprint values $h(A)$ and $h(B)$ such that the probability of a collision exactly equals their Jaccard similarity:

$$\Pr[h(A) = h(B)] = J(A, B)$$


This ensures that similar document sets frequently produce identical fingerprint values.

Theoretical Foundation

1. **Random Permutation (π):** Put the rows in a random order



2. **First Non-Zero Scan:** Let's take the first row containing 1 of each document
   - If both A and B have 1 in the same entry => **collision**
   - Otherwise => **no collision**



2 collisions out of 3 orders (J = 2/3)

Consequently, the probability of a collision is equal to the fraction of shared rows over all rows in the union, which is precisely the **Jaccard similarity** $J(A, B) = \frac{|A \cap B|}{|A \cup B|}$.

A single MinHash value produces only one binary outcome, that results in a collision with probability $J(A,B)$. However, since a single trial provides too little statistical certainty, we repeat the experiment across k independent random row orders $\pi_1, \dots, \pi_k$ to build a compact **signature vector** for each document set S:

$$\text{sig}(S) = \left(h_{\pi_1}(S), h_{\pi_2}(S), \dots, h_{\pi_k}(S)\right)$$

To estimate the Jaccard similarity between two documents A and B, we simply calculate the fraction of signature positions where their values match:

$$\hat{J}(A,B) = \frac{\text{number of positions where sig}(A) \text{ and sig}(B) \text{ agree}}{k}$$

For example, using $k = 3$ random orders where $\text{sig}(A) = (\text{the mat, sat on, on the})$ and $\text{sig}(B) = (\text{the cat, sat on, on the})$, the two signatures agree in 2 out of 3positions, with an estimated similarity of $\hat{J} = \frac{2}{3}$

Replacing Permutations with Hash Functions

Storing explicit random permutations is computationally infeasible at web scale. A typical shingle universe contains roughly 10^7 rows, meaning around 8 GB of permutations, that must be replicated across every machine in the cluster… It is prohibitive.

For this reason, practical implementations substitute permutations with **hash functions** of the linear form:

$$h(x) = (ax + b) \pmod{p}$$

where a and b are random integers and p is a prime number. Mapping each row index x to a hash value and sorting by that value plays the exact same role as a random permutation. Consequently, the MinHash value of a document set for a given hash function is simply the smallest $h(x)$ among all rows x present in that document.

Example: To observe this mechanic by hand, consider a small characteristic matrix with 5 shingles ($x \in \{0,1,2,3,4\}$) and 4 documents (S_1, S_2, S_3, S_4)

x	S_1	S_2	S_3	S_4	$h_1(x)$	$h_2(x)$
0	1	0	0	1	1	1
1	0	0	1	0	2	4
2	0	1	0	1	3	2
3	1	0	1	1	4	0
4	0	0	1	0	0	3

Evaluated using two hash functions:

$$h_1(x) = (x+1) \bmod 5 \qquad \text{and} \qquad h_2(x) = (3x+1) \bmod 5$$


Let's compute only the signature for S_1. To do it we inspect only the rows where document S_1 has a 1:

1. $h_1(0) = 1$ and $h_1(3) = 4$ => $\min(1,4) = 1$.
2. $h_2(0) = 1$ and $h_2(3) = 0$ => $\min(1,0) = 0$.

Combining these two minimum values produces the compact signature $\mathbf{sig(S_1) = (1,0)}$.

Signature Matrix and Similarity Estimation

Repeating the minimum-hash extraction across every document column in the characteristic matrix we get a **signature matrix**.



Regardless of how many millions of rows exist in the original shingle universe or how long an individual document is, each document column in the signature matrix contains strictly k integers (typically $k \approx 200$). This architecture delivers profound structural advantages:

- **Massive Space Reduction:** Document signatures are $25\times$ smaller than raw shingle sets.
- **Length Independence:** The size of a document's signature depends exclusively on the parameter k, meaning both a 50-word page and a 50,000-word page compress into the exact same number of registry values.
- **Scalable Computation:** Signatures can be computed in a single linear pass per document.

The statistical accuracy of the estimated similarity improves as the signature length k increases, with the maximum standard error bounded by:

$$\text{error} \leq \frac{0.5}{\sqrt{k}}$$

This relationship demonstrates that quadrupling the number of hash functions halves the estimation error, providing a predictable trade-off between computational cost and precision