

```
fun append (xs,ys) =  
  if xs=[]  
  then ys  
  else (hd xs)::append(tl xs,ys)  
  
fun map (f,xs) =  
  case xs of  
    [] => []  
  | x::xs' => (f x)::(map(f,xs'))  
  
val a = map (increment, [4,8,12,16])  
val b = map (hd, [[8,6],[7,5],[3,0,9]])
```

Programming Languages

Dan Grossman

Avoiding Unnecessary Computations

Avoiding expensive computations

Thunks let you skip expensive computations if they are not needed

Great if you take the true-branch:

```
(define (f th)
  (if (...) 0 (... (th) ...)))
```

But worse if you end up using the thunk more than once:

```
(define (f th)
  (... (if (...) 0 (... (th) ...))
       (if (...) 0 (... (th) ...))
       ...
       (if (...) 0 (... (th) ...))))
```

In general, might not know how many times a result is needed

Best of both worlds

Assuming some expensive computation has no side effects, ideally we would:

- Not compute it *until needed*
- *Remember the answer* so future uses complete immediately

Called *lazy evaluation*

Languages where most constructs, including function arguments, work this way are *lazy languages*

- Haskell

Racket predefines support for *promises*, but we can make our own

- Thunks and mutable pairs are enough