Privacy-Preserving Federated Synthetic Data Generation for Intrusion Detection in MQTT-Based IoT Gateways

Nam-Khanh Nguyen
Faculty of Information Assurance
FPT University
Hanoi, Vietnam
southkhanh@gmail.com

Son-Truong-Giang Nguyen
Faculty of Information Assurance
FPT University
Hanoi, Vietnam
giangnsthe190021@gmail.com

Tri-Dung Nguyen
Faculty of Information Assurance
FPT University
Hanoi, Vietnam
dungtn002@gmail.com

Duc-Lam Vu
Faculty of Information Assurance
FPT University
Hanoi, Vietnam
lamvdhe180242@fpt.edu.vn

Trong-Hoang-Dat Nguyen
Faculty of Information Assurance
FPT University
Hanoi, Vietnam
endi011005@gmail.com

Anh-Nhat Nguyen
Faculty of Information Assurance
FPT University
Hanoi, Vietnam
nhatna3@fe.edu.vn

Thanh-Tuan Nguyen
Faculty of Information Assurance
FPT University
Hanoi, Vietnam
tuannt84@fe.edu.vn

Minh-Tri Luu
Faculty of Information Assurance
FPT University
Hanoi, Vietnam
trilm29@fe.edu.vn

***Abstract*—Federated learning lets Internet of Things (IoT) gateways train an intrusion detection system (IDS) without pooling raw traffic, but rare attack classes are scattered across gateways and model updates can still leak training records. This paper presents PP-FedData, which adapts marginal-based private synthesis to IoT gateways. Its generator, FedDP-Marginal, releases noisy count tables in three rounds, splits integer Skellam noise across the gateways, sums the tables with the SecAgg+ secure aggregation protocol of Flower, and samples class-conditional packets from a Chow–Liu tree. A federated conditional variational autoencoder (CVAE) trained with differentially private stochastic gradient descent serves as the deep baseline under identical partitions, budgets and evaluation. On the DoS/DDoS-MQTT-IoT dataset, an IDS trained only on FedDP-Marginal data reaches a test macro-F1 of 0.389–0.429 at $\varepsilon = 1$–10 ($\delta = 10^{-5}$) with noise shared across honest gateways, against 0.227–0.289 for the CVAE, which adds its noise at each gateway; under that same trust model, FedDP-Marginal ties at $\varepsilon = 1$ and leads at $\varepsilon = 5$ and 10. It transmits 0.45–0.60 MB per run instead of 27–44 MB, and secure aggregation costs $1.34\times$ the bytes and no utility. Synthetic data do not improve an IDS when real data can be pooled; their value lies where raw traffic must stay local. A requirement-driven rule maps trust, privacy and bandwidth requirements to a configuration.**

***Index Terms*—Federated learning, differential privacy, secure aggregation, synthetic data, marginal-based synthesis, intrusion detection, MQTT, Internet of Things.**

I. Introduction

The Message Queuing Telemetry Transport (MQTT) protocol carries the publish–subscribe traffic of many Internet of Things (IoT) deployments, and its brokers are exposed to denial-of-service (DoS) and distributed DoS (DDoS) attacks that abuse the protocol itself. The DoS/DDoS-MQTT-IoT dataset, captured on a physical testbed, records normal MQTT traffic together with ten such attack scenarios [1]. Intrusion detection systems (IDSs) based on machine learning learn these attacks from labeled traffic, which in practice is spread over gateways that cannot pool it. Federated learning (FL) trains a shared model while the data stay local: a server aggregates the clients' updates over several rounds, for example by federated averaging (FedAvg) [2]; here the clients are the gateways. Keeping data local does not remove the privacy risk, because shared gradients can reveal training records [3], and privacy-preserving FL for IoT intrusion detection remains an active field [4].

Two difficulties combine in this setting. First, rare attack classes are scattered unevenly across gateways, so the data are not independent and identically distributed (non-IID): a gateway may hold a handful of packets of a rare attack, or none. Second, the two standard protections answer different threats. Secure aggregation (SecAgg) and its scalable variant SecAgg$^+$ hide each client's update from the server and reveal only their sum [5], [6], but say nothing about what the sum, the model or its synthetic data reveal. Differential privacy (DP) bounds that disclosure for any single record [7], at a cost in utility. Federated generative models have been proposed to synthesize the missing attack traffic [8]–[11]. They exchange full models over tens of rounds and, when trained with DP

stochastic gradient descent (DP-SGD) [12], spread the privacy noise over thousands of optimization steps.

Marginal-based synthesis instead measures low-order count tables with DP noise and samples records from a graphical model fitted to them [13]–[15]. Count tables are sums over records, which is exactly what secure aggregation computes, so discrete noise such as the Skellam distribution can be split across gateways and the server sees only the noisy sum [16], [17]. Federated marginal synthesizers exist [18], [19], but they have been evaluated on general tabular benchmarks rather than on downstream detection of rare attacks in IoT traffic, and not against a federated deep generator under the same protections.

This paper studies that comparison on MQTT traffic with PP-FedData, a privacy-preserving federated data generation framework, through four research questions:

- **RQ1:** How much IDS utility does federated synthetic data retain when raw traffic cannot be pooled, and does it add utility when real data are available?
- **RQ2:** Under the same (ε, δ) budget, how does a federated marginal generator compare with a federated conditional variational autoencoder (CVAE) trained with DP-SGD in utility, rare-class recall and communication?
- **RQ3:** What does each protection (DP, SecAgg$^+$, both) cost and protect, as a function of the protected unit (packet, TCP stream, capture) and of the number of honest gateways?
- **RQ4:** Which configuration should a deployment choose given its trust, privacy and bandwidth requirements?

We do not claim a new synthesis algorithm: FedDP-Marginal adapts tree-structured marginal synthesis [14], [20], and federated marginal synthesis has been studied before [18], [19]. Our contribution lies in combining these components for IoT gateways and in a controlled empirical comparison:

1) **FedDP-Marginal for IoT-MQTT traffic.** A three-release protocol in which gateways add shares of integer Skellam noise to their count tables and sum them with the SecAgg$^+$ implementation of the Flower framework; the privacy loss is accounted exactly and reported for every number of honest gateways, with options for a threshold of honest gateways, client-side DP, and stream- or capture-level protection.
2) **A controlled benchmark against a federated CVAE** on the same non-IID partitions, privacy budgets, secure aggregation and evaluation, which separates the cost of DP, the cost of SecAgg$^+$ and the effect of the generator family.
3) **A requirement-driven configuration guide**: a transparent rule that filters the measured configurations by trust, privacy budget, bandwidth and attack priority and selects from their Pareto front.

Section II reviews related work, Section III describes the system model and the two generators, Section IV gives the experimental setup, Section V reports and discusses the results, and Section VI concludes.

II. Related Work

A. Privacy Protection in Federated Learning

Surveys of privacy-preserving FL for IoT intrusion detection group the techniques into differential privacy, homomorphic encryption, secure multi-party computation (MPC), trusted execution environments and blockchain [4]. The last three require heavy computation, special hardware or consensus overhead on constrained gateways, so this work uses DP and secure aggregation.

Differential privacy limits how much a released output can change when one record is added or removed [7]. In the central model a trusted curator adds the noise; in the classical local model every individual record is randomized before it leaves its owner, at a much higher noise level. Between the two, this paper uses *client-side DP*: each gateway adds enough noise for its own release to satisfy DP by itself, so it needs to trust neither the server nor the other gateways. DP-SGD clips per-example gradients and adds Gaussian noise at every step [12]; its cumulative loss is tracked with Rényi DP (RDP) [21].

Secure aggregation lets the server learn only the sum of client vectors. The protocol of Bonawitz et al. uses pairwise masks and secret sharing to tolerate dropouts [5]; SecAgg$^+$ replaces the complete communication graph with a sparse random graph and reaches polylogarithmic overhead [6]. Secure aggregation adds no statistical noise, but it protects only the individual updates, not the aggregate.

Distributed DP combines both: each client adds a share of the noise and secure aggregation reveals only the sum, which then carries the full calibrated noise. Because secure aggregation works on integers modulo 2^b, discrete mechanisms are needed. Kairouz et al. proposed the distributed discrete Gaussian [16]. Agarwal et al. showed that the Skellam distribution is closed under summation and gave a tight RDP bound for it [17]. Both apply it to multi-round FL training, adding the noise once per round to the securely summed client updates; count tables, each a single sum, are a particularly simple fit.

B. Synthetic Data for Intrusion Detection

Oversampling such as the synthetic minority oversampling technique (SMOTE) interpolates between minority neighbors [22], which requires the minority records to be pooled and is therefore unavailable when a gateway holds few or no attack records. A systematic review of generative AI for IoT intrusion detection found that most studies use generative adversarial networks (GANs) or variational autoencoders for augmentation and class rebalancing, with mode collapse and training instability as recurring problems [8]. Hamouda et al. trained a federated conditional GAN on Edge-IIoTset and applied DP-SGD to the downstream classifier rather than to the generator; they identified cryptographic protection of the models as an open challenge [9]. Yao et al. protected the downlink broadcast of synthetic samples with dynamic (t, n)-threshold secret sharing, while the uplink gradients relied on Gaussian DP [10]. Shettar et al. reported a detection F1-score of 96.8% with a central aggregator under DP at $\varepsilon = 4.8$ [11].

TABLE I
COMPARISON WITH THE CLOSEST RELATED WORK

Work	FL	IoT	Syn.	DP	SA	Marg.	D-DP	IDS
Hamouda et al. [9]	✓	✓	✓	○	✗	✗	✗	✓
Yao et al. [10]	✓	✓	✓	✓	○	✗	✗	✓
Shettar et al. [11]	✓	✓	✓	✓	✗	✗	✗	✓
Kairouz et al. [16]	✓	✗	✗	✓	✓	✗	✓	✗
Agarwal et al. [17]	✓	✗	✗	✓	✓	✗	✓	✗
MST [14]	✗	✗	✓	✓	✗	✓	✗	✗
FLAIM [18]	✓	✗	✓	✓	✓	✓	✗	✗
CaPS [19]	✗	✗	✓	✓	✓	✓	✗	✗
PP-FedData	✓	✓	✓	✓	✓	✓	✓	✓

Syn.: synthetic data generation; SA: secure aggregation or MPC; Marg.: marginal-based DP synthesis; D-DP: distributed DP; IDS: downstream intrusion detection evaluated. ○: partly addressed (Hamouda et al. apply DP to the classifier, not the generator; Yao et al. use secret sharing on the downlink only).

None of these works applies secure aggregation to the generator updates or measures how DP and secure aggregation each affect rare-class detection.

C. Marginal-Based Private Synthesis

Marginal-based synthesizers avoid backpropagation altogether. PrivBayes fits a Bayesian network to noisy low-order marginals [13]; MST measures noisy two-way marginals along a maximum spanning tree and post-processes them with a graphical model [14]; AIM selects marginals adaptively and iteratively [15]. Two works move this family to distributed data. FLAIM adapts AIM to federated clients under zero-concentrated DP and compares it with a secure multi-party variant [18]. CaPS performs marginal selection and measurement inside secure multi-party computation ("DP-in-MPC") [19]. Both were evaluated mainly on general-purpose tabular benchmarks; FLAIM also used the legacy DARPA intrusion detection data, but measured workload error and negative log-likelihood rather than downstream rare-class detection. The family models only low-order dependencies, must discretize continuous attributes, and has a low signal-to-noise ratio in sparse cells.

D. Research Gap

Table I summarizes the closest works. Based on a non-systematic search of the literature, and to the best of our knowledge, no prior study (i) evaluates a federated marginal generator on IoT-MQTT traffic for downstream rare-class detection, (ii) compares it with a federated deep generator under identical partitions, budgets and secure aggregation, or (iii) combines distributed discrete DP with a working secure aggregation implementation and reports the guarantee as a function of the number of honest clients.

III. SYSTEM MODEL AND METHODOLOGY

A. Architecture and Threat Model

Fig. 1 shows the three parties of PP-FedData. A federation of K edge gateways $\mathcal{K} = \{1, \dots, K\}$ observes MQTT traffic; gateway k keeps its packets $\mathcal{D}_k$ locally. An aggregation server coordinates the rounds, reconstructs a global generator from the aggregated releases and samples synthetic packets for every class. A downstream IDS is trained on the synthetic packets, alone or with real ones, and is evaluated on real traffic. Two generator routes share this architecture: FedDP-Marginal, which exchanges count tables in three releases, and a federated CVAE, which exchanges model weights over tens of FedAvg rounds.

To model non-IID gateways, the training data are partitioned with the label-skew scheme of Hsu et al. [23]: for each class $c \in \{1, \dots, C\}$ the shares of the K gateways are drawn as

$$\mathbf{p}_c = (p_{c,1}, \dots, p_{c,K}) \sim \mathrm{Dir}(\alpha_{\mathrm{dir}} \mathbf{1}_K), \tag{1}$$

and each record of class c goes to gateway k with probability $p_{c,k}$. With $K = 5$ and $\alpha_{\mathrm{dir}} = 0.5$, some gateways receive few or no packets of a rare attack class.

Threat model. The server is honest-but-curious: it follows the protocol but inspects everything it receives. Gateways follow the protocol; poisoning and Byzantine behavior are out of scope. The two protections answer different threats. SecAgg$^+$ [6] hides each gateway's contribution from the server, which learns only the sum. DP bounds what the released sum, and every model or synthetic record derived from it, reveals about one record [7]. By default the protected record is one packet; Section III-C extends the unit to a TCP stream or a capture. Class labels, class quotas, the gateways' sample counts and the preprocessing statistics are treated as public side information outside ε.

B. FedDP-Marginal

FedDP-Marginal adapts tree-structured marginal synthesis [14], [20] to a federation. It models $d = 37$ attributes: 13 numeric attributes, discretized into $B_{\mathrm{fine}} = 64$ equal bins on the standardized range $[-5, 5]$; 19 binary attributes (7 protocol flags and 12 missingness indicators); and 5 categorical attributes (message type, two quality-of-service (QoS) fields, requested QoS and protocol). Every table is a sum over records, so each release is a single additive query. The protocol has three releases (Fig. 2):

1) **Release 1, fine one-way tables per class.** Each gateway counts every attribute per class on fine bins. From the noisy sum the server places B_{coarse} coarse bins at the quantiles of each numeric attribute and broadcasts the cut points.
2) **Release 2, coarse two-way tables pooled over classes.** Gateways count all $\binom{37}{2} = 666$ attribute pairs on coarse values. The server estimates the mutual information $\hat{I}$ of every pair from the noisy tables (counts clipped at zero and smoothed) and builds a single Chow–Liu tree [20]:
$$T^\star = \arg\max_{T} \sum_{(i,j)\in T} \hat{I}(X_i; X_j), \tag{2}$$
with $\hat{I}(X_i; X_j) = \sum_{a,b} \hat{p}(a,b) \log \frac{\hat{p}(a,b)}{\hat{p}(a)\hat{p}(b)}$, and broadcasts $T^\star$.
3) **Release 3, class-conditional tree tables.** Gateways count the (root, y) table and the $(\mathrm{parent}, \mathrm{child}, y)$ table of every tree edge on coarse values.

Pooling Release 2 over classes is deliberate: a per-class split would divide the signal of each cell by about C while the




Fig. 1. PP-FedData architecture. Gateways keep raw traffic; FedDP-Marginal sends three releases of noisy count tables and the federated CVAE sends model updates, both through SecAgg$^+$ to an honest-but-curious server, which samples synthetic packets for the downstream IDS.

sensitivity stays the same, which corrupts the tree. Class-specific structure enters through Release 3.

Sampling. For each class c the server samples records along $T^\star$ from the root to the leaves (conditioning on $y = c$ is written as c),

$$\hat{P}(\mathbf{x} \mid c) = \hat{P}(x_r \mid c) \prod_{(u,v)\in T^\star} \hat{P}(x_v \mid x_u, c), \tag{3}$$

where r is a fixed root attribute and every edge (u, v) of $T^\star$ is oriented away from r, so that u is the parent of v. A sampled coarse value of a numeric attribute is refined to a fine bin with the class's fine histogram from Release 1 and then drawn uniformly inside it. The records are mapped back to the feature space by inverting the preprocessing.

Post-processing (MGr). The refined variant combines every independent noisy estimate of an attribute's class-conditional marginal (from Release 1 and from the incident tree tables) by inverse-variance weighting, clips negative counts, and adjusts each edge table to the fused marginals with iterative proportional fitting. Because it only transforms released values, it costs no privacy budget [7].

C. Privacy Accounting

Sensitivity. Two datasets are neighbors if they differ by one packet. A packet adds one count to one cell of every table it touches, so a release of M_r tables (37, 666 and 37 for the three releases) has ℓ_1 and ℓ_2 sensitivities $\Delta_{1,r} = M_r$ and $\Delta_{2,r} = \sqrt{M_r}$. To protect a unit of several packets (a TCP stream or a capture), each unit is assigned to a single gateway, which uses at most m of its packets. The sensitivities then become

$$\Delta_{1,r} = m\, M_r, \qquad \Delta_{2,r} = m\sqrt{M_r}. \tag{4}$$

Skellam mechanism. The noise of each cell follows the Skellam distribution $\mathrm{Sk}(\mu) = \mathrm{Pois}(\mu/2) - \mathrm{Pois}(\mu/2)$, which has zero mean and variance μ and is closed under summation [17]. Agarwal et al. write the symmetric Skellam as $\mathrm{Sk}_{\mu,\mu}$, with variance 2μ; (5) is their bound rewritten in terms of the variance. For an integer order $\lambda > 1$, a release with variance μ_r per cell satisfies the RDP bound of Agarwal et al. [17, Cor. 3.6]:

$$\varepsilon_r(\lambda) \le \frac{\lambda \Delta_{2,r}^2}{2\mu_r} + \min\left(\frac{(2\lambda-1)\Delta_{2,r}^2 + 6\Delta_{1,r}}{4\mu_r^2}, \frac{3\Delta_{1,r}}{2\mu_r} \right). \tag{5}$$

RDP composes additively over the three releases [21], and the total is converted to (ε, δ)-DP with the conversion used by the Opacus accountant [24]:

$$\varepsilon = \min_{\lambda} \left[\sum_{r=1}^{3} \varepsilon_r(\lambda) - \frac{\ln\delta + \ln\lambda}{\lambda - 1} + \ln\frac{\lambda-1}{\lambda} \right], \tag{6}$$

over $\lambda \in \{2, \ldots, 63\} \cup \{64, 72, \ldots, 1024\}$. The budget is split over the releases by a vector $\mathbf{s} = (s_1, s_2, s_3)$ through $\mu_r = \Delta_{2,r}^2/(2 s_r \kappa)$, where κ is the largest value, found by bisection, for which (6) meets the target ε. The split and B_{coarse} are chosen on validation data from $\mathbf{s} \in \{(0.3, 0.1, 0.6), (0.5, 0.1, 0.4), (0.15, 0.05, 0.8)\}$ and $B_{\text{coarse}} \in \{4, 8, 16, 32\}$; the selected settings are $(0.3, 0.1, 0.6)$ with 32 bins at $\varepsilon = 1$, and $(0.15, 0.05, 0.8)$ with 4 and 8 bins at $\varepsilon = 5$ and 10, respectively; the larger number of bins at the smallest budget is what the validation search selected, and we did not isolate its cause.

Noise sharing and trust. Gateway k adds integer noise $\xi_k \sim \mathrm{Sk}(\mu_r/t)$ to every cell. With $t = K$ (the default, MGs and MGr) the full variance is reached when all gateways are honest. If only h gateways add their share, the aggregate variance is $h\mu_r/t$, and the guarantee is recomputed from (5)–(6) and reported for every h. A threshold $t < K$ keeps the target ε whenever at least t gateways are honest, at the price of more noise when all are. In the client-side variant (MGl), every gateway adds the full variance μ_r, so its own release is DP by itself and it trusts neither the server nor the other gateways; the sum then carries $K\mu_r$.




Fig. 2. Three-release protocol of FedDP-Marginal. Each release is a sum of count tables plus Skellam noise shares, computed with SecAgg$^+$ over $\mathbb{Z}_{2^{32}}$. The coarse cut points (after Release 1) and the tree $T^\star$ (after Release 2) are broadcast back before the next release.

Secure transport. The noisy integer tables are summed with Flower's SecAgg$^+$ [6], [25] over $\mathbb{Z}_{2^{32}}$:

$$S = \sum_{k \in \mathcal{K}} (\mathbf{x}_k + \boldsymbol{\xi}_k) \bmod 2^{32}, \tag{7}$$

where $\mathbf{x}_k$ are gateway k's counts; the server lifts every entry $S \geq 2^{31}$ to $S - 2^{32}$ to recover negative values. Since the counts are at most $n = 88{,}500$ and the noise is small compared with 2^{31}, the lifted sum equals the exact noisy sum: secure aggregation adds no rounding error and receives no privacy credit. Because each release is a single sum, splitting the noise across gateways is valid. The CVAE baseline instead runs record-level DP-SGD with many local steps per round, whose noise is added inside each gateway's optimization and cannot be split this way. FL training can use distributed noise when each gateway sends one clipped update per round and the noise is added to their sum [16], [17]; we implemented such a CVAE variant but did not run it.

D. Federated CVAE Baseline

The deep baseline is a label-conditional CVAE [26] on the $p = 60$ encoded features, without batch normalization so that per-example gradients are independent. It is trained with FedAvg [2] for 30 rounds of 2 local epochs (B3). The DP variant (M1) runs DP-SGD with Opacus 1.6.0 [12], [24]: per-example gradients are clipped and noised at every local step,

$$\tilde{g} = \frac{1}{b}\Big(\sum_{i=1}^{b} \frac{g_i}{\max(1, \|g_i\|_2 / G)} + \mathcal{N}(0, \sigma_k^2 G^2 \mathbf{I})\Big), \tag{8}$$

where g_i is the gradient of example i in a minibatch of size b, G is the clipping bound, and the noise multiplier σ_k is calibrated for each gateway; the federation reports the worst case $\varepsilon = \max_k \varepsilon_k$. M2 aggregates the weights with SecAgg$^+$ (5 shares, reconstruction threshold 3, clipping range 16, 2^{22} quantization levels), and M3 combines M1 and M2. Even with SecAgg$^+$, the CVAE route provides client-side DP only. Message sizes differ because the networks do: hidden layers (256, 128) for B3 and M2, (128, 64) for M1 and M3, and width 64 with latent size 8 for the re-tuned M1o-eps5. Synthetic records are decoded from $z \sim \mathcal{N}(0, \mathbf{I})$; the DP configurations use the plain decoder, which depends only on the DP-trained weights, whereas the non-private B3 and M2 use a residual-noise decoder with per-class variances estimated on the pooled training data. The federated CVAE was the initial design choice; because its utility under DP stayed low even after per-ε re-tuning at full federated scale (M1o, M3o), FedDP-Marginal became the main generator and the CVAE is retained as the baseline.

IV. Experimental Setup

A. Dataset and Preprocessing

We use the DoS/DDoS-MQTT-IoT dataset [1]: 59,624,826 packets, each described by 33 columns, with normal traffic and the DoS and DDoS variants of five MQTT attack families. The attack rows are the authors' CSV exports. Normal traffic is released only as packet capture (PCAP) files, so we exported every normal packet with TShark into the same columns; with the authors' export settings, the same procedure reproduces their attack rows. The DoS and DDoS sub-classes of each family are merged into one class, so that the IDS detects the attack family. Separating them is hard at the packet level: a random forest on real data reaches a macro-F1 of only 0.326 on the eleven sub-classes (normal traffic and ten attack sub-classes), and the two sub-classes of basic connect flooding are close to chance. Merging gives six classes (Table II).

Identifiers and capture metadata (frame number, absolute and relative timestamps, source address, free-text information) are removed to avoid leakage [27]. Numeric features with skewness above 2 are log-transformed, all numeric features are standardized and clipped at $\pm 5\sigma$, and categorical fields are one-hot encoded, giving $p = 60$ features. The preprocessing statistics are fitted on the pooled training split, a centralized step outside ε (Section V-E). Diagnostic checks found no shortcut

TABLE II
CLASSES, RAW PACKET COUNTS AND SPLIT QUOTAS

Class	Raw packets	Share	Train	Val.	Test
NORMAL	45,580,102	76.44%	60,000	2,000	5,000
BCF	12,280,874	20.60%	20,000	2,000	5,000
DELAYED	601,542	1.01%	3,000	2,000	5,000
SYN	601,439	1.01%	3,000	2,000	5,000
INVALID	290,340	0.49%	1,500	2,000	5,000
WILL	270,529	0.45%	1,000	2,000	5,000
Total	59,624,826	100%	88,500	12,000	30,000

BCF: basic connect flooding; DELAYED: delayed connect flooding; SYN: SYN TCP flooding; INVALID: invalid subscription flooding; WILL: connect flooding with WILL payload.

feature: no single column reaches a macro-F1 above 0.9, the missingness indicators alone reach 0.10 (chance 0.17), and a random row split scores only 0.0075 above a split by capture group.

Where a sub-class spans several capture groups (normal traffic has 49), whole groups are assigned to the training, validation or test split. Eight of the ten attack sub-classes come from a single capture file; as an exception, their validation and test rows are contiguous blocks of that capture, separated by 1,000-row buffers, and TCP streams crossing a block boundary are dropped. Neighbouring blocks can still share temporal context, so leakage is reduced but not excluded; re-running the study with two other choices of test groups kept 5 of 6 verdicts. Rows are then sampled to fixed quotas (Table II). The training quotas impose a 60:1 imbalance between NORMAL and WILL. The validation and test sets are class-balanced, so that the metrics are not dominated by the majority class. The test set (11 capture groups, 20,343 TCP streams) is used only once for the final evaluation. We call DELAYED, SYN, INVALID and WILL the rare classes.

B. Configurations

Table III lists the configurations. The real-data references B0, B1a and B1b pool the raw training data and are therefore not available in a federation. All federated configurations use $K = 5$ gateways and the partition of (1) with $\alpha_{\text{dir}} = 0.5$, drawn once per seed and shared by every configuration. Privacy budgets are $\varepsilon \in \{1, 5, 10\}$ with $\delta = 10^{-5}$ at the packet level; this δ is below $1/n \approx 1.13 \times 10^{-5}$ for the $n = 88{,}500$ training packets, but not far below it. The headline FedDP-Marginal configurations are MG-eps1 = MGr-eps1, MG-eps5 = MGs-eps5 and MG-eps10 = MGs-eps10, the variants selected on validation data. Hyperparameters were tuned on the validation split only (tree-structured Parzen search for the CVAE, a grid for FedDP-Marginal); this selection is not covered by ε.

C. Evaluation Protocols and Metrics

All protocols are scored on the same real test set. *Train on real, test on real* (TRTR) trains the IDS on the pooled real training data (B0, B1a, B1b). *Train on synthetic, test on real* (TSTR) [28] trains it on 5,000 synthetic rows per class only, which measures what a federation obtains when raw data cannot be pooled. *Training augmentation* (TAug) adds synthetic rows to the pooled real data until each class has at least 20,000 rows. *Local augmentation* lets each gateway train its own IDS on its local rows, topped up with synthetic rows for every class of which it holds fewer than 5,000 rows (5 gateways $\times$ 3 seeds $= 15$ models). The IDS is a random forest (RF) with 200 trees or a multilayer perceptron (MLP) with hidden layers (128, 64); for each protocol the classifier with the higher validation macro-F1 is reported.

TABLE III
EVALUATED CONFIGURATIONS

ID	Generator	Protection	Rounds
B0, B1a, B1b	none	pooled real data; B1a class weights, B1b SMOTE [22]	–
B3	CVAE	none (FedAvg)	30
M1-eps{1,5,10}	CVAE	DP-SGD at each gateway (client-side DP)	30
M2	CVAE	SecAgg$^+$	30
M3-eps5	CVAE	DP-SGD and SecAgg$^+$	30
M1o, M3o	CVAE	as M1, M3, re-tuned per ε at full scale	30–50
MGp-nodp	Marginal	none (plain Flower sum)	3
MGs-nodp	Marginal	SecAgg$^+$ without noise	3
MGs-eps{1,5,10}	Marginal	distributed Skellam DP and SecAgg$^+$	3
MGr-eps{1,5,10}	Marginal	MGs with post-processing (no extra ε)	3
MGl-eps{1,5,10}	Marginal	client-side DP, plain sum	3
FedMLP	none	IDS trained directly by FedAvg; none, SecAgg$^+$ or DP-SGD	30

Suffixes: $-\mathtt{t}t$ noise share $1/t$ (holds with t honest gateways); $-\mathtt{strm}m$ and $-\mathtt{cap}m$ protect a TCP stream or a capture with at most m packets each. Ablations shown only in Fig. 4: MGd (Gaussian noise, summed in-process) and MGb (second-order Bayesian network).

Utility is measured by macro-F1 over the six classes (primary metric), binary F1 (normal versus attack) and rare-class recall (mean recall of the four rare classes). Fidelity is measured by the Wasserstein-1 distance, the Jensen–Shannon divergence, a correlation distance, and a classifier two-sample test (C2ST) whose area under the ROC curve (AUC) is 0.5 when synthetic and real rows are indistinguishable [29]. Privacy is assessed with the formal ε, recomputed independently, and with three membership inference attacks (MIAs): one on the synthetic data, one with access to the released model and calibrated with a reference model [30], and one on the released tables of FedDP-Marginal. Each attack is checked against a positive control on which it must succeed. Communication is the payload measured on the Flower message grid, reported per round and per run.

D. Decision Rule and Environment

Every configuration is run with seeds $\{0, 1, 2\}$, which govern the partition, initialization and sampling. A configuration A is declared better or worse than B only if

$$0 \notin \mathrm{CI}_{95\%}(\bar{\Delta}) \quad \text{and} \quad |\bar{\Delta}| > \max(\mathrm{sd}_A, \mathrm{sd}_B), \tag{9}$$

where $\bar{\Delta}$ is the mean difference in macro-F1 over seeds, the interval comes from a paired bootstrap of the test rows (1,000 class-stratified resamples, identical for all runs), and sd is the seed standard deviation. Otherwise the difference is reported as no effect. Because packets of a TCP stream are correlated, every verdict is repeated with a bootstrap over whole streams. We report no p-values. The federation is simulated with Flower 1.39 [25] and Ray actors on a

single Windows 11 machine (CPU only, 16 GB RAM), with PyTorch 2.14, Opacus 1.6 and scikit-learn 1.9. Times therefore reflect computation, not network latency. Every run is recorded in a ledger with its configuration hash and code version, and a from-scratch re-run of the seed-0 matrix reproduced all 53 ledger rows exactly.

V. Results and Discussion

A. RQ1: Utility of Federated Synthetic Data

Packet-level detection of these attacks is hard even with all real data pooled. An RF trained on the imbalanced real training set (B0) reaches a test macro-F1 of 0.447 and a rare-class recall of 0.276; class weights (B1a) and SMOTE (B1b) raise the macro-F1 to 0.492 and 0.504. These references require pooling the raw traffic.

Synthetic data alone (TSTR). Without DP, an IDS trained only on FedDP-Marginal data reaches 0.444 ± 0.017, and one trained on the federated CVAE data (B3) reaches 0.420 ± 0.014. Synthetic-only training thus comes close to the imbalanced real reference while no raw packet leaves a gateway. It stays below the class-balanced references, so part of its value comes from the class balance of the synthetic set.

Synthetic data added to pooled real data (TAug). Here synthetic data do not help. With the RF, 1 of 13 generator configurations improves on B0 under (9), by at most $+0.002$, against $+0.057$ for SMOTE. With the MLP, 10 of 13 improve, by at most $+0.030$, against $+0.140$ for SMOTE. The recall of the rare classes moves by at most 0.012 for any generator, against $+0.063$ to $+0.102$ for class weights and SMOTE.

Local augmentation. The picture changes when the comparison is the gateway itself. A gateway's own IDS, trained on its non-IID local rows, reaches 0.387 ± 0.053. Topping up the classes it lacks with FedDP-Marginal data raises this to 0.419, 0.422 and 0.425 on average at $\varepsilon = 1$, 5 and 10 ($+0.033$, $+0.036$, $+0.039$). The gains are uneven: at $\varepsilon = 5$ all 15 gateway–seed pairs gain, six of them by less than 0.005 and six by 0.055–0.147, while at $\varepsilon = 1$ five pairs lose up to 0.007. These per-pair counts are raw differences, not verdicts of (9).

Training the detector directly. A detector can also be trained by FedAvg without synthetic data (FedMLP in Table III). Without protection it reaches 0.417–0.429, close to the non-private generators (0.420–0.444). With DP-SGD at each gateway it reaches 0.246, 0.285 and 0.292 at $\varepsilon = 1$, 5 and 10: about the level of FedDP-Marginal with client-side noise at $\varepsilon = 1$, and below it at $\varepsilon = 5$ and 10 (0.374, 0.413) and below FedDP-Marginal with distributed noise at every budget (0.389–0.429).

The answer to RQ1 is that federated synthetic data are useful where raw traffic cannot be pooled: to train a shared IDS, especially under DP, or to fill in the classes a gateway does not see. Without DP, a detector trained directly by FedAvg is a cheaper alternative when no shareable data are needed. Synthetic data do not improve an IDS whose real training data are already pooled.

TABLE IV
TSTR Utility and Communication at Equal Privacy Budgets

ε	Configuration	Macro-F1	Bin. F1	Rare rec.	MB/rd	MB/run
1	M1-eps1 (CVAE, cs)	0.227 ± 0.030	0.805	0.132	1.46	43.7
	MGl-eps1 (MG, cs)	0.253 ± 0.029	0.773	0.087	0.52*	1.56*
	MGr-eps1 (MG, dist.)	$\mathbf{0.389 \pm 0.010}$	0.875	0.253	0.20	0.60
5	M1o-eps5 (CVAE, cs)	0.287 ± 0.027	0.800	0.168	0.54	26.8
	MGl-eps5 (MG, cs)	0.374 ± 0.010	0.866	0.226	0.28*	0.83*
	MGs-eps5 (MG, dist.)	$\mathbf{0.408 \pm 0.003}$	0.901	0.293	0.15	0.45
10	M1o-eps10 (CVAE, cs)	0.289 ± 0.040	0.850	0.132	1.40	41.9
	MGl-eps10 (MG, cs)	0.413 ± 0.007	0.899	0.306	0.31*	0.93*
	MGs-eps10 (MG, dist.)	$\mathbf{0.429 \pm 0.008}$	0.906	0.331	0.16	0.47
∞	B3 (CVAE)†	0.420 ± 0.014	0.929	0.367	4.22	126.7
	MGs-nodp (MG)	0.444 ± 0.017	0.908	0.335	0.17	0.52

Bin. F1: binary F1 (normal vs. attack); Rare rec.: mean recall of `DELAYED`, `SYN`, `INVALID` and `WILL`; MB/rd: MB per round; MB/run: MB over all rounds (CVAE 30, 50 for M1o-eps5; FedDP-Marginal 3). cs: client-side DP (noise added at each gateway); dist.: distributed DP (noise shared across honest gateways). *Estimated: MGl is summed in-process, so its bytes use the bytes per value measured for M2. †Residual-noise decoder fitted on pooled data; with the plain decoder 0.388. Real-data references (TRTR): B0 0.447, B1a 0.492, B1b 0.504.

B. RQ2: FedDP-Marginal Versus the Federated CVAE Under DP

Table IV compares the routes at equal budgets; for the CVAE we report its best configuration on validation data at each ε, including the versions re-tuned at full scale. The CVAE adds its DP-SGD noise at each gateway, i.e., it provides client-side DP, whereas MG shares the noise across honest gateways. With shared noise, FedDP-Marginal reaches 0.389, 0.408 and 0.429 against 0.227, 0.287 and 0.289, and its rare-class recall is 1.7 to 2.5 times as high. Under the CVAE's own trust model (MGl), FedDP-Marginal reaches 0.253, 0.374 and 0.413. Judged by (9), both with the row and with the stream bootstrap, MGl and the CVAE cannot be separated at $\varepsilon = 1$: the gap of 0.026 [0.022, 0.030] is smaller than the seed standard deviation (0.030), and MGl recalls the rare classes less (-0.046). At $\varepsilon = 5$ and 10, MGl is better by 0.087 and 0.125, and FedDP-Marginal with shared noise by 0.12–0.16 at every budget. MG needs 3 rounds of 0.15–0.20 MB instead of 30–50 rounds of 0.54–1.46 MB, i.e., 0.45–0.60 MB per run against 27–44 MB, more than 98% less at each budget. Fig. 3 shows how utility varies with ε.

The cost of DP differs between the routes. Measured against its own non-private release with (9), FedDP-Marginal loses 0.055 (RF) and 0.063 (MLP) at $\varepsilon = 1$, 0.036 and 0.043 at $\varepsilon = 5$, and 0.031 and 0.016 at $\varepsilon = 10$; the last difference is within noise. For the CVAE route, 8 of 12 such comparisons are worse, with losses of up to 47% of the synthetic-only macro-F1. Without DP the marginal generator is also better than the CVAE (RF $+0.048$, MLP $+0.024$). Client-side noise costs FedDP-Marginal most at small budgets, because the sum then carries K times the variance.

In fidelity, FedDP-Marginal matches the per-column distributions more closely (Wasserstein distance 0.047–0.066 against 0.20–0.25 for the DP-trained CVAE). However, a classifier still separates synthetic from real rows almost perfectly for every generator, private or not (C2ST AUC 0.9995–1.0000). Utility for an IDS therefore does not mean that the synthetic packets




Fig. 3. TSTR macro-F1 (bars: one seed standard deviation) against the privacy budget for FedDP-Marginal with distributed noise (MG) and client-side noise (MGl), and for the best CVAE configuration. The ε axis is categorical (equal spacing). Dashed lines: RFs trained on pooled real data.

look real.

C. RQ3: What Each Protection Costs and Protects

Secure aggregation. For FedDP-Marginal, the release through SecAgg$^+$ (MGs-nodp) sends 1.34× the bytes per round of the same release in plain Flower rounds (MGp-nodp; 0.174 against 0.129 MB) and takes 1.10× the time of the three rounds (23.1 against 21.1 s, mostly simulator start-up). Utility is unchanged, because the secure sum equals the exact sum. For the CVAE, SecAgg$^+$ costs 1.12× the time per round and 1.52× the bytes per parameter, and none of 8 utility comparisons shows an effect. DP-SGD, in contrast, multiplies the time per round by 4.3–4.5.

Empirical leakage. The attack on the released tables of FedDP-Marginal passes its positive control (AUC 0.583). Averaged over the three seeds, its AUC is 0.560 without DP and 0.514, 0.522 and 0.531 with DP at $\varepsilon = 1$, 5 and 10; a record bootstrap puts the drops at 0.046 [0.038, 0.053], 0.038 [0.031, 0.044] and 0.029 [0.022, 0.034], all of which pass (9). In absolute terms the leakage is small: at 1% false positives the attack identifies 1.6% of the training records without DP and 1.1–1.3% with DP, against 1% for a random guess. SecAgg$^+$ alone does not change these numbers, since it hides each gateway's tables, not what their sum reveals. For the CVAE, the attack on synthetic data stays near chance (0.488–0.498) at every ε, including ∞, but fails its positive control (0.519), and the model-access attack passes its control (0.664) yet finds no leakage in the federated models (0.496–0.500); there, DP provides the formal guarantee rather than a measurable reduction.

Trust and protected unit. Table V summarizes the options of FedDP-Marginal at $\varepsilon = 5$. With the noise split over all five gateways, the guarantee degrades to $\varepsilon = 14.2$ if only one gateway is honest; this value grows with the federation (25.4 for 10 and 49.9 for 20 gateways). A threshold $t = 3$ keeps $\varepsilon \leq 5$ with any three honest gateways and changes the utility by only -0.001 to $+0.003$ across budgets. Protecting a whole TCP stream costs 0.02–0.04 macro-F1, because 90% of the streams contribute a single packet. A whole capture (up to 1,277 packets) can be protected only by bounding its contribution to $m = 25$ packets: the guarantee then covers the whole capture, but too little data remain (macro-F1 0.15–0.20). By design, the noise-free sums do not depend on how the rows are spread, nor the total noise on K when $t = K$. Single-seed runs at $\varepsilon = 5$ agree: $\alpha_{\text{dir}} = 0.1$ and 10 give the identical 0.412, and 10 and 20 gateways give 0.396 and 0.431, a spread due to the noise draws and the classifier selected on validation.

TABLE V
PROTECTION OPTIONS OF FEDDP-MARGINAL AT $\varepsilon = 5$, WITH THE NON-PRIVATE REFERENCES

Config.	Protection	Macro-F1	$\varepsilon_{h=5}$	$\varepsilon_{h=1}$	MIA
MGp-nodp	none	0.444 ± 0.017	∞	∞	0.560
MGs-nodp	SecAgg$^+$ only	0.444 ± 0.017	∞	∞	0.560
MGl-eps5	client-side DP	0.374 ± 0.010	5.00	5.00	–
MGs-eps5	distributed DP, $t = 5$	0.408 ± 0.003	5.00	14.2	0.522
MGs-t3-eps5	distributed DP, $t = 3$	0.408 ± 0.025	3.72	10.1	0.520
MGs-t2-eps5	distributed DP, $t = 2$	0.396 ± 0.005	2.94	7.6	0.511
MGs-strm2-eps5	stream unit, $m = 2$	0.371 ± 0.004	5.00	13.3	–
MGs-cap25-eps5	capture unit, $m = 25$	0.203 ± 0.037	5.00	13.0	–

ε_h: guarantee when h of the 5 gateways add their noise share; with $t < 5$ the target holds whenever t gateways are honest. MIA: mean calibrated AUC of the attack on the released tables over three seeds (positive control 0.583; –: not attacked).

D. RQ4: Requirement-Driven Configuration

A single utility ranking does not settle the choice: the best configurations differ more in what they protect and cost than in macro-F1. The recommendation rule therefore proceeds in five steps. It (i) keeps only valid configurations (those whose guarantee covers everything they release); (ii) applies the trust requirement (an untrusted server needs SecAgg$^+$ or client-side DP, and colluding gateways need client-side DP or a threshold t); (iii) removes configurations that exceed the limits on ε, bandwidth, rounds or MIA AUC; (iv) keeps the Pareto front over utility, ε and cost, where utility within the seed spread, ε within 2% and cost within 5% count as equal; and (v) breaks ties by the priority (macro-F1 or rare-class recall). Two conventions matter. First, ε is an axis even when no DP is required, so a configuration that adds a guarantee at no measurable loss of utility and with fewer bytes dominates its non-private counterpart: hidden-tables selects MGr-eps10 rather than MGs-nodp, while lab keeps the cheaper MGp-nodp. Second, a threshold configuration is credited with its target ε unless the scenario fixes the number of honest gateways; MGs-t3-eps5 thus counts as $\varepsilon = 5$, not 3.72, and MGs-eps5 also has the higher rare-class recall (0.293 vs. 0.269). Table VI lists the outcome for eleven deployment scenarios.

Fig. 4 places every valid configuration by utility and total traffic: all FedDP-Marginal variants stay below 2.5 MB per run, at least an order of magnitude below the CVAE routes (26.8–192 MB), and make up 9 of the 10 configurations on the Pareto front. A deployment that cannot trust the server but trusts its gateways should take MGs-eps5 or MGs-eps10; if

TABLE VI
RECOMMENDED CONFIGURATION PER DEPLOYMENT REQUIREMENT

Scenario	Requirement	Choice	F1	ε
lab	all parties trusted, no DP	MGp-nodp	0.444	∞
hidden-tables	untrusted server, no DP	MGr-eps10	0.433	10
cloud-aggregator	untrusted server, $\varepsilon \leq 5$	MGs-eps5	0.408	5
rare-attacks	as above, rare recall first	MGs-eps5	0.408	5
strict-privacy	untrusted server, $\varepsilon \leq 1$	MGr-t3-eps1	0.392	1
low-bandwidth	$\varepsilon \leq 10$, ≤ 100 MB total	MGr-eps10	0.433	10
consortium	gateways may collude, $\varepsilon \leq 10$	MGl-eps10	0.413	10
honest-majority	≥ 3 honest, $\varepsilon \leq 10$, MIA < 0.55	MGs-t3-eps10	0.428	10
gateway-dropout	≥ 3 honest, $\varepsilon \leq 5$	MGs-t2-eps5	0.396	3.94
session-privacy	TCP-stream unit, $\varepsilon \leq 5$	MGs-strm2-eps5	0.371	5
capture-privacy	capture unit, $\varepsilon \leq 10$	MGs-cap25-eps5†	0.203	5

F1: TSTR macro-F1; ε: the guarantee that holds under the scenario's trust assumption. †Holds formally by using at most 25 packets of each capture; not practical at this utility.




Fig. 4. TSTR macro-F1 against total traffic per run (log scale) for all valid configurations. MG: FedDP-Marginal, including its Gaussian ablation (MGd, summed in-process) and second-order ablation (MGb); MGp: plain Flower sum without SecAgg$^+$. The traffic of the client-side variants (MGl) is estimated, as in Table IV. Filled markers: Pareto front over utility, ε and cost.

gateways may collude, it needs client-side noise or a threshold, at the costs listed in Table VI.

E. Discussion and Limitations

Why the marginal route degrades less under DP. FedDP-Marginal spends its budget on three releases, each a single sum with a known sensitivity, so the noise is added once per cell. Its pooled pairwise release keeps the per-cell signal high. Because each release is a sum, distributed noise and secure aggregation fit it exactly. In the DP-SGD setup used here, noise is added at every local step and cannot be shared across gateways (Section III-C). In return, the marginal route captures only pairwise dependencies through one tree, and second-order structures did not help on this data.

Limitations.

- **Data:** The study uses one dataset at the packet level, and generated packets have no stream context. The normal traffic was re-exported from PCAP files and, unlike the attack rows, includes broker-sent packets (44.2% of the normal training rows). Re-scoring all runs on client-sent test rows changes the macro-F1 by -0.019 on average and keeps the order of the configurations (Spearman 0.993).
- **Privacy scope:** ε protects one packet by default. One capture group contributes up to 188 packets of a rare class, so the group bound for a whole capture is vacuous. Labels, class counts, preprocessing statistics and validation-based tuning lie outside ε.
- **Centralized preprocessing:** The standardization statistics, the skewness test, the clipping range and the category lists are fitted on the pooled training split. A deployment would need fixed public ranges, a secure protocol, or a DP release of these statistics before Release 1, which would consume part of the budget.
- **Trust and system:** The study assumes honest-but-curious parties, and the federation, including SecAgg$^+$, is simulated on one machine, so no real network or device costs are measured.
- **Statistics and scope:** Three seeds give a rough spread, and the verdicts hold for this test split. A CVAE with distributed noise (one noisy sum per round), federated SMOTE, FLAIM or AIM themselves, and other deep generators were not compared.

VI. CONCLUSION

PP-FedData generates synthetic IoT-MQTT traffic across gateways that cannot share raw packets; this paper compared two federated generators under the same partitions, privacy budgets and secure aggregation. FedDP-Marginal, which releases three sums of noisy count tables with Skellam noise split across gateways and summed by SecAgg$^+$, kept 0.389–0.429 test macro-F1 at $\varepsilon = 1$–10, against 0.227–0.289 for a federated CVAE trained with DP-SGD, while sending less than 1 MB per run. Under the CVAE's own trust model, with the noise added at each gateway, it could not be separated from the CVAE at $\varepsilon = 1$ and led at $\varepsilon = 5$ and 10. Secure aggregation cost little and no utility; DP cost FedDP-Marginal 0.02–0.06 macro-F1 and lowered the AUC of an attack on its released tables from 0.560 to 0.514–0.531, although the leakage was small in both cases. Synthetic data did not improve an IDS whose real data could be pooled, synthetic packets remained distinguishable from real ones, and the guarantee is per packet unless a stream-level unit is chosen. The framework is therefore a way to train or complete an IDS where traffic must stay local, and its requirement-driven rule tells a deployment which protection to choose and what it will cost.

Future work will re-extract the normal traffic with the dataset authors' export settings, evaluate other IoT datasets, compare against FLAIM, AIM and a CVAE with distributed noise, estimate the preprocessing statistics and select hyperparameters privately, and measure the protocols on physical gateways over a real network.

ACKNOWLEDGMENT

This research was conducted within the Capstone Project Program of the Faculty of Information Assurance, FPT University, Hanoi Campus.

REFERENCES

[1] A. Alatram, L. F. Sikos, M. Johnstone, P. Szewczyk, and J. J. Kang, "DoS/DDoS-MQTT-IoT: A dataset for evaluating intrusions in IoT networks using the MQTT protocol," *Comput. Netw.*, vol. 231, p. 109809, 2023.

[2] B. McMahan, E. Moore, D. Ramage, S. Hampson, and B. Agüera y Arcas, "Communication-efficient learning of deep networks from decentralized data," in *Proc. 20th Int. Conf. Artif. Intell. Statist. (AISTATS)*. PMLR, 2017, pp. 1273–1282.

[3] L. Zhu, Z. Liu, and S. Han, "Deep leakage from gradients," in *Adv. Neural Inf. Process. Syst. (NeurIPS)*, vol. 32, 2019, pp. 14 774–14 784.

[4] A. Vyas, P.-C. Lin, R.-H. Hwang, and M. Tripathi, "Privacy-preserving federated learning for intrusion detection in IoT environments: A survey," *IEEE Access*, vol. 12, pp. 127 018–127 050, 2024.

[5] K. Bonawitz, V. Ivanov, B. Kreuter, A. Marcedone, H. B. McMahan, S. Patel, D. Ramage, A. Segal, and K. Seth, "Practical secure aggregation for privacy-preserving machine learning," in *Proc. ACM SIGSAC Conf. Comput. Commun. Secur. (CCS)*. ACM, 2017, pp. 1175–1191.

[6] J. H. Bell, K. A. Bonawitz, A. Gascón, T. Lepoint, and M. Raykova, "Secure single-server aggregation with (poly)logarithmic overhead," in *Proc. ACM SIGSAC Conf. Comput. Commun. Secur. (CCS)*. ACM, 2020, pp. 1253–1269.

[7] C. Dwork and A. Roth, "The algorithmic foundations of differential privacy," *Found. Trends Theor. Comput. Sci.*, vol. 9, no. 3–4, pp. 211–407, 2014.

[8] Z. Deng, A. Torim, S. Ben Yahia, and H. Bahsi, "Generative AI in intrusion detection systems for internet of things: A systematic literature review," *IEEE Open J. Commun. Soc.*, vol. 6, pp. 4689–4717, 2025.

[9] D. Hamouda, M. A. Ferrag, N. Benhamida, H. Seridi, and M. C. Ghanem, "Revolutionizing intrusion detection in industrial IoT with distributed learning and deep generative techniques," *Internet Things*, vol. 26, p. 101149, 2024.

[10] W. Yao, H. Zhao, and H. Shi, "Privacy-preserving collaborative intrusion detection in edge of Internet of Things: A robust and efficient deep generative learning approach," *IEEE Internet Things J.*, vol. 11, no. 9, pp. 15 704–15 722, 2024.

[11] R. Shettar, R. Coelho, and S. S. Veerasagar, "SYNAPSE: Synthetic network-traffic agent pipeline for federated edge security," *IEEE Access*, vol. 14, pp. 117 847–117 860, 2026.

[12] M. Abadi, A. Chu, I. Goodfellow, H. B. McMahan, I. Mironov, K. Talwar, and L. Zhang, "Deep learning with differential privacy," in *Proc. ACM SIGSAC Conf. Comput. Commun. Secur. (CCS)*. ACM, 2016, pp. 308–318.

[13] J. Zhang, G. Cormode, C. M. Procopiuc, D. Srivastava, and X. Xiao, "PrivBayes: Private data release via Bayesian networks," *ACM Trans. Database Syst.*, vol. 42, no. 4, pp. 25:1–25:41, 2017.

[14] R. McKenna, G. Miklau, and D. Sheldon, "Winning the NIST contest: A scalable and general approach to differentially private synthetic data," *J. Privacy Confidentiality*, vol. 11, no. 3, pp. 1–35, 2021.

[15] R. McKenna, B. Mullins, D. Sheldon, and G. Miklau, "AIM: An adaptive and iterative mechanism for differentially private synthetic data," *Proc. VLDB Endow.*, vol. 15, no. 11, pp. 2599–2612, 2022.

[16] P. Kairouz, Z. Liu, and T. Steinke, "The distributed discrete Gaussian mechanism for federated learning with secure aggregation," in *Proc. 38th Int. Conf. Mach. Learn. (ICML)*, vol. 139. PMLR, 2021, pp. 5201–5212.

[17] N. Agarwal, P. Kairouz, and Z. Liu, "The Skellam mechanism for differentially private federated learning," in *Adv. Neural Inf. Process. Syst. (NeurIPS)*, vol. 34. Curran Associates, Inc., 2021, pp. 5052–5064.

[18] S. Maddock, G. Cormode, and C. Maple, "FLAIM: AIM-based synthetic data generation in the federated setting," in *Proc. 30th ACM SIGKDD Conf. Knowl. Discov. Data Mining (KDD)*. ACM, 2024, pp. 2165–2176.

[19] S. Pentyala, M. Pereira, and M. De Cock, "CaPS: Collaborative and private synthetic data generation from distributed sources," in *Proc. 41st Int. Conf. Mach. Learn. (ICML)*, vol. 235. PMLR, 2024, pp. 40 397–40 413.

[20] C. K. Chow and C. N. Liu, "Approximating discrete probability distributions with dependence trees," *IEEE Trans. Inf. Theory*, vol. 14, no. 3, pp. 462–467, 1968.

[21] I. Mironov, "Rényi differential privacy," in *Proc. IEEE 30th Comput. Secur. Found. Symp. (CSF)*. IEEE, 2017, pp. 263–275.

[22] N. V. Chawla, K. W. Bowyer, L. O. Hall, and W. P. Kegelmeyer, "SMOTE: Synthetic minority over-sampling technique," *J. Artif. Intell. Res.*, vol. 16, pp. 321–357, 2002.

[23] T.-M. H. Hsu, H. Qi, and M. Brown, "Measuring the effects of non-identical data distribution for federated visual classification," *arXiv preprint arXiv:1909.06335*, 2019.

[24] A. Yousefpour, I. Shilov, A. Sablayrolles, D. Testuggine, K. Prasad, M. Malek, J. Nguyen, S. Ghosh, A. Bharadwaj, J. Zhao, G. Cormode, and I. Mironov, "Opacus: User-friendly differential privacy library in PyTorch," *arXiv preprint arXiv:2109.12298*, 2021.

[25] D. J. Beutel, T. Topal, A. Mathur, X. Qiu, J. Fernandez-Marques, Y. Gao, L. Sani, K. Li, T. Parcollet, P. P. B. de Gusmão, and N. D. Lane, "Flower: A friendly federated learning research framework," *arXiv preprint arXiv:2007.14390*, 2020.

[26] K. Sohn, H. Lee, and X. Yan, "Learning structured output representation using deep conditional generative models," in *Adv. Neural Inf. Process. Syst. (NeurIPS)*, vol. 28. Curran Associates, Inc., 2015, pp. 3483–3491.

[27] D. Arp, E. Quiring, F. Pendlebury, A. Warnecke, F. Pierazzi, C. Wressnegger, L. Cavallaro, and K. Rieck, "Dos and don'ts of machine learning in computer security," in *Proc. 31st USENIX Secur. Symp.* USENIX Association, 2022, pp. 3971–3988.

[28] C. Esteban, S. L. Hyland, and G. Rätsch, "Real-valued (medical) time series generation with recurrent conditional GANs," *arXiv preprint arXiv:1706.02633*, 2017.

[29] D. Lopez-Paz and M. Oquab, "Revisiting classifier two-sample tests," in *Proc. 5th Int. Conf. Learn. Represent. (ICLR)*, 2017.

[30] N. Carlini, S. Chien, M. Nasr, S. Song, A. Terzis, and F. Tramèr, "Membership inference attacks from first principles," in *Proc. IEEE Symp. Secur. Privacy (SP)*. IEEE, 2022, pp. 1897–1914.