MINISTRY OF EDUCATION AND TRAINING

FPT UNIVERSITY

Capstone Project Document

Project Title

IAP491_G..		
Group Members	Họ tên SV 1	Mã SV
	Họ tên SV 2	Mã SV
	Họ tên SV 3	Mã SV
	Họ tên SV 4	Mã SV
	Họ tên SV 5	Mã SV
Advisor	Học vị. Họ tên GV	
Co-advisor (if any)	Học vị. Họ tên GV	
Capstone Project code		

- 11/2025 -

©IA Dept., FPT University, Hanoi

Acknowledgments

No one achieves something great without the help of those around them, whether directly or indirectly. To complete this capstone project, we were fortunate to receive tremendous support and assistance from our supervisors, lecturers, friends, and family. We would like to dedicate these opening pages to express our sincere gratitude to everyone who has accompanied us throughout this journey.

First and foremost, we would like to express our deepest appreciation to all the lecturers at FPT University Hanoi Campus, particularly those in the Information Technology Department. The valuable knowledge they have imparted, along with their dedicated support throughout the implementation process, has enabled us to complete this capstone project and achieve noteworthy results.

We would like to extend our special gratitude to our supervisor, MSc. Trịnh Tiến Đạt, and our co-supervisor, Dr. Nguyễn Anh Nhật, who have inspired us, provided dedicated guidance, and offered invaluable support in terms of knowledge. They have created a favorable environment for us to learn and exchange ideas with fellow students in the research group. These are precious knowledge and experiences that will benefit us not only in this capstone project but also in our future careers.

Finally, we wish to express our heartfelt thanks to our families and loved ones, who have always been our solid support and have encouraged every decision we have made.

Despite our best efforts to make this thesis as complete as possible, shortcomings and limitations are inevitable. We sincerely hope to receive your understanding and constructive feedback from our supervisors and readers.

Contents

Acknowledgments **ii**

Contents **iii**

List of Figures **v**

List of Tables **vi**

Abstract **vii**

List of Abbreviations **viii**

1 Introduction **1**

1.1 Background 1

1.2 Problem Statement 2

1.3 Research Objectives 2

1.4 Significance of the Study 2

1.5 Scope and Limitations 2

1.6 Thesis Structure 2

2 Literature Review **3**

2.1 Review of Previous Studies 3

2.2 Summary of the Literature Review 3

2.3 Contribution of Research 3

3 Methodology **4**

3.1 Research Design 4

3.2 Data Collection Methods 4
3.3 Sampling Data Analysis Techniques 4
3.4 Limitations of the Methodology 4

4 Experimental and Results **5**
4.1 Introduction 5
4.2 Presentation of Data 5
4.3 Analysis of Results 5
4.4 Interpretation of Results 5
4.5 Comparison with Literature 5
4.6 Implications of the Results 5

5 Discussion **6**
5.1 Restate the Research Problem or Objectives 6
5.2 Summarize Key Findings 6

6 Conclusion and Future Work **7**
6.1 Conclusion 7
6.2 Future Work 7

A If Any **8**

References **9**

List of Figures

List of Tables

Abstract

A good abstract is a stand-alone summary of the paper, and should summarize the key components of the manuscript. Generally, the abstract should be concise and informative within 200-300 words. As an abstract is a separate section, it should be a self-containing text (no abbreviations, no references, no URLs, no undefined concepts, etc.). For research articles, abstracts should give a pertinent overview of the work. We strongly encourage authors to use the following style of structured abstracts, but without headings: (1) Background: Place the question addressed in a broad context (research background) and highlight the purpose of the study; (2) Methods: Describe briefly the main methods or treatments applied; (3) Results: Summarize the article's main findings; and (4) Conclusions: Indicate the main conclusions or interpretations.

Keywords: cybersecurity, information security, threat analysis, resilience

List of Abbreviations

Acronym	**Definition**
DSP	Digital Service Providers
EU	European Union
GSP	Global Stability Protection
OES	Operators of Essential Services

Chapter 1

Introduction

1.1 Background

The Internet of Things (IoT) connects physical objects, sensors, and various devices through communication networks, enabling data-driven services in domains such as healthcare, industrial automation, and smart environments. Alongside the expansion of IoT deployments, the number of connected components exposed to cybersecurity threats increases correspondingly [1]. The Message Queuing Telemetry Transport (MQTT) protocol is commonly used for lightweight publish-subscribe communication in IoT environments. However, MQTT-based systems can become targets for denial-of-service (DoS) and distributed denial-of-service (DDoS) attacks. The DoS/DDoS-MQTT-IoT dataset, collected from a physical IoT testbed, provides normal MQTT traffic alongside ten DoS attack scenarios to facilitate the study of attacks in this context [2]. Intrusion Detection Systems (IDS) monitor network activity to identify traffic or behavior exhibiting malicious signs. Machine learning and deep learning methods have been utilized and researched for this task due to their ability to learn characteristic patterns directly from network traffic. Their effectiveness depends partly on the availability and representativeness of the training data [3]. Federated Learning (FL) allows multiple clients to collaboratively train a shared model while keeping their data local; a central server distributes the global model and aggregates updates from clients across training rounds [4]. This approach is highly suitable when IoT data is distributed across multiple devices or locations, although communication and computational costs remain critical factors to consider in resource-constrained environments [5, 6]. Keeping data local also does not equate to completely eliminating privacy concerns arising from the exchange of model updates [7].

Privacy-preserving synthetic data generation is a potential solution to address the shortage of training data for rare attack classes in IoT networks while still ensuring strict security guar-

antees. Rather than relying on deep neural networks that require substantial computational resources and face convergence difficulties on edge devices [8], the probabilistic graphical model paradigm (Probabilistic Graphical Models) approaches the problem by decomposing tabular data into low-dimensional marginal frequency distribution slices (low-dimensional marginals) [9]. Through the Chow-Liu dependency tree structure (Chow-Liu Tree) [10], this approach effectively captures the core correlations between traffic features and attack labels without being affected by the curse of dimensionality. When combined with Differential Privacy (DP) [9] on contingency tables and consistent graphical inference mechanisms (such as Private-PGM), the system can reconstruct a valid global distribution to generate conditional traffic data, establishing a foundation to enhance the performance of downstream intrusion detection systems (IDS) [11, 12].

1.2 Problem Statement

Building an effective IDS for IoT networks faces multiple challenges related to data privacy, the representation of attack classes, and the practical costs of the model training process. These challenges are particularly evident when training data is distributed among clients and synthetic attack samples are considered as a supplementary detection solution. The first problem relates to privacy risks during federated training. Although FL avoids the periodic transfer of raw local data, clients must still exchange model updates with the server. Previous studies have demonstrated that shared gradients can leak information about training data in certain attack scenarios [7]. Therefore, sharing model weights instead of raw data cannot be considered a comprehensive privacy protection measure. Depending on the threat model and the type of information to be protected, supplementary mechanisms may be mandatory. The second problem concerns the representation of attack classes in the training data. Class imbalance can bias the learning process towards majority classes, making it difficult to identify classes that account for a low percentage [3]. For the DoS/DDoS detection problem in MQTT, the impact of this issue depends on the dataset version, label mapping, preprocessing pipeline, and data partitioning strategy for clients. Therefore, the class distribution of the dataset after selection and preprocessing must be empirically verified rather than assumed by default. If some attack classes lack data, synthetic samples can supplement training examples. However, merely increasing the number of samples does not prove that the generated data is useful; their actual contribution must be evaluated through data quality metrics and the detection performance of

the downstream IDS model.

The third challenge pertains to the hardware constraints of edge devices, the "curse of dimensionality," and the intricate trade-off among privacy protection, data quality, and operational overhead: on the one hand, deploying traditional distributed deep generative models (such as GANs or CVAEs) requires substantial computational resources (GPU/CPU) and large RAM capacity at client nodes, which is infeasible for hardware-constrained edge IoT devices [8]. On the other hand, tabular MQTT network traffic inherently possesses a high-dimensional structure with numerous interdependent attributes. Applying Differential Privacy (DP) directly to this high-dimensional attribute space readily leads to a state-space explosion—reaching up to 10^{19} cells [11]—causing the injected differential privacy noise to completely overwhelm the original data signal and severely degrade the fidelity of the generated distributions [9].

A direct consequence is a severe tug-of-war among three factors: the degree of privacy protection (privacy budget ε), synthetic data utility for downstream IDS models, and computational/operational overhead across the IoT infrastructure. Specifically, tightening privacy guarantees (reducing the budget ε) injects heavy DP noise that destroys the core feature correlations of rare DoS/DDoS attack classes [9, 12]. Conversely, increasing the privacy budget and expanding model capacity to improve the quality of generated data causes computational costs and system runtime to surge drastically [12]. Consequently, finding a tabular data generation solution that simultaneously ensures rigorous privacy guarantees, remains computationally lightweight for edge devices, and preserves critical feature characteristics for rare attack classes remains a major, unresolved technical bottleneck.

1.3 Research Objectives

1.4 Significance of the Study

1.5 Scope and Limitations

1.6 Thesis Structure

Chapter 2

Literature Review

Reviews relevant existing research and demonstrates how your thesis fits into the broader academic conversation.

2.1 Review of Previous Studies

2.2 Summary of the Literature Review

2.3 Contribution of Research

Chapter 3

Methodology

Describes the research design, data collection methods, and analysis techniques.

3.1 Research Design

3.2 Data Collection Methods

3.3 Sampling Data Analysis Techniques

3.4 Limitations of the Methodology

Chapter 4

Experimental and Results

Provide a concise and precise description of the experimental results, their interpretation as well as the experimental conclusions that can be drawn. You should discuss the results and how they can be interpreted in perspective of previous studies and of the working hypotheses.

4.1 Introduction

4.2 Presentation of Data

4.3 Analysis of Results

4.4 Interpretation of Results

4.5 Comparison with Literature

4.6 Implications of the Results

Chapter 5

Discussion

The findings and their implications should be discussed in the broadest context possible and limitations of the work highlighted.

5.1 Restate the Research Problem or Objectives

5.2 Summarize Key Findings

Chapter 6

Conclusion and Future Work

The 'conclusions' are a key component of the paper. It should complement the 'abstract' and is normally used by experts to value the paper's engineering content. A conclusion is not merely a summary of the main topics covered or a re-statement of your research problem, but a synthesis of key points and, if applicable, where you recommend new areas for future research.

6.1 Conclusion

6.2 Future Work

Appendix A

If Any

References

[1] Luigi Atzori, Antonio Iera, and Giacomo Morabito. The Internet of Things: A survey. *Computer Networks*, 54(15):2787–2805, 2010. doi: 10.1016/j.comnet.2010.05.010.

[2] Abdulmohsen Alatram, Leslie F. Sikos, Michael Johnstone, Peter Szewczyk, and James J. Kang. DoS/DDoS-MQTT-IoT: A dataset for evaluating intrusions in IoT networks using the MQTT protocol. *Computer Networks*, 231:109809, 2023. doi: 10.1016/j.comnet.2023.109809.

[3] Haibo He and Edwardo A. Garcia. Learning from imbalanced data. *IEEE Transactions on Knowledge and Data Engineering*, 21(9):1263–1284, 2009. doi: 10.1109/TKDE.2008.239.

[4] Brendan McMahan, Eider Moore, Daniel Ramage, Seth Hampson, and Blaise Agüera y Arcas. Communication-efficient learning of deep networks from decentralized data. In *Proceedings of the 20th International Conference on Artificial Intelligence and Statistics (AISTATS)*, pages 1273–1282. PMLR, 2017.

[5] Weisong Shi, Jie Cao, Quan Zhang, Youhuizi Li, and Lanyu Xu. Edge computing: Vision and challenges. *IEEE Internet of Things Journal*, 3(5):637–646, 2016. doi: 10.1109/JIOT.2016.2579198.

[6] Ahmed Imteaj, Urmish Thakker, Shiqiang Wang, Jian Li, and M. Hadi Amini. Federated learning for resource-constrained IoT devices: Panoramas and state-of-the-art. *Machine Learning and Knowledge Extraction*, 2022. URL https://arxiv.org/abs/2002.10610.

[7] Ligeng Zhu, Zhijian Liu, and Song Han. Deep leakage from gradients. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 32, 2019. URL https://proceedings.neurips.cc/paper_files/paper/2019/file/60a6c4002cc7b29142def8871531281a-Paper.pdf.

[8] Monik Raj Behera, Sudhir Upadhyay, Suresh Shetty, Sudha Priyadarshini, Palka Patel, and Ker Farn Lee. FedSyn: Synthetic data generation using federated learning. *arXiv preprint arXiv:2203.05931*, 2022. doi: 10.48550/arXiv.2203.05931. URL https://arxiv.org/abs/2203.05931.

[9] Jun Zhang, Graham Cormode, Cecilia M. Procopiuc, Divesh Srivastava, and Xiaokui Xiao. PrivBayes: Private data release via Bayesian networks. *ACM Transactions on Database Systems*, 42(4):25:1–25:41, 2017. doi: 10.1145/3134428.

[10] C. K. Chow and C. N. Liu. Approximating discrete probability distributions with dependence trees. *IEEE Transactions on Information Theory*, 14(3):462–467, 1968. doi: 10.1109/TIT.1968.1054142.

[11] Ryan McKenna, Daniel Sheldon, and Gerome Miklau. Graphical-model based estimation and inference for differential privacy. In *Proceedings of the 36th International Conference on Machine Learning (ICML)*, volume 97 of *Proceedings of Machine Learning Research*, pages 4435–4444. PMLR, 2019. URL https://arxiv.org/abs/1901.09136.

[12] Ryan McKenna, Brett Mullins, Daniel Sheldon, and Gerome Miklau. AIM: An adaptive and iterative mechanism for differentially private synthetic data. *Proceedings of the VLDB Endowment*, 15(11):2599–2612, 2022. doi: 10.14778/3551793.3551817.