



**EN 62311: 2008**

**AS REFERENCED BY TEST PLAN 12511671-TP1V2**

**RF EXPOSURE ANALYSIS REPORT**

**FOR**

**MILLIMETER WAVE RADAR SENSOR DEVELOPMENT BOARD**


**MODELS: IWR6843ISK-ODS, MMWAVEBOOST**

**REPORT NUMBER: 12927418-E5V5**

**ISSUE DATE: NOVEMBER 12, 2020**

*Prepared for*  
**TEXAS INSTRUMENTS**  
**12500 TI BLVD.**  
**DALLAS**  
**TEXAS, 75243, USA**

*Prepared by*  
**UL VERIFICATION SERVICES INC.**  
**47173 BENICIA STREET**  
**FREMONT, CA 94538, U.S.A.**  
**TEL: (510) 771-1000**  
**FAX: (510) 661-0888**



Revision History

Rev.	Issue Date	Revisions	Revised By
V1	08/19/2019	Initial Issue	M. Heckrotte
V2	08/29/2019	Correct Typo in Mean Power Section	Conan Cheung
V3	08/24/2020	Revised RF report reference to 12927418-E4V2	M.Heckrotte
V4	11/09/2020	Revised RF report reference to 12927418-E4V3	M.Heckrotte
V5	11/12/2020	Revised RF report reference to 12927418-E4V4 Revised descriptions of EUT and antennas Revised separation distance to 7.5 cm	M.Heckrotte

## TABLE OF CONTENTS

<b>1. ATTESTATION OF TEST RESULTS .....</b>	<b>4</b>
<b>2. METHODOLOGY .....</b>	<b>5</b>
<b>3. REFERENCES .....</b>	<b>5</b>
<b>4. FACILITIES AND ACCREDITATION .....</b>	<b>5</b>
<b>5. EUT DESCRIPTION .....</b>	<b>5</b>
5.1. DESCRIPTION OF EUT .....	5
<b>6. EN 62311 REQUIREMENTS - LIMITATION OF EXPOSURE.....</b>	<b>6</b>
6.1. LIMITS.....	6
6.2. OPERATING MODES.....	6
6.3. RESULTS .....	6
<b>7. CONCLUSIONS .....</b>	<b>6</b>

## 1. ATTESTATION OF TEST RESULTS

**COMPANY NAME:** TEXAS INSTRUMENTS  
12500 TI BLVD.  
DALLAS, TEXAS 75243 USA

**EUT DESCRIPTION:** MILLIMETER WAVE RADAR SENSOR DEVELOPMENT BOARD

**MODELS:** IWR6843ISK-ODS, MMWAVEICBOOST

**SERIAL NUMBERS:** 5498300073 (IWR6843ISK-ODS)  
5498100089 (MMWAVEICBOOST)

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
EN 62311: 2008 as referenced by Test Plan 12511671-TP1V2	Complies


UL Verification Services Inc. tested the above equipment in accordance with the requirements set forth in the above standards. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. All samples tested were in good operating condition throughout the entire test program. Measurement Uncertainties are published for informational purposes only and were not taken into account unless noted otherwise.

This document may not be altered or revised in any way unless done so by UL Verification Services Inc. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Verification Services Inc. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST or any agency of the Federal Government.

Approved & Released For  
UL Verification Services Inc. By:

Tested By:



MICHAEL HECKROTTE  
PRINCIPAL ENGINEER  
UL Verification Services Inc.

STEVE AGUILAR  
TEST ENGINEER  
UL Verification Services Inc.

## 2. METHODOLOGY

All calculations were made in accordance with EN 62311: 2008 as referenced by Test Plan 12511671-TP1V2.

## 3. REFERENCES

EIRP measurements are documented in test report UL test report 12927418-E4V4.

## 4. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 47173 Benicia Street, Fremont, California, USA.

UL Verification Services Inc. is accredited by NVLAP, Laboratory Code 200065-0.

## 5. EUT DESCRIPTION

### 5.1. DESCRIPTION OF EUT

See Test Plan 12511671-TP1V2.

The IWR6843ISK-ODS is a 60 to 64 GHz mmWave radar sensor development board with integral short-range (~5 dBi) antennas on the printed circuit board.

The MMWAVEICBOOST is an interface board.

## 6. EN 62311 REQUIREMENTS - LIMITATION OF EXPOSURE

### 6.1. LIMITS

The following Reference levels for electric, magnetic, and /or electromagnetic fields as applicable, are excerpted from Table 2 as given in Council Recommendation 1999/519/EC:

Frequency Range	Equivalent plane wave power density (W/m <sup>2</sup> )
2 – 300 GHz	10

### 6.2. OPERATING MODES

The RF Exposure calculations in this report are based on a single band operating configuration where the 60 GHz radio is not transmitting simultaneously with any other co-located radio.

### 6.3. RESULTS

The far-field boundary distance of the EUT antenna array is 7.21 cm. A far-field RF Exposure analysis is performed for a separation distance of 7.5 cm.

Mode	Center Freq. (GHz)	Mean Power over TX Period (dBm EIRP)	Mean Power over TX Period (W EIRP)	Separation Distance (m)	Power Density (W/m <sup>2</sup> )	Power Density Limit (W/m <sup>2</sup> )
300 MHz	61.26	8.51	0.0071	0.075	0.10	10
1300 MHz	60.92	10.52	0.0113	0.075	0.16	10
4000 MHz	62.12	14.28	0.0268	0.075	0.38	10

## 7. CONCLUSIONS

The EUT complies with the RF Exposure Limits given in Council Recommendation 1999/519/EC for any separation distance greater than or equal to 7.5 cm under all modes of operation.

## END OF REPORT