Sheet: VeraModule

VERA FPGA

File: vera-fpga.sch

Sheet: BusDecoder

BUS DECODER

File: busdecoder.sch

Sheet: Vera FPGA flash

VERA SPI FLASH
SD CARD INTERFACE

File: vera-fpga-flash.sch

Sheet: CartridgeInterface

CARTRIDGE INTERFACE

File: cartridgeInterface.sch

Sheet: PowerSupply

POWER SUPPLY

File: powersupply.sch

Gianluca Renzi
RetroBit Lab

Sheet: /
File: VERA-MODULE-RBL.sch

Title: VERA FPGA Audio & Video Board

Size: A4	Date: 2025-09-08	**Rev: 1.0**
KiCad E.D.A. kicad 5.1.9+dfsg1-1+deb11u1		Id: 1/6

EXTERNAL VIDEO CONNECTOR



FPGA VERA LOGIC VIDEO & AUDIO CARD



ANALOG VGA SIGNALS



VERA FPGA PROGRAMMED OK



Gianluca Renzi
RetroBit Lab

Sheet: /VeraModule/
File: vera-fpga.sch

Title:

Size: A3	Date: 2025-09-08	**Rev: 1.0**
KiCad E.D.A. kicad 5.1.9+dfsg1-1+deb11u1		Id: 2/6

PBI Bus Interface Decoder:
$D1XX, $D1FF, MPD, $D8XX–$DFXX, EX(T)SEL

PBI DEVICE ID: software selectable only



mVCS0 active & A15..A0 $D8XX–$DFXX –> MPD active (Internal 2K ROM)

$D1FF access & DATABUS = PBI DEVICE ID –> mVCS0 active/deactive

JP12: CCTL REAL FROM ATARI (XE)
JP23: CCTL from MCU (PBI Bus has no CCTL signal)



Accessing $D5XX area space

JP12: D1XX REAL FROM ATARI (XE)
JP23: D1XX from MCU



Accessing $D1XX area space



R/$\overline{W}$
Adapter for $\overline{RE}$
and $\overline{WE}$
as VERA MODULE wants



Enternal Memory Setup:
The range must be defined in software
EXSEL

In PBI Atari XL there is EXTENB signal output and EXTSEL signal input
In PBI Atari XE there is only the EXSEL signal output

ESP32 RESET SWITCH



Gianluca Renzi
RetroBit Lab

Sheet: /BusDecoder/
File: busdecoder.sch

Title:

Size: A3	Date: 2025-09-08	**Rev: 1.0**
KiCad E.D.A. kicad 5.1.9+dfsg1-1+deb11u1		Id: 3/6

ATARI 130XE ECI & CARTRIDGE INTERFACE





AUDIO MIXER INSIDE ATARI



BUS LOGIC LEVEL SHIFTERS

All 8–Bit signals must be shifted from 5V to 3.3V and vice versa



UNCONNECTED IN THIS PROJECT











Gianluca Renzi
RetroBit Lab

Sheet: /CartridgeInterface/
File: cartridgeInterface.sch

Title:

Size: A3	Date: 2025–09–08	**Rev: 1.0**
KiCad E.D.A. kicad 5.1.9+dfsg1–1+deb11u1		Id: 4/6

FPGA/SSD Flash Glue Logic



SD/microSD INTERFACE



IC DAC/AUDIO 24BIT 192K 16TSSOP



SPI 16MB FLASH



Gianluca Renzi
RetroBit Lab

Sheet: /Vera FPGA flash/
File: vera-fpga-flash.sch

Title:

Size: A4	Date: 2025-09-08	**Rev: 1.0**
KiCad E.D.A. kicad 5.1.9+dfsg1-1+deb11u1		Id: 5/6









Gianluca Renzi
RetroBit Lab

Sheet: /PowerSupply/
File: powersupply.sch

Title: VERA-XE VGA BOARD

Size: A4	Date: 2025-09-08	**Rev: 1.0**
KiCad E.D.A. kicad 5.1.9+dfsg1-1+deb11u1		Id: 6/6