Sheet: VeraModule

VERA FPGA

File: vera-fpga.sch

Sheet: BusDecoder

BUS DECODER

File: busdecoder.sch

Sheet: Vera_FPGA_flash

VERA SPI FLASH
SD CARD INTERFACE

File: vera-fpga-flash.sch

Sheet: CartridgeInterface

CARTRIDGE INTERFACE

File: cartridgeInterface.sch

Sheet: PowerSupply

POWER SUPPLY

File: powersupply.sch

FIDUCIAL TOP

FID3 Fiducial FID4 Fiducial

FIDUCIAL BOTTOM

FID2 Fiducial FID1 Fiducial

LOGO1
VERA X16 LOGO

LOGO2
ATARI READY

LOGO3
KiCAD DESIGN

LOGO4
ATARI DUO BUS

LOGO5
ESP32_BOBOARD

LBL1

Gianluca Renzi
RetroBit Lab

Sheet: /
File: VERA-MODULE-RBL.sch

Title: VERA FPGA Audio & Video Board

Size: A3	Date: 2025-09-23	**Rev: 1.0**
KiCad E.D.A. kicad 5.1.9+dfsg1-1+deb11u1		Id: 1/6

FPGA VERA LOGIC VIDEO & AUDIO CARD



ANALOG VGA SIGNALS



VERA FPGA PROGRAMMED OK

EXTERNAL VIDEO CONNECTOR

iceprog programmer USB FTDI / SPI



Gianluca Renzi
RetroBit Lab

Sheet: /VeraModule/
File: vera-fpga.sch

Title: VERA MODULE AND EXTERNAL VIDEO CONNECTOR

Size: A3	Date: 2025-09-23	**Rev: 1.0**
KiCad E.D.A. kicad 5.1.9+dfsg1-1+deb11u1		Id: 2/6

PBI Bus Interface Decoder:
$D1XX, $D1FF, MPD, $D8XX–$DFXX, EX(T)SEL

PBI DEVICE ID: software selectable only



mVCS0 active & A15..A0 $D8XX–$DFXX –> MPD active (Internal 2K ROM)

$D1FF access & DATABUS = PBI DEVICE ID –> mVCS0 active/deactive

Those signals are valid in ATARI XE only





R/$\overline{W}$
Adapter for $\overline{RE}$
and $\overline{WE}$
as VERA MODULE wants



Enternal Memory Setup:
The range must be defined in software
EXSEL

In PBI Atari XL there is EXTENB signal output and EXTSEL signal input
In PBI Atari XE there is only the EXSEL signal output



Gianluca Renzi
RetroBit Lab

Sheet: /BusDecoder/		
File: busdecoder.sch		
Title: BUS DECODER		
Size: A3	Date: 2025-09-23	**Rev: 1.0**
KiCad E.D.A. kicad 5.1.9+dfsg1-1+deb11u1		Id: 3/6

ATARI 130XE ECI & CARTRIDGE INTERFACE



BUS LOGIC LEVEL SHIFTERS



Gianluca Renzi **RetroBit Lab**		
Sheet: /CartridgeInterface/ File: cartridgeInterface.sch		
Title: CARTRIDGE INTEFACE AND BUS LEVEL SHIFTERS		
Size: A3	Date: 2025-09-23	**Rev: 1.0**
KiCad E.D.A. kicad 5.1.9+dfsg1-1+deb11u1		Id: 4/6

FPGA/SSD Flash Glue Logic



SD/microSD INTERFACE



AUDIO SECTION

IC DAC/AUDIO 24BIT 192K 16TSSOP



AUDIO 3.5mm OUTPUT



SPI 16MB FLASH



Gianluca Renzi
RetroBit Lab

Sheet: /Vera FPGA flash/
File: vera-fpga-flash.sch

Title: uSD Card and FLASH for FPGA

Size: A3	Date: 2025-09-23	**Rev: 1.0**
KiCad E.D.A. kicad 5.1.9+dfsg1-1+deb11u1		Id: 5/6

USB ESP32 PROGRAMMING



POWER LED
5V: RED
3.3V: GREEN



POWER INPUT: from 5VDC...24VDC
Positive CENTRAL PIN



POWER 3.3V & POWER 1.2V



Gianluca Renzi **RetroBit Lab**		
Sheet: /PowerSupply/ File: powersupply.sch		
Title: POWERSUPPLY and USB		
Size: A3	Date: 2025-09-23	**Rev: 1.0**
KiCad E.D.A. kicad 5.1.9+dfsg1-1+deb11u1		Id: 6/6