빗썸 API 레퍼런스

apidocs.bithumb.com

목차

1. 1. Bithumb, the No. 1 virtual asset platform
2. 2. API Usage Guide
3. 3. Market Code Inquiry
4. 4. Announcement
5. 5. Bithumb, the No. 1 virtual asset platform
6. 6. Bithumb, the No. 1 virtual asset platform
7. 7. API Usage Guide
8. 8. API Request Limit Information
9. 9. Creating an authentication header
10. 10. API Major Error Codes
11. 11. Frequently Asked Questions (FAQ)
12. 12. API Usage Guide
13. 13. API Usage Guide
14. 14. Market Code Inquiry
15. 15. Minute candle
16. 16. Day candle
17. 17. Week candle
18. 18. Month candle
19. 19. Recent contract details
20. 20. Current price information
21. 21. Orderbook information inquiry
22. 22. Market alert system
23. 23. View notices
24. 24. Check deposit/withdrawal fees
25. 25. View all accounts
26. 26. Ordering Information
27. 27. Individual Order Inquiry
28. 28. View order list
29. 29. Order Request
30. 30. Order cancellation request
31. 31. Multi-order request
32. 32. Multiple order cancellations accepted
33. 33. TWAP - Order History
34. 34. TWAP - Cancel Order
35. 35. TWAP - Order
36. 36. View coin withdrawal list
37. 37. View the list of Korean won withdrawals
38. 38. Individual withdrawal inquiry
39. 39. Withdrawal information
40. 40. Withdrawing Virtual Assets
41. 41. Withdraw Korean won
42. 42. List of allowed withdrawal addresses inquiry
43. 43. Check coin deposit list
44. 44. Check the list of Korean won deposits
45. 45. Individual deposit inquiry
46. 46. Request to create a deposit address
47. 47. All deposit addresses inquiry
48. 48. Individual deposit addresses inquiry
49. 49. Deposit Korean won
50. 50. Deposit/Withdrawal Status
51. 51. API key list inquiry
52. 52. Basic information
53. 53. Request Method and Format
54. 54. Test and Request Examples
55. 55. Current price (Ticker)
56. 56. Trade
57. 57. Orderbook
58. 58. My Order and Execution (MyOrder)
59. 59. MyAsset
60. 60. WebSocket Error
61. 61. Connection Management
62. 62. Minute candle
63. 63. Market Code Inquiry
64. 64. Recent contract details
65. 65. Current price information
66. 66. Orderbook information inquiry
67. 67. Market alert system
68. 68. View all accounts
69. 69. Ordering Information
70. 70. TWAP - Order History
71. 71. View coin withdrawal list
72. 72. Check coin deposit list
73. 73. Deposit/Withdrawal Status
74. 74. Current price (Ticker)
75. 75. Current price information inquiry (ALL)
76. 76. Market Code Inquiry

1 Bithumb, the No. 1 virtual asset platform

한국어
Powered by Localize
English

API Usage Guide

Updated 4 months ago

API Request Limit Information

Did this page help you?

Yes

No

Market Code Inquiry

get
https://api.bithumb.com/v1/market/all

We provide information on markets and virtual assets available for trading on Bithumb.

Example code is provided only for JavaScript, Python, and JAVA.

Response

field	Details	Type
market	Market information provided by Bithumb	String
korean_name	Korean name of the digital asset to be traded	String
english_name	English name of the digital asset to be traded	String
market_warning	Investment Warning Status `NONE` (not applicable), `CAUTION` (Trading Caution) It returns the status of whether it is designated as an 'Investment Warning Item'. For the designation status of a 'Cautionary Item', please refer to the Alert System API.	String

Query Params

isDetails

boolean

Defaults to false

Whether to display detailed information such as the noteworthy item field (optional parameter)

Responses

200

200

Response body

json

```
400
400
```

Updated 4 months ago

Price candle inquiry

Did this page help you?

Yes

No

4 Announcement

Hello. This is Bithumb, your safe financial partner.

5 Bithumb, the No. 1 virtual asset platform

한국어
Powered by Localize
English

6 Bithumb, the No. 1 virtual asset platform

한국어
Powered by Localize
English

API Usage Guide

Updated 4 months ago

Did this page help you?

Yes

No

API Request Limit Information

To provide stable service, we limit the number of requests per second by API type.

Request Limit Criteria

Category	Maximum number of requests per second
Public API	150 times
Private API	140 times

> ⚠️
>
> **Additional restrictions on order-related APIs** — Order-related requests, such as creating or canceling orders, may be limited if they exceed **10 requests per second** .

Operation when limit is exceeded

API usage will be temporarily restricted if the request limit is exceeded.

- Please wait a moment until the restriction is lifted, then request again.

> 💡
>
> Distributing request intervals evenly can reduce the likelihood of hitting limits. Instead of sending a large volume of requests at once, it is recommended to make calls at regular intervals.

Note

- In the event of excessive traffic, such as a surge in users, we may limit or reduce API request volume **without prior notice** to ensure stable service provision.
- If API usage is restricted due to excessive requests and is not automatically released, please contact **the Customer Center at 1661-5566** .

Updated 12 days ago

API Usage Guide
Creating an authentication header

Did this page help you?
Yes
No

- Table of Contents
-
  - Request Limit Criteria
  - Operation when limit is exceeded
  - Note

Creating an authentication header

REST API request format

REST API calls are made via HTTP.

If a body exists in a POST, PUT, or DELETE request, parameters must be sent in JSON format.
Examples of valid content types are as follows, and may vary slightly depending on the programming language library.

```
Content-Type: application/json; charset=utf-8
```

Creating a JWT Authentication Token

When requesting a REST API, the issued `API Key` and `Secret Key` By creating a token `Authorization` It is transmitted through the header. The token is a JWT (https://jwt.io) follows the format.

The signing method is `HS256` It is recommended that you use the issued Secret for signing. `Secret Key` Use .
The payload consists of:

Issued when requesting a private API `API Key` and `Secret Key` It is transmitted by adding 5 parameters to the header using .

Request variables	Details	Type
access_key	User API Key	String / Required
nonce	A random UUID string	String / Required
timestamp	A value representing the current time in milliseconds (ms) (e.g. 1655280216476)	Number / Required
query_hash	Hashed query string (required if parameters are present)	String / Options
query_hash_alg	The algorithm used to generate query_hash (default: SHA512)	String / Options

Here is an example of the payload of the generated authentication header.

JSON

```
{
  "access_key": "L7rVaYfBIc2BDsnlQGfkR93d6DoOAJCw7mJr5Eso",
  "nonce": "6f5570df-d8bc-4daf-85b4-976733feb624",
  "timestamp": 1712230310689,
  "query_hash":
"1c2362ca9d79947582cae192acf63efb8756caa49af1eb64b12ba45617165431a3dd3e47d0476bc2a347b7a1ea5
  "query_hash_alg": "SHA512"
}
```

(Example) If there are no parameters

Node | Python | Java

```
const jwt = require('jsonwebtoken')
const { v4: uuidv4 } = require('uuid')

const accessKey = '발급받은 API KEY'
const secretKey = '발급받은 SECRET KEY'

const payload = {
    access_key: accessKey,
    nonce: uuidv4(),
    timestamp: Date.now()
};

console.log(payload);

const jwtToken = jwt.sign(payload, secretKey)
const authorizationToken = `Bearer ${jwtToken}`

console.log(authorizationToken);
```

```
# Python 3
# pip3 installl pyJwt
import jwt
import uuid
import time

accessKey = "발급받은 API KEY"
secretKey = "발급받은 SECRET KEY"

payload = {
    'access_key': accessKey,
    'nonce': str(uuid.uuid4()),
    'timestamp': round(time.time() * 1000)
}
```

```
print(payload, "\n")

jwt_token = jwt.encode(payload, secretKey)
authorization_token = 'Bearer {}'.format(jwt_token)

print(authorization_token)
```

```
// https://mvnrepository.com/artifact/com.auth0/java-jwt
import com.auth0.jwt.JWT;
import com.auth0.jwt.algorithms.Algorithm;

import java.util.UUID;

public class OpenAPIAuthSampleNoArgs {

    public static void main(String[] args) {
        String accessKey = "발급받은 API KEY";
        String secretKey = "발급받은 SECRET KEY";

        Algorithm algorithm = Algorithm.HMAC256(secretKey);

        String jwtToken = JWT.create()
                .withClaim("access_key", accessKey)
                .withClaim("nonce", UUID.randomUUID().toString())
                .withClaim("timestamp", System.currentTimeMillis())
                .sign(algorithm);

        String authenticationToken = "Bearer " + jwtToken;

        System.out.println(authenticationToken);
    }
}
```

(Example) If there are parameters

Whether you pass parameters via the HTTP query string or body, you must set the query_hash value in the JWT payload.

If an array exists among the parameter data types, the correct query string format is as follows:

```
key[]=value1&key[]=value2 ...
```

Please note that requesting in any other format may result in token verification failure.

Node | Python | Java

```
const jwt = require('jsonwebtoken');
const { v4: uuidv4 } = require('uuid');
const crypto = require('crypto');
```

```
const querystring = require('querystring');

const accessKey = '발급받은 API KEY'
const secretKey = '발급받은 SECRET KEY'

// GET (query parameters)
// const query = 'string=abc&number=123'
// POST (request body)
const query = querystring.encode({
    string: 'abc',
    number: 123
})

const alg = 'SHA512'
const hash = crypto.createHash(alg)
const queryHash = hash.update(query, 'utf-8').digest('hex')

const payload = {
    access_key: accessKey,
    nonce: uuidv4(),
    timestamp: Date.now(),
    query_hash: queryHash,
    query_hash_alg: alg
};

console.log(payload);

const jwtToken = jwt.sign(payload, secretKey)
const authorizationToken = `Bearer ${jwtToken}`

console.log(authorizationToken);
```

```
# Python 3
# pip3 installl pyJwt
import jwt
import uuid
import hashlib
import time
from urllib.parse import urlencode

accessKey = "발급받은 API KEY"
secretKey = "발급받은 SECRET KEY"

# GET (query parameters)
# query = 'string=abc&number=123'.encode()
# POST (request body)
query = urlencode(dict( string="abc", number=123 )).encode()

hash = hashlib.sha512()
hash.update(query)
query_hash = hash.hexdigest()
```

```
payload = {
    'access_key': accessKey,
    'nonce': str(uuid.uuid4()),
    'timestamp': round(time.time() * 1000),
    'query_hash': query_hash,
    'query_hash_alg': 'SHA512',
}

print(payload, "\n")

jwt_token = jwt.encode(payload, secretKey)
authorization_token = 'Bearer {}'.format(jwt_token)

print(authorization_token)
```

```
// https://mvnrepository.com/artifact/com.auth0/java-jwt
import com.auth0.jwt.JWT;
import com.auth0.jwt.algorithms.Algorithm;
// https://mvnrepository.com/artifact/org.apache.httpcomponents/httpclient
import org.apache.http.NameValuePair;
import org.apache.http.client.utils.URLEncodedUtils;
import org.apache.http.message.BasicNameValuePair;

import java.math.BigInteger;
import java.nio.charset.StandardCharsets;
import java.security.MessageDigest;
import java.security.NoSuchAlgorithmException;
import java.util.ArrayList;
import java.util.List;
import java.util.UUID;

public class OpenAPIAuthSampleArgs {

    public static void main(String[] args) throws NoSuchAlgorithmException {

        String accessKey = "발급받은 API KEY";
        String secretKey = "발급받은 SECRET KEY";

        // GET (query parameters)
                                // String query = "string=abc&number=123";
        // POST (request body)
        List<NameValuePair> queryParams = new ArrayList<>();
        queryParams.add(new BasicNameValuePair("string", "abc"));
        queryParams.add(new BasicNameValuePair("number", "123"));
        String query = URLEncodedUtils.format(queryParams, StandardCharsets.UTF_8);

        MessageDigest md = MessageDigest.getInstance("SHA-512");
        md.update(query.getBytes(StandardCharsets.UTF_8));

        String queryHash = String.format("%0128x", new BigInteger(1, md.digest()));
```

```
        Algorithm algorithm = Algorithm.HMAC256(secretKey);
        String jwtToken = JWT.create()
                .withClaim("access_key", accessKey)
                .withClaim("nonce", UUID.randomUUID().toString())
                .withClaim("timestamp", System.currentTimeMillis())
                .withClaim("query_hash", queryHash)
                .withClaim("query_hash_alg", "SHA512")
                .sign(algorithm);

        String authenticationToken = "Bearer " + jwtToken;

        System.out.println(authenticationToken);
    }
}
```

Updated about 1 year ago

API Request Limit Information

API Major Error Codes

Did this page help you?

Yes

No

- Table of Contents
-
  - REST API request format
  - Creating a JWT Authentication Token
  -
    - (Example) If there are no parameters
    - (Example) If there are parameters

API Major Error Codes

Outline

If the API request value is invalid or an error occurs during processing, a JSON body in the following format is returned along with an HTTP status code.

```
"error": {
  "message": "<오류에 대한 설명>",
  "name": "<오류 코드>"
}
```

The main error codes are:

400 Bad Request

cord	Details
invalid_parameter	Invalid parameter.
invalid_price	You entered the wrong order price unit. Please check and try again.
under_price_limit_ask under_price_limit_bid	The minimum order price is %s You can order as above.
invalid_price_ask invalid_price_bid	You entered the wrong order price unit. Please check and try again.
bank_account_required	You can use it after registering a real-name verification deposit/withdrawal account.

cord	Details
two_factor_auth_required	Please enter a valid authentication channel.
currency does not have a valid value	This coin is not supported by Bithumb.
cross_trading	The order you submitted has been cancelled as it may be combined with an existing order you submitted.
withdraw_insufficient_balance	The maximum withdrawal limit has been exceeded.

401 Unauthorized

The 401 Unauthorized error most often occurs when the JWT signature is not correct. Please refer to the Creating an Authentication Header document to ensure the signature is correct.

cord	Details
invalid_query_payload	Failed to validate JWT query.
jwt_verification	JWT token verification failed.
expired_jwt	JWT has expired.
NotAllowIP	not allowed client IP
out_of_scope	Insufficient permissions.

403 Forbidden

The 403 Forbidden error most often indicates insufficient access or a restricted feature due to operational policy. For further inquiries, please contact Customer Service.

cord	Details
blocked_member_id	Service usage has been restricted in accordance with our operational policy.

404 Not Found

cord	Details
order_not_found	The order could not be found.
deposit_not_found withdraw_not_found	Deposit/withdrawal information not found.

422 UNPROCESSABLE_ENTITY

cord	Details
order_not_ready	Your order is being processed. Please try again later.

500 Internal Server Error

A 500 Internal Server Error occurs when there's nothing wrong with the request, but the server encounters a temporary issue (e.g., a delayed response) while processing the data. Please try again later.

cord	Details
server_error	The system is not working properly. Please try again later.

Updated 4 months ago

Creating an authentication header
Frequently Asked Questions (FAQ)

Did this page help you?

Yes

No

- Table of Contents
-
  - Outline
  - 400 Bad Request
  - 401 Unauthorized
  - 403 Forbidden
  - 404 Not Found
  - 422 UNPROCESSABLE_ENTITY
  - 500 Internal Server Error

Frequently Asked Questions (FAQ)

I am getting an invalid parameter error when using the withdrawal API.

In accordance with the 'Act on Reporting and Use of Specific Financial Transaction Information', from March 25, 2022, when withdrawing virtual assets to wallets other than Bithumb, only transfers to VASPs that can provide virtual asset sender/recipient information will be permitted.

When withdrawing funds to a wallet other than Bithumb via the withdrawal API, please be sure to check the following:

- Required request parameters when withdrawing to a personal wallet
  - exchange_name: English name of the withdrawal exchange
  - receiver_type: Whether the recipient is an individual or corporation (individual: 'personal', corporation: 'corporation')
  - ko_name: Personal recipient information_Korean name
  - en_name: Personal recipient information_English name
- Required request parameters when withdrawing to a corporate wallet
  - exchange_name: English name of the withdrawal exchange
  - corp_ko_name: Corporate receipt information_Korean corporate name
  - corp_en_name: Corporate Recipient Information_English Corporate Name
  - corp_rep_ko_name: Corporate Recipient Information_Korean Corporate Representative Name
  - corp_rep_en_name: Corporate Recipient Information_English Corporate Representative Name

If you see an error message asking you to 'try again' other than 'invalid parameter', please double-check the recipient information as the recipient information you entered may be different from the actual recipient information.

When calling the API, it is confirmed that the IP is blocked

To ensure stable service, Bithumb Open API limits the number of requests per API. Please note that exceeding the limit will result in temporary IP blocking.

- Public API
  - Up to 150 requests per second
  - 1 minute limit for exceeding requests
- Private API
  - Up to 140 requests per second
  - In case of over-request, Private info: 5-minute limit / Private trade: 10-minute limit

Please note that the block will be automatically lifted when the time limit expires, and failed calls will also count towards the limit.

Updated 4 months ago

API Major Error Codes

Did this page help you?

Yes

No

- Table of Contents
-
  - I am getting an invalid parameter error when using the withdrawal API.
  - When calling the API, it is confirmed that the IP is blocked

API Usage Guide

Updated 4 months ago

API Request Limit Information

Did this page help you?

Yes

No

API Usage Guide

Updated 4 months ago

API Request Limit Information

Did this page help you?

Yes

No

Market Code Inquiry

get

https://api.bithumb.com/v1/market/all

We provide information on markets and virtual assets available for trading on Bithumb.

Example code is provided only for JavaScript, Python, and JAVA.

Response

field	Details	Type
market	Market information provided by Bithumb	String
korean_name	Korean name of the digital asset to be traded	String
english_name	English name of the digital asset to be traded	String
market_warning	Investment Warning Status `NONE` (not applicable), `CAUTION` (Trading Caution) It returns the status of whether it is designated as an 'Investment Warning Item'. For the designation status of a 'Cautionary Item', please refer to the Alert System API.	String

Query Params

isDetails

boolean

Defaults to false

Whether to display detailed information such as the noteworthy item field (optional parameter)

Responses

200

200

Response body

json

```
400
400
```

Updated 4 months ago

Price candle inquiry

Did this page help you?

Yes

No

Minute candle

get
https://api.bithumb.com/v1/candles/minutes/{unit}

Example code is provided only for JavaScript, Python, and JAVA.

Request Parameters

field	Details	Type
market	Market code (ex. KRW-BTC)	String
to	Last candle time (exclusive). ISO8061 format (yyyy-MM-dd HH:mm:ss or yyyy-MM-ddTHH:mm:ss). Default is KST time, and if left blank, the most recent candle will be requested.	String
count	Number of candles (up to 200 can be requested), default 1	Integer

Response

field	Details	Type
market	Market name	String
candle_date_time_utc	Candle reference time (UTC) Format: `yyyy-MM-dd'T'HH:mm:ss`	String
candle_date_time_kst	Candlestick reference time (KST) Format: `yyyy-MM-dd'T'HH:mm:ss`	String
opening_price	market price	Double
high_price	high price	Double
low_price	low price	Double

field	Details	Type
trade_price	Closing price	Double
timestamp	Candle closing time (based on KST)	Long
candle_acc_trade_price	Cumulative transaction amount	Double
candle_acc_trade_volume	Cumulative trading volume	Double
unit	Minutes (units)	Integer

Path Params

unit

int32

required

Defaults to 1

Minutes. Possible values: 1, 3, 5, 10, 15, 30, 60, 240

Query Params

market
string
required
Defaults to KRW-BTC

Market code (ex. KRW-BTC)

to
string

Last candle time (exclusive). Leave blank to request the most recent candle.

count
int32
Defaults to 1

Number of candles (up to 200 can be requested)

Responses

200

200

Response body

array of objects

object

market

string

candle_date_time_utc

string

candle_date_time_kst

string

opening_price

integer

Defaults to 0

high_price

integer

Defaults to 0

low_price

integer
Defaults to 0
trade_price
integer
Defaults to 0
timestamp
integer
Defaults to 0
candle_acc_trade_price
number
Defaults to 0
candle_acc_trade_volume
number
Defaults to 0
unit
integer
Defaults to 0

400
400

Updated 30 days ago

Market Code Inquiry
Day candle
Did this page help you?
Yes
No

Day candle

get

https://api.bithumb.com/v1/candles/days

Example code is provided only for JavaScript, Python, and JAVA.

Request Parameters

field	Details	Type
market	Market code (ex. KRW-BTC)	String
to	Last candle time (exclusive) • ISO8061 format (yyyy-MM-dd HH:mm:ss or yyyy-MM-ddTHH:mm:ss) • Standard time KST • Empty to return the most recent candle on request	String
count	Number of candles (up to 200 can be requested), default 1	Integer
convertingPriceUnit	Currency unit for conversion to closing price (can be omitted, if entered in KRW, it will be returned as the price converted to Korean Won)	String

Response

field	Details	Type
market	Market name	String
candle_date_time_utc	Candlestick Reference Time (UTC) Format: `yyyy-MM-dd'T'HH:mm:ss`	String
candle_date_time_kst	Candlestick Time (KST) Format: `yyyy-MM-dd'T'HH:mm:ss`	String
opening_price	market price	Double

field	Details	Type
high_price	high price	Double
low_price	low price	Double
trade_price	Closing price	Double
timestamp	Candle closing time (based on KST)	Long
candle_acc_trade_price	Cumulative transaction amount	Double
candle_acc_trade_volume	Cumulative trading volume	Double
prev_closing_price	Previous day's closing price (as of 00:00 UTC)	Double
change_price	Change from the previous day's closing price	Double
change_rate	Change compared to the previous day's closing price	Double
converted_trade_price	Price converted to the closing price currency (on request) `convertingPriceUnit` If there is no parameter, the field is not returned)	Double

`convertingPriceUnit` In the case of parameters, when requesting a daily chart for a market other than the KRW market (e.g., BTC), the closing price is converted to the specified parameter value. `converted_trade_price` Add to field and return.

Currently, the won (`KRW`) only provides the ability to convert to and the functionality can be expanded in the future.

Query Params

market
string
required

Market code (ex. KRW-BTC)

to
string

Last candle time (exclusive). Leave blank to request the most recent candle.

count
int32
Defaults to 1

Number of candles (up to 200 can be requested)

convertingPriceUnit
string

Currency unit for conversion to closing price (optional; if specified as KRW, the price converted to Korean Won will be returned)

Responses

200

200

Response body

array of objects

object

market

string

candle_date_time_utc

string

candle_date_time_kst

string

opening_price

integer

Defaults to 0

high_price

integer

Defaults to 0

low_price

integer
Defaults to 0
trade_price
integer
Defaults to 0
timestamp
integer
Defaults to 0
candle_acc_trade_price
number
Defaults to 0
candle_acc_trade_volume
number
Defaults to 0
prev_closing_price
integer
Defaults to 0
change_price
integer
Defaults to 0
change_rate
number
Defaults to 0

400
400

Updated 30 days ago

Minute candle
Week candle

Did this page help you?
Yes
No

Week candle

get
https://api.bithumb.com/v1/candles/weeks

Example code is provided only for JavaScript, Python, and JAVA.

Request Parameters

field	Details	Type
market	Market code (ex. KRW-BTC)	String
to	Last candle time (exclusive). ISO8061 format (yyyy-MM-dd HH:mm:ss or yyyy-MM-ddTHH:mm:ss). Default is KST time, and if left blank, the most recent candle will be requested.	String
count	Number of candles (up to 200 can be requested), default 1	Integer

Response

field	Details	Type
market	Market name	String
candle_date_time_utc	Candle reference time (UTC) Format: `yyyy-MM-dd'T'HH:mm:ss`	String
candle_date_time_kst	Candlestick reference time (KST) Format: `yyyy-MM-dd'T'HH:mm:ss`	String
opening_price	market price	Double
high_price	high price	Double
low_price	low price	Double

field	Details	Type
trade_price	Closing price	Double
timestamp	Candle closing time (based on KST)	Long
candle_acc_trade_price	Cumulative transaction amount	Double
candle_acc_trade_volume	Cumulative trading volume	Double
first_day_of_period	The very first day of the candle period	String

Query Params

market
string
required

Market code (ex. KRW-BTC)

to
string

Last candle time (exclusive). Leave blank to request the most recent candle.

count
int32
Defaults to 1

Number of candles (up to 200 can be requested)

Responses

200

200

Response body

array of objects

object

market

string

candle_date_time_utc

string

candle_date_time_kst

string

opening_price

integer

Defaults to 0

high_price

integer

Defaults to 0

low_price

integer

Defaults to 0

trade_price

integer

Defaults to 0

timestamp

integer

Defaults to 0

candle_acc_trade_price

number

Defaults to 0

candle_acc_trade_volume

number

Defaults to 0

first_day_of_period

string

400

400

Updated 30 days ago

Day candle

Month candle

Did this page help you?

Yes

No

Month candle

get
https://api.bithumb.com/v1/candles/months

Example code is provided only for JavaScript, Python, and JAVA.

Request Parameters

field	Details	Type
market	Market code (ex. KRW-BTC)	String
to	Last candle time (exclusive). ISO8061 format (yyyy-MM-dd HH:mm:ss or yyyy-MM-ddTHH:mm:ss). Default is KST time, and if left blank, the most recent candle will be requested.	String
count	Number of candles (up to 200 can be requested), default 1	Integer

Response

field	Details	Type
market	Market name	String
candle_date_time_utc	Candle reference time (UTC) Format: `yyyy-MM-dd'T'HH:mm:ss`	String
candle_date_time_kst	Candlestick reference time (KST) Format: `yyyy-MM-dd'T'HH:mm:ss`	String
opening_price	market price	Double
high_price	high price	Double
low_price	low price	Double

field	Details	Type
trade_price	Closing price	Double
timestamp	Candle closing time (based on KST)	Long
candle_acc_trade_price	Cumulative transaction amount	Double
candle_acc_trade_volume	Cumulative trading volume	Double
first_day_of_period	The very first day of the candle period	String

Query Params

market
string
required

Market code (ex. KRW-BTC)

to
string

Last candle time (exclusive). Leave blank to request the most recent candle.

count
int32
Defaults to 1

Number of candles (up to 200 can be requested)

Responses

200

200

Response body

array of objects

object

market

string

candle_date_time_utc

string

candle_date_time_kst

string

opening_price

integer

Defaults to 0

high_price

integer

Defaults to 0

low_price

integer

Defaults to 0

trade_price

integer

Defaults to 0

timestamp

integer

Defaults to 0

candle_acc_trade_price

number

Defaults to 0

candle_acc_trade_volume

number

Defaults to 0

first_day_of_period

string

400

400

Updated 30 days ago

Week candle

Price execution inquiry

Did this page help you?

Yes

No

Recent contract details

get

https://api.bithumb.com/v1/trades/ticks

Example code is provided only for JavaScript, Python, and JAVA.

Response

field	Details	Type
market	Market classification code	String
trade_date_utc	Date of execution (UTC) Format: `yyyy-MM-dd`	String
trade_time_utc	Execution time (UTC) Format: `HH:mm:ss`	String
timestamp	Execution timestamp	Long
trade_price	Execution price	Double
trade_volume	Execution amount	Double
prev_closing_price	Previous day's closing price (as of 00:00 UTC)	Double
change_price	Amount of change	Double
ask_bid	Sell/Buy	String
sequential_id	Contract Number (Unique)	Long

- `sequential_id` Fields can be used as a basis for determining the uniqueness of a transaction, but do not guarantee the order of transactions.

Query Params

market
string
required

Market code (ex. KRW-BTC)

to
string

Last transaction time. Format: [HHmmss or HH:mm:ss]. Leave blank to request the most recent data (00:00:00 to 23:59:59).

count
int32
Defaults to 1

Number of contracts (1-500)

cursor
string

Pagination Cursor (sequentialId)

daysAgo
int32

You can view data from up to 7 days prior to the most recent transaction date. If left blank, the most recent transaction date will be returned. (Range: 1 to 7)

Responses

200

200

Response body

array of objects

object

market

string

trade_date_utc

string

trade_time_utc

string

timestamp

integer

Defaults to 0

trade_price

integer

Defaults to 0

trade_volume

number

Defaults to 0

prev_closing_price

integer

Defaults to 0

chane_price

integer

Defaults to 0

ask_bid

string

400

400

Updated 4 months ago

Month candle

Current price (Ticker) inquiry

Did this page help you?

Yes

No

Current price information

get

https://api.bithumb.com/v1/ticker

A snapshot of the stock at the time of request is provided.

Example code is provided only for JavaScript, Python, and JAVA.

Response

field	Details	Type
market	Item classification code	String
trade_date	Last transaction date (UTC) Format: `yyyyMMdd`	String
trade_time	Last transaction time (UTC) Format: `HHmmss`	String
trade_date_kst	Last transaction date (KST) Format: `yyyyMMdd`	String
trade_time_kst	Last trading time (KST) Format: `HHmmss`	String
trade_timestamp	Last transaction date (UTC) Format: `Unix Timestamp`	Long
opening_price	market price	Double
high_price	high price	Double
low_price	low price	Double
trade_price	closing price (current price)	Double

field	Details	Type
prev_closing_price	Previous day's closing price (as of 00:00 KST)	Double
change	EVEN: Consolidated RISE: Rise FALL: decline	String
change_price	Absolute value of change	Double
change_rate	Absolute value of rate of change	Double
signed_change_price	Signed change amount	Double
signed_change_rate	Signed rate of change	Double
trade_volume	Most recent trading volume	Double
acc_trade_price	Cumulative transaction amount (as of 00:00 KST)	Double
acc_trade_price_24h	24-hour cumulative trading volume	Double
acc_trade_volume	Cumulative trading volume (as of 00:00 KST)	Double
acc_trade_volume_24h	24-hour cumulative trading volume	Double
highest_52_week_price	52-week high	Double
highest_52_week_date	52-week high achieved date Format: `yyyy-MM-dd`	String
lowest_52_week_price	52-week low	Double
lowest_52_week_date	52-week low achieved date Format: `yyyy-MM-dd`	String
timestamp	timestamp	Long

*The above response `change`, `change_price`, `change_rate`, `signed_change_price`, `signed_change_rate` The field is the comparison value of the previous day's closing price.

Query Params

markets

string

required

Market codes separated by dots (e.g. KRW-BTC, BTC-ETH)

Responses

200

200

Response body

array of objects

object

market

string

trade_date

string

trade_time

string

trade_date_kst

string

trade_time_kst

string

trade_timestamp

integer

Defaults to 0

opening_price
integer
Defaults to 0
high_price
integer
Defaults to 0
low_price
integer
Defaults to 0
trade_price
integer
Defaults to 0
prev_closing_price
integer
Defaults to 0
change
string
change_price
integer
Defaults to 0
change_rate
number
Defaults to 0
signed_change_price
integer
Defaults to 0
signed_change_rate
number
Defaults to 0
trade_volume
number
Defaults to 0
acc_trade_price
number
Defaults to 0
acc_trade_price_24h
number
Defaults to 0
acc_trade_volume
number
Defaults to 0
acc_trade_volume_24h
number
Defaults to 0
highest_52_week_price
integer
Defaults to 0
highest_52_week_date

string

lowest_52_week_price

integer

Defaults to 0

lowest_52_week_date

string

timestamp

integer

Defaults to 0

400

400

Updated 9 months ago

Recent contract details

Market price information (Orderbook) inquiry

Did this page help you?

Yes

No

Orderbook information inquiry

get

https://api.bithumb.com/v1/orderbook

Example code is provided only for JavaScript, Python, and JAVA.

Response

field	Details	Type
market	Market Code	String
timestamp	Orderbook generation time	Long
total_ask_size	Total remaining quantity of asks	Double
total_bid_size	Total remaining quantity of bids	Double
orderbook_units	Orderbook	List of Objects
ask_price	Sell price	Double
bid_price	Bid price	Double
ask_size	Ask size	Double
bid_size	Bid size	Double

`orderbook_units` The list contains information in order of 15 (1, 2, ... 15). However, `market` When entering only a single market code `orderbook_units` The list provides information up to 30 units.`

Query Params

markets

array of strings

required

List of market codes (ex. KRW-BTC, BTC-ETH)

markets *

ADD string

Responses

200

200

Response body

array of objects
object
market
string
timestamp
integer
Defaults to 0
total_ask_size
number
Defaults to 0
total_bid_size
number
Defaults to 0
orderbook_units
array of objects

orderbook_units
object
ask_price
integer
Defaults to 0
bid_price
integer
Defaults to 0
ask_size
number
Defaults to 0
bid_size
number
Defaults to 0

400

400

Updated 9 months ago

Current price information
Service Information
Did this page help you?
Yes
No

Market alert system

get

https://api.bithumb.com/v1/market/virtual_asset_warning

View the list of markets and coins under alert

Example code is provided only for JavaScript, Python, and JAVA.

Response

field	Details	Type
market	Market information provided by Bithumb	String

warning_type	Alert Type
	`- PRICE_SUDDEN_FLUCTUATION : 가격 급등락`
	`- PRICE_DIFFERENCE_HIGH : 글로벌 시세차이`
	`- SPECIFIC_ACCOUNT_HIGH_TRANSACTION : 소수계정 거래 집중`
	`- TRADING_VOLUME_SUDDEN_FLUCTUATION : 거래량 급등`
	`- DEPOSIT_AMOUNT_SUDDEN_FLUCTUATION : 입금량 급등`
		String

warning_step	Alert level
	`- CAUTION : 주의`
	`- WARNING : 경고`
	`- DANGER : 위험`
		String

end_date	Virtual asset alert end date (based on KST) Format: `yyyy-MM-dd HH:mm:ss`	String

Responses

200

200

Response body

array of objects

object

market

string

warning_type

string

warning_step

string

end_date

string

400

400

Updated 30 days ago

Orderbook information inquiry

View notices

Did this page help you?

Yes

No

View notices

get

https://api.bithumb.com/v1/notices

Check Bithumb's Notices

Example code is provided only for JavaScript, Python, and JAVA.

Request Parameters

field	Details	Type
count	Number of notice posts viewed (default: 5, minimum: 1, maximum: 20)	Number

🚧

notification

- The current API call limit is set to **one call per second per IP** . However, this limit may change depending on system conditions or traffic.

Response

field	Details	Type
categories	Notice Category	Array[String]
title	Notice Title	String
pc_url	Notice URL	String
published_at	Notice posting time (yyyy-MM-dd hh:mm:ss)	String
modified_at	Notice modification time (yyyy-MM-dd hh:mm:ss)	String

📘

Information

- The list of notice is provided in chronological order based on the posting time (published_at).

Responses

200

200

Response body

json

```
400
400
```

Updated 12 months ago

Market alert system

Check deposit/withdrawal fees

Did this page help you?

Yes

No

Check deposit/withdrawal fees

get

https://api.bithumb.com/v2/fee/inout/{currency}

We provide the minimum deposit/withdrawal amount and deposit/withdrawal fees for virtual assets listed on Bithumb.

Example code is provided only for JavaScript, Python, JAVA, and Shell.

Request Parameters

field	Details	Type
currency	English capital letter code for currency (all responses when requested as ALL)	String

Response

field	Details	Type
name	Coin name	String
currency	Coin Symbol	String
networks	Deposit/Withdrawal Network Information	Array[Object]
networks.net_name	Deposit/Withdrawal Network Name	String
networks.deposit_fee_quantity	Deposit fee	NumberString
networks.deposit_minimum_quantity	Minimum deposit amount (if deposit is less than the minimum amount, a fee will be charged)	NumberString
networks.withdraw_fee_quantity	Withdrawal fee	NumberString
networks.withdraw_minimum_quantity	Minimum withdrawal amount	NumberString

Path Params

currency
string
required

Responses

200

200

Response body

array of objects

object

name

string

currency

string

networks

array of objects

networks

object

net_name

string

deposit_fee_quantity

string

deposit_minimum_quantity

string

withdraw_fee_quantity

string

withdraw_minimum_quantity

string

400

400

Updated 5 months ago

View notices

Asset

Did this page help you?

Yes

No

View all accounts

get

https://api.bithumb.com/v1/accounts

View information about the assets you hold.

Example code is provided only for JavaScript, Python, and JAVA.

Response

field	Details	Type
currency	English capital letter code for currency	String
balance	Orderable amount/quantity	NumberString
locked	Amount/quantity tied to the order	NumberString
avg_buy_price	Average purchase price	NumberString
avg_buy_price_modified	Whether to revise the average purchase price	Boolean
unit_currency	Currency based on average price	String

Headers

Authorization
string
required

Authorization token (JWT)

Responses

200

200

Response body

array of objects

object

currency

string

balance

string

locked

string

avg_buy_price

string

avg_buy_price_modified

boolean

Defaults to true

unit_currency

string

400

400

Updated 9 months ago

Check deposit/withdrawal fees

Order

Did this page help you?

Yes

No

Ordering Information

get

https://api.bithumb.com/v1/orders/chance

Check order availability information by market.

Example code is provided only for JavaScript, Python, and JAVA.

Request Parameters

field	Details	Type
market *	Market ID (ex.KRW-BTC)	String

Response

field	Details	Type
bid_fee	buying commission rate	NumberString
ask_fee	Selling commission rate	NumberString
maker_bid_fee	Market buying commission rate	NumberString
maker_ask_fee	Market Selling Fee Rate	NumberString
market	Information about the market	Object
market.id	The only key in the market	String
market.name	Market name	String
market.order_types	Support Order Method	Array[String]
market.ask_types	Sell order support method	Array[String]
market.bid_types	Buy order support method	Array[String]
market.order_sides	Support Order Types	Array[String]
market.bid	Restrictions on purchase	Object
market.bid.currency	English capital letter code for currency	String
market.bid.price_unit	Order amount unit	NumberString
market.bid.min_total	Minimum buy/sell amount	NumberString
market.ask	Restrictions on selling	Object
market.ask.currency	English capital letter code for currency	String
market.ask.price_unit	Order amount unit	NumberString

field	Details	Type
market.ask.min_total	Minimum buy/sell amount	NumberString
market.max_total	Maximum sell/buy amount	NumberString
market.state	Market operating status	String
bid_account	Account status of the currency used for purchase	Object
bid_account.currency	English capital letter code for currency	String
bid_account.balance	Orderable amount/quantity	NumberString
bid_account.locked	Amount/quantity tied to the order	NumberString
bid_account.avg_buy_price	Average purchase price	NumberString
bid_account.avg_buy_price_modified	Whether to revise the average purchase price	Boolean
bid_account.unit_currency	Currency based on average price	String
ask_account	Account status of the currency used when selling	Object
ask_account.currency	English capital letter code for currency	String
ask_account.balance	Orderable amount/quantity	NumberString
ask_account.locked	Amount/quantity tied to the order	NumberString
ask_account.avg_buy_price	Average purchase price	NumberString
ask_account.avg_buy_price_modified	Whether to revise the average purchase price	Boolean
ask_account.unit_currency	Currency based on average price	String

Query Params

market
string
required

Market ID

Headers

Authorization
string
required

Authorization token (JWT)

Responses

200

200

Response body

object

bid_fee

string

ask_fee

string

maker_bid_fee

string

maker_ask_fee

string

market

object

id

string

name

string

order_types
array of strings
order_types
order_sides
array of strings
order_sides
bid_types
array of strings
bid_types
ask_types
array of strings
ask_types
bid
object
bid object
ask
object
ask object
max_total
string
state
string
bid_account
object
currency
string
balance
string
locked
string
avg_buy_price
string
avg_buy_price_modified
boolean
Defaults to true
unit_currency
string
ask_account
object
currency
string
balance
string
locked
string
avg_buy_price
string
avg_buy_price_modified

boolean

Defaults to true

unit_currency

string

400

400

Updated 30 days ago

View all accounts

Individual Order Inquiry

Did this page help you?

Yes

No

Individual Order Inquiry

get

https://api.bithumb.com/v1/order

View individual order history.

Example code is provided only for JavaScript, Python, and JAVA.

📌

Input rules

`uuid` or `client_order_id` At least one of them must be passed, and if both values are passed `uuid` takes precedence.

📘

Advance Notice

Previously, orders were not accepted if there was a possibility of wash trading; however, following the improvement, wash trading will be detected during the execution phase after order acceptance, and only the quantity of conflicting new orders **will be** canceled. Please refer to the announcement for details (Update date: April 2, 2026, after 12:00 PM).

Response Item "Wash Trading Prevention Type" `stp_type` , "Cancellation Type" `cancel_type` , "Cancelled Order Unique ID" `canceling_uuid` It is scheduled to be newly added.

Query Params

uuid
string

Unique ID of the order

client_order_id
string

Order ID assigned by the server (`uuid` A unique ID directly specified by the user when creating an order, separate from)

- Allowed characters: English upper/lowercase letters, numbers, -, _
- Length: 1–36 characters

Headers

Authorization
string
required

Authorization token (JWT)

Responses

200

200

Response body

object
uuid
string
required

Unique ID of the order

client_order_id
string

Order ID assigned by the server (`uuid` A unique ID directly specified by the user when creating an order, separate from)

side
string
enum

required

Order Type

- `bid` : buy
- `ask` : Sell

`bid` `ask`

ord_type
string
enum
required

How to order

- `limit` : Limit
- `price` : Market price (buy)
- `market` : Market price (sell)

`limit` `price` `market`

price
string
required

Order price

state
string
enum
required

Order Status

- `wait` Waiting for execution
- `watch` Waiting for order
- `done` : Transaction completed
- `cancel` : withdraw order

`wait` `watch` `done` `cancel`

market
string
required

Unique symbol of the trading pair

Example) KRW-BTC

created_at
date-time
required

Order creation time

volume
string
required

The order quantity entered by the user

remaining_volume
string
required

Remaining order quantity after execution

reserved_fee
string
required

Amount reserved as a fee

remaining_fee
string
required

Remaining commission amount

paid_fee
string
required

Amount of fees used

locked
string
required

Amount being used for the transaction

executed_volume
string
required

Contracted quantity

trades_count
integer
required

Number of executed orders

trades
array of objects
required

Transaction details

trades*

object
market
string

Unique symbol of the trading pair

Example) KRW-BTC

uuid
string

Unique ID of the transaction

price
string

Execution price

volume
string

Transaction quantity

funds
string

Contract amount

side
string
enum

Type of contract

- `bid` : buy
- `ask` : Sell

`bid` `ask`

created_at
date-time

Closing time

400

400

401

401

404

Not Found

Updated 7 days ago

Ordering Information

View order list

Did this page help you?

Yes

No

View order list

get

https://api.bithumb.com/v1/orders

View your order list.

Example code is provided only for JavaScript, Python, and JAVA.

📌

Input rules

- `uuids` or `client_order_ids` 두 값을 모두 전달한 경우 `uuids` It searches based on, and if neither is delivered, it searches for the latest order history.
- `state` and `states` It cannot be used simultaneously.

📘

Advance Notice

Previously, orders were not accepted if there was a possibility of wash trading; however, following the improvement, wash trading will be detected during the execution phase after order acceptance, and only the quantity of conflicting new orders **will be** canceled. Please refer to the announcement for details (Update date: April 2, 2026, after 12:00 PM).

Response Item "Wash Trading Prevention Type" `stp_type` This is scheduled to be newly added.

Query Params

market
string

Unique symbol of the trading pair

Example) KRW-BTC

state
string
enum
Defaults to wait

Order Status

- `wait` : Waiting for execution (default)
- `watch` Waiting for order
- `done` : Transaction completed

- `cancel` : withdraw order

Allowed:

`wait` `watch` `done` `cancel`

states
array of strings

Order Status List

- General Order(`wait` , `done` , `cancel`) and automatic ordering(`watch` You cannot search for) in combination.

states
ADD string
uuids
array of strings

List of unique order IDs (max 30)

uuids
ADD string
client_order_ids
array of strings

Order ID assigned by the server (`uuid` A list of unique IDs (max 30) directly specified by the user when creating an order, separate from)

client_order_ids
ADD string
page
int32
Defaults to 1

Page number to look up in the pagination response

limit
int32
Defaults to 100

Number of orders to view

order_by
string
enum
Defaults to desc

Search result sorting method

- `asc` : Ascending order
- `desc` : Descending order (default)

Allowed:

`asc` `desc`

Headers

Authorization
string
required

Authorization token (JWT)

Responses

200

200

Response body

array of objects
object
uuid
string
required

Unique ID of the order

client_order_id
string

Order ID assigned by the server (`uuid` A unique ID directly specified by the user when creating an order, separate from)

side
string

enum
required

Order Type

- `bid` : buy
- `ask` : Sell

`bid` `ask`

ord_type
string
enum
required

How to order

- `limit` : Limit
- `price` : Market price (buy)
- `market` : Market price (sell)

`limit` `price` `market`

price
string
required

Order price

state
string
enum
required

Order Status

- `wait` Waiting for execution
- `watch` Waiting for order
- `done` : Transaction completed
- `cancel` : withdraw order

`wait` `watch` `done` `cancel`

market
string
required

Unique symbol of the trading pair

Example) KRW-BTC

created_at
date-time
required

Order creation time
volume
string
required

Order quantity

remaining_volume
string
required

Remaining quantity after execution

reserved_fee
string
required

Amount reserved as a fee

remaining_fee
string
required

Remaining commission amount

paid_fee
string
required

Amount of fees used

locked
string
required

Amount being used for the transaction

executed_volume
string
required

Contracted quantity

trades_count
integer
required

Number of orders placed for that order

400

400

Updated 7 days ago

Individual Order Inquiry

Order Request

Did this page help you?

Yes

No

Order Request

post

https://api.bithumb.com/v2/orders

I would like to request an order.

Example code is provided only for JavaScript, Python, and JAVA.

📌

Input rules

- Limit Order: Requires both price and volume
- Market buy: price(total amount) required
- Sell at market price: volume required

📘

Advance Notice

Previously, orders were not accepted if there was a possibility of wash trading; however, following the improvement, wash trading will be detected during the execution phase after order acceptance, and only the quantity of conflicting new orders **will be** canceled. Please refer to the announcement for details (Update date: April 2, 2026, after 12:00 PM).

Response Item "Wash Trading Prevention Type" `stp_type` This is scheduled to be newly added.

Body Params

market
string
required

Unique symbol of the trading pair

Example) KRW-BTC

side
string
enum
required

Order Type

- `bid` : buy
- `ask` : Sell

Allowed:

`bid` `ask`

price

string

Order price (required for limit orders and market buy orders)

- Limit Order: Order Unit Price
- Market buy order: Total order amount

volume

string

Order quantity (required for limit orders and market sell orders)

order_type

string

enum

required

Ordering method (old `ord_type`)

- `limit` : Limit
- `price` : Market price (buy)
- `market` : Market price (sell)

Allowed:

`limit` `price` `market`

client_order_id

string

Order ID assigned by the server (`order_id` A unique ID directly specified by the user when creating an order, separate from).

- Allowed characters: English upper/lowercase letters, numbers, -, _
- Length: 1–36 characters

Headers

Authorization
string
required

Authorization token (JWT)

Responses

201

201

Response body

object

order_id

string

required

Unique ID of the order (old `uuid`)

market

string

required

Unique symbol of the trading pair

Example) KRW-BTC

side

string

enum
required

Order Type

- `bid` : buy
- `ask` : Sell

`bid` `ask`
order_type
string
required

Ordering method (old `ord_type`)

- `limit` : Limit
- `price` : Market price (buy)
- `market` : Market price (sell)

created_at
date-time
required

Order creation time

client_order_id
string

Order ID assigned by the server (`order_id` A unique ID directly specified by the user when creating an order, separate from)

400

400

Updated 7 days ago

View order list
Order cancellation request
Did this page help you?
Yes
No

Order cancellation request

delete

https://api.bithumb.com/v2/order

I request an order cancellation.

Example code is provided only for JavaScript, Python, and JAVA.

📌

Input rules

`order_id` or `client_order_ids` At least one of them must be passed, and if both values are passed `order_id` Process based on .

Query Params

order_id
string

Unique ID of the order (old `uuid`)

client_order_id
string

Order ID assigned by the server (`order_id` A unique ID directly specified by the user when creating an order, separate from)

- Allowed characters: English upper/lowercase letters, numbers, -, _
- Length: 1–36 characters

Headers

Authorization
string
required

Authorization token (JWT)

Responses

200

200

Response body

object
order_id
string
required

Unique ID of the order (old `uuid`)

client_order_id
string

Order ID assigned by the server (`order_id` A unique ID directly specified by the user when creating an order, separate from)

created_at
date-time
required

Order creation time

400

400

404

404

422

422

Updated 13 days ago

Order Request

Multi-order request

Did this page help you?

Yes

No

Multi-order request

post

https://api.bithumb.com/v2/orders/batch

Create multiple orders in a single request. Up to 20 orders are allowed per request.

Example code is provided only for JavaScript, Python, and JAVA.

📌

Input rules

- Limit Order: Requires both price and volume
- Market buy: price(total amount) required
- Sell at market price: volume required
- `client_order_id` It must be unique per member. Identical requests(`batch_orders` If duplicate IDs are included within), only the first item is accepted successfully, and subsequent duplicates are processed as failed.

📘

notification

- If the server successfully receives and processes the request, it returns a status code of 200 OK even if some individual orders fail.
- The current API call limit is set to **20 calls per second per IP** . However, this limit may change depending on system conditions or traffic.
- Previously, orders were not accepted if there was a possibility of wash trading; however, following the improvement, wash trading will be detected during the execution phase after order acceptance, and only the quantity of conflicting new orders **will be** canceled. Please refer to the announcement for details (Update date: April 2, 2026, after 12:00 PM).

  Response Item "Wash Trading Prevention Type" `stp_type` This is scheduled to be newly added.

Classification of response items

`batch_orders_response` Each item (Object) in the array is returned as either a success object or a failure object depending on the order processing result, and the included fields differ.

✅ Fields included in the success object

- client_order_id (only if provided in the request)
- order_id

- market
- side
- order_type
- created_at

❌ Fields included in the failure object

- client_order_id (only if provided in the request)
- name
- message

Criteria for distinguishing success/failure

- `order_id` If the field exists **success**
- `order_id` There is no field and `name`, `message` If exists **failure**

Body Params

batch_orders
array of objects
required

Multi-order list (min 1, max 20)

batch_orders*
ADD object

Headers

Authorization
string
required

Authorization token (JWT)

Responses

200

OK

Response body

object
batch_orders_response
array of objects
required
batch_orders_response*
object
client_order_id
string

Order ID assigned by the server (`order_id` A unique ID directly specified by the user when creating an order, separate from)

order_id
string

Unique ID of the order (old `uuid`)

market
string

Unique symbol of the trading pair

Example) KRW-BTC

side
string

Order Type

- `bid` : buy
- `ask` : Sell

order_type
string

Ordering method (old `ord_type`)

- `limit` : Limit
- `price` : Market price (buy)
- `market` : Market price (sell)

created_at
date-time

Order creation time

name
string

Error name of failed order

message
string

Error message for failed orders

400

Bad Request

Updated 7 days ago

Order cancellation request
Multiple order cancellations accepted

Did this page help you?
Yes
No

Multiple order cancellations accepted

post

https://api.bithumb.com/v2/orders/cancel

Request bulk cancellation for multiple orders. Up to 30 items can be processed per request.

Example code is provided only for JavaScript, Python, and JAVA.

📌

Input rules

`order_ids` or `client_order_ids` At least one of them must be passed, and if both values are passed `order_ids` Process based on .

📘

notification

The current API call limit is set to **20 calls per second per IP** . However, this limit may change depending on system conditions or traffic.

Body Params

order_ids
array of strings

Unique ID of the order to be canceled (old `uuid`) List(max 30)

order_ids
ADD string
client_order_ids
array of strings

Order ID assigned by the server (old `uuid` A list of unique IDs (max 30) directly specified by the user when creating an order, separate from)

- Allowed characters: English upper/lowercase letters, numbers, -, _
- Length: 1–36 characters

client_order_ids

ADD string

Headers

Authorization

string

required

Authorization token (JWT)

Responses

200

200

Response body

object
success
array of objects
required

List of successful order cancellations

success*
object
order_id
string

Unique ID of the order (old `uuid`)

client_order_id
string

Order ID assigned by the server (`order_id` A unique ID directly specified by the user when creating an order, separate from).

In that order `client_order_id` Return if present
created_at
date-time

Time of order cancellation request
fail
array of objects
required

List of failed order cancellations

fail*
object
order_id
string

Unique ID of the order (old `uuid`). `client_order_id` If you search but find no matching orders, it may not be returned.

client_order_id
string

Order ID assigned by the server (`order_id` A unique ID directly specified by the user when creating an order, separate from).

error
object
error object

400
Result

422
422

Updated 16 days ago

Multi-order request
TWAP
Did this page help you?
Yes
No

TWAP - Order History

get

https://api.bithumb.com/v1/twap

View your order list.

Example code is provided only for JavaScript, Python, and JAVA.

Request Parameters

field	Details	Type
market	Market ID (ex.KRW-BTC)	String
uuids	TWAP Order ID List	Array

state	TWAP Order Status
	`- progress : 진행중 (default)`
	`- done : 주문 완료`
	`- cancel : 취소`
		String

next_key	Cursor value for viewing the next page	String
limit	Number limit (default: 100, limit: 100)	Number

order_by	Sorting method
	`- asc : 오름차순`
	`- desc : 내림차순 (default)`
		String

Responses

field	Details	Type
has_next	Whether the next page exists	Boolean

field	Details	Type
next_key	Cursor value for next page lookup (`Base64 인코딩된 문자열`). `- hasNext 가 false 면 null`	String
uuid	TWAP Order ID `- algo_order_id 와 동일`	String
side	Order Type	String
price	Currency price at the time of order	NumberString

state	TWAP Order Status
	`- progress : 진행중 (default)`
	`- done : 주문 완료`
	`- cancel : 취소`
		String

market	The only key in the market	String
created_at	Order creation time	DateString
volume	The order quantity entered by the user	NumberString

finished_at	Order closing time
	`- done 상태일 시 완료시간 노출`
	`- cancel 상태일 시 미노출`
		DateString

total_order_count	Total number of orders	Number
total_trades_count	Total number of executed orders	Number
progress_count	Number of processed orders	Number
total_executed_amount	Total order execution amount	NumberString
total_executed_volume	Total order quantity	NumberString
avg_trade_price	Average order execution price	NumberString

field	Details	Type

canceled_at	Order cancellation time
	`- done 상태일 시 미노출`
	`- cancel 상태일 시 취소시간 노출`
		DateString

cancel_type	Order cancellation type
	`- user : 사용자 취소`
	`- asset : 자산 부족`
	`- admin : 관리자 취소`
	`- system : 시스템 취소`
		String

Query Params

market

string

마켓 ID
uuids
string

TWAP Order ID List

state
string

Order Status

next_key
array of strings

Cursor value for viewing the next page

next_key
ADD string
limit
int32
Defaults to 100

Number limit

order_by
int32
Defaults to desc

Sorting method

Headers

Authorization
string
required

Authorization token (JWT)

Responses

200

200

Response body

array of objects
object
has_next
boolean

Whether the next page exists

next_key
string

Cursor value for viewing the next page

uuid
string

TWAP Order ID

side
string

Order Type

price
string

Currency price at the time of order

state
string

Order Status

market
string

The only key in the market

created_at
date

Order creation time

volume
string

The order quantity entered by the user

finished_at
date

Order closing time

total_order_count
number

Total number of orders

total_trades_count
number

Total number of executed orders

progress_count
number

Number of processed orders

total_executed_amount
string

Total order execution amount

total_executed_volume

string

Total order quantity

avg_trade_price

string

Average order execution price

canceled_at

date

Defaults to 0

Order cancellation time

cancel_type

string

Order cancellation type

400

400

Updated 13 days ago

Multiple order cancellations accepted

TWAP - Cancel Order

Did this page help you?

Yes

No

TWAP - Cancel Order

delete

https://api.bithumb.com/v1/twap

View your order list.

Example code is provided only for JavaScript, Python, and JAVA.

Request Parameters

field	Details	Type
algo_order_id *	TWAP order ID to cancel	String

Responses

field	Details	Type
algo_order_id *	Canceled TWAP Order ID	String

Query Params

algo_order_id

string

required

TWAP order ID to cancel

Headers

Authorization
string
required

Authorization token (JWT)

Responses

200

200

Response body

array of objects

object

algo_order_id

string

required

Canceled TWAP Order ID

400

400

Updated 13 days ago

TWAP - Order History

TWAP - Order

Did this page help you?

Yes

No

TWAP - Order

post

https://api.bithumb.com/v1/twap

View your order list.

Example code is provided only for JavaScript, Python, and JAVA.

Request Parameters

field	Details	Type
market *	Market ID (ex.KRW-BTC)	String

side *	Order Type
	`- bid : 매수`
	`- ask : 매도`
		String

volume	Order quantity (required for selling)	NumberString
price	Order price. (Required for purchases)	NumberString
duration *	Order time (Time for twap order to be processed) - seconds `- Min 300, Max 43200`	NumberString
frequency*	Order interval - seconds `- 5, 15, 20, 30, 60, 120 값 중에 하나 입력 가능`	NumberString

Responses

field	Details	Type
algo_order_id *	TWAP Order ID	String

Query Params

market
string
required

Market ID

side
string
required

Order types (bid buy, ask sell)

volume
string

Order Quantity (Required for Sale)

price
string

Order price (required for purchase)

duration
string
required

Order time (Time for twap order to be processed) - seconds

frequency
string
required

Order interval - seconds

Headers

Authorization

string
required

Authorization token (JWT)

Responses

200

200

Response body

array of objects

object

algo_order_id

string

required

TWAP Order ID

400

400

Updated 13 days ago

TWAP - Cancel Order

Withdrawal

Did this page help you?

Yes

No

View coin withdrawal list

get

https://api.bithumb.com/v1/withdraws

View the list of virtual asset withdrawals.

Example code is provided only for JavaScript, Python, and JAVA.

Request Parameters

field	Details	Type
currency	English capital letter code for currency	String
state	Withdrawal status -PROCESSING: In progress -DONE: Completed -CANCELED: Cancelled	String
uuids	List of withdrawal UUIDs	Array
txids	List of withdrawal TXIDs	Array
page	Number of pages (default: 1)	Number
limit	Number limit (default: 100, max: 100)	Number
order_by	Sorting method -asc: ascending order -desc: descending order (default)	String

Response

field	Details	Type
type	Deposit/Withdrawal Types	String

field	Details	Type
uuid	Unique ID for withdrawal	String
currency	English capital letter code for currency	String
net_type	Withdrawal network (ex. BTC, DASH)	String
txid	Transaction ID of withdrawal	String
state	Withdrawal status -PROCESSING: In progress -DONE: Completed -CANCELED: Cancelled	String
created_at	Withdrawal creation time	DateString
done_at	Withdrawal completion time	DateString
amount	Withdrawal amount/quantity	NumberString
fee	Withdrawal fee	NumberString
transaction_type	Withdrawal Type -default: general withdrawal	String

Query Params

currency
string

English capital letter code for currency

state
string

Withdrawal status

uuids
array of strings

List of withdrawal UUIDs

uuids
ADD string

txids
array of strings

List of withdrawal TXIDs

txids
ADD string
page
int32
Defaults to 1

Number of pages

limit
int32
Defaults to 100

Number limit

order_by
string
Defaults to desc

Sorting method

Headers

Authorization
string
required

Authorization token (JWT)

Responses

200

200

Response body

array of objects

object

type

string

uuid

string

currency

string

net_type

string

txid

string

state

string

created_at

string
done_at
string
amount
string
fee
string
transaction_type
string

400
400

Updated 30 days ago

TWAP - Order
View the list of Korean won withdrawals
Did this page help you?
Yes
No

View the list of Korean won withdrawals

get

https://api.bithumb.com/v1/withdraws/krw

View the list of Korean Won withdrawals.

Example code is provided only for JavaScript, Python, and JAVA.

Request Parameters

field	Details	Type
state	Withdrawal status -PROCESSING: In progress -DONE: Completed -CANCELED: Cancelled	String
uuids	List of withdrawal UUIDs	Array
txids	List of withdrawal TXIDs	Array
page	Number of pages (default: 1)	Number
limit	Number limit (default: 100, max: 100)	Number
order_by	Sorting method -asc: ascending order -desc: descending order (default)	String

Response

field	Details	Type
type	Deposit/Withdrawal Types	String
uuid	Unique ID for withdrawal	String

field	Details	Type
currency	English capital letter code for currency	String
txid	Transaction ID of withdrawal	String
state	Withdrawal status -PROCESSING: In progress -DONE: Completed -CANCELED: Cancelled	String
created_at	Withdrawal creation time	DateString
done_at	Withdrawal completion time	DateString
amount	Withdrawal amount/quantity	NumberString
fee	Withdrawal fee	NumberString
transaction_type	Withdrawal Type -default: general withdrawal	String

Query Params

state
string

Withdrawal status

uuids
array of strings

List of withdrawal UUIDs

uuids
ADD string
txids
array of strings

List of withdrawal TXIDs

txids

ADD string

page

int32

Defaults to 1

Number of pages

limit

int32

Defaults to 100

Number limit

order_by

string

Defaults to desc

Sorting method

Headers

Authorization
string
required

Authorization token (JWT)

Responses

200

200

Response body

array of objects

object

type

string

uuid

string

currency

string

net_type

string

txid

string

state

string

created_at

string
done_at
string
amount
string
fee
string
transaction_type
string

400
400

Updated 30 days ago

View coin withdrawal list
Individual withdrawal inquiry
Did this page help you?
Yes
No

Individual withdrawal inquiry

get

https://api.bithumb.com/v1/withdraw

Check the withdrawal details for the withdrawal transaction using the withdrawal UUID.

Example code is provided only for JavaScript, Python, and JAVA.

Request Parameters

field	Details	Type
currency *	English capital letter code for currency	String
uuid	Unique ID for withdrawal	String
txid	Transaction ID of withdrawal	String

Response

field	Details	Type
type	Deposit/Withdrawal Types	String
uuid	Unique ID for withdrawal	String
currency	English capital letter code for currency	String
net_type	Withdrawal Network	String
txid	Transaction ID of withdrawal	String
state	Withdrawal status -PROCESSING: In progress -DONE: Completed -CANCELED: Cancelled	String
created_at	Withdrawal creation time	DateString

field	Details	Type
done_at	Withdrawal completion time	DateString
amount	Withdrawal amount/quantity	NumberString
fee	Withdrawal fee	NumberString
transaction_type	Withdrawal Type -default: general withdrawal	String

Query Params

currency

string
required

English capital letter code for currency
uuid
string

Withdrawal UUID

txid
string

Withdrawal TXID

Headers

Authorization
string
required

Authorization token (JWT)

Responses

200

200

Response body

object
type
string
uuid
string
currency
string
net_type
string
txid
string
state
string
created_at
string

done_at
string
amount
string
fee
string
transaction_type
string

400
400

Updated 30 days ago

View the list of Korean won withdrawals
Withdrawal information
Did this page help you?
Yes
No

Withdrawal information

get

https://api.bithumb.com/v1/withdraws/chance

Check the withdrawal availability of the currency in question.

Example code is provided only for JavaScript, Python, and JAVA.

Request Parameters

field	Details	Type
currency *	English capital letter code for currency	String
net_type *	Withdrawal network (ex. BTC, DASH)	String

Response

field	Details	Type
member_level	User security level information	Object
member_level.security_level	User's security level	Integer
member_level.fee_level	User's fee level	Integer
member_level.email_verified	Whether the user's email is authenticated	Boolean
member_level.identity_auth_verified	Whether the user's real name is verified	Boolean
member_level.bank_account_verified	Whether the user's account is authenticated	Boolean
member_level.two_factor_auth_verified	Whether 2FA authentication method is activated	Boolean
member_level.locked	User's account protection status	Boolean
member_level.wallet_locked	User's withdrawal protection status	Boolean
currency	Currency Information	Object
currency.code	English capital letter code for currency	String
currency.withdraw_fee	Withdrawal fees for that currency	NumberString
currency.is_coin	Whether the currency is a digital asset	Boolean
currency.wallet_state	Wallet status of the currency in question	String
currency.wallet_support	Deposit and withdrawal information supported by the currency	Array[String]
account	User's account information	Object
account.currency	English capital letter code for currency	String

field	Details	Type
account.balance	Orderable amount/quantity	NumberString
account.locked	Amount/quantity tied to the order	NumberString
account.avg_buy_price	Average purchase price	NumberString
account.avg_buy_price_modified	Whether the average purchase price has been revised	Boolean
account.unit_currency	Currency based on average price	String
withdraw_limit	Withdrawal Restrictions Information	Object
withdraw_limit.currency	English capital letter code for currency	String
withdraw_limit.minimum	Minimum withdrawal amount/quantity	NumberString
withdraw_limit.onetime	Single withdrawal limit	NumberString
withdraw_limit.daily	Daily withdrawal limit	NumberString
withdraw_limit.remaining_daily	1 day remaining withdrawal limit	NumberString
withdraw_limit.fixed	Withdrawal amount/quantity number of decimal places	Integer
withdraw_limit.can_withdraw	Whether withdrawal is supported	Boolean
withdraw_limit.remaining_daily_krw	Integrated daily remaining withdrawal limit	NumberString

Query Params

currency
string
required

English capital letter code for currency

net_type
string
required

Withdrawal Network

Headers

Authorization
string
required

Authorization token (JWT)

Responses

200

200

Response body

object

member_level

object

security_level

string

fee_level

string

email_verified

string

identity_auth_verified

string

bank_account_verified

string

two_factor_auth_verified

string

locked
string
wallet_locked
string
currency
object
code
string
withdraw_fee
string
is_coin
boolean
Defaults to true
wallet_state
string
wallet_support
array of strings
wallet_support
account
object
currency
string
balance
string
locked
string
avg_buy_price
string
avg_buy_price_modified
boolean
Defaults to true
unit_currency
string
withdraw_limit
object
currency
string
onetime
string
daily
string
remaining_daily
string
remaining_daily_fiat
string
fiat_currency
string
minimum

string
fixed
integer
Defaults to 0
withdraw_delayed_fiat
string
can_withdraw
boolean
Defaults to true
remaining_daily_krw
string

400
400

Updated 30 days ago

Individual withdrawal inquiry
Withdrawing Virtual Assets

Did this page help you?

Yes
No

Withdrawing Virtual Assets

post

https://api.bithumb.com/v1/withdraws/coin

Request a withdrawal of virtual assets.

Example code is provided only for JavaScript, Python, and JAVA.

Request Parameters

field	Details	Type
currency *	English capital letter code for currency	String
net_type *	Withdrawal network (ex. BTC, DASH)	String
amount *	Withdrawal amount	Number
address *	Withdrawal address registered in the withdrawal address list	String
secondary_address	Secondary withdrawal address (only for required digital assets)	String
exchange_name	Withdrawal Exchange Name (English)	String
receiver_type	Whether the recipient is an individual or a corporation -personal: personal -corporation: corporation	String
receiver_ko_name	Recipient's Korean name (Individual: Individual's Korean name, Corporation: Corporation's representative's Korean name)	String
receiver_en_name	Recipient's English name (Individual: Individual's English name, Corporation: Corporation's representative's English name)	String
receiver_corp_ko_name	Korean name of the corporation (required if the recipient is a corporation)	String

field	Details	Type
receiver_corp_en_name	English name of the corporation (required if the recipient is a corporation)	String

Response

field	Details	Type
type	Deposit/Withdrawal Types	String
uuid	Unique ID for withdrawal	String
currency	English capital letter code for currency	String
net_type	Withdrawal Network	String
txid	Transaction ID of withdrawal	String
state	Withdrawal status	String
created_at	Withdrawal creation time	DateString
done_at	Withdrawal completion time	DateString
amount	Withdrawal amount/quantity	NumberString
fee	Withdrawal fee	NumberString
krw_amount	Price in KRW	NumberString
transaction_type	Withdrawal type -default: general withdrawal	String

Body Params

currency
string
required

English capital letter code for currency

net_type
string
required

Withdrawal Network

amount
string
required

Withdrawal amount of digital assets

address
string
required

Withdrawal wallet address

secondary_address
string

Secondary withdrawal address (only for required digital assets)

exchange_name
string

Withdrawal Exchange Name (English)

receiver_type
string

Whether the recipient is an individual or a corporation

receiver_ko_name
string

Recipient's Korean name (Individual: Individual's Korean name, Corporation: Corporation's representative's Korean name)

receiver_en_name
string

Recipient's English name (Individual: Individual's English name, Corporation: Corporation's representative's English name)

receiver_corp_ko_name
string

Korean name of the corporation (required if the recipient is a corporation)

receiver_corp_en_name
string

English name of the corporation (required if the recipient is a corporation)

Headers

Authorization
string
required

Authorization token (JWT)

Responses

201

201

Response body

object
type
string
uuid
string
currency
string
net_type
string
state
string
created_at
string
done_at
string

amount
string
fee
string
krw_amount
string
transaction_type
string
txid
string

400

400

Updated about 2 months ago

Withdrawal information
Withdraw Korean won

Did this page help you?
Yes
No

Withdraw Korean won

post

https://api.bithumb.com/v1/withdraws/krw

Request a withdrawal in Korean Won to your registered withdrawal account.

Example code is provided only for JavaScript, Python, and JAVA.

Request Parameters

field	Details	Type
amount *	Withdrawal amount	NumberString
two_factor_type *	Secondary authentication method -kakao: Kakao authentication	String

Response

field	Details	Type
type	Deposit/Withdrawal Types	String
uuid	Unique ID for withdrawal	String
currency	English capital letter code for currency	String
txid	Transaction ID of withdrawal	String
state	Withdrawal status	String
created_at	Withdrawal creation time	DateString
done_at	Withdrawal completion time	DateString

field	Details	Type
amount	Withdrawal amount/quantity	NumberString
fee	Withdrawal fee	NumberString
transaction_type	Withdrawal type -default: general withdrawal	String

Body Params

amount
string
required

Amount of KRW to be withdrawn

two_factor_type

string

required

Secondary authentication method (Kakao)

Headers

Authorization

string

required

Authorization token (JWT)

Responses

201

201

Response body

object
type
string
uuid
string
currency
string
net_type
string
txid
string
state
string
created_at
string

done_at
string
amount
string
fee
string
transaction_type
string

400
400

Updated 30 days ago

Withdrawing Virtual Assets
List of allowed withdrawal addresses inquiry

Did this page help you?

Yes
No

List of allowed withdrawal addresses inquiry

get

https://api.bithumb.com/v1/withdraws/coin_addresses

View the list of registered withdrawal allowed addresses (addresses that allow withdrawals of 1 million won or more).

Example code is provided only for JavaScript, Python, and JAVA.

Response

field	Details	Type
currency	English capital letter code for currency	String
net_type	Withdrawal Network Type	String
network_name	Withdrawal network name	String
withdraw_address	Withdrawal address	String
secondary_address	Secondary withdrawal address (only for required digital assets)	String
exchange_name	Withdrawal Exchange Name (English)	String
owner_type	Address Owner Customer Type -personal: personal -corporation: corporation	String
owner_ko_name	Address owner's Korean name	String
owner_en_name	English name of address owner	String
owner_corp_ko_name	Address Ownership Corporation Korean Name	String
owner_corp_en_name	English name of the address-owning corporation	String

Headers

Authorization
string
required

Authorization token (JWT)

Responses

200

200

Response body

array of objects

object

currency

string

net_type

string

network_name

string

withdraw_address

string

secondary_address

string

exchange_name

string

owner_type

string

owner_ko_name

string

owner_en_name

string

owner_corp_ko_name

string

owner_corp_en_name

string

400

400

Updated 30 days ago

Withdraw Korean won

Deposit

Did this page help you?

Yes

No

Check coin deposit list

get

https://api.bithumb.com/v1/deposits

View the list of virtual asset deposits.

Example code is provided only for JavaScript, Python, and JAVA.

Request Parameters

field	Details	Type
currency	English capital letter code for currency	String
state	Deposit status • Deposit request • Waiting for deposit: `REQUESTED_PENDING` • Waiting for return request: `REQUESTED_SYSTEM_REJECTED` • Deposit request pending: `REQUESTED_PROCESSING` • Deposit review in progress: `REQUESTED_PROCESSING` • Deposit review rejection: `REQUESTED_ADMIN_REJECTED` • Deposit • Waiting for deposit: `DEPOSIT_PROCESSING` • Deposit completed: `DEPOSIT_ACCEPTED` • Deposit Cancellation: `DEPOSIT_CANCELLED` • Return request • Waiting for return review: `REFUNDING_PENDING` • Cancellation of return: `REFUNDING_SYSTEM_REJECTED` • Return review in progress: `REFUNDING_PROCESSING` • Cancellation of return: `REFUNDING_ADMIN_REJECTED` • Return Completed: `REFUNDING_ACCEPTED` • Withdrawal of refund request • Return Approval: `REFUNDED_PROCESSING` • Return Completed: `REFUNDED_ACCEPTED` • Cancellation of return: `REFUNDED_CANCELLED`	String
uuids	List of deposit UUIDs	Array
txids	List of deposit TXIDs	Array

field	Details	Type
page	Number of pages (default: 1)	Number
limit	Number limit (default: 100, limit: 100)	Number
order_by	Sorting method -asc: ascending order -desc: descending order (default)	String

Response

field	Details	Type
type	Deposit/Withdrawal Types	String
uuid	Unique ID for deposit	String
currency	English capital letter code for currency	String
net_type	Deposit Network	String
txid	Transaction ID of the deposit	String
state	Deposit status • Deposit request • Waiting for deposit: `REQUESTED_PENDING` • Waiting for return request: `REQUESTED_SYSTEM_REJECTED` • Deposit request pending: `REQUESTED_PROCESSING` • Deposit review in progress: `REQUESTED_PROCESSING` • Deposit review rejection: `REQUESTED_ADMIN_REJECTED` • Deposit • Waiting for deposit: `DEPOSIT_PROCESSING` • Deposit completed: `DEPOSIT_ACCEPTED` • Deposit Cancellation: `DEPOSIT_CANCELLED` • Return request • Waiting for return review: `REFUNDING_PENDING` • Cancellation of return: `REFUNDING_SYSTEM_REJECTED` • Return review in progress: `REFUNDING_PROCESSING` • Cancellation of return: `REFUNDING_ADMIN_REJECTED` • Return Completed: `REFUNDING_ACCEPTED` • Withdrawal of refund request	String

field	Details	Type
	• Return Approval: `REFUNDED_PROCESSING` • Return Completed: `REFUNDED_ACCEPTED` • Cancellation of return: `REFUNDED_CANCELLED`	
created_at	Deposit creation time	DateString
done_at	Deposit completion time	DateString
amount	Deposit quantity	NumberString
fee	Deposit fee	NumberString
transaction_type	Deposit Type -default: general deposit	String

Query Params

currency
string

English capital letter code for currency

state
string

Deposit status

uuids
array of strings

List of deposit UUIDs

uuids
ADD string

txids
array of strings

List of deposit TXIDs

txids
ADD string
page
int32
Defaults to 1

Number of pages

limit
int32
Defaults to 100

Number limit

order_by
string
Defaults to desc

Sorting method

Headers

Authorization
string
required

Authorization token (JWT)

Responses

200

200

Response body

array of objects

object

type

string

uuid

string

currency

string

net_type

string

txid

string

state

string

created_at

string
done_at
string
amount
string
fee
string
transaction_type
string

400
400

Updated 30 days ago

List of allowed withdrawal addresses inquiry
Check the list of Korean won deposits
Did this page help you?
Yes
No

Check the list of Korean won deposits

get

https://api.bithumb.com/v1/deposits/krw

View the list of KRW deposits.

Example code is provided only for JavaScript, Python, and JAVA.

Request Parameters

field	Details	Type
state	Deposit status -PROCESSING: In progress -ACCEPTED: Completed -CANCELED: Cancelled	String
uuids	List of deposit UUIDs	Array
txids	List of deposit TXIDs	Array
page	Number of pages (default: 1)	Number
limit	Number limit (default: 100, limit: 100)	Number
order_by	Sorting method -asc: ascending order -desc: descending order (default)	String

Response

field	Details	Type
type	Deposit/Withdrawal Types	String
uuid	Unique ID for deposit	String

field	Details	Type
currency	English capital letter code for currency	String
txid	Transaction ID of the deposit	String
state	Deposit status -PROCESSING: In progress -ACCEPTED: Completed -CANCELED: Cancelled	String
created_at	Deposit creation time	DateString
done_at	Deposit completion time	DateString
amount	Deposit quantity	NumberString
fee	Deposit fee	NumberString
transaction_type	Deposit Type -default: general deposit	String

Query Params

state
string

Deposit status

uuids
array of strings

List of deposit UUIDs

uuids
ADD string
txids
array of strings

List of deposit TXIDs

txids

ADD string

page

int32

Defaults to 1

Number of pages

limit

int32

Defaults to 100

Number limit

order_by

string

Defaults to desc

Sorting method

Headers

Authorization
string
required

Authorization token (JWT)

Responses

200

200

Response body

json

```
400
400
```

Updated 30 days ago

Check coin deposit list

Individual deposit inquiry

Did this page help you?

Yes

No

Individual deposit inquiry

get

https://api.bithumb.com/v1/deposit

Check the deposit details for the deposit by using the deposit UUID.

Example code is provided only for JavaScript, Python, and JAVA.

Request Parameters

field	Details	Type
currency *	English capital letter code for currency	String
uuid	Deposit UUID	String
txid	Deposit TXID	String

Response

field	Details	Type
type	Deposit/Withdrawal Types	String
uuid	Unique ID for deposit	String
currency	English capital letter code for currency	String
net_type	Deposit Network	String
txid	Transaction ID of the deposit	String
state	Deposit status	String
created_at	Deposit creation time	DateString
done_at	Deposit completion time	DateString

field	Details	Type
amount	Deposit quantity	NumberString
fee	Deposit fee	NumberString
transaction_type	Deposit Type -default: general deposit	String

Query Params

currency
string
required

English capital letter code for currency

uuid

string

UUID of individual deposit

txid

string

TXID of individual deposit

Headers

Authorization

string

required

Authorization token (JWT)

Responses

200

200

Response body

object
type
string
uuid
string
currency
string
net_type
string
txid
string
state
string
created_at
string

done_at
string
amount
string
fee
string
transaction_type
string

400
400

Updated 30 days ago

Check the list of Korean won deposits
Request to create a deposit address
Did this page help you?
Yes
No

Request to create a deposit address

post

https://api.bithumb.com/v1/deposits/generate_coin_address

Request to create a deposit address.

Example code is provided only for JavaScript, Python, and JAVA.

Request Parameters

field	Details	Type
currency *	English capital letter code for currency (ex. BTC)	String
net_type *	Deposit network (ex. BTC, DASH)	String

Response

field	Details	Type
currency	English capital letter code for currency	String
net_type	Deposit Network	String
deposit_address	Deposit address	String
secondary_address	Second deposit address	String

Body Params

currency
string
required

English capital letter code for currency

net_type
string
required

Deposit Network

Headers

Authorization
string
required

Authorization token (JWT)

Responses

201

201

Response body

object

currency

string

net_type

string

deposit_address

string

secondary_address

string

400

400

Updated 30 days ago

Individual deposit inquiry

All deposit addresses inquiry

Did this page help you?

Yes

No

All deposit addresses inquiry

get

https://api.bithumb.com/v1/deposits/coin_addresses

View the full deposit address.

Example code is provided only for JavaScript, Python, and JAVA.

Response

field	Details	Type
currency	English capital letter code for currency	String
net_type	Deposit Network	String
deposit_address	Deposit address	String
secondary_address	Second deposit address	String

Headers

Authorization
string
required

Authorization token (JWT)

Responses

200

200

Response body

array of objects

object

currency

string

net_type

string

deposit_address

string

secondary_address

string

400

400

Updated 9 months ago

Request to create a deposit address

Individual deposit addresses inquiry

Did this page help you?

Yes

No

Individual deposit addresses inquiry

get

https://api.bithumb.com/v1/deposits/coin_address

Check the deposit address for each virtual asset.

Example code is provided only for JavaScript, Python, and JAVA.

Request Parameters

field	Details	Type
currency *	English capital letter code for currency (ex. BTC)	String
net_type *	Deposit network (ex. BTC, DASH)	String

Response

field	Details	Type
currency	English capital letter code for currency	String
net_type	Deposit Network	String
deposit_address	Deposit address	String
secondary_address	Second deposit address	String

Query Params

currency
string
required

English capital letter code for currency

net_type
string
required

Deposit Network

Headers

Authorization
string
required

Authorization token (JWT)

Responses

200

200

Response body

object

currency

string

net_type

string

deposit_address

string

secondary_address

string

400

400

Updated 30 days ago

All deposit addresses inquiry

Deposit Korean won

Did this page help you?

Yes

No

Deposit Korean won

post

https://api.bithumb.com/v1/deposits/krw

I would like to request a deposit in Korean Won.

Example code is provided only for JavaScript, Python, and JAVA.

Request Parameters

field	Details	Type
amount *	Deposit amount	NumberString
two_factor_type *	Secondary authentication method -kakao: Kakao authentication	String

Response

field	Details	Type
type	Deposit/Withdrawal Types	String
uuid	Unique ID of the deposit	String
currency	English capital letter code for currency	String
txid	Transaction ID of the deposit	String
state	Deposit status	String
created_at	Deposit creation time	DateString
done_at	Deposit completion time	DateString

field	Details	Type
amount	Deposit amount/quantity	NumberString
fee	Deposit fee	NumberString
transaction_type	Deposit Type -default: general deposit	String

Body Params

amount
string
required

Deposit amount

two_factor_type

string

required

Secondary authentication method (Kakao)

Headers

Authorization

string

required

Authorization token (JWT)

Responses

201

201

Response body

object
type
string
uuid
string
currency
string
net_type
string
txid
string
state
string
created_at
string

done_at
string
amount
string
fee
string
transaction_type
string

400
400

Updated 30 days ago

Individual deposit addresses inquiry
Service Information
Did this page help you?
Yes
No

Deposit/Withdrawal Status

get

https://api.bithumb.com/v1/status/wallet

Check deposit/withdrawal status and block status.

Example code is provided only for JavaScript, Python, and JAVA.

Response

field	Details	Type
currency	English capital letter code for currency	String
wallet_state	Deposit/Withdrawal Status -working: Deposits and withdrawals possible -withdraw_only: Withdrawal only -deposit_only: Deposit only -paused: Deposits and withdrawals paused	String
block_state	Block status -normal: normal -delayed: delayed -inactive: inactive (under maintenance, etc.)	String
block_height	Block height	Integer
block_updated_at	Block update time	DateString
block_elapsed_minutes	Time elapsed since last block information update (minutes)	Integer
net_type	Network type to be specified when requesting deposits or withdrawals	String
network_name	Deposit/Withdrawal Network Name	String

Headers

Authorization
string
required

Authorization token (JWT)

Responses

200

200

Response body

array of objects

object

currency

string

wallet_state

string

block_state

string

block_height

integer

Defaults to 0

block_updated_at

string

block_elapsed_minutes

integer

Defaults to 0

net_type

string

network_name

string

400

400

Updated 30 days ago

Deposit Korean won

API key list inquiry

Did this page help you?

Yes

No

API key list inquiry

get
https://api.bithumb.com/v1/api_keys

View a list of API keys and their expiration dates.

Example code is provided only for JavaScript, Python, and JAVA.

The API can be used after receiving an API key from the relevant page .
When issuing an API Key, you must register the API activation item and the IP address that will use the API Key. You can register up to 5 IP addresses, and the API Key can only be used when accessing with a registered IP address.
You can receive up to 10 API keys per account. Once an API key has been issued, you will no longer be able to access additional secret keys. Please keep your secret key in a safe place after receiving it.
Issued API keys are valid for one year from the date of issuance and cannot be extended. After one year, please delete the API key and request a new one.
When issuing, modifying, or deleting an API Key, additional two-channel authentication is required. If you need to change the API activation items, you must delete the API Key in API Key Management and then reissue it.

Response

field	Details	Type
access_key	API KEY	String
expire_at	Expiration date	DateString

Headers

Authorization
string
required

Authorization token (JWT)

Responses

200

200

Response body

array of objects

object

access_key

string

expire_at

string

400

400

Updated 30 days ago

Deposit/Withdrawal Status

Basic information

Did this page help you?

Yes

No

Basic information

1. API Information

- public type: `wss://ws-api.bithumb.com/websocket/v1`
- private type: `wss://ws-api.bithumb.com/websocket/v1/private`

2. Rate limit

WebSocket connection requests are limited to 10 per second per IP address (same for both public and private).

※ Data such as transaction/price received after connection is completed are not subject to restrictions.

3. Data Type

Each piece of information is divided into snapshot and real-time information, and each piece of information can be requested via WebSocket.

Depending on the request method, the data you can receive may vary `스냅샷` and `실시간` You may request both or just one piece of information.

- Snapshot: refers to the state at the time of the request.
- Real-time: Request information is continuously delivered in a stream format.

Public type

This data can be received without any special authentication (provides snapshots and real-time information)

- `ticker` : Current price
- `trade` : Execution
- `orderbook` : Orderbook

Private type

This is a data type that can only be received after authentication.

For more information about authentication, please see [the Request Methods and Format](#) page.

- `myOrder` : My order
- `myAsset` : My assets

Updated about 2 months ago

API key list inquiry
Request Method and Format
Did this page help you?

Yes
No

Request Method and Format

Certification

WebSockets are classified as Public and Private. Public can receive data without separate authentication, while Private can receive data only after successful authentication during the WebSocket connection.

- Authentication is performed via the Authorization header, just like with REST API.
- Please see Creating an Authentication Header .

(Example) Connecting a Websocket with authentication information in the header

mdx

```
```node
const jwt = require("jsonwebtoken");
const {v4: uuidv4} = require('uuid');
const WebSocket = require("ws");

const accessKey = '발급받은 API KEY'
const secretKey = '발급받은 SECRET KEY'

const payload = {
    access_key: accessKey,
    nonce: uuidv4(),
    timestamp: Date.now()
};

console.log(payload);

const jwtToken = jwt.sign(payload, secretKey);

const ws = new WebSocket("wss://ws-api.bithumb.com/websocket/v1/private", {
    headers: {
        authorization: `Bearer ${jwtToken}`
    }
});

ws.on("open", () => {
    console.log("connected!");
    // Request after connection

    ws.send('[{"ticket":"test example"},{"type":"myOrder","codes":["KRW-BTC"]}]');
});

ws.on("error", console.error);

ws.on("message", (data) => console.log(data.toString()));
```
```

```
ws.on("close", () => console.log("closed!"));
```

Request Format

Once the connection is established, you can make various requests to the WebSocket server.
Requests and responses use JSON Objects.

The request is `ticket field`, `type field`, `format field`, and each field consists of the following elements:

Shell

```
[
  `{ticket field}`
  , `{type field}`
          .
          .
          .
  , `{type field}`
  , `{format field}`
]
```

Ticket Field

We recommend using a unique value such as a UUID to identify the recipient of the price by using the field values required to identify the requester.

Field name	Type	detail	Required
ticket	String	A value that can identify the requester	O

Type Field

A field listing the quote information you would like to receive in one request. `type field` Multiple can be specified.

Please check [the request and response by type](#) for detailed request method.

`is_only_snapshot`, `is_only_realtime` Fields can be omitted, and if all are omitted, both snapshot and real-time data will be received.

Format Field

This is a method used when the traffic load is high `simple` If specified, the response field names will be simplified.

Field name	Type	detail	Required	Default value
format	String	Format to receive - `DEFAULT` : Basic type - `SIMPLE` : abbreviation	X	`DEFAULT`

Updated about 2 months ago

Basic information

Test and Request Examples

Did this page help you?

Yes

No

Test and Request Examples

If you are testing receiving prices using WebSocket, you can use telsocket or wscat.

When using wscat

Shell

```
$ npm install -g wscat
$ wscat -c wss://ws-api.bithumb.com/websocket/v1
connected!
```

When using telsocket

Shell

```
$ telsocket -url wss://ws-api.bithumb.com/websocket/v1
connected!
```

If you would like to view real-time information on the KRW-Bitcoin (KRW-BTC) market, you can request it as follows:

Shell

```
$ wscat -c wss://ws-api.bithumb.com/websocket/v1
Connected (press CTRL+C to quit)

[{"ticket":"test example"},{"type":"ticker","codes":["KRW-BTC"]}]

{"type":"ticker","code":"KRW-
BTC","opening_price":484500,"high_price":493100,"low_price":472500,"trade_price":493100,"prev_clo
06-18","lowest_52_week_price":1000,"lowest_52_week_date":"2024-06-
18","market_state":"ACTIVE","is_trading_suspended":false,"delisting_date":null,"market_warning":"
{"type":"ticker","code":"KRW-
BTC","opening_price":484500,"high_price":493100,"low_price":472500,"trade_price":493100,"prev_clo
06-18","lowest_52_week_price":1000,"lowest_52_week_date":"2024-06-
18","market_state":"ACTIVE","is_trading_suspended":false,"delisting_date":null,"market_warning":"
...
```

If you want to receive information from multiple markets simultaneously, enter each market in the codes field, separated by a comma (,).
For example, if you want to receive real-time transaction information for the KRW-Bitcoin (KRW-BTC) and Bitcoin-Ethereum (BTC-ETH) markets in a simplified format, you can request it as follows:

Shell

```
$ wscat -c wss://ws-api.bithumb.com/websocket/v1
Connected (press CTRL+C to quit)

[{"ticket":"test example"},{"type":"ticker","codes":["KRW-BTC","BTC-ETH"]},{"format":"SIMPLE"}]

{"ty":"ticker","cd":"KRW-
BTC","op":484500,"hp":493100,"lp":471300,"tp":493100,"pcp":484500,"c":"RISE","cp":8600,"scp":8600
06-18","l52wp":1000,"l52wdt":"2024-06-
18","ms":"ACTIVE","its":false,"dd":null,"mw":"NONE","tms":1725927582208,"st":"SNAPSHOT"}
{"ty":"ticker","cd":"BTC-
ETH","op":47890,"hp":48310,"lp":47700,"tp":47820,"pcp":47890,"c":"FALL","cp":70,"scp":-70,"cr":0.
01-23","l52wp":254,"l52wdt":"2024-06-
20","ms":"ACTIVE","its":false,"dd":null,"mw":"CAUTION","tms":1725927601272,"st":"SNAPSHOT"}
{"ty":"ticker","cd":"KRW-
BTC","op":484500,"hp":493100,"lp":471300,"tp":489100,"pcp":484500,"c":"RISE","cp":4600,"scp":4600
06-18","l52wp":1000,"l52wdt":"2024-06-
18","ms":"ACTIVE","its":false,"dd":null,"mw":"NONE","tms":1725927608323,"st":"REALTIME"}
{"ty":"ticker","cd":"BTC-
ETH","op":47890,"hp":48310,"lp":47570,"tp":47570,"pcp":47890,"c":"FALL","cp":320,"scp":-320,"cr":
01-23","l52wp":254,"l52wdt":"2024-06-
20","ms":"ACTIVE","its":false,"dd":null,"mw":"CAUTION","tms":1725927614457,"st":"REALTIME"}
 ...
```

You can see that the snapshot is downloaded first and then the real-time transaction status is received.
All of the above requests assume that the WebSocket is successfully connected.

Updated about 1 year ago

Request Method and Format
Requests and responses by type
Did this page help you?
Yes
No

Current price (Ticker)

Request

The request is large `ticket field`, `type field`, `format field` are classified as and multiple requests can be made in one request. `type field` You can specify. For more details, Request Method and Format Please check the page.

Type Field

This field lists the quote information you wish to receive.
`is_only_snapshot`, `is_only_realtime` Fields can be omitted, and if both are omitted, both snapshot and real-time data will be received.

Field name	Type	detail	Required	Default value
type	String	Data type -`ticker` : Current price	O	
codes	List	Market Code List • Requests must be made in capital letters.	O	
isOnlySnapshot	Boolean	Only snapshot prices are provided	X	false
isOnlyRealtime	Boolean	Only real-time prices are provided	X	false

Response

Field name	Abbreviation (format :SIMPLE)	detail	Type	value
type	ty	Type	String	`ticker` : Current price
code	CD	Market code (ex. KRW-BTC)	String	
opening_price	op	market price	Double	

Field name	Abbreviation (format :SIMPLE)	detail	Type	value
high_price	hp	high price	Double	
low_price	lp	low price	Double	
trade_price	tp	Current price	Double	
prev_closing_price	pcp	Previous day's closing price	Double	
change	c	Compared to the previous day	String	`RISE` : Rise `EVEN` : Consolidated `FALL` : decline
change_price	cp	Unsigned previous day's value	Double	
signed_change_price	scp	Value compared to the previous day	Double	
change_rate	cr	Previous day's change rate without sign	Double	
signed_change_rate	scr	Rate of change compared to the previous day	Double	
trade_volume	TV	Most recent trading volume	Double	
acc_trade_volume	atv	Cumulative trading volume (as of 00:00 KST)	Double	
acc_trade_volume_24h	atv24h	24-hour cumulative trading volume	Double	
acc_trade_price	atp	Cumulative transaction amount (as of 00:00 KST)	Double	
acc_trade_price_24h	atp24h	24-hour cumulative trading volume	Double	

Field name	Abbreviation (format :SIMPLE)	detail	Type	value
trade_date	tdt	Last transaction date (KST)	String	yyyyMMdd
trade_time	ttm	Last trading time (KST)	String	HHmmss
trade_timestamp	ttms	Transaction timestamp (milliseconds)	Long	
ask_bid	ab	Buy/Sell distinction	String	`ASK` : Sell `BID` : buy
acc_ask_volume	aav	Cumulative selling volume	Double	
acc_bid_volume	abv	Cumulative bid amount	Double	
highest_52_week_price	h52wp	52-week high	Double	
highest_52_week_date	h52wdt	52-week high achieved date	String	yyyy-MM-dd
lowest_52_week_price	l52wp	52-week low	Double	
lowest_52_week_date	l52wdt	52-week low achieved date	String	yyyy-MM-dd
market_state	ms	Transaction status	String	
is_trading_suspended	its	Trading Suspension Status	Boolean	
delisting_date	dd	Transaction support end date	Date	
market_warning	mw	Investment Warning Status	String	`NONE` : Not applicable `CAUTION` : Transaction caution
timestamp	tms	timestamp (millisecond)	Long	

Field name	Abbreviation (format :SIMPLE)	detail	Type	value
stream_type	st	Stream type	String	`SNAPSHOT` : snapshot `REALTIME` : Real-time

Example

Request

- `KRW-BTC` , `KRW-ETH`

JSON

```
[
  {
    "ticket": "test example"
  },
  {
    "type": "ticker",
    "codes": [
      "KRW-BTC",
      "KRW-ETH"
    ]
  },
  {
    "format": "DEFAULT"
  }
]
```

Response

JSON

```
{
    "type": "ticker",
    "code": "KRW-BTC",
    "opening_price": 484500,
    "high_price": 493100,
    "low_price": 472500,
    "trade_price": 493100,
    "prev_closing_price": 484500,
    "change": "RISE",
    "change_price": 8600,
    "signed_change_price": 8600,
```

```
    "change_rate": 0.01775026,
    "signed_change_rate": 0.01775026,
    "trade_volume": 1.2567,
    "acc_trade_volume": 225.622,
    "acc_trade_volume_24h": 13386.15417512,
    "acc_trade_price": 108663718.238256,
    "acc_trade_price_24h": 8230696760.346009,
    "trade_date": "20240910",
    "trade_time": "091617",
    "trade_timestamp": 1725927377820,
    "ask_bid": "BID",
    "acc_ask_volume": 106.7561,
    "acc_bid_volume": 118.8659,
    "highest_52_week_price": 999999000,
    "highest_52_week_date": "2024-06-18",
    "lowest_52_week_price": 1000,
    "lowest_52_week_date": "2024-06-18",
    "market_state": "ACTIVE",
    "is_trading_suspended": false,
    "delisting_date": null,
    "market_warning": "NONE",
    "timestamp": 1725927377931,
    "stream_type": "REALTIME"
}
```


Updated about 2 months ago

Test and Request Examples

Trade

Did this page help you?

Yes

No

Trade

Request

The request is large `ticket field`, `type field`, `format field` are classified as and multiple requests can be made in one request. `type field` You can specify. For more details, Request Method and Format Please check the page.

Type Field

This field lists the quote information you wish to receive.
`is_only_snapshot`, `is_only_realtime` Fields can be omitted, and if all are omitted, both snapshot and real-time data will be received.

Field name	Type	detail	Required	Default value
type	String	Data type -`trade` : Execution	O	
codes	List	Market Code List • Requests must be made in capital letters.	O	
isOnlySnapshot	Boolean	Only snapshot prices are provided	X	false
isOnlyRealtime	Boolean	Only real-time prices are provided	X	false

Response

Field name	Abbreviation (format :SIMPLE)	detail	Type	value
type	ty	Type	String	`trade` : Execution
code	CD	Market code (ex. KRW-BTC)	String	
trade_price	tp	Execution price	Double	

Field name	Abbreviation (format :SIMPLE)	detail	Type	value
trade_volume	TV	Execution amount	Double	
ask_bid	ab	Buy/Sell distinction	String	`ASK` : Sell `BID` : buy
prev_closing_price	pcp	Previous day's closing price	Double	
change	c	Compared to the previous day	String	`RISE` : Rise `EVEN` : Consolidated `FALL` : decline
change_price	cp	Unsigned previous day's value	Double	
trade_date	tdt	Last transaction date (KST)	String	yyyy-MM-dd
trade_time	ttm	Last trading time (KST)	String	HH:mm:ss
trade_timestamp	ttms	Transaction timestamp (milliseconds)	Long	
timestamp	tms	timestamp (millisecond)	Long	
sequential_id	sid	Contract Number (Unique)	Long	
stream_type	st	Stream type	String	`SNAPSHOT` : snapshot `REALTIME` : Real-time

*`sequential_id` Fields can be used to determine the uniqueness of a transaction, but they do not guarantee the order of transactions.

Example

Request

- `KRW-BTC` , `KRW-ETH`

JSON

```
[
  {
    "ticket": "test example"
  },
  {
    "type": "trade",
    "codes": [
      "KRW-BTC",
      "KRW-ETH"
    ]
  },
  {
    "format": "DEFAULT"
  }
]
```

Response

JSON

```
{
    "type": "trade",
    "code": "KRW-BTC",
    "trade_price": 489700,
    "trade_volume": 1.4825,
    "ask_bid": "BID",
    "prev_closing_price": 484500,
    "change": "RISE",
    "change_price": 5200,
    "trade_date": "2024-09-10",
    "trade_time": "09:58:54",
    "trade_timestamp": 1725929934373,
    "sequential_id": 17259299343730000,
    "timestamp": 1725929934483,
    "stream_type": "REALTIME"
}
```

Updated about 2 months ago

Current price (Ticker)

Orderbook

Did this page help you?

Yes

No

Orderbook

Request

The request is large `ticket field`, `type field`, `format field` are classified as and multiple requests can be made in one request. `type field` You can specify. For more details, Request Method and Format Please check the page.

Type Field

This field lists the quote information you wish to receive.
`is_only_snapshot`, `is_only_realtime` Fields can be omitted, and if all are omitted, both snapshot and real-time data will be received.

Field name	Type	detail	Required	Default value
type	String	Data type -`orderbook` : Orderbook	O	
codes	List	Market Code List • Requests must be made in capital letters.	O	
level	Double	Collection unit	X	1
isOnlySnapshot	Boolean	Only snapshot prices are provided	X	false
isOnlyRealtime	Boolean	Only real-time prices are provided	X	false

Response

Field name	Abbreviation (format :SIMPLE)	detail	Type	value
type	ty	Type	String	`orderbook` : Orderbook

Field name	Abbreviation (format :SIMPLE)	detail	Type	value
code	CD	Market code (ex. KRW-BTC)	String	
total_ask_size	tas	Total remaining quantity of asks	Double	
total_bid_size	tbs	Total remaining quantity of bids	Double	
orderbook_units	obu	Orderbook	List of Objects	
orderbook_units.ask_price	obu.ap	Selling price	Double	
orderbook_units.bid_price	obu.bp	Buy price	Double	
orderbook_units.ask_size	obu.as	Ask size	Double	
orderbook_units.bid_size	obu.bs	Bid size	Double	
timestamp	tms	timestamp (millisecond)	Long	
level	lv	Price Grouping Unit (default: 1, default household unit)	Double	Collection unit

Example

Request

- `level` The value is not required and if omitted, it will be lowered to DEFAULT(1), the default unit of measure.

JSON

```
[
  {
    "ticket": "test example"
  },
```

```
  {
    "type": "orderbook",
    "codes": [
      "KRW-BTC",
      "KRW-ETH.3"
    ],
    "level": 10
  },
  {
    "format": "DEFAULT"
  }
]
```

Different collections by category `level` To specify a value, you can request it as follows:

JSON

```
[
    {
        "ticket": "test example"
    },
    {
        "type": "orderbook",
        "codes": [
            "KRW-BTC"
        ],
        "level": 1000
    },
    {
        "type": "orderbook",
        "codes": [
            "KRW-XRP"
        ],
        "level": 1
    },
    {
        "format": "DEFAULT"
    }
]
```

Response

JSON

```
{
    "type": "orderbook",
    "code": "KRW-BTC",
    "total_ask_size": 450.3526,
    "total_bid_size": 63.3006,
```

```
    "orderbook_units": [
        {
            "ask_price": 478800,
            "bid_price": 478300,
            "ask_size": 4.3478,
            "bid_size": 5.6370
        },
        {
            "ask_price": 489700,
            "bid_price": 477900,
            "ask_size": 2.3642,
            "bid_size": 0.9705
        },
        {
            "ask_price": 493100,
            "bid_price": 471200,
            "ask_size": 411.8686,
            "bid_size": 3.9279
        },
        {
            "ask_price": 493300,
            "bid_price": 471100,
            "ask_size": 2.0241,
            "bid_size": 1.4699
        },
        {
            "ask_price": 493700,
            "bid_price": 471000,
            "ask_size": 1.7870,
            "bid_size": 2.2573
        },
        {
            "ask_price": 493800,
            "bid_price": 470700,
            "ask_size": 3.9372,
            "bid_size": 9.7805
        },
        {
            "ask_price": 494900,
            "bid_price": 470400,
            "ask_size": 5.7560,
            "bid_size": 0.8093
        },
        {
            "ask_price": 495300,
            "bid_price": 470300,
            "ask_size": 3.6418,
            "bid_size": 4.6606
        },
        {
            "ask_price": 495700,
            "bid_price": 470100,
            "ask_size": 2.9617,
            "bid_size": 5.4907
```

```
        },
        {
            "ask_price": 495800,
            "bid_price": 469700,
            "ask_size": 0.2349,
            "bid_size": 2.3941
        },
        {
            "ask_price": 496100,
            "bid_price": 469600,
            "ask_size": 2.6019,
            "bid_size": 4.5505
        },
        {
            "ask_price": 496800,
            "bid_price": 469500,
            "ask_size": 3.4651,
            "bid_size": 5.4469
        },
        {
            "ask_price": 496900,
            "bid_price": 469200,
            "ask_size": 0.8400,
            "bid_size": 10.1685
        },
        {
            "ask_price": 497400,
            "bid_price": 469100,
            "ask_size": 2.1924,
            "bid_size": 5.1646
        },
        {
            "ask_price": 497900,
            "bid_price": 469000,
            "ask_size": 2.3299,
            "bid_size": 0.5723
        }
    ],
    "level": 1,
    "timestamp": 1725930007672,
    "stream_type": "REALTIME"
}
```


Updated about 2 months ago

Trade

My Order and Execution (MyOrder)

Did this page help you?

Yes

No

My Order and Execution (MyOrder)

> 📘
>
> **Advance Notice**
>
> Previously, orders were not accepted if there was a possibility of wash trading; however, following the improvement, wash trading will be detected during the execution phase after order acceptance, and only the quantity of conflicting new orders **will be** canceled. Please refer to the announcement for details (Update date: April 2, 2026, after 12:00 PM).
>
> Response item "Cancellation Order Unique ID" `canceling_uuid`, "Cancellation Type" `cancel_type` This is scheduled to be newly added.

Request

The request is large `ticket field`, `type field`, `format field` are classified as and multiple requests can be made in one request. `type field` You can specify. For more details, Request Method and Format Please check the page.

Type Field

This field lists the quote information you wish to receive.

Field name	Type	detail	Required	Default value
type	String	Data type - `myOrder` : My order	O	
codes	List	Market Code List • Requests must be made in capital letters.	X	If omitted or requested with an empty array, information for all markets will be received.

Response

Field name	Abbreviation (format :SIMPLE)	detail	Type	value
type	ty	Type	String	`myOrder` : My order
code	CD	Market code (ex. KRW-BTC)	String	
client_order_id	coid	User-defined identification ID	String	
uuid	uid	Unique order ID	String	
ask_bid	ab	Buy/Sell distinction	String	`ASK` : Sell `BID` : buy
order_type	ot	Order Type	String	`limit` : Limit order `price` : Market order (buy) `market` : Market order (sell)
state	s	Order Status	String	`wait` : Waiting for conclusion `trade` : Conclusion occurs `done` : Full contract completed `cancel` : withdraw order
trade_uuid	tuid	Unique ID of the contract	String	
price	p	Order price, Settlement price (when state: trade)	Double	
volume	v	Order quantity, Transaction volume (when state: trade)	Double	
remaining_volume	rv	Order quantity remaining after conclusion	Double	
executed_volume	ev	Amount concluded	Double	

Field name	Abbreviation (format :SIMPLE)	detail	Type	value
trades_count	tc	Number of orders placed for that order	Double	
reserved_fee	rsf	Costs reserved as fees	Double	
remaining_fee	rmf	Remaining fees	Double	
paid_fee	pf	Fees used	Double	
executed_funds	ef	Amount agreed upon	Double	
trade_timestamp	ttms	Transaction timestamp (millisecond)	Long	
order_timestamp	otms	Order timestamp (millisecond)	Long	
timestamp	tms	timestamp (millisecond)	Long	
stream_type	st	Stream type	String	`REALTIME` : Real-time

Example

Request

- Receive all market information

JSON

```
[
  {
    "ticket": "test example"
  },
  {
    "type": "myOrder",
    "codes": []
  }
]
```

- Receive specific market information

JSON

```
[
  {
    "ticket": "test example"
  },
  {
    "type": "myOrder",
    "codes": ["KRW-BTC"]
  }
]
```

Response

JSON

```
{
    "type": "myOrder",
    "code": "KRW-BTC",
    "client_order_id": "my-client-order-id-1",
    "uuid": "C0101000000001818113",
    "ask_bid": "BID",
    "order_type": "limit",
    "state": "trade",
    "trade_uuid": "C0101000000001744207",
    "price": 1927000,
    "volume": 0.4697,
    "remaining_volume": 0.0803,
    "executed_volume": 0.4697,
    "trades_count": 1,
    "reserved_fee": 0,
    "remaining_fee": 0,
    "paid_fee": 0,
    "executed_funds": 905111.9000,
    "trade_timestamp": 1727052318148,
    "order_timestamp": 1727052318074,
    "timestamp": 1727052318369,
    "stream_type": "REALTIME"
}
```

Updated 7 days ago

Orderbook
MyAsset

Did this page help you?

Yes

No

MyAsset

Request

The request is large `ticket field`, `type field`, `format field` are classified as and multiple requests can be made in one request. `type field` You can specify. For more details, Request Method and Format Please check the page.

Type Field

This field lists the quote information you wish to receive.

Field name	Type	detail	Required	Default value
type	String	Data type - `myAsset` : My assets	O	

Response

Field name	Abbreviation (format :SIMPLE)	detail	Type	value
type	ty	Type	String	`myAsset` : My assets
assets	ast	Asset List	List of Objects	
assets.currency	ast.cu	English capital letter code for currency	String	
assets.balance	ast.b	Quantity available for ordering	Double	
assets.locked	ast.l	Quantity tied to order	Double	
asset_timestamp	asttms	Asset timestamp (millisecond)	Long	

Field name	Abbreviation (format :SIMPLE)	detail	Type	value
timestamp	tms	timestamp (millisecond)	Long	
stream_type	st	Stream type	String	`REALTIME` : Real-time

Example

Request

- Receive all market information

JSON

```
[
  {
    "ticket": "test example"
  },
  {
    "type": "myAsset"
  }
]
```

Response

JSON

```
{
    "type": "myAsset",
    "assets": [
        {
            "currency": "KRW",
            "balance": "2061832.35",
            "locked": "3824127.3"
        }
    ],
    "asset_timestamp": 1727052537592,
    "timestamp": 1727052537687,
    "stream_type": "REALTIME"
}
{
    "type": "myAsset",
```

```
    "assets": [
        {
            "currency": "BTC",
            "balance": "156.70564833",
            "locked": "38.81945789"
        }
    ],
    "asset_timestamp": 1727052537592,
    "timestamp": 1727052537690,
    "stream_type": "REALTIME"
}
```


Updated about 2 months ago

[My Order and Execution (MyOrder)](#)

[WebSocket Error](#)

Did this page help you?

Yes

No

WebSocket Error

Format

When an error occurs, an error message in JSON format is sent down.

Response

Field name	detail	Type
error	Error object	`Object`
error.name	type	`String`
error.message	message	`String`

Error types

WRONG_FORMAT

JSON

```
{"error":{"name":"WRONG_FORMAT","message":"Format 이 맞지 않습니다."}}
```

NO_TICKET

JSON

```
{"error":{"name":"NO_TICKET","message":"티켓이 존재하지 않거나, 유효하지 않습니다."}}
```

NO_TYPE

JSON

```
{"error":{"name":"NO_TYPE","message":"type 필드가 존재하지 않습니다."}}
```

NO_CODES

JSON

```
{"error":{"name":"NO_CODES","message":"codes 필드가 존재하지 않습니다."}}
```

INVALID_PARAM

JSON

```
{"error":{"name":"INVALID_PARAM","message":"codes 필드가 비어 있습니다."}}
```

INVALID_PARAM_FORMAT

JSON

```
{"error":{"name":"INVALID_PARAM","message":"{}은 지원하지 않는 포맷입니다."}}
```

Updated about 1 year ago

MyAsset
Connection Management

Did this page help you?

Yes

No

Connection Management

Connection Management

PING/PONG

The Bithumb API WebSocket server provides WebSocket PING/PONG Frames to stably manage/maintain connections.
(Reference documents: https://tools.ietf.org/html/rfc6455#section-5.5.2)

Client to Server PING

- By default, the server closes the WebSocket Connection with Idle Timeout after approximately 120 seconds without receiving or sending any data.
- To prevent this, you can keep the connection open by sending a PING message from the client to the server and check the status of the WebSocket server and the WebSocket Connection Status.
- The Bithumb API WebSocket server is equipped to receive PING frames. With a simple implementation, clients can monitor server status through PING requests and PONG responses (PING response frames).
- Please check the relevant client development documentation for configuration.
  (Most libraries will likely have a ping function built-in.)
- Additionally, you can maintain the connection by sending a PING message.
  If the connection is maintained, you will receive a {"status":"UP"} response every 10 seconds.

Shell

```
$ wscat -c wss://ws-api.bithumb.com/websocket/v1
Connected (press CTRL+C to quit)

PING

{"status":"UP"}
{"status":"UP"}
{"status":"UP"}
...
```

Updated about 1 year ago

WebSocket Error

Did this page help you?

Yes

No

Minute candle

get
https://api.bithumb.com/v1/candles/minutes/{unit}

Example code is provided only for JavaScript, Python, and JAVA.

Request Parameters

field	Details	Type
market	Market code (ex. KRW-BTC)	String
to	Last candle time (exclusive). ISO8061 format (yyyy-MM-dd HH:mm:ss or yyyy-MM-ddTHH:mm:ss). Default is KST time, and if left blank, the most recent candle will be requested.	String
count	Number of candles (up to 200 can be requested), default 1	Integer

Response

field	Details	Type
market	Market name	String
candle_date_time_utc	Candle reference time (UTC) Format: `yyyy-MM-dd'T'HH:mm:ss`	String
candle_date_time_kst	Candlestick reference time (KST) Format: `yyyy-MM-dd'T'HH:mm:ss`	String
opening_price	market price	Double
high_price	high price	Double
low_price	low price	Double

field	Details	Type
trade_price	Closing price	Double
timestamp	Candle closing time (based on KST)	Long
candle_acc_trade_price	Cumulative transaction amount	Double
candle_acc_trade_volume	Cumulative trading volume	Double
unit	Minutes (units)	Integer

Path Params

unit

int32

required

Defaults to 1

Minutes. Possible values: 1, 3, 5, 10, 15, 30, 60, 240

Query Params

market
string
required
Defaults to KRW-BTC

Market code (ex. KRW-BTC)

to
string

Last candle time (exclusive). Leave blank to request the most recent candle.

count
int32
Defaults to 1

Number of candles (up to 200 can be requested)

Responses

200

200

Response body

array of objects

object

market

string

candle_date_time_utc

string

candle_date_time_kst

string

opening_price

integer

Defaults to 0

high_price

integer

Defaults to 0

low_price

integer
Defaults to 0
trade_price
integer
Defaults to 0
timestamp
integer
Defaults to 0
candle_acc_trade_price
number
Defaults to 0
candle_acc_trade_volume
number
Defaults to 0
unit
integer
Defaults to 0

400
400

Updated 30 days ago

Market Code Inquiry
Day candle
Did this page help you?
Yes
No

Market Code Inquiry

get
https://api.bithumb.com/v1/market/all

We provide information on markets and virtual assets available for trading on Bithumb.

Example code is provided only for JavaScript, Python, and JAVA.

Response

field	Details	Type
market	Market information provided by Bithumb	String
korean_name	Korean name of the digital asset to be traded	String
english_name	English name of the digital asset to be traded	String
market_warning	Investment Warning Status `NONE` (not applicable), `CAUTION` (Trading Caution) It returns the status of whether it is designated as an 'Investment Warning Item'. For the designation status of a 'Cautionary Item', please refer to the Alert System API.	String

Query Params

isDetails

boolean

Defaults to false

Whether to display detailed information such as the noteworthy item field (optional parameter)

Responses

200

200

Response body

json

```
400
400
```

Updated 4 months ago

Price candle inquiry

Did this page help you?

Yes

No

Recent contract details

get

https://api.bithumb.com/v1/trades/ticks

Example code is provided only for JavaScript, Python, and JAVA.

Response

field	Details	Type
market	Market classification code	String
trade_date_utc	Date of execution (UTC) Format: `yyyy-MM-dd`	String
trade_time_utc	Execution time (UTC) Format: `HH:mm:ss`	String
timestamp	Execution timestamp	Long
trade_price	Execution price	Double
trade_volume	Execution amount	Double
prev_closing_price	Previous day's closing price (as of 00:00 UTC)	Double
change_price	Amount of change	Double
ask_bid	Sell/Buy	String
sequential_id	Contract Number (Unique)	Long

- `sequential_id` Fields can be used as a basis for determining the uniqueness of a transaction, but do not guarantee the order of transactions.

Query Params

market
string
required

Market code (ex. KRW-BTC)

to
string

Last transaction time. Format: [HHmmss or HH:mm:ss]. Leave blank to request the most recent data (00:00:00 to 23:59:59).

count
int32
Defaults to 1

Number of contracts (1-500)

cursor
string

Pagination Cursor (sequentialId)

daysAgo
int32

You can view data from up to 7 days prior to the most recent transaction date. If left blank, the most recent transaction date will be returned. (Range: 1 to 7)

Responses

200

200

Response body

array of objects

object

market

string

trade_date_utc

string

trade_time_utc

string

timestamp

integer

Defaults to 0

trade_price

integer

Defaults to 0

trade_volume

number

Defaults to 0

prev_closing_price

integer

Defaults to 0

chane_price

integer

Defaults to 0

ask_bid

string

400

400

Updated 4 months ago

Month candle

Current price (Ticker) inquiry

Did this page help you?

Yes

No

Current price information

get

https://api.bithumb.com/v1/ticker

A snapshot of the stock at the time of request is provided.

Example code is provided only for JavaScript, Python, and JAVA.

Response

field	Details	Type
market	Item classification code	String
trade_date	Last transaction date (UTC) Format: `yyyyMMdd`	String
trade_time	Last transaction time (UTC) Format: `HHmmss`	String
trade_date_kst	Last transaction date (KST) Format: `yyyyMMdd`	String
trade_time_kst	Last trading time (KST) Format: `HHmmss`	String
trade_timestamp	Last transaction date (UTC) Format: `Unix Timestamp`	Long
opening_price	market price	Double
high_price	high price	Double
low_price	low price	Double
trade_price	closing price (current price)	Double

field	Details	Type
prev_closing_price	Previous day's closing price (as of 00:00 KST)	Double
change	EVEN: Consolidated RISE: Rise FALL: decline	String
change_price	Absolute value of change	Double
change_rate	Absolute value of rate of change	Double
signed_change_price	Signed change amount	Double
signed_change_rate	Signed rate of change	Double
trade_volume	Most recent trading volume	Double
acc_trade_price	Cumulative transaction amount (as of 00:00 KST)	Double
acc_trade_price_24h	24-hour cumulative trading volume	Double
acc_trade_volume	Cumulative trading volume (as of 00:00 KST)	Double
acc_trade_volume_24h	24-hour cumulative trading volume	Double
highest_52_week_price	52-week high	Double
highest_52_week_date	52-week high achieved date Format: `yyyy-MM-dd`	String
lowest_52_week_price	52-week low	Double
lowest_52_week_date	52-week low achieved date Format: `yyyy-MM-dd`	String
timestamp	timestamp	Long

*The above response `change`, `change_price`, `change_rate`, `signed_change_price`, `signed_change_rate` The field is the comparison value of the previous day's closing price.

Query Params

markets

string

required

Market codes separated by dots (e.g. KRW-BTC, BTC-ETH)

Responses

200

200

Response body

array of objects

object

market

string

trade_date

string

trade_time

string

trade_date_kst

string

trade_time_kst

string

trade_timestamp

integer

Defaults to 0

opening_price
integer
Defaults to 0
high_price
integer
Defaults to 0
low_price
integer
Defaults to 0
trade_price
integer
Defaults to 0
prev_closing_price
integer
Defaults to 0
change
string
change_price
integer
Defaults to 0
change_rate
number
Defaults to 0
signed_change_price
integer
Defaults to 0
signed_change_rate
number
Defaults to 0
trade_volume
number
Defaults to 0
acc_trade_price
number
Defaults to 0
acc_trade_price_24h
number
Defaults to 0
acc_trade_volume
number
Defaults to 0
acc_trade_volume_24h
number
Defaults to 0
highest_52_week_price
integer
Defaults to 0
highest_52_week_date

string

lowest_52_week_price

integer

Defaults to 0

lowest_52_week_date

string

timestamp

integer

Defaults to 0

400

400

Updated 9 months ago

Recent contract details

Market price information (Orderbook) inquiry

Did this page help you?

Yes

No

Orderbook information inquiry

get

https://api.bithumb.com/v1/orderbook

Example code is provided only for JavaScript, Python, and JAVA.

Response

field	Details	Type
market	Market Code	String
timestamp	Orderbook generation time	Long
total_ask_size	Total remaining quantity of asks	Double
total_bid_size	Total remaining quantity of bids	Double
orderbook_units	Orderbook	List of Objects
ask_price	Sell price	Double
bid_price	Bid price	Double
ask_size	Ask size	Double
bid_size	Bid size	Double

`orderbook_units` The list contains information in order of 15 (1, 2, ... 15). However, `market` When entering only a single market code `orderbook_units` The list provides information up to 30 units.`

Query Params

markets

array of strings

required

List of market codes (ex. KRW-BTC, BTC-ETH)

markets *

ADD string

Responses

200

200

Response body

array of objects
object
market
string
timestamp
integer
Defaults to 0
total_ask_size
number
Defaults to 0
total_bid_size
number
Defaults to 0
orderbook_units
array of objects

orderbook_units
object
ask_price
integer
Defaults to 0
bid_price
integer
Defaults to 0
ask_size
number
Defaults to 0
bid_size
number
Defaults to 0

400
400

Updated 9 months ago

Current price information
Service Information
Did this page help you?
Yes
No

Market alert system

get

https://api.bithumb.com/v1/market/virtual_asset_warning

View the list of markets and coins under alert

Example code is provided only for JavaScript, Python, and JAVA.

Response

field	Details	Type
market	Market information provided by Bithumb	String

warning_type	Alert Type
	`- PRICE_SUDDEN_FLUCTUATION : 가격 급등락`
	`- PRICE_DIFFERENCE_HIGH : 글로벌 시세차이`
	`- SPECIFIC_ACCOUNT_HIGH_TRANSACTION : 소수계정 거래 집중`
	`- TRADING_VOLUME_SUDDEN_FLUCTUATION : 거래량 급등`
	`- DEPOSIT_AMOUNT_SUDDEN_FLUCTUATION : 입금량 급등`
		String

warning_step	Alert level
	`- CAUTION : 주의`
	`- WARNING : 경고`
	`- DANGER : 위험`
		String

end_date	Virtual asset alert end date (based on KST) Format: `yyyy-MM-dd HH:mm:ss`	String

Responses

200

200

Response body

array of objects

object

market

string

warning_type

string

warning_step

string

end_date

string

400

400

Updated 30 days ago

Orderbook information inquiry

View notices

Did this page help you?

Yes

No

View all accounts

get

https://api.bithumb.com/v1/accounts

View information about the assets you hold.

Example code is provided only for JavaScript, Python, and JAVA.

Response

field	Details	Type
currency	English capital letter code for currency	String
balance	Orderable amount/quantity	NumberString
locked	Amount/quantity tied to the order	NumberString
avg_buy_price	Average purchase price	NumberString
avg_buy_price_modified	Whether to revise the average purchase price	Boolean
unit_currency	Currency based on average price	String

Headers

Authorization
string
required

Authorization token (JWT)

Responses

200

200

Response body

array of objects

object

currency

string

balance

string

locked

string

avg_buy_price

string

avg_buy_price_modified

boolean

Defaults to true

unit_currency

string

400

400

Updated 9 months ago

Check deposit/withdrawal fees

Order

Did this page help you?

Yes

No

Ordering Information

get

https://api.bithumb.com/v1/orders/chance

Check order availability information by market.

Example code is provided only for JavaScript, Python, and JAVA.

Request Parameters

field	Details	Type
market *	Market ID (ex.KRW-BTC)	String

Response

field	Details	Type
bid_fee	buying commission rate	NumberString
ask_fee	Selling commission rate	NumberString
maker_bid_fee	Market buying commission rate	NumberString
maker_ask_fee	Market Selling Fee Rate	NumberString
market	Information about the market	Object
market.id	The only key in the market	String
market.name	Market name	String
market.order_types	Support Order Method	Array[String]
market.ask_types	Sell order support method	Array[String]
market.bid_types	Buy order support method	Array[String]
market.order_sides	Support Order Types	Array[String]
market.bid	Restrictions on purchase	Object
market.bid.currency	English capital letter code for currency	String
market.bid.price_unit	Order amount unit	NumberString
market.bid.min_total	Minimum buy/sell amount	NumberString
market.ask	Restrictions on selling	Object
market.ask.currency	English capital letter code for currency	String
market.ask.price_unit	Order amount unit	NumberString

field	Details	Type
market.ask.min_total	Minimum buy/sell amount	NumberString
market.max_total	Maximum sell/buy amount	NumberString
market.state	Market operating status	String
bid_account	Account status of the currency used for purchase	Object
bid_account.currency	English capital letter code for currency	String
bid_account.balance	Orderable amount/quantity	NumberString
bid_account.locked	Amount/quantity tied to the order	NumberString
bid_account.avg_buy_price	Average purchase price	NumberString
bid_account.avg_buy_price_modified	Whether to revise the average purchase price	Boolean
bid_account.unit_currency	Currency based on average price	String
ask_account	Account status of the currency used when selling	Object
ask_account.currency	English capital letter code for currency	String
ask_account.balance	Orderable amount/quantity	NumberString
ask_account.locked	Amount/quantity tied to the order	NumberString
ask_account.avg_buy_price	Average purchase price	NumberString
ask_account.avg_buy_price_modified	Whether to revise the average purchase price	Boolean
ask_account.unit_currency	Currency based on average price	String

Query Params

market
string
required

Market ID

Headers

Authorization
string
required

Authorization token (JWT)

Responses

200

200

Response body

object

bid_fee

string

ask_fee

string

maker_bid_fee

string

maker_ask_fee

string

market

object

id

string

name

string

order_types
array of strings
order_types
order_sides
array of strings
order_sides
bid_types
array of strings
bid_types
ask_types
array of strings
ask_types
bid
object
bid object
ask
object
ask object
max_total
string
state
string
bid_account
object
currency
string
balance
string
locked
string
avg_buy_price
string
avg_buy_price_modified
boolean
Defaults to true
unit_currency
string
ask_account
object
currency
string
balance
string
locked
string
avg_buy_price
string
avg_buy_price_modified

boolean

Defaults to true

unit_currency

string

400

400

Updated 30 days ago

View all accounts

Individual Order Inquiry

Did this page help you?

Yes

No

TWAP - Order History

get

https://api.bithumb.com/v1/twap

View your order list.

Example code is provided only for JavaScript, Python, and JAVA.

Request Parameters

field	Details	Type
market	Market ID (ex.KRW-BTC)	String
uuids	TWAP Order ID List	Array

state	TWAP Order Status
	`- progress : 진행중 (default)`
	`- done : 주문 완료`
	`- cancel : 취소`
		String

next_key	Cursor value for viewing the next page	String
limit	Number limit (default: 100, limit: 100)	Number

order_by	Sorting method
	`- asc : 오름차순`
	`- desc : 내림차순 (default)`
		String

Responses

field	Details	Type
has_next	Whether the next page exists	Boolean

field	Details	Type
next_key	Cursor value for next page lookup (`Base64 인코딩된 문자열`). `- hasNext 가 false 면 null`	String
uuid	TWAP Order ID `- algo_order_id 와 동일`	String
side	Order Type	String
price	Currency price at the time of order	NumberString

state	TWAP Order Status
	`- progress : 진행중 (default)`
	`- done : 주문 완료`
	`- cancel : 취소`
		String

market	The only key in the market	String
created_at	Order creation time	DateString
volume	The order quantity entered by the user	NumberString

finished_at	Order closing time
	`- done 상태일 시 완료시간 노출`
	`- cancel 상태일 시 미노출`
		DateString

total_order_count	Total number of orders	Number
total_trades_count	Total number of executed orders	Number
progress_count	Number of processed orders	Number
total_executed_amount	Total order execution amount	NumberString
total_executed_volume	Total order quantity	NumberString
avg_trade_price	Average order execution price	NumberString

field	Details	Type

canceled_at	Order cancellation time
	`- done 상태일 시 미노출`
	`- cancel 상태일 시 취소시간 노출`
		DateString

cancel_type	Order cancellation type
	`- user : 사용자 취소`
	`- asset : 자산 부족`
	`- admin : 관리자 취소`
	`- system : 시스템 취소`
		String

Query Params

market

string

마켓 ID
uuids
string

TWAP Order ID List

state
string

Order Status

next_key
array of strings

Cursor value for viewing the next page

next_key
ADD string
limit
int32
Defaults to 100

Number limit

order_by
int32
Defaults to desc

Sorting method

Headers

Authorization
string
required

Authorization token (JWT)

Responses

200

200

Response body

array of objects
object
has_next
boolean

Whether the next page exists

next_key
string

Cursor value for viewing the next page

uuid
string

TWAP Order ID

side
string

Order Type

price
string

Currency price at the time of order

state
string

Order Status

market
string

The only key in the market

created_at
date

Order creation time

volume
string

The order quantity entered by the user

finished_at
date

Order closing time

total_order_count
number

Total number of orders

total_trades_count
number

Total number of executed orders

progress_count
number

Number of processed orders

total_executed_amount
string

Total order execution amount

total_executed_volume

string

Total order quantity

avg_trade_price

string

Average order execution price

canceled_at

date

Defaults to 0

Order cancellation time

cancel_type

string

Order cancellation type

400

400

Updated 13 days ago

[Multiple order cancellations accepted]

[TWAP - Cancel Order]

Did this page help you?

Yes

No

View coin withdrawal list

get

https://api.bithumb.com/v1/withdraws

View the list of virtual asset withdrawals.

Example code is provided only for JavaScript, Python, and JAVA.

Request Parameters

field	Details	Type
currency	English capital letter code for currency	String
state	Withdrawal status -PROCESSING: In progress -DONE: Completed -CANCELED: Cancelled	String
uuids	List of withdrawal UUIDs	Array
txids	List of withdrawal TXIDs	Array
page	Number of pages (default: 1)	Number
limit	Number limit (default: 100, max: 100)	Number
order_by	Sorting method -asc: ascending order -desc: descending order (default)	String

Response

field	Details	Type
type	Deposit/Withdrawal Types	String

field	Details	Type
uuid	Unique ID for withdrawal	String
currency	English capital letter code for currency	String
net_type	Withdrawal network (ex. BTC, DASH)	String
txid	Transaction ID of withdrawal	String
state	Withdrawal status -PROCESSING: In progress -DONE: Completed -CANCELED: Cancelled	String
created_at	Withdrawal creation time	DateString
done_at	Withdrawal completion time	DateString
amount	Withdrawal amount/quantity	NumberString
fee	Withdrawal fee	NumberString
transaction_type	Withdrawal Type -default: general withdrawal	String

Query Params

currency
string

English capital letter code for currency

state
string

Withdrawal status

uuids
array of strings

List of withdrawal UUIDs

uuids
ADD string

txids
array of strings

List of withdrawal TXIDs

txids
ADD string
page
int32
Defaults to 1

Number of pages

limit
int32
Defaults to 100

Number limit

order_by
string
Defaults to desc

Sorting method

Headers

Authorization
string
required

Authorization token (JWT)

Responses

200

200

Response body

array of objects

object

type

string

uuid

string

currency

string

net_type

string

txid

string

state

string

created_at

string

done_at

string

amount

string

fee

string

transaction_type

string

400

400

Updated 30 days ago

TWAP - Order

View the list of Korean won withdrawals

Did this page help you?

Yes

No

Check coin deposit list

get

https://api.bithumb.com/v1/deposits

View the list of virtual asset deposits.

Example code is provided only for JavaScript, Python, and JAVA.

Request Parameters

field	Details	Type
currency	English capital letter code for currency	String
state	Deposit status • Deposit request • Waiting for deposit: `REQUESTED_PENDING` • Waiting for return request: `REQUESTED_SYSTEM_REJECTED` • Deposit request pending: `REQUESTED_PROCESSING` • Deposit review in progress: `REQUESTED_PROCESSING` • Deposit review rejection: `REQUESTED_ADMIN_REJECTED` • Deposit • Waiting for deposit: `DEPOSIT_PROCESSING` • Deposit completed: `DEPOSIT_ACCEPTED` • Deposit Cancellation: `DEPOSIT_CANCELLED` • Return request • Waiting for return review: `REFUNDING_PENDING` • Cancellation of return: `REFUNDING_SYSTEM_REJECTED` • Return review in progress: `REFUNDING_PROCESSING` • Cancellation of return: `REFUNDING_ADMIN_REJECTED` • Return Completed: `REFUNDING_ACCEPTED` • Withdrawal of refund request • Return Approval: `REFUNDED_PROCESSING` • Return Completed: `REFUNDED_ACCEPTED` • Cancellation of return: `REFUNDED_CANCELLED`	String
uuids	List of deposit UUIDs	Array
txids	List of deposit TXIDs	Array

field	Details	Type
page	Number of pages (default: 1)	Number
limit	Number limit (default: 100, limit: 100)	Number
order_by	Sorting method -asc: ascending order -desc: descending order (default)	String

Response

field	Details	Type
type	Deposit/Withdrawal Types	String
uuid	Unique ID for deposit	String
currency	English capital letter code for currency	String
net_type	Deposit Network	String
txid	Transaction ID of the deposit	String
state	Deposit status • Deposit request • Waiting for deposit: `REQUESTED_PENDING` • Waiting for return request: `REQUESTED_SYSTEM_REJECTED` • Deposit request pending: `REQUESTED_PROCESSING` • Deposit review in progress: `REQUESTED_PROCESSING` • Deposit review rejection: `REQUESTED_ADMIN_REJECTED` • Deposit • Waiting for deposit: `DEPOSIT_PROCESSING` • Deposit completed: `DEPOSIT_ACCEPTED` • Deposit Cancellation: `DEPOSIT_CANCELLED` • Return request • Waiting for return review: `REFUNDING_PENDING` • Cancellation of return: `REFUNDING_SYSTEM_REJECTED` • Return review in progress: `REFUNDING_PROCESSING` • Cancellation of return: `REFUNDING_ADMIN_REJECTED` • Return Completed: `REFUNDING_ACCEPTED` • Withdrawal of refund request	String

field	Details	Type
	• Return Approval: `REFUNDED_PROCESSING` • Return Completed: `REFUNDED_ACCEPTED` • Cancellation of return: `REFUNDED_CANCELLED`	
created_at	Deposit creation time	DateString
done_at	Deposit completion time	DateString
amount	Deposit quantity	NumberString
fee	Deposit fee	NumberString
transaction_type	Deposit Type -default: general deposit	String

Query Params

currency
string

English capital letter code for currency

state
string

Deposit status

uuids
array of strings

List of deposit UUIDs

uuids
ADD string

txids
array of strings

List of deposit TXIDs

txids
ADD string
page
int32
Defaults to 1

Number of pages

limit
int32
Defaults to 100

Number limit

order_by
string
Defaults to desc

Sorting method

Headers

Authorization
string
required

Authorization token (JWT)

Responses

200

200

Response body

array of objects

object

type

string

uuid

string

currency

string

net_type

string

txid

string

state

string

created_at

string
done_at
string
amount
string
fee
string
transaction_type
string

400
400

Updated 30 days ago

List of allowed withdrawal addresses inquiry
Check the list of Korean won deposits
Did this page help you?
Yes
No

Deposit/Withdrawal Status

get

https://api.bithumb.com/v1/status/wallet

Check deposit/withdrawal status and block status.

Example code is provided only for JavaScript, Python, and JAVA.

Response

field	Details	Type
currency	English capital letter code for currency	String
wallet_state	Deposit/Withdrawal Status -working: Deposits and withdrawals possible -withdraw_only: Withdrawal only -deposit_only: Deposit only -paused: Deposits and withdrawals paused	String
block_state	Block status -normal: normal -delayed: delayed -inactive: inactive (under maintenance, etc.)	String
block_height	Block height	Integer
block_updated_at	Block update time	DateString
block_elapsed_minutes	Time elapsed since last block information update (minutes)	Integer
net_type	Network type to be specified when requesting deposits or withdrawals	String
network_name	Deposit/Withdrawal Network Name	String

Headers

Authorization
string
required

Authorization token (JWT)

Responses

200

200

Response body

array of objects

object

currency

string

wallet_state

string

block_state

string

block_height

integer

Defaults to 0

block_updated_at

string

block_elapsed_minutes

integer

Defaults to 0

net_type

string

network_name

string

400

400

Updated 30 days ago

Deposit Korean won

API key list inquiry

Did this page help you?

Yes

No

Current price (Ticker)

Request

The request is large `ticket field`, `type field`, `format field` are classified as and multiple requests can be made in one request. `type field` You can specify. For more details, Request Method and Format Please check the page.

Type Field

This field lists the quote information you wish to receive.
`is_only_snapshot`, `is_only_realtime` Fields can be omitted, and if both are omitted, both snapshot and real-time data will be received.

Field name	Type	detail	Required	Default value
type	String	Data type -`ticker` : Current price	O	
codes	List	Market Code List • Requests must be made in capital letters.	O	
isOnlySnapshot	Boolean	Only snapshot prices are provided	X	false
isOnlyRealtime	Boolean	Only real-time prices are provided	X	false

Response

Field name	Abbreviation (format :SIMPLE)	detail	Type	value
type	ty	Type	String	`ticker` : Current price
code	CD	Market code (ex. KRW-BTC)	String	
opening_price	op	market price	Double	

Field name	Abbreviation (format :SIMPLE)	detail	Type	value
high_price	hp	high price	Double	
low_price	lp	low price	Double	
trade_price	tp	Current price	Double	
prev_closing_price	pcp	Previous day's closing price	Double	
change	c	Compared to the previous day	String	`RISE` : Rise `EVEN` : Consolidated `FALL` : decline
change_price	cp	Unsigned previous day's value	Double	
signed_change_price	scp	Value compared to the previous day	Double	
change_rate	cr	Previous day's change rate without sign	Double	
signed_change_rate	scr	Rate of change compared to the previous day	Double	
trade_volume	TV	Most recent trading volume	Double	
acc_trade_volume	atv	Cumulative trading volume (as of 00:00 KST)	Double	
acc_trade_volume_24h	atv24h	24-hour cumulative trading volume	Double	
acc_trade_price	atp	Cumulative transaction amount (as of 00:00 KST)	Double	
acc_trade_price_24h	atp24h	24-hour cumulative trading volume	Double	

Field name	Abbreviation (format :SIMPLE)	detail	Type	value
trade_date	tdt	Last transaction date (KST)	String	yyyyMMdd
trade_time	ttm	Last trading time (KST)	String	HHmmss
trade_timestamp	ttms	Transaction timestamp (milliseconds)	Long	
ask_bid	ab	Buy/Sell distinction	String	`ASK` : Sell `BID` : buy
acc_ask_volume	aav	Cumulative selling volume	Double	
acc_bid_volume	abv	Cumulative bid amount	Double	
highest_52_week_price	h52wp	52-week high	Double	
highest_52_week_date	h52wdt	52-week high achieved date	String	yyyy-MM-dd
lowest_52_week_price	l52wp	52-week low	Double	
lowest_52_week_date	l52wdt	52-week low achieved date	String	yyyy-MM-dd
market_state	ms	Transaction status	String	
is_trading_suspended	its	Trading Suspension Status	Boolean	
delisting_date	dd	Transaction support end date	Date	
market_warning	mw	Investment Warning Status	String	`NONE` : Not applicable `CAUTION` : Transaction caution
timestamp	tms	timestamp (millisecond)	Long	

Field name	Abbreviation (format :SIMPLE)	detail	Type	value
stream_type	st	Stream type	String	`SNAPSHOT` : snapshot `REALTIME` : Real-time

Example

Request

- `KRW-BTC` , `KRW-ETH`

JSON

```
[
  {
    "ticket": "test example"
  },
  {
    "type": "ticker",
    "codes": [
      "KRW-BTC",
      "KRW-ETH"
    ]
  },
  {
    "format": "DEFAULT"
  }
]
```

Response

JSON

```
{
    "type": "ticker",
    "code": "KRW-BTC",
    "opening_price": 484500,
    "high_price": 493100,
    "low_price": 472500,
    "trade_price": 493100,
    "prev_closing_price": 484500,
    "change": "RISE",
    "change_price": 8600,
    "signed_change_price": 8600,
```

```
    "change_rate": 0.01775026,
    "signed_change_rate": 0.01775026,
    "trade_volume": 1.2567,
    "acc_trade_volume": 225.622,
    "acc_trade_volume_24h": 13386.15417512,
    "acc_trade_price": 108663718.238256,
    "acc_trade_price_24h": 8230696760.346009,
    "trade_date": "20240910",
    "trade_time": "091617",
    "trade_timestamp": 1725927377820,
    "ask_bid": "BID",
    "acc_ask_volume": 106.7561,
    "acc_bid_volume": 118.8659,
    "highest_52_week_price": 999999000,
    "highest_52_week_date": "2024-06-18",
    "lowest_52_week_price": 1000,
    "lowest_52_week_date": "2024-06-18",
    "market_state": "ACTIVE",
    "is_trading_suspended": false,
    "delisting_date": null,
    "market_warning": "NONE",
    "timestamp": 1725927377931,
    "stream_type": "REALTIME"
}
```


Updated about 2 months ago

Test and Request Examples

Trade

Did this page help you?

Yes

No

Current price information inquiry (ALL)

get
https://api.bithumb.com/public/ticker/ALL_{payment_currency}

We provide information on the current price of virtual assets on the Bithumb exchange at the time of request.

Response

field	Details	Type
status	Result status code (Normal: 0000, see other error codes)	String
opening_price	As of 00:00	Number (String)
closing_price	As of 00:00 closing price	Number (String)
min_price	Low price as of 00:00	Number (String)
max_price	As of 00:00	Number (String)
units_traded	Trading volume as of 00:00	Number (String)
acc_trade_value	Transaction amount as of 00:00	Number (String)
prev_closing_price	Previous day's closing price	Number (String)
units_traded_24H	Last 24-hour trading volume	Number (String)
acc_trade_value_24H	Last 24-hour trading amount	Number (String)
fluctate_24H	Last 24-hour price fluctuations	Number (String)
fluctate_rate_24H	Last 24-hour change rate	Number (String)

field	Details	Type
date	timestamp	Integer(String)

> 📘
>
> **What is recent?**
>
> Based on the time at which the API was called

Path Params

payment_currency

string

required

Defaults to KRW

결제 통화(마켓), 입력값 : KRW, BTC

KRW

Responses

200

200

Response body

object

status

string

data

object

BTC

object

BTC object

ETH

object

ETH object

400

400

Updated 6 months ago

Current price information inquiry (by asset)

Did this page help you?

Yes

No

Market Code Inquiry

get
https://api.bithumb.com/v1/market/all

We provide information on markets and virtual assets available for trading on Bithumb.

Example code is provided only for JavaScript, Python, and JAVA.

Response

field	Details	Type
market	Market information provided by Bithumb	String
korean_name	Korean name of the digital asset to be traded	String
english_name	English name of the digital asset to be traded	String
market_warning	Investment Warning Status `NONE` (not applicable), `CAUTION` (Trading Caution) It returns the status of whether it is designated as an 'Investment Warning Item'. For the designation status of a 'Cautionary Item', please refer to the Alert System API.	String

Query Params

isDetails

boolean

Defaults to false

Whether to display detailed information such as the noteworthy item field (optional parameter)

Responses

200

200

Response body

json

```
400
400
```

Updated 4 months ago

Price candle inquiry

Did this page help you?

Yes

No