Distributed by:

JAMECO

ELECTRONICS

www.Jameco.com + 1-800-831-4242

The content and copyrights of the attached material are the property of its owner.

Jameco Part Number 29082

The state of the s	CO-800 02 LAMORDO 500		31		9	٠ 		§ •		
5	PECIFIC	AT	ION OF	CARBON (Сомра	OSITIO	N VARIA	BLE RES	ISTOR	S
Cus	TOMER							CODE NO		
PAR	T No 2	29082		TYPE CODE		SAMPLES	Spec No			
Mod	ELNo			24N= 10 KB.15R			DRWG No			
DRV	rg No					KITS/PCS	DATE		- 10	
EO	NOMINAL I		RESISTANC	10 Kc	HMS ±	20 %	- 450	TAPER B CURVE		
E 0			CURVE =	FIGURE AT RIGHT						
E 0	Power_ I		RATINGS	125 V	0,0	5 w	l a con	TIL		
E 04	RESIDUAL		T1-T2	LESS THAN	20	OHMS	1 60		-1/	
E O	RESISTAN	CE	T2-T3	LESS THAN	20	OHMS	EE 40		4	
E 06	TRACKING ERROR(dBm) (FOR GANG TYPE ONLY)		Volume	± FOR	. TO		OUTPUT V INPUT V			Щ
			TONE	AT S	50%	TRAVEL	δl 11_9	20 40	60	80 100
E 07	Switch		RATINGS	V A		ccv	V+ EFFEC	TIVE TRA	WEL-C	
			CONTACT	LESS THAN OHMS		FOR TYPES WITH SWITCH				
E 08	SLIDING	SLIDING NOISE			LESS THAN 47 mV			CTIVE TRAN		CH TRAVE
E 09	INSULATION	N F	ESISTANCE	DC 500V	100	Онмѕ		Nut	OD.	T 2 1
Ξ 10	DIELECTRI	DIELECTRIC STRENGTH			AC1000V FOR 1 MINUTE			ES WASH	00 F	0.51
M 01	DIMENSIONS			FIGURE ATTACHED				SCRE	M 1.7	1
402	STOPPER	PER STRENGTH		More THAN 7 Kg		Notes			N-1111-1-171	
M 03	OVERALL	I	ROTATION	300 ±	5	٥				
	TRAVEL		STROKE	mm		. BUSH	ING-3	/8		
104	TORQUE		SLIDING	50 -	350	gcm				A
105			Switch	- gcm						
406			ROTATION	* mm		8.4				
			STROKE				2			
107	Switch T		PE .			2	*			
.01	Working	Lı	FE	MORE THAN 1	5,000	CYCLES			(ii)	
AUTH	ORIZED	AP	PROVED	CHECKED	WRIT	TEN		5		
							2.60			
		5				,	71			

