

Edward Agent Stack

Install this on an intern Mac so Codex starts with Edward's workflow: ask Codex first, use gstack when stuck, and write project decisions down.

What This Gives The Intern

- A one-command setup path Codex can run and verify.
- Edward's default engineering rules without private personal context.
- A place to record project facts and decisions so Edward is not asked the same thing twice.

1. Paste This Into Codex

Install Edward's agent stack on this fresh MacBook. Clone <https://github.com/giaphutran12/edward-agent-stack> to ~/edward-agent-stack, read AGENTS.md, then run ./scripts/bootstrap-macos.sh, ./scripts/install.sh, ./scripts/verify.sh, and ./scripts/auth-doctor.sh. Use /caveman ultra. Do not inspect or print local real env/secret files. If a tool needs login, API key, license acceptance, or GUI first-run, stop and tell me exactly what is missing.

2. Default Tools

Codex Caveman codex-gstack MemPalace
Repowise Nia Supabase Vercel Claude GitHub
ripgrep tmux Docker Python/uv Bun/Node jq

3. Not Default

- Bitwarden: not default; does not stop raw key copying.
- Notion, TinyFish, OMX, Kiro, mlx_whisper.
- New databases/vector stores unless Edward approves.

4. Daily Start

- Load /caveman ultra.
- Load \$edward-rules.
- Read project PROJECT.md and recent decisions.
- Read AGENTS.local.md if present.

5. Ask Edward Only When Needed

- Business/company context only Edward knows.
- Architecture or data change with real blast radius.
- Tradeoff still unclear after Codex, docs, and tests.

Secret Rule

No real secrets should be committed. Local ignored env files may exist for execution, but agents should not inspect or print them. For interns, prefer per-user accounts, staging/low-scope keys, logs, revocation, and rotation.