

Day 8: Dictionaries and Maps

☆

7 more challenges

to get your next star!

Points:

8/15



30

Days of Code

★★

Problem

Submissions

Leaderboard

Discussions

Editorial

Tutorial

Objective

Today, we're learning about Key-Value pair mappings using a Map or Dictionary data structure. Check out the [Tutorial](#) tab for learning materials and an instructional video!

Task

Given *n* names and phone numbers, assemble a phone book that maps friends' names to their respective phone numbers. You will then be given an unknown number of names to query your phone book for. For each *name* queried, print the associated entry from your phone book on a new line in the form name=phoneNumber; if an entry for *name* is not found, print Not found instead.

Note: Your phone book should be a Dictionary/Map/HashMap data structure.

Input Format

The first line contains an integer, *n*, denoting the number of entries in the phone book.

Each of the *n* subsequent lines describes an entry in the form of **2** space-separated values on a single line. The first value is a friend's name, and the second value is an **8**-digit phone number.

After the *n* lines of phone book entries, there are an unknown number of lines of queries. Each line (query) contains a *name* to look up, and you must continue reading lines until there is no more input.

Note: Names consist of lowercase English alphabetic letters and are first names only.

Constraints

- $1 \leq n \leq 10^5$
- $1 \leq queries \leq 10^5$

Output Format

On a new line for each query, print Not found if the name has no corresponding entry in the phone book; otherwise, print the full *name* and *phoneNumber* in the format name=phoneNumber.

Sample Input

Author

Shafaet

Difficulty

Easy

Max Score

30

Submitted By

158155

NEED HELP?

📖

View tutorial

💬

View discussions

📖

View editorial

🏆

View top submissions

RATE THIS CHALLENGE

☆ ☆ ☆ ☆ ☆

MORE DETAILS

⬇

Download problem statement

⬇

Download sample test cases

✍

Suggest Edits

📘

🐦

🌐

3

sam 99912222
tom 11122222
harry 12299933
sam
edward
harry

Sample Output

sam=99912222
Not found
harry=12299933

Explanation

We add the following $n = 3$ (Key,Value) pairs to our map so it looks like this:

$phoneBook = \{(sam, 99912222), (tom, 11122222), (harry, 12299933)\}$

We then process each query and print key=value if the queried *key* is found in the map; otherwise, we print Not found.

Query 0: sam

Sam is one of the keys in our dictionary, so we print sam=99912222.

Query 1: edward

Edward is not one of the keys in our dictionary, so we print Not found.

Query 2: harry

Harry is one of the keys in our dictionary, so we print harry=12299933.

Change Theme

Java 8



```
1 //Complete this code or write your own from scratch
2 import java.util.*;
3 import java.io.*;
4
5 class Solution{
6     public static void main(String []argh){
7         Scanner in = new Scanner(System.in);
8         int n = in.nextInt();
9         for(int i = 0; i < n; i++){
10             String name = in.next();
11             int phone = in.nextInt();
12             // Write code here
13
14         }
15         while(in.hasNext()){
```

```
15         String s = in.next();
16         // Write code here
17     }
18     in.close();
19 }
20 }
21
22
```

Line: 22 Col: 1

 Upload Code as File

☐ Test against custom input

Run Code

Submit Code

[Contest Calendar](#) | [Blog](#) | [Scoring](#) | [Environment](#) | [FAQ](#) | [About Us](#) | [Support](#) | [Careers](#) | [Terms Of Service](#) | [Privacy Policy](#) | [Request a Feature](#)