

Day 4: Class vs. Instance

☆

3 more challenges to get your next star!

Points: 4/7



30

Days of Code

★

Problem

Submissions

Leaderboard

Discussions

Editorial

Tutorial

Objective

In this challenge, we're going to learn about the difference between a class and an instance; because this is an Object Oriented concept, it's only enabled in certain languages. Check out the [Tutorial](#) tab for learning materials and an instructional video!

Task

Write a Person class with an instance variable, *age*, and a constructor that takes an integer, *initialAge*, as a parameter. The constructor must assign *initialAge* to *age* after confirming the argument passed as *initialAge* is not negative; if a negative argument is passed as *initialAge*, the constructor should set *age* to 0 and print Age is not valid, setting age to 0.. In addition, you must write the following instance methods:

- yearPasses() should increase the *age* instance variable by 1.
- amIOld() should perform the following conditional actions:
 - If *age* < 13, print You are young..
 - If *age* ≥ 13 and *age* < 18, print You are a teenager..
 - Otherwise, print You are old..

To help you learn by example and complete this challenge, much of the code is provided for you, but you'll be writing everything in the future. The code that creates each instance of your Person class is in the main method. Don't worry if you don't understand it all quite yet!

Note: Do not remove or alter the stub code in the editor.

Input Format

Input is handled for you by the stub code in the editor.

The first line contains an integer, *T* (the number of test cases), and the *T* subsequent lines each contain an integer denoting the *age* of a Person instance.

Constraints

- $1 \leq T \leq 4$
- $-5 \leq age \leq 30$

Output Format

Author

blondiebytes

Difficulty

Easy

Max Score

30

Submitted By

229633

NEED HELP?

View tutorial

View discussions

View editorial

View top submissions

RATE THIS CHALLENGE

☆

☆

☆

☆

☆

MORE DETAILS

Download problem statement

Download sample test cases

Suggest Edits

f

in

Complete the method definitions provided in the editor so they meet the specifications outlined above; the code to test your work is already in the editor. If your methods are implemented correctly, each test case will print **2** or **3** lines (depending on whether or not a valid *initialAge* was passed to the constructor).

Sample Input

```
4
-1
10
16
18
```

Sample Output

```
Age is not valid, setting age to 0.
You are young.
You are young.

You are young.
You are a teenager.

You are a teenager.
You are old.

You are old.
You are old.
```

Explanation

Test Case 0: *initialAge* = -1
Because *initialAge* < 0, our code must set *age* to 0 and print the "Age is not valid..." message followed by the young message. Three years pass and *age* = 3, so we print the young message again.

Test Case 1: *initialAge* = 10
Because *initialAge* < 13, our code should print that the person is young. Three years pass and *age* = 13, so we print that the person is now a teenager.

Test Case 2: *initialAge* = 16
Because 13 ≤ *initialAge* < 18, our code should print that the person is a teenager. Three years pass and *age* = 19, so we print that the person is old.

Test Case 3: *initialAge* = 18
Because *initialAge* ≥ 18, our code should print that the person is old. Three years pass and the person is still old at *age* = 21, so we print the old message again.

The extra line at the end of the output is supposed to be there and is trimmed before being compared against the test case's expected output. If you're failing this challenge, check your logic and review your print statements for spelling

errors.

Change Theme

Java 8



```
1  import java.io.*; ...
3
4  public class Person {
5      private int age;
6
7      public Person(int initialAge) {
8          // Add some more code to run some checks on initialAge
9      }
10
11     public void amIOld() {
12         // Write code determining if this person's age is old and print the correct
13         // statement:
14         System.out.println(/*Insert correct print statement here*/);
15     }
16
17     public void yearPasses() {
18         // Increment this person's age.
19     }
20
21     public static void main(String[] args) {
22         Scanner sc = new Scanner(System.in);
23         int T = sc.nextInt();
24         for (int i = 0; i < T; i++) {
25             int age = sc.nextInt();
26             Person p = new Person(age);
27             p.amIOld();
28             for (int j = 0; j < 3; j++) {
29                 p.yearPasses();
30             }
31             p.amIOld();
32             System.out.println();
33         }
34         sc.close();
35     }
}
```



Upload Code as File

☐ Test against custom input

Run Code

Submit Code

[Contest Calendar](#)

[|](#)

[Blog](#)

[|](#)

[Scoring](#)

[|](#)

[Environment](#)

[|](#)

[FAQ](#)

[|](#)

[About Us](#)

[|](#)

[Support](#)

[|](#)

[Careers](#)

[|](#)

[Terms Of Service](#)

[|](#)

[Privacy Policy](#)

[|](#)

[Request a Feature](#)