

coexnet: An R package to build CO-EXpression NETworks from Microarray Data

Juan David Henao

2017-02-07

Contents

1	Abstract	1
2	Introduction	1
3	Workflow	1
3.1	get.info	1
3.2	get.affy	2
3.3	gene.symbol	2
3.4	exprs.mat	3
3.5	cof.var	3
3.6	dif.exprs	3
3.7	find.threshold	3
3.8	create.net	3

1 Abstract

2 Introduction

3 Workflow

3.1 get.info

All microarray raw data associated with the same study is stored in a CEL file, this file contains the GSM files, each one corresponding to each sample inside of the study, you can obtain each GSM file in an individual way, but, it is rather to obtain all the samples in the CEL file to avoid the work to join each GSM and additionally the way to analyse this kind of data is simultaneously (in future normalization process for example). Therefore, all the microarray chips are documented in the GEO Datasets database. Each one of them is identified with the letters GPL followed by a unique number. The information in the GPL file is related with the information of every probe set in the microarray chip, including the gene, function, type and another information to take advantage of the analysis of the results.

This function will create in your actual pathfile a folder with the GSE(unique number) name where are stored the GSM download files and otherwise the file GPL(unique number).soft file with the information of the microarray chip.

```
# Downloading the microarray raw data from GSE8216 study  
# The accession number of the microarray chip related with this study is GPL2025  
  
get.info(GSE = "GSE8216", GPL = "GPL2025", dir = ".")
```

```
# Show the actual pathfile with the folder with the GSE number and the .soft file
```

```
dir()
```

Take account

In some cases the information in the GPL file are partial, take this in mind in the future analysis and is recommended not store the files in a temporal folder due to in many cases you will need the raw data to re-process the expression values using different methods.

3.2 get.affy

The AffyBatch object is one of the most widely kind of data used to process and analyse microarray expression data. The AffyBatch object store information about the data of scan to each one of the samples, the information related with the phenotype, the raw expression values to each probe in the microarray chip, the kind of library to read the expression data and another one.

You can use the AffyBatch object in many different packages mainly in the affy package, additionally you can modify the AffyBatch object if you consider it necessary.

This function search in your actual or designaded pathfile the folder with the GSE accession number and read the filelist.txt file with the name of the every GSM samples to recognize them and join in an only AffyBatch object.

```
# Reading some GSM samples from GSE4773 study, the folder with the  
# GSM files are called GSE1234
```

```
affy <- get.affy(GSE = "GSE1234",dir = system.file("extdata",package = "coexnet"))
```

Take account

In some cases the AffyBatch doesn't have all the information and a warning message is shown when you view the variable with the AffyBatch object, but you can edit the AffyBatch to fill all the required information. If you try to process the AffyBatch in some of the packages that use this kind of object you will receive an error message.

```
# The variable affy doesn't have the CDF (Chip Definition File) information.  
# You can include this information modifying the AffyBatch object.
```

```
affy@cdfName <- "HG-U133_Plus_2"
```

3.3 gene.symbol

Take account

3.4 `exprs.mat`

3.5 `cof.var`

3.6 `dif.exprs`

3.7 `find.threshold`

3.8 `create.net`