

```
pi@gibsgibs: ~  
pi@gibsgibs:~ $ vim asml7_1.s  
pi@gibsgibs:~ $ as -o asml7_1.o asml7_1.s  
pi@gibsgibs:~ $ gcc -o asml7_1 asml7_1.o  
pi@gibsgibs:~ $ ./asml7_1  
pi@gibsgibs:~ $ ./asml7_1 ; echo $?  
54  
pi@gibsgibs:~ $
```

```
pi@gibsgibs: ~  
pi@gibsgibs:~ $ vim asml7_2.s  
pi@gibsgibs:~ $ as -o asml7_2.o asml7_2.s  
pi@gibsgibs:~ $ gcc -o asml7_2 asml7_2.o  
pi@gibsgibs:~ $ ./asml7_2  
pi@gibsgibs:~ $ ./asml7_2 ; echo $?  
17  
pi@gibsgibs:~ $
```

```
pi@gibsgibs: ~  
For bug reporting instructions, please see:  
<http://www.gnu.org/software/gdb/bugs/>.  
Find the GDB manual and other documentation resources online at:  
<http://www.gnu.org/software/gdb/documentation/>.  
For help, type "help".  
Type "apropos word" to search for commands related to "word"...  
Reading symbols from ./asml7_2...(no debugging symbols found)...done.  
(gdb) start  
Temporary breakpoint 1 at 0x103e8  
Starting program: /home/pi/asml7_2  
  
Temporary breakpoint 1, 0x000103e8 in main ()  
(gdb) break end  
Breakpoint 2 at 0x10410  
(gdb) continue  
Continuing.  
  
Breakpoint 2, 0x00010410 in end ()  
(gdb) info registers r0 r1 r2 r3  
r0          0x12511  75025  
r1          0xb520   46368  
r2          0x12511  75025  
r3          0x17     23  
(gdb)
```