1. Why is it safer to block compute_fare overrides in **__init_subclass__** than to rely on a comment saying "do not override"?

Answer: It is safer because the program can stop other classes from changing the compute_fare method. A comment is just a reminder, and someone might ignore it. This helps keep the original method safe.

2. Explain how your drone was added without editing existing files. Which principle does this demonstrate?

Answer: I added the drone by making a new class without changing the existing classes. This shows the Open/Closed Principle because I can add something new without editing the old code.

3. What is the difference between DeliveryVehicle and Insurable in terms of design purpose, even though both are ABCs?

Answer: DeliveryVehicle is used for vehicles that deliver items and calculate their fare. Insurable is used for vehicles that can have insurance. They have different purposes even if both are ABCs.

4. Why is isinstance(v, Insurable) acceptable while isinstance(v, Truck) is not?

Answer: isinstance(v, Insurable) checks if a vehicle can be insured, no matter what type it is. But isinstance(v, Truck) only checks if it is a truck. Using Insurable makes the program work with more types of vehicles.

5. What would break if PEAK_MULTIPLIER were stored as an instance attribute instead of a class attribute?

Answer: If PEAK_MULTIPLIER is an instance attribute, every vehicle can have a different value. This might cause different fare calculations. Using a class attribute makes all vehicles share the same value.