

**Höhere Technische Bundeslehranstalt Kaindorf an der Sulm**

**Abteilung Informatik**

**Diplomarbeit**

im Rahmen der Reife- und Diplomprüfung

# Königskarte



informatik

Leon Edlinger  
Paul Gigler  
Andreas Weissl

5BHIF  
2024/2025

Betreuer: Prof. DI Johannes Loibner, BSc  
Projektpartner: Prof. DI Robert Müllerferli  
Datum: MISSING DATE

---

All rights reserved. No part of the work may be reproduced in any form (printing, photocopying, microfilm or any other process) without the written permission of all authors or processed, duplicated or distributed using electronic systems. The authors assume no liability for the functions of individual programs or parts thereof. In particular, they assume no liability for any consequential damages resulting from the use.

The reproduction of utility names, trade names, product descriptions, etc. in this work, even without special marking, does not justify the assumption that such names are to be regarded as free within the meaning of trademark and trademark protection legislation and may therefore be used by everyone.

---

## Statutory declaration

I declare under oath that I have written the present diploma thesis independently and without outside help, have not used sources and aids other than those indicated and have identified the passages taken from the sources used literally and in terms of content as such.

---

Ort, Datum

---

Leon Edlinger

---

Ort, Datum

---

Paul Gigler

---

Ort, Datum

---

Andreas Weissl

---

## **Abstract**

Abstract in English

## **Kurzfassung**

Kurzfassung in Deutsch

---

## Thanks

It would not have been possible to carry out this thesis to this extent without the active support of a number of people. We would therefore like to thank everyone who supported us in the implementation of this thesis.

...

# Table of Contents

|          |   |           |
|----------|---|-----------|
| <b>1</b> | <b>Introduction</b>                                     | <b>1</b>  |
| 1.1      | Team . . . . .  | 2         |
| <b>2</b> | <b>Technologies</b>                                     | <b>3</b>  |
| 2.1      | LaTeX . . . . .   | 3         |
| 2.2      | Frontend . . . . .                                      | 3         |
| 2.2.1    | Dart . . . . .  | 3         |
| 2.2.2    | Flutter . . . . .                                       | 3         |
| 2.3      | Backend . . . . .                                       | 5         |
| 2.3.1    | Java Spring . . . . .                                   | 5         |
| 2.3.2    | PostgreSQL . . . . .                                    | 5         |
| 2.4      | Version Control . . . . .                               | 6         |
| 2.4.1    | Git . . . . .   | 6         |
| 2.4.2    | GitHub . . . . .  | 6         |
| 2.5      | Map Data . . . . .                                      | 7         |
| 2.5.1    | OpenStreetMap . . . . .                                 | 7         |
| 2.5.2    | Graphhopper . . . . .                                   | 7         |
| 2.6      | Development Tools . . . . .                             | 8         |
| 2.6.1    | VS Code . . . . .                                       | 8         |
| 2.6.2    | IntelliJ . . . . .                                      | 8         |
| 2.6.3    | Android Studio . . . . .                                | 8         |
| 2.6.4    | Postman . . . . .                                       | 8         |
| 2.6.5    | Figma . . . . .   | 8         |
| 2.7      | Deployment . . . . .                                    | 9         |
| 2.7.1    | Docker . . . . .  | 9         |
| 2.7.2    | Uberspace . . . . .                                     | 9         |
| 2.7.3    | Webmin . . . . .  | 9         |
| <b>3</b> | <b>Research Questions</b>                               | <b>9</b>  |
| 3.1      | Leon Edlinger . . . . .                                 | 9         |
| 3.2      | Paul Gigler . . . . .                                   | 9         |
| 3.3      | Andreas Weissl . . . . .                                | 9         |
| <b>4</b> | <b>Spring Framework</b>                                 | <b>9</b>  |
| 4.1      | Spring Boot . . . . .                                   | 9         |
| 4.2      | Spring Data JPA . . . . .                               | 10        |
| 4.3      | Lombok . . . . .  | 11        |
| 4.4      | Spring Security . . . . .                               | 12        |
| 4.5      | Advantages . . . . .                                    | 12        |
| <b>5</b> | <b>Structure of the Backend</b>                         | <b>12</b> |
| 5.1      | Controller Layer . . . . .                              | 12        |
| 5.2      | Service Layer . . . . .                                 | 13        |
| 5.3      | Repository Layer . . . . .                              | 13        |
| 5.4      | Persistence Layer (Entity Classes) . . . . .            | 14        |
| 5.5      | Applied Design Principles (DTOs) . . . . .              | 14        |
| <b>6</b> | <b>Area Borders</b>                                     | <b>16</b> |
| 6.1      | Purpose of Area Borders in the App . . . . .            | 16        |
| 6.2      | Overview of the Convex Hull Algorithm . . . . .         | 16        |
| 6.3      | Use Cases of the Convex Hull in Industry . . . . .      | 17        |
| 6.4      | Alternate Methods for Area Border Calculation . . . . . | 17        |
| 6.5      | Rationale for Choosing the Convex Hull Method . . . . . | 17        |
| 6.6      | Integration of the Algorithm into the Backend . . . . . | 17        |
| 6.7      | Challenges and Adjustments . . . . .                    | 17        |

|           |  |           |
|-----------|--|-----------|
| <b>7</b>  | <b>Defining usability</b>  | <b>17</b> |
| 7.1       | Why it is important . . . . .                                      | 17        |
| 7.2       | Fundamental concepts of usability . . . . .                        | 17        |
| 7.3       | Challenges in designing for a broad user spectrum . . . . .        | 17        |
| <b>8</b>  | <b>Usability in context of maps</b>                                | <b>18</b> |
| 8.1       | Basic Analysis of the Google Maps interface . . . . .              | 18        |
| 8.2       | Identifying Flaws in Googles Design . . . . .                      | 18        |
| 8.3       | How could specific user groups struggle with this design . . . . . | 18        |
| <b>9</b>  | <b>Adaptive algorithms and real-time data integration</b>          | <b>20</b> |
| 9.1       | Theoretical Framework . . . . .                                    | 20        |
| 9.1.1     | Traditional Methods for Address Database Management . . . . .      | 20        |
| 9.1.2     | Adaptive Algorithms: Concepts and Applications . . . . .           | 20        |
| 9.1.3     | Real-Time Data Integration Frameworks . . . . .                    | 20        |
| 9.2       | Technical Framework . . . . .                                      | 20        |
| 9.2.1     | Data Sources . . . . .   | 20        |
| 9.2.2     | Adaptive Algorithms . . . . .                                      | 20        |
| 9.2.3     | Evaluation Metrics . . . . .                                       | 20        |
| <b>10</b> | <b>Traditional Methods for Address Database Management</b>         | <b>20</b> |
| <b>11</b> | <b>Adaptive Algorithms: Concepts and Applications</b>              | <b>20</b> |
| <b>12</b> | <b>Real-Time Data Integration Frameworks</b>                       | <b>20</b> |
| <b>13</b> | <b>Implementation of the Backend</b>                               | <b>20</b> |
| 13.1      | Config of Spring Boot (application.properties) . . . . .           | 21        |
| 13.2      | Entity Classes (Structure/Purpose) . . . . .                       | 21        |
| 13.3      | JPA-Repositories (DB Access and CRUD Operations) . . . . .         | 21        |
| 13.4      | Service Classes . . . . .  | 21        |
| 13.5      | Rest Controller (API Endpoints and their Functions) . . . . .      | 21        |
| <b>14</b> | <b>GraphHopper Setup</b>   | <b>21</b> |
| 14.1      | Why use GraphHopper? . . . . .                                     | 21        |
| 14.2      | Configuration . . . . .  | 21        |
| 14.3      | Local hosting . . . . .  | 21        |
| <b>15</b> | <b>Working out the Wireframes</b>                                  | <b>21</b> |
| 15.1      | Map View . . . . .   | 21        |
| 15.2      | List View . . . . .  | 21        |
| 15.3      | Possible improvements for future versions . . . . .                | 21        |
| <b>16</b> | <b>Functional implementation behind the application</b>            | <b>22</b> |
| 16.1      | Address-Provider . . . . .   | 22        |
| 16.2      | HTTP-Requests . . . . .  | 22        |
| 16.3      | Implementation of the Flutter Map Component . . . . .              | 22        |
| <b>17</b> | <b>The app in use</b>  | <b>23</b> |
| 17.1      | Introducing new users . . . . .                                    | 23        |
| 17.2      | The app in operation . . . . .                                     | 23        |
| 17.3      | User Feedback . . . . .  | 23        |
| <b>18</b> | <b>Final Thoughts</b>  | <b>24</b> |
| 18.1      | Leon Edlinger . . . . .  | 24        |
| 18.2      | Paul Gigler . . . . .  | 24        |
| 18.3      | Andreas Weissl . . . . .   | 24        |
| <b>19</b> | <b>Meetings</b>  | <b>25</b> |

|                                 |           |
|---------------------------------|-----------|
| <b>20 Working Hours</b>         | <b>26</b> |
| <b>21 Source code directory</b> | <b>27</b> |
| <b>22 List of figures</b>       | <b>28</b> |
| <b>23 List of tables</b>        | <b>29</b> |
| <b>24 Bibliography</b>          | <b>30</b> |
| <b>25 Abbreviation</b>          | <b>31</b> |



# 1 Introduction

TODO: Is halt die frage ob ma den anfang einfach so schreiben, war ja eigentlich net ganz so xD

Mobile apps are utilized for virtually all aspects of daily life in the modern world. So after we noticed that there is no application that allows the efficient planning of campaigns like the "Sternsinger-Aktion" we asked ourselves why, and furthermore, how hard it is to create an App with intuitive usability with the main purpose of simplifying the process of managing such a campaign and gaining a general overview of the progress made by the groups.

The app needs to comply with specific criteria we defined in cooperation with Prof. DI Robert Müllerferli. He is the main organizer of the campaign in the parish of Lieboch and helped us to work out the key aspects our project should implement. In the finished product, every user should be able to scan a QR-Code, through which the area of this group gets assigned to the device. These areas must be dynamically adjustable, so an admin can coordinate the workload of each area more efficiently. The areas also need to be clearly visible by an outline which gets drawn through "Border" addresses. These border addresses get calculated by an algorithm implemented by us. It should be visible at a glance if there is an "specification", which can be assigned by admins, set for an address. This should be realized through the use of different icons instead of the default icon. Apart from the app itself, we also implemented a web-portal through which administrators can manage and supervise the campaign.

TODO: vielleicht noch was rein bezüglich der borders und dann unten nurmehr drauf referenzieren?

The research part of this thesis will be dedicated to how components should act and look, so that new users can use this tool without requiring a long "onboarding" phase. It should feel familiar to interact with elements and the borders of what users can and can not do need to be clearly defined. Because our application also needs a reliable data source to guarantee the consistency and accuracy of marked addresses, we researched ways to keep our database up-to-date, without the need of much manual intervention. After defining the project requirements, we noticed that we need to calculate which addresses are border addresses. So we decided to take a look into different algorithms for this task and compare them concerning their efficiency, decide on one of them and implement it.

This thesis contains an in-depth description of our thought and development process, as well as any other steps we took to achieve our goal of a functional mobile application that can be used by volunteers in course of the "Sternsinger-Aktion 2025" taking place in the parish of Lieboch.

## 1.1 Team

This thesis was created by three Students attending the BHIF20 at the HTBLA Kaindorf Computer Science Department.

TODO: andis bild anpassen

**Leon Edlinger**



Database, Admin-Panel

**Paul Gigler**



Deployment, Mobile App

**Andreas Weissl**



Backend

## 2 Technologies

Development would not have been possible without making use of many tools, frameworks and environments. In this chapter each tool used in the creation of our software will be described briefly.

### 2.1 LaTeX

Hier kommt eine Beschreibung zu Latex hin

### 2.2 Frontend

#### 2.2.1 Dart

Dart is a programming language initially designed for web development, with the goal, of replacing JavaScript, in mind. Today it gets used in a variety of software products, mainly because of the flutter framework. It can be compiled for many platforms and architectures (ARM, x64, RISC-V, JavaScript or WebAssembly) and is loved for its combination of High-Level Features, with practical language features like Garbage collection and optional Type annotation. It was developed by Google and is now an open-source project.

[]



#### 2.2.2 Flutter

Flutter is an Open-Source software development framework. It allows programmers to compile their application for different platforms including Web, macOS, IOS as well as Windows and any type of Linux-based systems, all from one code-base, written in Dart. This allows for more efficient and faster cross-platform development. Another benefit of Google's toolkit are the highly customizable predefined UI components. Developers can mix and match these components however needed which makes them an applicable choice.

We chose flutter mainly for these reasons, but also because of our previous experience with Java to which Dart is quite similar. Through it, we were able to get started quickly, learn what we need along the way. Having a design through the components was also very helpful and saved us some time.

[25] [Dag19]



## 2.3 Backend

### 2.3.1 Java Spring

Lorem ipsum dolor sit amet, consetetur sadipscing elitr, sed diam nonumy eirmod tempor invidunt ut labore et dolore magna aliquyam erat, sed diam voluptua. At vero eos et accusam et justo duo dolores et ea rebum. Stet clita kasd gubergren, no sea takimata sanctus est Lorem ipsum dolor sit amet. Lorem ipsum dolor sit amet, consetetur sadipscing elitr, sed diam nonumy eirmod tempor invidunt ut labore et dolore magna aliquyam erat, sed diam voluptua. At vero eos et accusam et justo duo dolores et ea rebum. Stet clita kasd gubergren, no sea takimata sanctus est Lorem ipsum dolor sit amet. Lorem ipsum dolor sit amet, consetetur sadipscing elitr, sed diam nonumy eirmod tempor invidunt ut labore et dolore magna aliquyam erat, sed diam voluptua. At vero eos et accusam et justo duo dolores et ea rebum. Stet clita kasd gubergren, no sea takimata sanctus est Lorem ipsum dolor sit amet.

Duis autem vel eum iriure dolor in hendrerit in vulputate velit esse molestie consequat, vel illum dolore eu feugiat nulla facilisis at vero eros et accumsan et iusto odio dignissim qui blandit praesent luptatum zzril delenit augue dui dolore te feugait nulla facilisi. Lorem ipsum dolor sit amet,

### 2.3.2 PostgreSQL

Lorem ipsum dolor sit amet, consetetur sadipscing elitr, sed diam nonumy eirmod tempor invidunt ut labore et dolore magna aliquyam erat, sed diam voluptua. At vero eos et accusam et justo duo dolores et ea rebum. Stet clita kasd gubergren, no sea takimata sanctus est Lorem ipsum dolor sit amet. Lorem ipsum dolor sit amet, consetetur sadipscing elitr, sed diam nonumy eirmod tempor invidunt ut labore et dolore magna aliquyam erat, sed diam voluptua. At vero eos et accusam et justo duo dolores et ea rebum. Stet clita kasd gubergren, no sea takimata sanctus est Lorem ipsum dolor sit amet. Lorem ipsum dolor sit amet, consetetur sadipscing elitr, sed diam nonumy eirmod tempor invidunt ut labore et dolore magna aliquyam erat, sed diam voluptua. At vero eos et accusam et justo duo dolores et ea rebum. Stet clita kasd gubergren, no sea takimata sanctus est Lorem ipsum dolor sit amet.

Duis autem vel eum iriure dolor in hendrerit in vulputate velit esse molestie consequat, vel illum dolore eu feugiat nulla facilisis at vero eros et accumsan et iusto odio dignissim qui blandit praesent luptatum zzril delenit augue dui dolore te feugait nulla facilisi. Lorem ipsum dolor sit amet,

## 2.4 Version Control

### 2.4.1 Git

Lorem ipsum dolor sit amet, consetetur sadipscing elitr, sed diam nonumy eirmod tempor invidunt ut labore et dolore magna aliquyam erat, sed diam voluptua. At vero eos et accusam et justo duo dolores et ea rebum. Stet clita kasd gubergren, no sea takimata sanctus est Lorem ipsum dolor sit amet. Lorem ipsum dolor sit amet, consetetur sadipscing elitr, sed diam nonumy eirmod tempor invidunt ut labore et dolore magna aliquyam erat, sed diam voluptua. At vero eos et accusam et justo duo dolores et ea rebum. Stet clita kasd gubergren, no sea takimata sanctus est Lorem ipsum dolor sit amet. Lorem ipsum dolor sit amet, consetetur sadipscing elitr, sed diam nonumy eirmod tempor invidunt ut labore et dolore magna aliquyam erat, sed diam voluptua. At vero eos et accusam et justo duo dolores et ea rebum. Stet clita kasd gubergren, no sea takimata sanctus est Lorem ipsum dolor sit amet.

Duis autem vel eum iriure dolor in hendrerit in vulputate velit esse molestie consequat, vel illum dolore eu feugiat nulla facilisis at vero eros et accumsan et iusto odio dignissim qui blandit praesent luptatum zzril delenit augue dui dolore te feugait nulla facilisi. Lorem ipsum dolor sit amet,

### 2.4.2 GitHub

Lorem ipsum dolor sit amet, consetetur sadipscing elitr, sed diam nonumy eirmod tempor invidunt ut labore et dolore magna aliquyam erat, sed diam voluptua. At vero eos et accusam et justo duo dolores et ea rebum. Stet clita kasd gubergren, no sea takimata sanctus est Lorem ipsum dolor sit amet. Lorem ipsum dolor sit amet, consetetur sadipscing elitr, sed diam nonumy eirmod tempor invidunt ut labore et dolore magna aliquyam erat, sed diam voluptua. At vero eos et accusam et justo duo dolores et ea rebum. Stet clita kasd gubergren, no sea takimata sanctus est Lorem ipsum dolor sit amet. Lorem ipsum dolor sit amet, consetetur sadipscing elitr, sed diam nonumy eirmod tempor invidunt ut labore et dolore magna aliquyam erat, sed diam voluptua. At vero eos et accusam et justo duo dolores et ea rebum. Stet clita kasd gubergren, no sea takimata sanctus est Lorem ipsum dolor sit amet.

Duis autem vel eum iriure dolor in hendrerit in vulputate velit esse molestie consequat, vel illum dolore eu feugiat nulla facilisis at vero eros et accumsan et iusto odio dignissim qui blandit praesent luptatum zzril delenit augue dui dolore te feugait nulla facilisi. Lorem ipsum dolor sit amet,

## 2.5 Map Data

### 2.5.1 OpenStreetMap

Lorem ipsum dolor sit amet, consetetur sadipscing elitr, sed diam nonumy eirmod tempor invidunt ut labore et dolore magna aliquyam erat, sed diam voluptua. At vero eos et accusam et justo duo dolores et ea rebum. Stet clita kasd gubergren, no sea takimata sanctus est Lorem ipsum dolor sit amet. Lorem ipsum dolor sit amet, consetetur sadipscing elitr, sed diam nonumy eirmod tempor invidunt ut labore et dolore magna aliquyam erat, sed diam voluptua. At vero eos et accusam et justo duo dolores et ea rebum. Stet clita kasd gubergren, no sea takimata sanctus est Lorem ipsum dolor sit amet. Lorem ipsum dolor sit amet, consetetur sadipscing elitr, sed diam nonumy eirmod tempor invidunt ut labore et dolore magna aliquyam erat, sed diam voluptua. At vero eos et accusam et justo duo dolores et ea rebum. Stet clita kasd gubergren, no sea takimata sanctus est Lorem ipsum dolor sit amet.

Duis autem vel eum iriure dolor in hendrerit in vulputate velit esse molestie consequat, vel illum dolore eu feugiat nulla facilisis at vero eros et accumsan et iusto odio dignissim qui blandit praesent luptatum zzril delenit augue dui dolore te feugait nulla facilisi. Lorem ipsum dolor sit amet,

### 2.5.2 Graphhopper

Lorem ipsum dolor sit amet, consetetur sadipscing elitr, sed diam nonumy eirmod tempor invidunt ut labore et dolore magna aliquyam erat, sed diam voluptua. At vero eos et accusam et justo duo dolores et ea rebum. Stet clita kasd gubergren, no sea takimata sanctus est Lorem ipsum dolor sit amet. Lorem ipsum dolor sit amet, consetetur sadipscing elitr, sed diam nonumy eirmod tempor invidunt ut labore et dolore magna aliquyam erat, sed diam voluptua. At vero eos et accusam et justo duo dolores et ea rebum. Stet clita kasd gubergren, no sea takimata sanctus est Lorem ipsum dolor sit amet. Lorem ipsum dolor sit amet, consetetur sadipscing elitr, sed diam nonumy eirmod tempor invidunt ut labore et dolore magna aliquyam erat, sed diam voluptua. At vero eos et accusam et justo duo dolores et ea rebum. Stet clita kasd gubergren, no sea takimata sanctus est Lorem ipsum dolor sit amet.

Duis autem vel eum iriure dolor in hendrerit in vulputate velit esse molestie consequat, vel illum dolore eu feugiat nulla facilisis at vero eros et accumsan et iusto odio dignissim qui blandit praesent luptatum zzril delenit augue dui dolore te feugait nulla facilisi. Lorem ipsum dolor sit amet,

## 2.6 Development Tools

### 2.6.1 VS Code

Lorem ipsum dolor sit amet, consetetur sadipscing elitr, sed diam nonumy eirmod tempor invidunt ut labore et dolore magna aliquyam erat, sed diam voluptua. At vero eos et accusam et justo duo dolores et ea rebum. Stet clita kasd gubergren, no sea takimata sanctus est Lorem ipsum dolor sit amet.

### 2.6.2 IntelliJ

Lorem ipsum dolor sit amet, consetetur sadipscing elitr, sed diam nonumy eirmod tempor invidunt ut labore et dolore magna aliquyam erat, sed diam voluptua. At vero eos et accusam et justo duo dolores et ea rebum. Stet clita kasd gubergren, no sea takimata sanctus est Lorem ipsum dolor sit amet.

### 2.6.3 Android Studio

Lorem ipsum dolor sit amet, consetetur sadipscing elitr, sed diam nonumy eirmod tempor invidunt ut labore et dolore magna aliquyam erat, sed diam voluptua. At vero eos et accusam et justo duo dolores et ea rebum. Stet clita kasd gubergren, no sea takimata sanctus est Lorem ipsum dolor sit amet.

### 2.6.4 Postman

Lorem ipsum dolor sit amet, consetetur sadipscing elitr, sed diam nonumy eirmod tempor invidunt ut labore et dolore magna aliquyam erat, sed diam voluptua. At vero eos et accusam et justo duo dolores et ea rebum. Stet clita kasd gubergren, no sea takimata sanctus est Lorem ipsum dolor sit amet.

### 2.6.5 Figma

Lorem ipsum dolor sit amet, consetetur sadipscing elitr, sed diam nonumy eirmod tempor invidunt ut labore et dolore magna aliquyam erat, sed diam voluptua. At vero eos et accusam et justo duo dolores et ea rebum. Stet clita kasd gubergren, no sea takimata sanctus est Lorem ipsum dolor sit amet.



## 2.7 Deployment

### 2.7.1 Docker

### 2.7.2 Uberspace

### 2.7.3 Webmin

## 3 Research Questions

### 3.1 Leon Edlinger

### 3.2 Paul Gigler

### 3.3 Andreas Weissl

## 4 Spring Framework

This chapter concentrates on exploring the Spring ecosystem and covers core components like Spring Framework, Spring Boot and Spring Data JPA. It highlights the advantages of this ecosystem in simplifying Java development and improving the efficiency.

### 4.1 Spring Boot

Spring Boot is a tool which makes developing web applications and microservices with the Java Spring Framework faster and easier. As powerful as the Spring Framework on its own is, it still requires much time and knowledge to configure, set-up and deploy Spring apps. Spring Boot tries to mitigate this effort with three features

#### **Autoconfigure:**

- Autoconfigure initializes Spring apps with a preset of dependencies so that the developer does not have to configure those manually. Spring Boot comes with this feature to automatically configure the Spring Framework and third-party packages based on your needs for the project. Even though you can override the default configuration after the initialization, the initial setup makes the development process faster and more efficient. Meanwhile the autoconfiguration also reduces the possibility of many human errors which can occur during the configuration of an Java application.

#### **Opinionated Approach:**

- Spring Boot uses an opinionated approach while adding and configuring the starter dependencies which is based on the needs of the project. Rather than requiring you to make all the decisions yourself and setup everything manually, Spring Boot uses its own common sense to choose which packages to install and which default values to use. During the initialization, you can define the needs and requirements of your project. Throughout this process you can choose from a huge collection of starter dependencies which are called "Spring Starters" that cover every day use cases. To give an example, the "Spring Web" dependency

simplifies building Spring-based web apps which require minimal configuration work by adding all the other necessary dependencies that you may need for creating such an app. "Spring Security" is another popular starter dependency which automatically adds authentication and access-control features to an application. Spring Boot on its own includes over 50 Spring Starters. However there are many more third-party starters that are also available.

### **Stand-Alone Application:**

- Spring Boot also helps developers create apps that just run. What that means is that you can create stand-alone applications that run on their own without needing any external web servers. This can be done by including(/embedding) a web server such as Tomcat into your app during the initialization process. As a consequence of this you can start your app on any platform by using the command to run the app.

### **Setting up a Spring Boot app:**

You can easily setup a Spring Boot project using the **Spring Initializr**. If you want to create your own Spring Boot-based project, you can just visit the **Spring Initializr**, fill in your project details and download a bundled up project as a .zip file. During the initialization process you have to choose a couple of factors that impact the structure of the project such as the programming language, the Spring Boot version and of course any other dependency you may need to make the development easier and more efficient. Depending on the IDE (vergiß net des zu includen am ende) you use to develop the app, you maybe able to create a Spring Boot project in the IDE itself. Creating a new Spring Boot project in the IDE gives you the same options to choose to make your life easier while developing the app. However, not all IDEs support creating such a project on their own, so you may need to install a addon to create a Spring Boot project.

### **Difference between Spring Boot and Spring Framework:**

The biggest advantages of using Spring Boot and not Spring alone are the easier use and faster development. Theoretically, this advantage of Spring Boot comes at the cost of the greater flexibility you would get from working directly wit Spring Framework. However, in practice, using Spring Boot is worth the trade because you are still able to use Spring Framework's annotation system to inject extra dependencies more easily into you app. Furthermore you still get access to all of Spring Framework's features which include easy event handling and built-in security.

## **4.2 Spring Data JPA**

Spring Data JPA stands for Java Persistence API and provides a specification for persisting, reading and managing data from the object in your program, which are called entities, to your tables in the database. JPA specifies a set of rules for developing interfaces that follow specific standards. As a result, JPA is just some guidelines to implement ORM. ORM is the process of persisting an object in java directly into a database table.

The goal of Spring Data JPA is to create classes called "Repositories" which significantly reduce the amount of unnecessary code to access and manipulate data from the database of your project.

### **Entities:**

As already mentioned, the object from which Spring Data JPA manages the data are called entities. Every table of your database is an entity with each attribute being a column in the respective table. You can use

the `@Entity` annotation in your code to specify that said class is an entity and needs to be in the database. However, this annotation is not the only one which is supported by JPA. Using annotations such as `@Id` or `@GeneratedValue`, you can define different features of your entity and therefore your table in the database. Those annotations are a way to make the development of the project much faster and even more efficient.

#### **Data access object layer:**

Although there are many annotations that are usable for your entity, there is one annotation which is a core feature in JPA. The `@Repository` annotation is a marker for a class that fulfills the role of a repository which is also known as a Data Access Object. However, something else needs to be done when using the `@Repository` annotation. If you use this annotation, you also need to extend your repository class with the `JpaRepository`-class which implements many methods to manage, manipulate and sort or filter all the data in any Table of the Database. You can too make custom queries in your repository class if the operation you need is not available by standard.

#### **Service Layer:**

Classes that use the `@Service` annotation are used with classes that provide some data manipulation methods such as a repository-class. By implementing such a class, the project structure is better understandable and more clear to other developers which may work on this project later on.

#### **Controller Layer:**

This Layer provides the applications with the routes with which the data can get manipulated through a GUI. With the `@RestController` annotation, you can declare a class as an actual controller. The controller uses the service classes from the service layer to get the data or manipulate it in any way. It also specifies the routes which you can then access in any form of user interface so that the user can actually use or see the data.

#### **Mappings:**

There are some annotations which define the routes with all its features and where you can access the route. The `@GetMapping` gives the user data in any form. This can be all the data from a table or a specific entry in a table based on any filter. The `@PostMapping` is used if a user would want to create a new entry in a specific table. For example if you have a management program in your company, you may want to add an employee and this annotation is used to create the route which can then be used by the manager to add a new employee to the database. If, for example, the address or surname of this employee would change, you would need the `@PutMapping` to update the data stored for this employee in the database. However, if this said employee would resign from your company, then you would need the `@DeleteMapping` annotation for the manager to be able to clear this employee out of the company's database. Now you can access all those routes through your graphical interface to show the user the data they can and need to access, manage or even delete.

## **4.3 Lombok**

**TODO: ich würde gern mehr über Lombok schreiben weiß aber net genau was noch, bitte vorschläge**

In the modern days of Java development, one big challenge developers face is writing boilerplate code which are code segments that repeat itself over and over again and get used often in a project. This is especially the case in frameworks like Spring Boot where we use classes like the service layer that involve a significant amount of repetitive code. "Project Lombok" is a Java library that has the aim to reduce this boilerplate code

by automatically generating the code for commonly used patterns. By integrating Lombok in your Spring Boot project, you can not only simplify your code but make it easier to read maintain and write. Lombok works great with the whole Spring framework. If you would want to use a project with Spring Data JPA, you would not get that far without using any annotations provided by Project Lombok. To flag an entity class for Spring Data JPA, you need to use the `@Entity` annotation. This annotation comes from the Lombok library and adds a couple of features to this class so that JPA recognizes it as an entity for the database.

## 4.4 Spring Security

this is where the Spring Security part is but i have to do it first so pls this part has to chill now

## 4.5 Advantages

Now in retrospect, what are the advantages by/with using the Spring Framework and why did we choose it for our backend. **Reduced Boilerplate Code:** A huge factor of the Spring framework is its ability to reduce repetitive code segments. Mainly through the Lombok library, the Spring framework gives the developer many ways to exchange repetitive code with annotations. **Enhanced Testability:** With Spring's huge library of dependencies you can not only get dependencies which make the coding easier but the testing too. Some dependencies gave us mock data to test the backend endpoints easier. **Flexibility:** The same thing that helped us testing, gave us and other projects the flexibility with which you can for example expand or change certain things in your project. This was extremely helpful for us because a certain requirement changed while we were developing the backend. **Consistency:** Spring provides consistent programming and configurations models across many different types of applications. Whether you would want to develop a web application or a microservice, Spring offers a unified approach which improves developer productivity. **Improved Productivity:** Tools like Spring Boot, which are part of the Spring ecosystem, significantly enhance developer productivity by providing better approaches to different problems and embedded servers.

# 5 Structure of the Backend

A well-structured backend is essential for building a scalable and maintainable application. This chapter explores the different layer of our backend. Each layer has its own purpose in handling client requests, processing logic in the code or managing database operations. Furthermore, this chapter provides an overview of the applied design principles we used in our backend.

## 5.1 Controller Layer

The controller layer of a Spring Boot application is a significant layer that takes care of incoming HTTP requests and decides the appropriate response. It serves as the interface between the client and the backend which receives requests, hands over the tasks to the service layer and provides the responses accordingly. It ensures that the data which is used by the logic in the application is properly and effectively processed.

In a standard configuration, controllers handle a collection of HTTP methods. Amongst those HTTP methods

are GET, POST, PUT and DELETE. Each methods has a certain function or action that are then performed by the application. Furthermore, every type of method corresponds to different operations on the data, such as retrieving, creating, updating or deleting information. Each controller belongs to a unique endpoint which serves as the interface for interacting with the application. The controller then uses service methods to execute the logic and return and appropriate response.

To ensure effective management of routing, Spring Boot uses annotations like `@GetMapping`, `@PostMapping`, `@PutMapping` and `@DeleteMapping`. These annotations identify the mapping between some of the HTTP methods and their respective handler methods in the controller. For example, the `@GetMapping` annotation is used for reading data, whereas the `@PostMapping` is applied for adding new data. The `@PutMapping` is utilized for updating existing data and the `@DeleteMapping` for deleting data.

One of the characteristics of the controller layer is the way it communicates with DTOs and entity classes. While the controller gets HTTP requests, it typically utilizes DTOs to enable data transfer between the client and the backend in a secure and effective manner.

## 5.2 Service Layer

The service layer plays a significant role in the backend organization to process the logic and serve as a buffer layer between the repository and controller layers. It makes the application modular, maintainable and scalable since it decouples request handling and data access. This separation is necessary to provide flexibility in changes and additions to the application without impacting other parts of the project.

One of the primary advantages of having a dedicated service layer is that it can be reused. Rather than duplicating the logic all over the system, controllers and other code snippets can use service methods when they need them. Not only does this save code duplication, but it also simplifies future changes, since logic changes can be implemented in a single location without having an impact on the application overall.

Another significant aspect of this layer is transaction management. When an operation has more than one step and consists of a sequence of action, a guarantee that either all or none of those steps are executed is an absolute necessity. By defining such transactional boundaries at the service level, the application ensures data consistency and prohibits incomplete operations from triggering undesired actions.

Wrapping complex logic within the service layer keeps the backend organized and clean. Rather than adding several conditions and operations directly into controllers or repositories, the service layer offers an organized area for processing the data.

## 5.3 Repository Layer

The repository layer is in charge of managing interactions with the database by exposing efficient methods for storing, reading, updating and deleting data. By using this layer, the backend is kept modular which results in the application being more maintainable and scalable.

Spring Data JPA comes with numerous in-built methods supporting most of the common database operations. By utilizing the repository layer, operations like saving new data, getting all existing data sets, updating data and deleting data are automatically available. This cuts down a lot of unnecessary code required for database

operations. Furthermore, it also accelerates the development process by providing many of methods. Although built-in repository methods cover most scenarios, there are time when more complicated queries are required. To handle such cases, Spring Data JPA supports defining custom queries through annotations. This allows developers to get certain data in an efficient way without performing unnecessary database operations.

### 5.4 Persistence Layer (Entity Classes)

The Spring Boot application's persistence layer handles database communication, entity classes and how different entities are related along with ensuring data consistency. With JPA in Spring Boot, developers can create a well-structured and optimized data model which enhances the performance and scalability of the application. Entity classes are used to represent database tables and need to be defined with an annotation to be scanned by Spring Boot JPA. If the table name is different from the class name, it can be annotated explicitly. In addition, unique identifiers need to be defined to ensure that every entity is unique.

Cascading operations automatically persistence and deletion but must be dealt with cautiously in order to not lose data. Validation maintains the integrity of data by placing constraints like mandatory fields and length limitations.

Auditing enables tracking when and by whom entities are modified which provides more accountability. Restricting field values to predefined choices guarantees information consistency and using DTOs optimize queries by retrieving only necessary fields.

### 5.5 Applied Design Principles (DTOs)

During the development of a Spring Boot application, having an efficient data communication between different layers is crucial. And exactly this is where DTOs are needed.

DTOs are objects that carry data between layers in an application. They are used to encapsulate and transport data mostly between a server and a client.

#### Why Use DTOs?

DTOs are crucial for a backend architecture due to their abilities to enhance the security, maintainability, as well as the performance of the data. Their ability to hide data is among their major strengths because they support exposing only the necessary information to clients without showing sensitive data.

From a performance-perspective, DTOs maximize network efficiency by only sending the data that is required for the current action performed by the backend. This advantage is particularly valuable in systems where bandwidth and response time are essential.

Lastly, DTOs are adaptable which allows developers to customize responses to specific use cases. They can support data combination from different entities or the exclusion of unnecessary fields which then results in more efficient responses and easier processing.

By utilizing DTOs as they are intended, applications can achieve better modularity, security and overall performance.

#### Example for Using DTOs

A common scenario where DTOs are useful is when managing user information in an application.

Imagine a system that stores user details such as first name, last name, email and password. If the application exposes the user data to external clients, it could lead to security risks, as sensitive information like passwords should never be shared. Instead of exposing the entire user object, a DTO can be used to filter out unnecessary or sensitive data and only transfer the relevant information.

Therefore, when a user requests a list of other users in an application, the system does not need to send private details like passwords. As an alternative, the application can create an DTO that only contains essential information, such as first name, last name and email. This would ensure that the system remains secure while still providing necessary data for the application to function properly.

DTOs also help optimizing performance by limiting the amount of data transferred. In this case, the application would send the passwords between a client and a server every time the backend needs to send data. However, by using DTOs, the application is limited by sending the first name, last name and email but not the password.

### **Best Practices for Using DTOs**

To ensure DTOs are as efficient as possible within a backend application, certain best practices should be followed.

#### **Keeping DTOs Simple:**

- DTOs should only contain the necessary fields required for the specific use case that its needed for. Having too much data makes them harder to maintain and can lead to unnecessary complexity. By keeping DTOs organized, they remain efficient and can be used as they are intended.

#### **Using Validation:**

- Data validation in DTOs is required to maintain data integrity and prevent processing invalid or incomplete data. By applying validation rules, such as not allowing a field to be empty or limiting the length of different fields, errors are caught early. This prevents incorrect data from being passed on to the logic or inserted to the database.

#### **Using Automation Tools:**

- Manually constructing an DTO based off of an entity is known to create errors and to be time consuming. To simplify this, there are tools that can be used to map objects automatically. They reduce the usage of unnecessary code and speed up the development process by getting DTOs properly filled without writing manual code.

#### **Documenting the DTOs:**

- Proper documentation of every DTO created in the application is crucial. Frameworks like Swagger or SpringFox provide the possibility of auto-generated API documentation, which is easily understandable by other developers concerning the structure and expected data of each DTO. This makes collaboration easier and consistent within the project.

While DTOs provide numerous benefits in organizing data transfer between the layers of an application, there are some challenges that come with them. As a project grows in complexity, it may take more effort to keep the

DTO approach organized. It is wise to know the possible disadvantages so that DTOs can be utilized effectively without introducing unnecessary overhead.

### **Maintenance Overhead:**

- As an application evolves, the number of DTOs can grow extensively. Monitoring these DTOs, modifying them as new requirements emerge and maintaining them synchronized with the logic can prove to be an overwhelming task. Without proper structuring and an explicit DTO strategie, their maintenance can introduce excessive complexity.

### **Performance Impact:**

- While DTOs are used to reduce the amount of data transferred over the network, mapping entities to DTOs and vice versa is extra processing. This process will be a bottleneck in performance in high-traffic applications. Using optimized mapping strategies and automated tools for this purpose can help this problem. This still needs to be taken into consideration when implementing DTOs.

### **Consistency:**

- Keeping DTOs and entity models in sync over time is challenging. When there are any changes in the underlying data structure, it is essential that the impacted DTOs are also adjusted accordingly. If these changes are not carefully handled, inconsistencies may arise which leads to potential data mismatches and errors in API responses.

### **Complexity:**

- In use cases involving simple data interactions, DTOs may not be required. Adding DTOs to every operation will probably add a layer of abstraction that will not be as valuable. In this scenario, working with entities directly could be a simpler and cleaner approach.

## **6 Area Borders**

The area borders feature addresses the research question by implementing computational geometry algorithms for precise geographical boundary calculations.

### **6.1 Purpose of Area Borders in the App**

Accurate area borders are essential for defining regions based on user input, supporting the app's mapping functionality.

### **6.2 Overview of the Convex Hull Algorithm**

The convex hull algorithm identifies the smallest convex polygon enclosing a set of points, making it a suitable choice for this project.



### **6.3 Use Cases of the Convex Hull in Industry**

Applications of convex hulls in mapping, computer graphics, and robotics highlight their importance in solving real-world problems.

### **6.4 Alternate Methods for Area Border Calculation**

Alternative methods like Voronoi diagrams and alpha shapes were considered but found less suitable due to complexity or computational demands.

### **6.5 Rationale for Choosing the Convex Hull Method**

The convex hull algorithm offers a balance of simplicity, efficiency, and accuracy, aligning with the project's requirements.

### **6.6 Integration of the Algorithm into the Backend**

The algorithm is implemented in the service layer, ensuring smooth integration with other backend components.

### **6.7 Challenges and Adjustments**

Challenges included handling edge cases like collinear points, which were resolved through specific algorithm adjustments.

## **7 Defining usability**

### **7.1 Why it is important**

### **7.2 Fundamental concepts of usability**

### **7.3 Challenges in designing for a broad user spectrum**

## **8 Usability in context of maps**

### **8.1 Basic Analysis of the Google Maps interface**

### **8.2 Identifying Flaws in Googles Design**

### **8.3 How could specific user groups struggle with this design**



## **9 Adaptive algorithms and real-time data integration**

### **9.1 Theoretical Framework**

#### **9.1.1 Traditional Methods for Address Database Management**

#### **9.1.2 Adaptive Algorithms: Concepts and Applications**

#### **9.1.3 Real-Time Data Integration Frameworks**

### **9.2 Technical Framework**

#### **9.2.1 Data Sources**

##### **9.2.1.1 GPS Data**

##### **9.2.1.2 External APIs**

##### **9.2.1.3 User Inputs**

#### **9.2.2 Adaptive Algorithms**

##### **9.2.2.1 Fuzzy Matching**

##### **9.2.2.2 Machine Learning Model**

##### **9.2.2.3 Rule-Based Filters**

##### **9.2.2.4 Dynamic Duplicate Resolution**

##### **9.2.2.5 Real-Time Address Normalization**

#### **9.2.3 Evaluation Metrics**

##### **9.2.3.1 Accuracy**

##### **9.2.3.2 Latency**

## **10 Traditional Methods for Address Database Management**

## **11 Adaptive Algorithms: Concepts and Applications**

## **12 Real-Time Data Integration Frameworks**

## **13 Implementation of the Backend**

The backend implementation combines theoretical concepts with practical solutions to ensure functionality and scalability.

### **13.1 Config of Spring Boot (application.properties)**

The `application.properties` file configures essential settings, including database connections, logging, and server parameters.

### **13.2 Entity Classes (Structure/Purpose)**

Entity classes define the application's data model, using annotations to map fields to database tables.

### **13.3 JPA-Repositories (DB Access and CRUD Operations)**

Repositories simplify database access by providing methods for CRUD operations and enabling custom queries.

### **13.4 Service Classes**

Service classes encapsulate business logic, coordinating data flow between controllers and repositories.

### **13.5 Rest Controller (API Endpoints and their Functions)**

REST controllers define API endpoints, processing requests and returning responses to ensure seamless interaction with the frontend.

## **14 GraphHopper Setup**

### **14.1 Why use GraphHopper?**

### **14.2 Configuration**

### **14.3 Local hosting**

## **15 Working out the Wireframes**

### **15.1 Map View**

### **15.2 List View**

### **15.3 Possible improvements for future versions**

## **16 Functional implementation behind the application**

### **16.1 Address-Provider**

### **16.2 HTTP-Requests**

### **16.3 Implementation of the Flutter Map Component**

## **17 The app in use**

### **17.1 Introducing new users**

### **17.2 The app in operation**

### **17.3 User Feedback**

## **18 Final Thoughts**

### **18.1 Leon Edlinger**

### **18.2 Paul Gigler**

### **18.3 Andreas Weissl**



## **19 Meetings**

Protokolle der Meetings, vielleicht auch ein zeitplan wann immer und wie lang

## 20 Working Hours

| Arbeitspaket-Nr. | Beschreibung   | Dauer        |
|------------------|--|--------------|
| 1                | Einführung und Einarbeitung                                | 8 h          |
| 2                | Grundkonzept erstellen                                     | 8 h          |
| 3                | Struktur der App festlegen                                 | 6 h          |
| 5                | Wifi-Socket in App implementieren                          | 39 h         |
| 6                | Write-Funktionalität in App implementieren                 | 14 h         |
| 7                | Read-Funktionalität in App implementieren                  | 19 h         |
| 8                | Trim-Funktionalität in App implementieren                  | 10 h         |
| 9                | Konfigurationsmöglichkeiten für Flug in App implementieren | 16 h         |
| 10               | Höhenregelung-Funktionalität in App implementieren         | 14 h         |
| 12               | Graphische Darstellung der Flugdaten                       | 18 h         |
| 14               | App testen und debuggen                                    | 19 h         |
| 26               | Gesamtkonzept testen und debuggen                          | 16 h         |
| <b>Summe</b>     |  | <b>187 h</b> |

Table 1: Arbeitszeitznachweis

## **21 Source code directory**

Source Code directory, kein plan was des is

## **22 List of figures**

## 23 List of tables

|   |                                |    |
|---|--------------------------------|----|
| 1 | Arbeitszeitznachweis . . . . . | 26 |
|---|--------------------------------|----|

## 24 Bibliography

- [] *Flutter for Beginners*. URL: [https://books.google.at/books?hl=de&lr=&id=pF6vDwAAQBAJ&oi=fnd&pg=PP1&dq=benefits+dart+language&ots=dZJWUGVs4x&sig=a196WqhXmQzuy23cmcKpEpIqn\\_k&redir\\_esc=y#v=onepage&q=benefits%20dart%20language&f=false](https://books.google.at/books?hl=de&lr=&id=pF6vDwAAQBAJ&oi=fnd&pg=PP1&dq=benefits+dart+language&ots=dZJWUGVs4x&sig=a196WqhXmQzuy23cmcKpEpIqn_k&redir_esc=y#v=onepage&q=benefits%20dart%20language&f=false).
- [25] *flutter/README.md at master · flutter/flutter*. [Online; accessed 23. Jan. 2025]. Jan. 2025. URL: <https://github.com/flutter/flutter/blob/master/README.md>.
- [Dag19] Lukas Dagne. "Flutter for cross-platform App and SDK development". In: (2019).

## 25 Abbreviation

|                  |   |
|------------------|---|
| ADC              | Analog Digital Converter                    |
| API              | Application Programming Interface           |
| BLE              | Bluetooth Low Energy                        |
| CPU              | Central Processing Unit                     |
| DAC              | Digital Analog Converter                    |
| DAVE             | Digital Application Virtual Engineer        |
| DSP              | Digital Signal Processor                    |
| FPU              | Floating Point Unit                         |
| FPV              | First Person View, First Pilot View         |
| GPIO             | General Purpose Input/Output                |
| GPS              | Global Positioning System                   |
| GUI              | Graphical User Interface                    |
| HDMI             | High Definition Multimedia Interface        |
| I <sup>2</sup> C | Inter-Integrated Circuit                    |
| IDE              | Integrated Development Environment          |
| IP               | Internet Protocol                           |
| RPI              | Raspberry Pi                                |
| SD               | Secure Digital                              |
| SPI              | Serial Peripheral Interface                 |
| USB              | Universal Serial Bus                        |
| TCP              | Transmission Control Protocol               |
| UART             | Universal Asynchronous Receiver Transmitter |
| WLAN             | Wireless Local Area Network                 |
| WPA              | WiFi Protected Access                       |
| XML              | Extensible Markup Language                  |