

**Höhere Technische Bundeslehranstalt Kaindorf an der Sulm**

**Abteilung Informatik**

## **Diplomarbeit**

im Rahmen der Reife- und Diplomprüfung

# **Königskarte**



informatik

Leon Edlinger  
Paul Gigler  
Andreas Weissl

5BHIF  
2024/2025

Betreuer: Prof. DI Johannes Loibner, BSc  
Projektpartner: Prof. DI Robert Müllerferli  
Datum: MISSING DATE

---

All rights reserved. No part of the work may be reproduced in any form (printing, photocopying, microfilm or any other process) without the written permission of all authors or processed, duplicated or distributed using electronic systems. The authors assume no liability for the functions of individual programs or parts thereof. In particular, they assume no liability for any consequential damages resulting from the use.

The reproduction of utility names, trade names, product descriptions, etc. in this work, even without special marking, does not justify the assumption that such names are to be regarded as free within the meaning of trademark and trademark protection legislation and may therefore be used by everyone.

---

## Statutory declaration

I declare under oath that I have written the present diploma thesis independently and without outside help, have not used sources and aids other than those indicated and have identified the passages taken from the sources used literally and in terms of content as such.

---

Ort, Datum

---

Leon Edlinger

---

Ort, Datum

---

Paul Gigler

---

Ort, Datum

---

Andreas Weissl

---

## **Abstract**

The Sternsinger Aktion in Lieboch traditionally used manual, paper-based planning. While functional, it lacked the convenience and adaptability of digital solutions. This thesis aimed to improve the process by digitalizing the planning and execution, making it more efficient and manageable.

Three tools were developed: an Admin Panel for address assignment, a mobile app for participants to view their assigned addresses, and a software component for managing data exchange between the applications and the database. The software adapts to changes, such as last-minute adjustments to group assignments.

This thesis introduces the technologies used and key features of the tools, including adaptive algorithms, area border consideration for group assignments, and a focus on usability. Instructions for using the tools are also provided.

The software was successfully tested with four groups in Lieboch. Overall, the digitalization of the Sternsinger Aktion was successful. The software created in this thesis offers a reliable solution, showcasing the benefits of digital tools in event planning and will be used and developed further.

---

## **Zusammenfassung**

Die Sternsinger-Aktion in Lieboch verwendete traditionell eine manuelle, papierbasierte Planung. Diese war zwar funktional, bot aber nicht den Komfort und die Anpassungsfähigkeit digitaler Lösungen. Ziel dieser Arbeit war es, den Prozess zu verbessern, indem die Planung und Durchführung digitalisiert und damit effizienter und überschaubarer gemacht wird.

Es wurden drei Tools entwickelt: ein Admin-Panel für die Adresszuweisung, eine mobile App, mit der die Teilnehmer ihre zugewiesenen Adressen einsehen können, und eine Softwarekomponente zur Verwaltung des Datenaustauschs zwischen den Anwendungen und der Datenbank. Die Software passt sich an Änderungen an, wie Anpassungen der Gruppenzuweisungen in letzter Minute.

In dieser Arbeit werden die verwendeten Technologien und die wichtigsten Merkmale der Tools vorgestellt, darunter adaptive Algorithmen, die Berücksichtigung von Bereichsgrenzen bei Gruppenzuweisungen und ein Schwerpunkt auf der Benutzerfreundlichkeit. Außerdem werden Anleitungen zur Nutzung der Tools gegeben.

Die Software wurde mit vier Gruppen in Lieboch erfolgreich getestet. Insgesamt war die Digitalisierung der Sternsingeraktion erfolgreich. Die in dieser Arbeit erstellte Software bietet eine verlässliche Lösung, die die Vorteile digitaler Tools in der Veranstaltungsplanung aufzeigt und weiter genutzt und entwickelt werden soll.

---

## Thanks

It would not have been possible to carry out this thesis to this extent without the active support of a number of people. We would therefore like to thank everyone who supported us in the implementation of this thesis.

...

## Table of Contents

<b>1</b>	<b>Introduction</b>	<b>1</b>
1.1	Team . . . . .	3
<b>2</b>	<b>Technologies</b>	<b>4</b>
2.1	Frontend . . . . .	4
2.1.1	Dart . . . . .	4
2.1.2	Flutter . . . . .	4
2.2	Backend . . . . .	6
2.2.1	Java Spring . . . . .	6
2.2.2	PostgreSQL . . . . .	6
2.3	Version Control . . . . .	8
2.3.1	Git . . . . .	8
2.3.2	GitHub . . . . .	8
2.4	Map Data . . . . .	9
2.4.1	OpenStreetMap . . . . .	9
2.4.2	GraphHopper . . . . .	9
2.5	Development Tools . . . . .	11
2.5.1	VS Code . . . . .	11
2.5.2	IntelliJ . . . . .	11
2.5.3	Android Studio . . . . .	11
2.5.4	Postman . . . . .	12
2.6	Deployment . . . . .	13
2.6.1	Docker . . . . .	13
<b>3</b>	<b>Research Questions</b>	<b>14</b>
3.1	Leon Edlinger . . . . .	14
3.2	Paul Gigler . . . . .	14
3.3	Andreas Weissl . . . . .	14
<b>4</b>	<b>Spring Framework</b>	<b>14</b>
4.1	Spring Boot . . . . .	14
4.2	Spring Data JPA . . . . .	16
4.3	Lombok . . . . .	18
4.4	Advantages . . . . .	19
<b>5</b>	<b>Structure of the Backend</b>	<b>20</b>
5.1	Controller Layer . . . . .	20
5.2	Service Layer . . . . .	21
5.3	Repository Layer . . . . .	22
5.4	Persistence Layer (Entity Classes) . . . . .	22
5.5	Applied Design Principles (Data Transfer Objects) . . . . .	23
<b>6</b>	<b>Area Borders</b>	<b>26</b>
6.1	Purpose of Area Borders in the App . . . . .	26
6.1.1	What are Border Addresses? . . . . .	26
6.1.2	Why Do We Use Border Addresses? . . . . .	26

6.2	Overview of the Convex Hull Algorithm . . . . .	27
6.2.1	Why Use the Convex Hull? . . . . .	29
6.2.2	Types of Convex Hull Algorithms . . . . .	29
6.2.3	Key concepts in the Convex Hull Algorithm . . . . .	30
6.3	Use Cases of the Convex Hull in Industry . . . . .	31
6.4	Alternate Methods for Area Border Calculation . . . . .	33
6.5	Rationale for Choosing the Convex Hull Method . . . . .	35
6.6	Integration of the Algorithm into the Backend . . . . .	35
<b>7</b>	<b>Defining usability</b>	<b>36</b>
7.1	Why it is important . . . . .	36
7.2	Components of Usability . . . . .	37
7.3	Fundamental concepts . . . . .	38
7.4	Challenges in designing for a broad user spectrum . . . . .	42
<b>8</b>	<b>Usability in context of maps</b>	<b>43</b>
8.1	Basic Analysis of the Google Maps Interface . . . . .	43
8.2	Identifying Flaws in Google's Design . . . . .	44
8.3	How Could Specific User Groups Struggle with This Design . . . . .	44
<b>9</b>	<b>Adaptive Algorithms and Real-Time Data Integration</b>	<b>46</b>
9.1	Traditional Methods for Address Database Management . . . . .	46
9.1.1	Manual Entry and Batch Updates . . . . .	46
9.1.2	Static Validation Rules . . . . .	47
9.1.3	Third-Party Data Purchasing . . . . .	47
9.2	Adaptive Algorithms . . . . .	47
9.2.1	Fuzzy Matching . . . . .	48
9.2.2	Machine Learning Model . . . . .	48
9.2.3	Rule-Based Filters . . . . .	49
9.3	Real-Time Data Integration Frameworks . . . . .	49
9.3.1	Challenges . . . . .	50
9.3.2	Core Components . . . . .	50
9.3.3	Popular Frameworks . . . . .	50
9.3.4	Evaluation Metrics . . . . .	51
<b>10</b>	<b>Implementation of the Backend</b>	<b>52</b>
10.1	Config of Spring Boot (application.properties) . . . . .	52
10.2	Entity Classes (Structure/Purpose) . . . . .	52
10.3	JPA-Repositories (DB Access and CRUD Operations) . . . . .	52
10.4	Service Classes . . . . .	52
10.5	Rest Controller (API Endpoints and their Functions) . . . . .	52
<b>11</b>	<b>GraphHopper Setup</b>	<b>53</b>
11.1	Why use GraphHopper? . . . . .	53
11.2	Configuration . . . . .	53
11.3	Local hosting . . . . .	53



<b>12 Working out the Wireframes</b>	<b>53</b>
12.1 Map View . . . . .	53
12.2 List View . . . . .	53
12.3 Possible improvements for future versions . . . . .	53
<b>13 Functional implementation behind the application</b>	<b>54</b>
13.1 Address-Provider . . . . .	54
13.2 HTTP-Requests . . . . .	54
13.3 Implementation of the Flutter Map Component . . . . .	54
<b>14 The app in use</b>	<b>55</b>
14.1 Introducing new users . . . . .	55
14.2 The app in operation . . . . .	55
14.3 User Feedback . . . . .	55
<b>15 Implementation Admin Panel</b>	<b>56</b>
15.1 Navigation . . . . .	57
15.2 AddressPage . . . . .	57
15.2.1 Add Address . . . . .	59
15.2.2 Edit Address . . . . .	59
15.2.3 Delete Address . . . . .	60
15.2.4 Validation . . . . .	60
15.2.5 Additional Functionalities . . . . .	62
15.2.6 Edit multiple Addresses . . . . .	63
15.2.7 Edit all Addresses from a Street . . . . .	64
15.2.8 Edit Odd / Even Streets . . . . .	65
15.2.9 Filter . . . . .	65
15.3 ListEditPage . . . . .	66
15.3.1 QR-Code Visualization for Areas . . . . .	67
15.3.2 QR-Code-PDF Download . . . . .	67
15.3.3 Icon for Special Features . . . . .	68
15.4 Components . . . . .	69
15.4.1 AdminMapComponent . . . . .	69
15.4.2 DatabaseViewComponent . . . . .	71
15.4.3 PDFSaver . . . . .	71
15.4.4 AdminAddressProvider . . . . .	72
15.5 Models . . . . .	72
15.5.1 AreaWithBorder . . . . .	73
15.5.2 ScreenItem . . . . .	73
15.6 Widgets . . . . .	73
15.6.1 InputField . . . . .	73
15.6.2 FilterRow . . . . .	74
<b>16 Final Thoughts</b>	<b>75</b>
16.1 Leon Edlinger . . . . .	75
16.2 Paul Gigler . . . . .	75
16.3 Andreas Weissl . . . . .	75
<b>17 Meetings</b>	<b>76</b>

<b>18 Working Hours</b>	<b>77</b>
<b>19 Source code directory</b>	<b>78</b>
<b>20 List of figures</b>	<b>79</b>
<b>21 List of tables</b>	<b>81</b>
<b>22 Bibliography</b>	<b>82</b>
<b>23 Abbreviation</b>	<b>87</b>

# 1 Introduction

Mobile apps are utilized for virtually all aspects of daily life in the modern world. So after we noticed that there is no application that allows the efficient planning of campaigns like the "Sternsinger-Aktion" we asked ourselves why, and furthermore, how hard it is to create an App with intuitive usability with the main purpose of simplifying the process of managing such a campaign and gaining a general overview of the progress made by the groups.

The app needs to comply with specific criteria we defined in cooperation with Prof. DI Robert Müllerferli. He is the main organizer of the campaign in the parish of Lieboch and helped us to work out the key aspects our project should implement. In the finished product, every user should be able to scan a QR-Code, through which the area of this group gets assigned to the device. These areas must be dynamically adjustable, so an admin can coordinate the workload of each area more efficiently. The areas also need to be clearly visible by an outline which gets drawn through "Border" addresses. These border addresses get calculated by an algorithm implemented by us. It should be visible at a glance if there is a "specification", which can be assigned by admins, set for an address. This should be realized through the use of different icons instead of the default icon. Apart from the app itself, we also implemented a web-portal through which administrators can manage and supervise the campaign.

The investigative aspect of this thesis will focus on how components should behave and appear, so that new users can use this tool without requiring a long "onboarding" phase. Interacting with elements should feel familiar, and the limits of what users can and cannot do need to be clearly defined. Because our application also needs a reliable data source to guarantee the consistency and accuracy of marked addresses, we researched ways to keep our database up to date with minimal manual intervention. After defining the project requirements, we noticed the need to determine which addresses qualify as border addresses. In our context, an area consists of multiple addresses, each with a defined location represented by latitude and longitude coordinates. Border addresses are the addresses that form the outer boundary of an area. For example, given five addresses with the following coordinates:

- A (0,0)
- B (2,0)

- C (0,2)
- D (-2,0)
- E (0,-2)

In this case, addresses B, C, D, and E are border addresses because they outline the area, enclosing A at the center. Thus, we explored different algorithms for this task, compared them in terms of efficiency, selected the most suitable one, and implemented it.

This thesis contains an in-depth description of our thought and development process, as well as the steps we took to achieve our goal of a functional mobile application that can be used by volunteers during the "Sternsinger-Aktion 2025," which took place in the parish of Lieboch in January 2025.

**TODO: Wortwiederholung austauschen**

The result of this thesis should be a mobile app that provides users with the addresses that they need to visit on this day. They then should be able to easily mark the houses they already visited. If something unusual happens at this address, the user should be able to take note of this, so the organizers have knowledge of it and can account to it in the following year.

**TODO: Maybe auf verschiedene Parts aufteilen, also das man zuerst sagt Problemstellung, dann Zielsetzung damit die Introduction übersichtlicher ist**

## 1.1 Team

This thesis was created by three Students attending the BHIF20 at the HTBLA Kaindorf Computer Science Department.

TODO: andis bild anpassen

**Leon Edlinger**



Database, Admin-Panel

**Paul Gigler**



Deployment, Mobile App

**Andreas Weissl**



Backend

## 2 Technologies

Development would not have been possible without making use of many tools, frameworks and environments. In this chapter each tool used in the creation of our software will be described briefly.

### 2.1 Frontend

#### 2.1.1 Dart

Dart is a programming language initially designed for web development, with the goal of replacing JavaScript. Today, it is used in a variety of software products, mainly because of the flutter framework. Dart can be compiled for many platforms and architectures, including ARM, x64, RISC-V, JavaScript or WebAssembly and is highly popular for its combination of high-level features, combined with practical language features like garbage collection and optional type annotation. It was developed by Google and is now an open-source project. [Bie19]



Fig. 1: Dart Logo (Source: <https://dart.dev>)

#### 2.1.2 Flutter

Flutter is an open-source software development framework. It allows programmers to compile their applications for different platforms including Web, macOS, iOS as well as Windows and any type of Linux-based systems, all from a single codebase, written in Dart. This allows for more efficient and faster cross-platform development. Another benefit of Google's toolkit are the highly customizable, predefined UI components. Developers can mix and match these components as needed which makes them an applicable choice. [25h][Dag19]

We chose flutter mainly for these reasons, but also because of our previous experience with Java to which Dart is quite similar. Through it, we were able to get started quickly, learn what we need along the way. Having a design through the components was also very helpful and saved us some time.



Fig. 2: Flutter Logo (Source: <https://flutter.dev/>)

## 2.2 Backend

### 2.2.1 Java Spring

Java on its own is an object-oriented programming language which is designed to be platform-independent. It allows programs to run on any device that has a Java Virtual Machine installed. Java is particularly useful for its strong security features and extensive community support.



Fig. 3: Java Logo (Source: <https://logodownload.org/java-logo/>)

Java Spring is an open-source framework and is based on Java. The Java Spring Framework is an in-depth programming and configuration language that simplifies development of Java applications. The most used Spring Framework is Spring Boot. Spring Boot simplifies the application process with not much need for preconfigured logic. Other Spring Frameworks which have a huge impact on Java programming are Spring Security for authentication/authorization and Spring Data for database injection. We chose Java Spring as our backend development tool, because of its simplicity and flexibility. As a framework, Spring allowed us to develop a well scalable and maintainable backend to generate APIs and connect to the database.

### 2.2.2 PostgreSQL

PostgreSQL is an open-source relational database management system. It is known for its reliability and scalability. It complies with SQL standard. Databases, which use PostgreSQL, are designed to handle a huge amount of data efficiently. Those databases support more advanced features such as full-text search and JSON data storage.

One of PostgreSQL's strengths is its flexibility. Developers are able to create custom data types



and functions to customize the database to their specific needs. It also provides security mechanisms which include role-based access control and encryption.

We used PostgreSQL in our project as our database due to its ability to handle complex queries and its scalability which then allowed us to manage and store all the data reliably.

### 2.3 Version Control

#### 2.3.1 Git

Git is a distributed VCS that was developed by Linus Torvalds in 2005. The main benefit of a VCS is to easily keep track of different versions of files. Git is the most widely used option, concerning this area of application. [25u] This is due to the fact it is open-source, therefore free, as well as reliable and easy to learn. It gets used in almost every, but not only, development project, not just for tracking the history of files, but also for developing cooperatively making use of it's branching feature. This allows for development while maintaining a stable version on the main branch. [25i]



Fig. 4: Git Logo (Source: <https://git-scm.com/>)

#### 2.3.2 GitHub

GitHub is a platform maintained by Microsoft. As the Name implies, it is based on Git and provides the opportunity to easily share your Git repositories with other users. It is free to use for non-commercial applications and a very popular option when it comes to developing in a team. [25a] Furthermore, it also implements handy extensions that integrate tightly with Git, for example GitHub-Actions, which is their solution for CI/CD Pipelines. There are many alternatives to GitHub, like, GitLab, which is open-source and can be self-hosted or BitBucket, a solution by Atlassian. [25r]



Fig. 5: GitHub Logo (Source: <https://github.com/>)

## 2.4 Map Data

### 2.4.1 OpenStreetMap

The project OpenStreetMap (OSM) is an open-source initiative that aims to make high quality map data available to everyone for free. It was created in 2004 by Steve Coast. It was later widely adopted, with the main push being the pricing Google introduced to the embedding of Google Maps, so that today it can be found in all kinds of applications. Reaching from simple embedded web-components, all the way into video games like the Microsoft Flight Simulator, which relies on OSM for its building models. The GIS behind OSM gets maintained by volunteers and is feed not only using GPS-Data but also image data and other different formats.

OSM is the backbone of this thesis and without it, it wouldn't have been possible to develop this tool. [25n] [Wik24]



Fig. 6: OSM Logo (Source: <https://wiki.openstreetmap.org/>)

### 2.4.2 GraphHopper

GraphHopper (GH) in its core is an open-source routing engine written in Java. It can be deployed as a web server and is used to calculate the optimal route, distance or time between multiple different points. It supports multiple modes of transportation as well as "snap to road" technology. [25j] GH also provides a ready to go API that you can access for free, but we choose to deploy our own instance since the requests we needed to make exceed the limits of the free version. [24c]



Fig. 7: GraphHopper Logo (Source: <https://brandfetch.com/graphhopper.com>)

## 2.5 Development Tools

### 2.5.1 VS Code

Visual Studio Code (VS Code) is a version of the Code-OSS project with Microsoft-specific customizations, making it a closed-source product licensed by Microsoft. VS Code is highly customizable, with support for community-made plugins and many options for the user to define how things should act and look. [25y] There are many handy features implemented out of the box, such as native VCS support. Since VS Code is an electron based application, it can not only be used on a desktop computer, but also directly in the browser of any device. [25z] [25x]




Fig. 8: VS Code Logo (Source: <https://code.visualstudio.com/brand>)

### 2.5.2 IntelliJ

IntelliJ IDEA is an IDE primarily designed for Java and Kotlin developers, published by JetBrains. In comparison to VS Code, it is more resource-intensive due to included tools like the direct integration of a database connection via the embedded DataGrip version. IntelliJ is the base framework used for other, more specific IDEs by JetBrains, like Android Studio, WebStorm or DataGrip. Its functionality can also be extended through plugins. [25k] [Con25e]



Fig. 9: IntelliJ IDEA Logo (Source: <https://www.jetbrains.com/company/brand/>)

### 2.5.3 Android Studio

Android Studio is based on the IntelliJ framework, but, as the name suggests, with the specification to developing Android apps. Aside from Java and Kotlin based pure Android apps, it can also be used for developing cross-platform applications using the flutter framework. The

IDE introduced by Google also features an Emulator for Pixel devices which simplifies testing. Lastly, it provides an intuitive way to compile the app and flash it to a physical Android device using ADB and USB-debugging.




Fig. 10: Android Studio Logo (Source: <https://img.icons8.com/?size=100&id=040Frkjznvcd&format=png&color=000000>)

### 2.5.4 Postman

Postman is an API platform, primarily used to test APIs. It features collaboration and an automatic code-generation, allowing users to design requests directly in postman and export them into any of the supported languages. We used it to develop and test our API, without a frontend application to minimize potential points of failure.



Fig. 11: Postman Logo (Source: <https://www.postman.com/legal/logo-usage/>)

## 2.6 Deployment

### 2.6.1 Docker

Docker is a tool for containerization and one of the most popular options in this field. Through containerization, it is possible to isolate a process from the host machine, in a virtual environment. Furthermore, docker is portable which makes it a great choice for software projects that many developers with different environments work on. It is used to create a controlled infrastructure which guarantees the correct configuration for the production server. We used Docker to host our PostgreSQL database across multiple different systems throughout the development process.



Fig. 12: Docker Logo (Source: <https://www.docker.com/>)

## 3 Research Questions

### 3.1 Leon Edlinger

### 3.2 Paul Gigler

### 3.3 Andreas Weissl

## 4 Spring Framework

This chapter concentrates on exploring the Spring ecosystem and covers core components like Spring Framework, Spring Boot and Spring Data JPA. It highlights the advantages of this ecosystem in simplifying Java development and improving the efficiency.

### 4.1 Spring Boot

Spring Boot is a tool which makes developing web applications and microservices with the Java Spring Framework faster and easier. As powerful as the Spring Framework on its own is, it still requires much time and knowledge to configure, set-up and deploy Spring apps. Spring Boot tries to mitigate this effort with three features

#### **Autoconfigure:**

- Autoconfigure initializes Spring apps with a preset of dependencies so that the developer does not have to configure those manually. Spring Boot comes with this feature to automatically configure the Spring Framework and third-party packages based on the project requirements.
- Even though the developer can override the default configuration after the initialization, the initial setup makes the development process faster and more efficient.
- Meanwhile the autoconfiguration also reduces the possibility of many human errors which can occur during the configuration of an Java application.

#### **Opinionated Approach:**

- When adding and configuring startup dependencies, Spring Boot takes a subjective approach, customizing them to the requirements of the project. The right packages



and default values are chosen automatically by Spring Boot, eliminating the need for human setup and decision-making for each configuration.

- During initialization, project requirements can be specified, allowing selection from a vast collection of starter dependencies, known as "Spring Starters," which cover most common use cases. For example, the "Spring Web" dependency simplifies the development of Spring-based web applications by including all necessary dependencies with minimal configuration. Likewise, "Spring Security" provides built-in authentication and access control features.
- More than 50 official Spring Starters are offered by Spring Boot, and there are numerous other third-party starters accessible.

### **Stand-Alone Application:**

- With the help of Spring Boot, applications can be developed that function without the need for an external web server. This is accomplished by immediately integrating a web server, such as Tomcat, with the application as it is initializing. As a result, the application can be launched with the appropriate command on any platform.

[25s; lbm24]

### **Setting up a Spring Boot app:**

A Spring Boot project can be initialized quickly using the **Spring Initializr**. For a new Spring Boot-based project, the **Spring Initializr** can be opened, where the project details are filled in and a packaged project is downloaded as a.zip file. While initializing, a number of factors have to be chosen that determine the project structure, such as the programming language, the version of Spring Boot, and any other dependencies required to support development. Depending on the IDE where the development is being performed, a Spring Boot project can be directly developed inside the IDE itself. Even this method supports the same amount of configuration to simplify the process of development. Not all IDEs are capable of creating a Spring Boot project out of the box, and sometimes a separate plugin needs to be installed.[Cod25]




Fig. 13: GUI of the Spring Initializr

[Cod25]

### Difference between Spring Boot and Spring Framework:

Spring Boot's greatest strengths over the standard Spring Framework are its simplicity and quicker development. Theoretically, this is at the expense of the higher degree of flexibility that direct Spring Framework usage would provide. Practically, the compromise is more than worth it, as the Spring Framework's annotation system can still be utilized to inject other dependencies effectively. Besides, all Spring Framework functionalities like easy event handling and native security continue to be accessible. [lbn24]

## 4.2 Spring Data JPA

Spring Data JPA stands for Java Persistence API and provides a specification for persisting, reading and managing data from the object in the program, which are called entities, to project's tables in the database. JPA specifies a set of rules for developing interfaces that follow specific standards. As a result, JPA is just some guidelines to implement ORM. ORM is the process of persisting an object in java directly into a database table.

The goal of Spring Data JPA is to create classes called "Repositories" which significantly reduce the amount of unnecessary code to access and manipulate data from the database of a project.

**Entities:**

As already mentioned, the object from which Spring Data JPA manages the data are called entities. Every table of a database is an entity with each attribute being a column in the respective table. The `@Entity` annotation can be used to define the entity, guaranteeing that the class is understood as a component of the database structure and handled appropriately. However, this annotation is not the only one which is supported by JPA. By using annotations such as `@Id` or `@GeneratedValue`, different custom features of the entity, and therefore the database table, can be defined. Those annotations are a way to make the development of the project much faster and even more efficient. [25p; Tri23; 24a]

**Data access object layer:**

Although there are many annotations that are usable for an entity, there is one annotation which is a core feature in JPA. The `@Repository` annotation is a marker for a class that fulfills the role of a repository which is also known as a Data Access Object. However, something else needs to be done when using the `@Repository` annotation. When this annotation is used, the repository class must extend the `JpaRepository` class, which provides many built-in methods for managing, manipulating, sorting, and filtering data in the respective database table. If a required operation is not available by default, custom queries can also be defined within the repository class. [De 24c]

**Service Layer:**

Classes that use the `@Service` annotation are used with classes that provide some data manipulation methods such as a repository-class. By implementing such a class, the project structure is better understandable and more clear to other developers which may work on this project later on. [Mee24; De 24a]

**Controller Layer:**

This Layer provides the applications with the routes with which the data can get manipulated through a GUI. By using the `@RestController` annotation, an actual controller class can be defined. The controller uses the service classes from the service layer to get the data or manipulate it in any way. It also specifies the routes which the code can then access in any form of user interface so that the user can actually use or see the data. [De 24b]

### Mappings:

There are numerous annotations that define routes along with all their features and how they can be accessed. The `@GetMapping` gives the user data in any form. This can be all the data from a table or a specific entry in a table based on any filter. The `@PostMapping` is used if a user would want to create a new entry in a specific table.

For example, in a company's management system, the `@PostMapping` annotation can be used to build a route for adding a new employee to the database. If the employee's address or surname were to change, the `@PutMapping` annotation would be used to update the stored data for that employee. On the other side, if the employee were to resign, the `@DeleteMapping` annotation would be used to enable the manager to remove the employee from the company's database.

These routes can then be accessed through a GUI, allowing the user to manage, update, or delete data as needed. [Cim23]

## 4.3 Lombok

In the modern days of Java development, one big challenge developers face is writing boilerplate code which are code segments that repeat itself over and over again and get used often in a project. This is especially the case in frameworks like Spring Boot where we use classes like the service layer that involve a significant amount of repetitive code.

"Project Lombok" is a Java library that has the aim to reduce this boilerplate code by automatically generating the code for commonly used patterns. By integrating Lombok in your Spring Boot project, you can not only simplify your code but make it easier to read maintain and write. Lombok works great with the whole Spring framework. If you would want to use a project with Spring Data JPA, you would not get that far without using any annotations provided by Project Lombok. To flag an entity class for Spring Data JPA, you need to use the `@Entity` annotation. This annotation comes from the Lombok library and adds a couple of features to this class so that JPA recognizes it as an entity for the database.

Lombok injects the needed methods directly into the compiled class files when the program is getting build, which reduces the need to manually write common functions like constructors, getter and setters. When an annotation like `@Getter`, `@Setter`, `@AllArgsConstructor` is used, Lombok modifies the code before the compilation is done. This ensures that the

generated methods are available at runtime while keeping the source code clean and minimal. For example, using `@AllArgsConstructor` tells Lombok to generate a constructor with all the variables of a class. Another useful annotation is `@Data`, which combines many methods like the `@Getter` and `@Setter`. Using this annotation further reduces repetitive code.

Since Lombok creates these methods during the compilation process, developers can keep their code clean while still having fully functional classes. [25t; 25l; Men24]

## 4.4 Advantages

The Spring Framework has a range of advantages that make it a popular choice among developers. These benefits shorten the development process and help in designing scalable and maintainable apps.

### Reduced Boilerplate Code:

A huge factor of the Spring framework is its ability to reduce repetitive code segments. Mainly through the Lombok library, the Spring framework gives the developer many ways to exchange repetitive code with annotations.

### Enhanced Testability:

With Spring's huge library of dependencies you can not only get dependencies which make the coding easier but the testing too. Some dependencies gave us mock data to test the backend endpoints easier.

### Flexibility:

The same thing that helped us testing, gave us and other projects the flexibility with which you can for example expand or change certain things in your project. This was extremely helpful for us because a certain requirement changed while we were developing the backend.

### Consistency:

Spring provides consistent programming and configurations models across many different types of applications. Whether you would want to develop a web application or a microservice, Spring offers a unified approach which improves developer productivity.

**Improved Productivity:**

Tools like Spring Boot, which are part of the Spring ecosystem, significantly enhance developer productivity by providing better approaches to different problems and embedded servers. [Ibm24]

## 5 Structure of the Backend

A well-structured backend is essential for building a scalable and maintainable application. This chapter explores the different layers of our backend. Each layer has its own purpose in handling client requests, processing logic in the code or managing database operations. Furthermore, this chapter provides an overview of the applied design principles we used in our backend.




Fig. 14: Layers of Spring Boot

[Pat24]

### 5.1 Controller Layer

The controller layer of a Spring Boot application is a significant layer that takes care of incoming HTTP requests and decides the appropriate response. It serves as the interface between the client and the backend which receives requests, hands over the tasks to the service layer

and provides the responses accordingly. It ensures that the data which is used by the logic in the application is properly and effectively processed.

In a standard configuration, controllers handle a collection of HTTP methods. Amongst those HTTP methods are GET, POST, PUT and DELETE. Each method has a certain function or action that is then performed by the application. Furthermore, every type of method corresponds to different operations on the data, such as retrieving, creating, updating or deleting information. Each controller belongs to a unique endpoint which serves as the interface for interacting with the application. The controller then uses service methods to execute the logic and return an appropriate response.

To ensure effective management of routing, Spring Boot uses annotations like `@GetMapping`, `@PostMapping`, `@PutMapping` and `@DeleteMapping`. These annotations identify the mapping between some of the HTTP methods and their respective handler methods in the controller. For example, the `@GetMapping` annotation is used for reading data, whereas the `@PostMapping` is applied for adding new data. The `@PutMapping` is utilized for updating existing data and the `@DeleteMapping` for deleting data.

One of the characteristics of the controller layer is the way it communicates with DTOs and entity classes. While the controller gets HTTP requests, it typically utilizes DTOs to enable data transfer between the client and the backend in a secure and effective manner.

## 5.2 Service Layer

The service layer plays a significant role in the backend organization to process the logic and serve as a buffer layer between the repository and controller layers. It makes the application modular, maintainable and scalable since it decouples request handling and data access. This separation is necessary to provide flexibility in changes and additions to the application without impacting other parts of the project.

One of the primary advantages of having a dedicated service layer is that it can be reused. Rather than duplicating the logic all over the system, controllers and other code snippets can use service methods when they need them. Not only does this save code duplication, but it also simplifies future changes, since logic changes can be implemented in a single location without having an impact on the application overall.

Another significant aspect of this layer is transaction management. When an operation has more than one step and consists of a sequence of actions, a guarantee that either all or none

of those steps are executed is an absolute necessity. By defining such transactional boundaries at the service level, the application ensures data consistency and prohibits incomplete operations from triggering undesired actions.

Wrapping complex logic within the service layer keeps the backend organized and clean. Rather than adding several conditions and operations directly into controllers or repositories, the service layer offers an organized area for processing the data.

### 5.3 Repository Layer

The repository layer is in charge of managing interactions with the database by exposing efficient methods for storing, reading, updating and deleting data. By using this layer, the backend is kept modular which results in the application being more maintainable and scalable.

Spring Data JPA comes with numerous in-built methods supporting most of the common database operations. By utilizing the repository layer, operations like saving new data, getting all existing data sets, updating data and deleting data are automatically available. This cuts down a lot of unnecessary code required for database operations. Furthermore, it also accelerates the development process by providing many methods.

Although built-in repository methods cover most scenarios, there are times when more complicated queries are required. To handle such cases, Spring Data JPA supports defining custom queries through annotations. This allows developers to get certain data in an efficient way without performing unnecessary database operations.

### 5.4 Persistence Layer (Entity Classes)

The Spring Boot application's persistence layer handles database communication, entity classes and how different entities are related along with ensuring data consistency. With JPA in Spring Boot, developers can create a well-structured and optimized data model which enhances the performance and scalability of the application.

Entity classes are used to represent database tables and need to be defined with an annotation to be scanned by Spring Boot JPA. If the table name is different from the class name, it can be annotated explicitly. In addition, unique identifiers need to be defined to ensure that every entity is unique.

Cascading operations automatically persistence and deletion but must be dealt with cau-



tiously in order not to lose data. Validation maintains the integrity of data by placing constraints like mandatory fields and length limitations.

Auditing enables tracking when and by whom entities are modified which provides more accountability. Restricting field values to predefined choices guarantees information consistency and using DTOs optimize queries by retrieving only necessary fields.

### **5.5 Applied Design Principles (Data Transfer Objects)**

During the development of a Spring Boot application, having an efficient data communication between different layers is crucial. And exactly this is where DTOs are needed.

DTOs are objects that carry data between layers in an application. They are used to encapsulate and transport data mostly between a server and a client.

#### **Why Use DTOs?**

DTOs are crucial for a backend architecture due to their abilities to enhance the security, maintainability, as well as the performance of the data. Their ability to hide data is among their major strengths because they support exposing only the necessary information to clients without showing sensitive data.

From a performance-perspective, DTOs maximize network efficiency by only sending the data that is required for the current action performed by the backend. This advantage is particularly valuable in systems where bandwidth and response time are essential.

Lastly, DTOs are adaptable which allows developers to customize responses to specific use cases. They can support data combination from different entities or the exclusion of unnecessary fields which then results in more efficient responses and easier processing.

By utilizing DTOs as they are intended, applications can achieve better modularity, security and overall performance.

#### **Example for Using DTOs**

A common scenario where DTOs are useful is when managing user information in an application.

Imagine a system that stores user details such as first name, last name, email and password. If the application exposes the user data to external clients, it could lead to security risks, as sensitive information like passwords should never be shared. Instead of exposing the entire

user object, a DTO can be used to filter out unnecessary or sensitive data and only transfer the relevant information.

Therefore, when a user requests a list of other users in an application, the system does not need to send private details like passwords. As an alternative, the application can create a DTO that only contains essential information, such as first name, last name and email. This would ensure that the system remains secure while still providing necessary data for the application to function properly.

DTOs also help optimizing performance by limiting the amount of data transferred. Without DTOs, the application would send the passwords between a client and a server every time the backend needs to send data. However, by using DTOs, the application is limited by sending the first name, last name and email but not the password.

To ensure DTOs are as efficient as possible within a backend application, certain best practices should be followed.

### **Keeping DTOs Simple:**

- DTOs should only contain the necessary fields required for the specific use case that its needed for. Having too much data makes them harder to maintain and can lead to unnecessary complexity. By keeping DTOs organized, they remain efficient and can be used as they are intended.

### **Using Validation:**

- Data validation in DTOs is required to maintain data integrity and prevent processing invalid or incomplete data. By applying validation rules, such as not allowing a field to be empty or limiting the length of different fields, errors are caught early. This prevents incorrect data from being passed on to the logic or inserted to the database.

### **Using Automation Tools:**

- Manually constructing an DTO based off of an entity is known to create errors and to be time consuming. To simplify this, there are tools that can be used to map objects automatically. They reduce the usage of unnecessary code and speed up the development process by getting DTOs properly filled without writing manual code.

### **Documenting the DTOs:**

- Proper documentation of every DTO created in the application is crucial. Frameworks like Swagger or SpringFox provide the possibility of auto-generated API documentation, which is easily understandable by other developers concerning the structure and expected data of each DTO. This makes collaboration easier and consistent within the project.

While DTOs provide numerous benefits in organizing data transfer between the layers of an application, there are some challenges that come with them. As a project grows in complexity, it may take more effort to keep the DTO approach organized. It is wise to know the possible disadvantages so that DTOs can be utilized effectively without introducing unnecessary overhead.

### **Maintenance Overhead:**

- As an application evolves, the number of DTOs can grow extensively. Monitoring these DTOs, modifying them as new requirements emerge and maintaining them synchronized with the logic can prove to be a daunting task. Without proper structuring and an explicit DTO strategy, their maintenance can introduce excessive complexity.

### **Performance Impact:**

- While DTOs are used to reduce the amount of data transferred over the network, mapping entities to DTOs and vice versa is extra processing. This process will be a bottleneck in performance in high-traffic applications. Using optimized mapping strategies and automated tools for this purpose can help this problem. This still needs to be taken into consideration when implementing DTOs.

### **Consistency:**

- Keeping DTOs and entity models in sync over time is challenging. When there are any changes in the underlying data structure, it is essential that the impacted DTOs are also adjusted accordingly. If these changes are not carefully handled, inconsistencies may arise which leads to potential data mismatches and errors in API responses.

### **Complexity:**

- In use cases involving simple data interactions, DTOs may not be required. Adding DTOs to every operation will probably add a layer of abstraction that will not be as valuable. In this scenario, working with entities directly could be a simpler and cleaner approach.

[Lal23]

## 6 Area Borders

This chapter describes the use of a convex hull algorithm to define the boundaries of an area. It is a process of determining the outermost points of an area and joining them to create a border. This chapter also explains the fundamentals of the convex hull algorithm, other possible ways of calculating such a boundary and why we used this method in our project.

### 6.1 Purpose of Area Borders in the App

The convex hull algorithm is used in the app to define certain addresses which form the boundaries of an area. These boundaries are crucial to better organize and manage all areas which are assigned to all groups within the application. Below is a screenshot of the app that shows the highlighted borders of an area to visually demonstrate how these areas are shown within the app.

#### 6.1.1 What are Border Addresses?

Border addresses are certain points that define the outer boundaries of an area. Furthermore, an area is defined by a set of addresses which get added to a certain area prior to the caroler campaign (Königskarten Aktion). Once the area is created, the convex hull algorithm can be applied on the list of addresses to find the border addresses. These border addresses just go around the perimeter of the area. Therefore, the outcome is a precise, convex shape that covers the entire area.

#### 6.1.2 Why Do We Use Border Addresses?

Border addresses are important for a number of reasons. They give the visual definition of each area's boundaries, making it easy to manage and navigate through the different areas for admins and making it easier for each group to see the boundaries of their respective area. The use of the convex hull algorithm ensures that the boundary defined is the smallest convex shape possible that incorporates all the addresses in this area. The importance of the border addresses is outlined in the following points:

**For the Admin:**

1. **Clear Visual Representation:** In the app interface, each area is shown in a different colour and border addresses are highlighted by a line which goes through all the border addresses of an area. This makes it easy for the admin to see where each area is and how big they are.
2. **Efficient Area management:** By visualizing the areas with the border addresses highlighted, the admin can rapidly evaluate the boundaries of each area. Based on the result of each area's boundaries, the admin can remove or add addresses if necessary. The management process is therefore improved by its flexibility.
3. **Better Decision Making:** The admin can make a well-informed decision about adding or removing addresses from an area by visually seeing how big an area is or how many addresses are in an area. Besides other factor, this information guarantees better decision making from the admin on how to distribute the addresses to each area.

**For Each Group:**

1. **Clear Understanding of Area Boundaries:** The border addresses give guides of each group a clear idea of the addresses they are in charge of. Each group can also more easily see the boundaries of their area, which helps to avoid misunderstanding of where each group has to go and where they must not go.
2. **Improved Navigation and Accuracy:** Guides are able to navigate better in their areas when they have a visual representation of their area. By keeping them within their area, this visual aid helps them avoid errors in for example visiting addresses from other areas.
3. **Increased Efficiency:** The guides are able to finish their work more quickly because the boundaries of each area are clearly marked. They can focus on their designated area and plan their routes to be as efficient as possible and to not cross any other areas in the process.

## 6.2 Overview of the Convex Hull Algorithm

The convex hull algorithm is a fundamental concept in computational geometry. On a two-dimensional system, it is used to find the smallest convex polygon that can hold a specific

## 6.2 Overview of the Convex Hull Algorithm

sets of points. Simply put, it determines the outer border or edge that surrounds each of the specified points. The convex hull, which is the outer boundary, is the tightest shape that can enclose every point without any spaces in between.

To better understand the concept, consider a set of points randomly placed on a flat surface. If a rubber band would be stretched around those points, it would form a shape that encloses the outermost points. This resulting shape is the convex hull, which is the smallest convex polygon that fully encloses all points. The image below shows exactly this process, with the points being surrounded by the convex hull. This gives a visual representation of the convex hull algorithm.




Fig. 15: Process of the Convex Hull Algorithm

[Gee24a]

A convex polygon is a shape where all the corners point outward and there are no inward curves or sharp angles. To put it simply, if you draw a straight line between any two points inside the shape, it will always remain inside or on the shape's edge. This indicates that there are never any inward corners on the convex hull. In contrast, a concave polygon has at least one or more inward curves where the interior angle is greater than 180 degrees.

To better visualize the difference, the image below shows that all the angles of the convex polygon have less than 180 degrees, therefore they are "pointy". However, on the concave polygon it is visible that the angles on top has more than 180 degrees, therefore the polygon

has an inwards curve [25g]




Fig. 16: Difference between a convex/concave polygon

[McB25]

### 6.2.1 Why Use the Convex Hull?

The convex hull algorithm is especially helpful for identifying a set of points' boundary and eliminating any extra points that fall inside it. In the case of the addresses of each area, for example, the convex hull algorithm helps in defining the outermost boundaries that enclose these points in the smallest possible area. Whether in pathfinding, geographical mapping or other spatial analysis applications that demand distinct boundary limits, this procedure is crucial.

### 6.2.2 Types of Convex Hull Algorithms

The convex hull can be calculated using a variety of algorithms, with the most popular being **Graham's Scan** and the **Monotone Chain algorithm**. Because of their effectiveness and capacity to manage sizable datasets, these algorithms have been widely adopted.

#### Graham's Scan Algorithm:

- Graham's Scan is a method which was introduced in 1972 to find the convex hull of a set of points. The process starts by sorting the points based on the "polar angle" of each

point relative to the bottom-most point. Simply speaking, the polar angle is the angle between a point and a reference direction which is often the horizontal axis (the x-axis).

- As soon as the points are sorted, the algorithm builds the convex hull by looking at each point in the sorted list. It moves from one point to the next, while going through each point it checks if the previous three points form a right or a left turn. As soon as a right turn is detected, the last point is removed, because it would create an inward curves in the shape, which would then result in a concave hull and not a convex hull. The algorithm continues with this until the hull is fully formed.
- The time it takes to run the Graham's Scan is  **$O(N \log N)$** , with  $N$  as the total number of points. Therefore, the required time grows reasonably with a larger dataset which makes it efficient for moderately large sets of points.

### Monotone Chain Algorithm:

- The Monotone Chain algorithm was introduced in 1979 and is another efficient way to calculate a convex hull. It begins by sorting the points based on their horizontal position (x-coordinate), from the leftmost to the rightmost.
- The algorithm then makes two steps to construct the convex hull. First is the upper hull and then the lower hull. The algorithm goes through the sorted list of points, adding them to the hull and ensures that each new point does not cause a inward curve by checking whether the last three points form a right or left turn, just like in Graham's Scan.
- The run time is the same as the Graham's Scan with  **$O(N \log N)$** , which makes it well-suited for larger datasets.

[25e; Gee24a]

### 6.2.3 Key concepts in the Convex Hull Algorithm

The convex hull algorithm has a number of key concepts, all of which are essential to guaranteeing the algorithm's accuracy and effectiveness.

#### Orientation:



- This is a reference to the relative orientation of three consecutive points. The convex hull algorithm determines whether to add the next point to the hull based on the orientation of a triplet of points. There are three possible orientations for the points: clockwise, anticlockwise and collinear. Only if the points are oriented counterclockwise, should the point be part of the hull. Otherwise it should be discarded.

**Polar Angle Sorting:**

- A key step in convex hull algorithms is sorting the points according to their polar angle relative to a fixed point which is usually the lowest or leftmost point. By sorting the points, this process guarantees that they are processed in a way that minimises computing resources during hull construction.

**Stack Operations:**

- Convex hull algorithms often use a stack data structure to keep track of all points that are currently part of the hull. To guarantee that only the outermost points stay in the stack, points are added and removed according to their orientation relative to their earlier points.

**Convexity:**

- The convexity of the polygon that is formed by a convex hull algorithm ensures that there are no inward curves. This is crucial because the convex hull represents the smallest possible polygon that does not have any concave edges or inward curves.

[25f]

## 6.3 Use Cases of the Convex Hull in Industry

The ability of the convex hull algorithm to define boundaries of a complex dataset in an efficient way makes it widely used across a variety of fields. Convex hulls offer crucial tools for examining spatial relationships, visualising data and resolving optimisation issues in a variety of fields. Here are some fields that use this algorithm.

**Geographical Mapping**

- In geographic mapping, convex hulls are used to define the borders of regions. For example, while mapping a region with multiple data points, such as cities or landmarks, the convex hull helps outline the area that encloses all the points. This makes it easier to visualize and analyze the overall shape of a region which helps with urban planning, resource management and environmental studies.

### **Image Processing and Computer Vision**

- Convex hulls are used in image processing to determine the shape of an object. This is helpful for tasks like object recognition, where the convex hull helps defining and object's boundaries which improves detection. It makes it easier for algorithms to process and categorise objects in an image by reducing complex shapes to convex polygons.

### **Computational Geometry**

- Convex hulls are crucial in computational geometry for solving issues such as determining the smallest polygon possible that contains a set of points. This has uses in fields like pattern recognition. By providing this convex hull, algorithms can concentrate on the outermost points and ignore the inner one which lowers processing cost.

### **Animal Behavior**

- In ethology, the study of animal behavior, convex hulls are used to identify and animal's home range. The convex hull gives the estimated area an animal needs to be provided with for its inhabitat. In ecological sutdies, this approach is helpful for tracking animal movement patterns, determining territories and keeping an eye on endangered species.

### **Astronomy and Astrophysics**

- Astronomers utilise convex hulls to define the limits of star clusters and other celestial bodies. Scientists can determine a cluster's outer limit by looking at the convex hull of stars which helps them study things like galactic formation, star density and gravitational impacts in space.

[Con25b]

## 6.4 Alternate Methods for Area Border Calculation

The convex hull algorithm is a widely used approach for calculating area boundaries. However, there are other methods that may be more suitable depending on the application requirements. These alternative methods offer different ways to calculate area boundaries with varying levels of complexity and accuracy.

### Minimum Bounding Box (MBB)

- The simplest technique for calculating area boundaries is the MBB. It determines the smallest rectangle that completely encloses a specified set of points. The Edges of the box is normally aligned with the coordinate axes, which makes it efficient with the computing resources and easy to implement. Applications like spatial indexing in databases and image processing use this technique. However, because it does not consider things like concavities and irregularities in the point distribution which may lead to the MBB not always correctly reflecting the data. The Picture below shows a figure which visualizes the difference between the MBB and the convex hull. The convex hull is the gray inner area and the outer line is the MBB. This shows that the convex hull is more precise. [Con24b]




Fig. 17: Difference between MBB and Convex Hull

[24b]

### Alpha Shapes

- By adding a new parameter,  $\alpha$ , that controls how closely the boundary should attach to the specified point, alpha shapes offer a more flexible method of defining area bounds.

This approach is more accurate than the convex hull for irregular shapes because it may capture concave features by decreasing this new parameter  $\alpha$ . This method is especially helpful in fields like shape recognition, molecular modeling and terrain analysis where precisely recording complex boundaries is crucial. Choosing an appropriate  $\alpha$  value is the main challenge with Alpha Shapes as different datasets may require different levels of precision. In the picture below there is the difference between convex hull and Alpha Shapes. It shows that in this case the Alpha Shapes actually make a better job than the convex hull. [Con25a]




Fig. 18: Difference between Alpha Shape and Convex Hull

[13]

### **Delaunay Triangulation**

- Delaunay Triangulation is a method that makes a mesh of triangles which connect a set of points while maximizing the minimum angle of each triangle. This ensures a well-formed structure. A border can be roughly approximated by using the Triangulation's outside edges, especially when pairing this method with techniques like Alpha Shapes. This method is mostly used in geographic information systems (GIS). While it provides a more structured representation of an area, it often requires post-processing to extract a meaningful boundary.

[Con25d]




Fig. 19: Mesh of Triangles from Delaunay Triangulation

[Luc25]

## 6.5 Rationale for Choosing the Convex Hull Method

Accuracy, computational efficiency and implementation ease had to be balanced when choosing a method for identifying area borders. The convex hull was selected as the best strategy for our application after a number of approaches were taken into consideration.

One major reason for this choice was that the convex hull method was precise enough in comparison with more complex methods like the alpha shapes. Since our application did not need such fine control, the additional complexity of alpha shapes was unnecessary.

Furthermore, the convex hull approach offers a significant advantage in terms of speed. It enables quick computing in comparison to other methods which makes it ideal for our application as our resources were somewhat limited for the border addresses.

Finally, our choice was significantly influenced by ease of implementation. The convex hull approach does not require a lot of parameter adjusting, is well-documented, and is simple to incorporate. This made it a practical choice which allows for a reliable and efficient solution without adding unnecessary complexity.

A fair balance between accuracy and efficiency was achieved by selecting the convex hull method which allowed area borders to be calculated quickly while still providing a clear visual representation of each area.

## 6.6 Integration of the Algorithm into the Backend

The convex hull algorithm is implemented within the backend as a part of the service class which analyses an area's allocated addresses to identify its boundaries. The frontend can

request and use the calculated border addresses thanks to this functionality which is made available through a dedicated route.

As soon as a request is made to the route, the service class gets the area for which the border addresses are needed. The program then retrieves all the addresses in the respective area which then get processed by the convex hull algorithm. This then determines the smallest convex shape that encloses all points. The result list of all border addresses are then returned as a response to the frontend, where they are getting used for visualization and management. The server-side calculation load is effectively managed by implementing the convex hull calculation directly in the backend, guaranteeing reliable and consistent results on all client devices.

## 7 Defining usability

Since my research question "How can user-experience principals add to an intuitive map displayment for nonprofit activities in which people of different technical know-how levels collaborate?" is all about usability, I want to introduce you to its basic concepts and challenges but also provide some examples on how usability can impact a software's revenue and perception.

Usability is a critical aspect of software and interface design, ensuring that users can efficiently and effectively interact with a product or system. Its job is to provide clear feedback and "experiences" to the user, so interactions between software and human feel smooth and straight forward. Because each human being is different in its emotional experiences, it is difficult to design a kind of "one size fits all" solution. Due to this circumstance, many studies and experiments were conducted. [Nie24a]

### 7.1 Why it is important

Usability ensures that users can accomplish their goals with minimal frustration and maximum efficiency. With the increasing reliance on digital tools, usability plays a key role, not only, in shaping user experiences but also accessibility of software for diverse user groups. A well-designed and thought-out usability concept can go a long way from refining a once tedious and complicated to use product, to one that can be operated even by non-familiar users or

disabled people. This plays a big part in the inclusion of all age and knowledge groups as well as the general market share through mass adoption because of the easiness.

## 7.2 Components of Usability

According to Jakob Nielsen, usability consists of five core components. To achieve the best possible usability, each of factors must be taken into account and be improved to its maximum.

- Learnability

How **easy** it is to accomplish basic tasks the first time

- Efficiency

How **quickly** task can be accomplished after an initial learning period

- Memorability

How **memorable** actions are to users so, after an extended period of not using a software

- Error handling

How **many** errors users make while using the design and how **sever** they are

- Satisfaction

How **pleasant** the overall experience of using the product is

[Nie24a]


Now that we are aware of these key points, what measures can we take to reach the goal of great usability? According to Nasrullah Hamidli, human-computer-interaction relies on consistency, visibility, feedback, and simplicity. Consistency ensures users do not need to learn new interactions for each task. For example, buttons should look alike and be in a similar location. This makes for a more natural navigation across the product and an overall familiar feel. Simplicity connects directly to this. Its goal is to minimize clutter and make user interfaces easy to understand and provide one, clear way to accomplish a task, not many possible, but complicated and unintuitive ways. It also aims to reduce distractions. Visibility allows users

to clearly understand their options at any given moment, this is most often achieved through visual cues, like, grayed out buttons. This goes hand in hand with the feedback aspect, which provides immediate confirmation of actions. Loading indicators, color-changes and alike get used most often.

Another important part of designing a good UI are typography and colors. These can act as parameters for the attention and emotions of users, as well as establish visual hierarchies, which intern, contribute again to a simpler to navigate interface. [Ham23]

### 7.3 Fundamental concepts

In this section we will look further into these basic concepts and examine what designers can concretely do to improve usability. To make more descriptive, what impacts usability, we will, along the way, modify a simple website.



The image shows a web form with a light gray border. At the top, the title 'Fundamental Concepts' is displayed in a bold, dark blue font. Below it, the word 'Introduction' is in a smaller, bold, dark blue font. A text input field is preceded by the label 'Enter Text:'. Below the input field, a paragraph of text explains the website's purpose: 'This website exists to demonstrate the affect of small design changes. We will add colors, different font-sizes and animations step by step, so we can see how the usability of a website like this one can be improved.' At the bottom left, there are two buttons: 'Cancel' and 'Submit', both in a light gray box with dark gray text.

Fig. 20: Starting point of usability example website

#### Visual Hierarchy


Starting of with Visual hierarchy. It is the most basic principle in UI/UX design and dictates, how users perceive and navigate content. A strong visual hierarchy contributes to simplicity and ensures that important elements are more visually prominent, guiding users toward essential actions and information. Factors include the text size, weight and spacing.

In the initial version, visitors of our website are not able to clearly and promptly differentiate



between headings and actual text. This is due to the use of only a single font size and weight.

If these attributes get tuned just a little, it becomes suddenly much easier to distinguish primary content from secondary information. Headings are bold and larger, while body text is appropriately sized for readability. Proper spacing and alignment create a structured and pleasant reading experience.



**Fundamental Concepts**

**Visual Hierarchy**

Enter Text:

This website exists to demonstrate the effect of small design changes. We will add colors, different font sizes, and animations step by step, so we can see how the usability of a website like this one can be improved.

Cancel Submit

Fig. 21: Example with better visual Hierarchy through different font size and weight

### Color Theory & Contrast

Color selection plays a critical role in usability and aesthetics. Well-chosen colors draw the attention to important elements while poor color choices can make content inaccessible, especially for users with visual impairments. The advantages of attention through colors can also be used in reverse, for example, a button to delete something important may be colored red, to indicate a fatal action, but could also be gray, so the user must consciously decide to press it. This acts as a safety measure.

To help designer with their color choices and visualize what colors work together, the color wheel was invented. On it, relations between colors can be shown easily. It consists of three groups of colors.

- **Primary**

These are the fundamental colors that cannot be created by mixing other colors. They

vary, depending on the media format they will be used on. On screens the *RGB Model* is in use, while when printing color, cyan, magenta and yellow (CMY Model) get used.

- **Secondary**

*Secondary colors* arise by mixing two primary colors to equal amounts. In designing applications, they often get used for buttons or highlighting important information.

- **Tertiary** They are often associated with a calm and refined aesthetic. They are not quite the same eye-catchers as primary colors, rather they have their value in creating appealing combinations.




Fig. 22: Color wheel with primary, secondary and tertiary colors sorted (Source: <https://www.template.net/editable/114132/simple-color-wheel-chart>)

Relationship Type	Description	Use case
Complementary	Colors opposite each other	Creating bold contrast
Analogous	Colors next to each other	Harmonious, natural looks
Triadic	Three evenly spaced colors	Balanced, vibrant designs
Split Complementary	One color + two adjacent to its complement	Softer contrast than complementa

Table 1: Key color combinations with effects(Source: <https://colorpage.ai/blog/color-theory-for-beginners>)

The current design doesn't feature any color at all. To highlight the buttons, we can give them a color. Now we also need to change the text color, because, if left as is, the contrast would not be great, and therefor the text harder to read. [25c, vgl.]




Fig. 23

Consistency

Consistency in design enhances user experience by ensuring that UI elements and interactions are predictable across different states of the application. Also, a consistent aesthetic can create familiarity, brand recognition and improves the overall visual appeal.

Button Placement & Behavior

Buttons are a critical and one of the most common interactive elements in UI design. Their placement, size and responsiveness affects usability and efficiency. Since the first graphical UIs, the actions to move forward were always on the right side. In contrast, actions to cancel

## 7.4 Challenges in designing for a broad user spectrum

---

are most commonly placed somewhere on the left. If designers choose to deliberately change this universal agreement, it leads to potential user errors. Also, a color-change on hover got implemented, so the user now gets clearly informed that all required fields are populated, and he can move on.

This design highlights the "Submit" Button, and places it in the correct location. Through this, the simplicity to use is improved because users do not have to search for the button that lets them continue.

TODO: Gendern?

### **Feedback**

Providing immediate and clear feedback enhances user confidence and prevents frustration. There are many forms in which such feedback can be provided, for example, vibrations, sounds or pop-up messages. Feedback can also be supplied by something like a grayed-out button, to signal that this action is not currently available. Success messages or error messages also add to the usability of a website, as well as loading indicators and different animations.

## **7.4 Challenges in designing for a broad user spectrum**

Designing for a diverse user base requires the addressing of varying levels of experience, prior knowledge, cognitive abilities, and accessibility needs. Failure to account for these differences can lead to usability issues, preventing certain groups from effectively using a system. Designers must implement features such as adjustable text sizes, screen reader compatibility, and intuitive navigation to ensure accessibility for all users.

Interfaces should always be tailored to the needs and expectations of the end-user. This leads to challenges when the user-group is not clearly defined or consists of people with widely different backgrounds. For example elderly people often need further guidance when interacting with digital solutions than members of younger generations. This leads back to the core components of usability-design, interfaces need to be simple and unmistakable in their functionality. Failing to provide these core concepts will sooner or later result in a frustrated and shrinking user base. [Ham23]

## 8 Usability in context of maps

In this section we will further inspect the usability of mapping solutions like Google Maps. We will identify some flaws of Google's design choices and how they could influence specific user groups.

### 8.1 Basic Analysis of the Google Maps Interface

Google Maps is one of the most widely used mapping and navigation applications globally. Its feature set includes real-time traffic updates, route planning, and location discovery. Generally speaking, it is quite difficult to design a simultaneously user-friendly and functional mapping application. Maps get overloaded and confusing quite easily. They are bloated with information like street names, house numbers, borders, and geographical features like rivers or lakes. Due to this fact, maps are not easy to design according to the principles of usability. But Google developed a very good and intuitive concept on which we now will take a look.

The interface of Google Maps consists of a map, search bar, and a menu for additional settings. The search function is prominently displayed as it is the most common tool used. This is a good use of *visual hierarchy* as the initial focus when opening the app immediately gets drawn to the bigger hint text in the search bar on top. Below it, there is a list of buttons, so users can quickly search for local places that match a specific category, like restaurants, cafés, or gas stations. Notably, there are no buttons for movement actions such as zooming or panning; all this is controlled through swipe and pinch gestures directly on the map. [BG08]

To start navigating to a specific area, you can search for the street name and house number, or the name of a company or other details. Maps gives you recommendations and tries to provide auto-suggestions for your target. When the user selects a destination, the navigation can be started through a big blue button. This is an example of applied *color theory*. The route gets marked by an again bright blue line, which creates a good contrast to the other colors used on the map and captures the attention of the user. This line also has multiple purposes other than displaying the route; for example, if a part is orange, that means the traffic at this point is beginning to jam. If then there is a full stop traffic jam, the line turns red at this section.

Also, icons for speed cameras or accidents that other users reported get displayed along it.

One of the core strengths of Google Maps is its interactive and responsive design. Users can zoom in and out using intuitive pinch gestures on mobile devices or scroll actions on desktops. The transition between zoom levels is smooth, preserving context and avoiding disorientation through too big scaling steps. Additionally, the map changes depending on the zoom level. Street names and buildings get displayed only if the user has zoomed in enough. The same happens with markers for businesses and other map data. Through this concept, Google ensures that users do not get overwhelmed. [BG08]

## 8.2 Identifying Flaws in Google's Design

While Maps is a well-polished product, it is not perfect. One significant flaw is the cognitive overload caused by excessive information. The inclusion of business listings, other suggested routes, live traffic data, and user-generated content can make it difficult for users to focus on their primary navigation tasks. [BG08]

## 8.3 How Could Specific User Groups Struggle with This Design

Google Maps caters to a broad spectrum of users, but its design can pose difficulties for certain demographics:

**Elderly Users:** Many elderly individuals may find the interface overwhelming due to small text sizes, densely packed information, and complex menus. Their unfamiliarity with modern digital navigation tools may lead to confusion, especially when trying to search for locations or adjust route preferences. A lack of prominent, simplified navigation options tailored to this group amplifies the issue. [All22]

**Users with Low Digital Literacy:** People who are not well-versed in digital technology could struggle with Google Maps' multitude of features. They may have difficulty understanding icons, switching between different map modes, or using advanced functionalities like saved locations and street view. A more guided and *simplified* mode could enhance their experience.

**Users with Disabilities:** Visually impaired users may struggle with *insufficient contrast*, small

icons, and the *lack of tactile feedback*. While screen readers can assist, Google Maps does not always provide clear, structured data for these tools. Additionally, users with motor impairments may find it hard to navigate menus and interact with small buttons, particularly on touch screens. [Fro+19]

By addressing these usability concerns, Google Maps could enhance its interface to be more intuitive and accessible for diverse user groups.

## 9 Adaptive Algorithms and Real-Time Data Integration

Mobile field teams need address databases that stay up-to-date in real time. However, traditional methods cannot keep up with fast changes, like road closures, new buildings, or street name changes. Manual updates take time, and fixed validation rules do not account for regional differences or typos. These issues can lead to wasted time or even serious risks in critical situations.

This chapter explains how adaptive algorithms and real-time data integration can help solve these problems. Adaptive algorithms improve address databases by learning from new data, while real-time systems process live updates instantly. Together, they help mobile apps keep up with changing environments.

### 9.1 Traditional Methods for Address Database Management

Traditional address database management relies on manual or semi-automated processes that lack real-time adaptability. These methods were designed for stable environments with occasional data changes, which makes them less effective for modern mobile applications requiring constant updates. This chapter outlines common challenges faced by traditional systems and their limitations.

#### 9.1.1 Manual Entry and Batch Updates


In the past, address databases were updated through periodic batch uploads, such as monthly CSV files, which store data in a table format with each value separated by commas. Organizations often relied on printed address lists given to field teams, with corrections submitted on paper. This method caused delays. For example, if a street name changed due to construction, mobile teams could work with outdated data for extended periods. [25d]

Manual data entry by administrators was another common practice. Human errors, such as typos, worsen the problem, making the system less reliable. A study conducted by the Journal of Accountancy found that human error rates in manual data entry can range from 1% to 5%. [25v]



### 9.1.2 Static Validation Rules

Address database management systems often rely on strict validation rules, such as regular expressions, to verify address formats. Regular expressions define patterns for strings, making them useful for enforcing specific formats. For example, a regex pattern might require the full word "Street" instead of abbreviations like "St." or "Str.". [Aut02]



```
r'^-[0-9.]*'
```

Fig. 24: Regular Expression Example

### 9.1.3 Third-Party Data Purchasing

Third-party data purchasing involves obtaining address datasets from external providers to update and maintain address information. These datasets are usually updated on a regular schedule and cover a wide area. However, the data can quickly become outdated, especially in areas where changes occur rapidly.

Temporary road closures or infrastructure damage might not be reflected in these datasets if updates are infrequent. As a result, teams relying on outdated maps may encounter roads that are blocked or no longer accessible. This lack of real-time updates can cause delays in reaching critical locations or reduce the efficiency of field teams.

## 9.2 Adaptive Algorithms

Adaptive algorithms are methods that continuously adjust their parameters in response to new data and changing environmental conditions. These techniques are vital for applications where real-time adaptation is necessary. The following sections describe several core approaches within this domain. [Con24a]

### 9.2.1 Fuzzy Matching

Fuzzy Matching, also known as Approximate String-Matching or Fuzzy Logic Name Matching, is a string-matching algorithm that helps identify duplicate strings, words, or entries that closely resemble each other, even when there are abbreviations or misspellings. The technique works by applying edit operations such as insertion, deletion, substitution, and transposition to adjust the strings. These operations are measured in terms of an "editing distance," which influences the match score.

Fuzzy matching is widely applied in various fields, such as document data extraction, spell-checking suggestions, deduplication, and even genome sequencing. It helps achieve high data accuracy by identifying and matching errors. [Nie24b]




Fig. 25: Fuzzy Matching Example

### 9.2.2 Machine Learning Model

Machine learning models can be trained to identify patterns in incoming data and update the database dynamically, eliminating the need for manual intervention. These models are particularly effective in rapidly changing environments, as they continuously learn from new data and provide insights to refine address information in real time.

For example, an ML model can detect and predict changes in street names, new construction sites, or temporary roadblocks based on GPS data, social media updates, or traffic reports. By integrating these data streams, the model can anticipate issues not yet reflected in official datasets and make real-time adjustments to the address database. Moreover, as new information becomes available, the machine learning model continuously improves its predictions, adapting to evolving patterns and ensuring the database remains accurate and up-to-date. [Enc23]

### 9.2.3 Rule-Based Filters

Rule-based filters enforce logical constraints on address data to maintain quality and relevance in dynamic environments. A filter could flag addresses lacking GPS coordinates during emergency responses, enforcing manual verification before navigation.

#### Structure of Rule-Based Filters

A rule-based filter consists of logical conditions applied to address attributes:

- **AND:** All rules must be true.
- **OR:** At least one rule must be true.

#### Types of Rule-Based Filters

- **Threshold-Based Rules:** Automatically reject addresses with missing or implausible values.
- **Geospatial Rules:** Flag addresses that fall outside predefined operational zones.
- **Historical Consistency Checks:** Detect frequently modified addresses and prompt for manual review.

#### Integration with Adaptive Algorithms

While rule-based filters provide a structured approach to data validation, they can be enhanced with adaptive algorithms. Machine learning models can analyze user corrections over time and adjust rules dynamically. For instance, if multiple users correct the same address format, the system can learn from these patterns and refine its filtering criteria automatically.

## 9.3 Real-Time Data Integration Frameworks

Real-time data integration frameworks are systems designed to collect, process, and deliver data instantly as it is generated. Unlike traditional batch processing, which handles data in chunks, these frameworks enable continuous updates. This makes them ideal for applications where delays are unacceptable.

### 9.3.1 Challenges

Real-time data integration faces several challenges, particularly in dynamic environments such as mobile field operations: [hel24]

- **Data Quality:** Errors such as typos or GPS drift require adaptive algorithms for correction.
- **Scalability:** Systems must handle thousands of users and sudden data spikes, especially during disasters or high-demand situations.
- **Fault Tolerance:** Data loss due to network failures must be prevented.
- **Consistency:** Conflicting address data from multiple sources needs resolution.

### 9.3.2 Core Components

A robust real-time data integration framework consists of four key components: [Lim25]

- **Data Sources:** These include GPS sensors, external databases, and other input streams.
- **Data Ingestion:** Tools and frameworks collect and efficiently route data streams.
- **Data Processing:** Engines process, clean, analyze, and enhance the data.
- **Storage & Delivery:** Processed data is stored in databases and accessed via APIs.

### 9.3.3 Popular Frameworks

Three frameworks dominate real-time integration:

**Apache Kafka:** A high-throughput streaming platform. It could process GPS and traffic data to reroute teams around road closures.

**Apache Flink:** A low-latency engine for complex workflows. Flink could power ML models predicting address changes.

**AWS Kinesis:** A cloud-native service for scalability. Kinesis merges regional address updates into a global view for international teams.

Choosing between them depends on needs: Kafka for volume, Flink for processing, Kinesis for cloud scalability. [Ran24]

### 9.3.4 Evaluation Metrics

To assess the effectiveness of adaptive algorithms and real-time data integration, two critical metrics are analyzed: accuracy and latency.

#### 9.3.4.1 Accuracy

Accuracy measures how closely the addresses in the database match real-world locations, ensuring reliable address information. Traditional methods often suffer from decay over time due to manual updates or infrequent batch imports, leading to outdated or incorrect data.

Inaccurate data can lead to inefficiencies, delays, or even costly mistakes. Furthermore, achieving high accuracy often involves continuous updates and validation of data, particularly when using multiple data sources. [Gee24b]

Accuracy is calculated as:

$$\text{Accuracy} = \frac{\text{Correct Addresses}}{\text{Total Addresses}} \times 100$$

#### 9.3.4.2 Latency

Latency measures the delay between data generation and its availability in the app. For mobile teams, latency above 30 seconds can render updates useless during fast-moving operations. Reducing latency is critical for ensuring timely decision-making and operational efficiency. Key factors influencing latency include: [Gee24b]

- **Data Ingestion Speed:** Fast ingestion ensures data is quickly captured, minimizing delays and speeding up availability.
- **Edge Processing:** Local data processing speeds up decision-making by filtering data before transmission, reducing network load.
- **Network Bandwidth:** Latency is affected by network bandwidth; poor conditions, like low signal or congestion, increase delays.
- **Data Prioritization:** Algorithms that prioritize critical data reduce perceived latency by processing urgent updates first.

## 10 Implementation of the Backend

The backend implementation combines theoretical concepts with practical solutions to ensure functionality and scalability.

### 10.1 Config of Spring Boot (`application.properties`)

The `application.properties` file configures essential settings, including database connections, logging, and server parameters.

### 10.2 Entity Classes (Structure/Purpose)

Entity classes define the application's data model, using annotations to map fields to database tables.

### 10.3 JPA-Repositories (DB Access and CRUD Operations)

Repositories simplify database access by providing methods for CRUD operations and enabling custom queries.

### 10.4 Service Classes

Service classes encapsulate business logic, coordinating data flow between controllers and repositories.

### 10.5 Rest Controller (API Endpoints and their Functions)

REST controllers define API endpoints, processing requests and returning responses to ensure seamless interaction with the frontend.

## **11 GraphHopper Setup**

### **11.1 Why use GraphHopper?**

### **11.2 Configuration**

### **11.3 Local hosting**

## **12 Working out the Wireframes**

### **12.1 Map View**

### **12.2 List View**

### **12.3 Possible improvements for future versions**

## **13 Functional implementation behind the application**

### **13.1 Address-Provider**

### **13.2 HTTP-Requests**

### **13.3 Implementation of the Flutter Map Component**



## **14 The app in use**

### **14.1 Introducing new users**

### **14.2 The app in operation**

### **14.3 User Feedback**

# 15 Implementation Admin Panel

The Admin Panel is an administrative control center to efficiently manage all addresses within a single environment. It is used for planning upcoming "Sternsinger" events, ensuring that all required addresses are covered and effectively distributed among participating groups. Additionally, it provides a way to assign areas containing addresses that a group needs to visit. This zoning feature ensures that each group is responsible for only the addresses within their designated area.

This tool enables authorized users to perform CRUD operations (Create, Read, Update, Delete) on addresses, streets, and areas. These features make it easy to address issues quickly and make changes to the areas that participants need to visit. For example, when a new street is added to the neighborhood, the administrator can update the system to include it and assign it to the appropriate area. Similarly, if a group withdraws from the event, the administrator can reassign any unvisited addresses to other groups. This ensures that the data remains up-to-date, allowing quick reactions to special cases, helping with the planning and execution of "Sternsinger" events.

This chapter will outline the implementation of the Admin Panel, detailing its components, functionalities, and widgets, and providing guidance on how to use them.

## 15.1 Navigation

To navigate between pages, a sidebar on the left is used, which can be toggled with a button in the top-left corner of the page. It displays a list of all pages, allowing users to switch between them with a click.

The navigation is implemented in the `AdminNavigation` component. The menu contains a list of `ScreenItems` (see 15.5.2), which store the title with the corresponding page. These titles are displayed at the top of the screen above the page. To keep track of the currently selected page, an internal state (`indexState`) is used. Whenever a page is selected in the sidebar, the `indexState` is updated, and the corresponding page is displayed. This widget is the main component. It ensures that all pages are properly displayed.




Fig. 26: Navigation in Admin Panel

## 15.2 AddressPage

The first page, called `AddressPage`, provides an interface for managing address data, including creation, modification, and deletion. It uses a form with various input fields and a visualization component that displays addresses on a map or in a database view. The layout is divided into two parts:

- On the right side, all addresses are shown in either the `AdminMapComponent` (15.4.1), displaying addresses on a map, or the `DatabaseViewComponent` (15.4.2), showing them in a table.
- On the left side of the page, there are `InputFields` (15.6.1), which are used to enter new information about a new address or edit existing ones.

The following elements overlay the `AdminMapComponent` :

- A field to filter the addresses that are displayed.
- A button with a dropdown menu to select and edit a street.
- A switch to toggle between the `AdminMapComponent` and the `DatabaseViewComponent`.
- An information box in the bottom left corner to display `Notifications` (15.2.5.1) about the completed operations.
- A field in the bottom right corner to display the coordinates of the mouse pointer on the map.




Fig. 27: AddressPage

### 15.2.1 Add Address

To add a new address, the "Neue Adresse" button is pressed. This triggers the `onClickNewAddress` method, which performs several key operations:

- All `InputFields` are cleared.
- The boolean variable `isNewAddress` is set to `true`, indicating that a new address is being created.

The cleared fields can then be filled with the new information. When the "Speichern" button is pressed, the `saveAddress` method is called. This method performs several validation checks, as shown in 15.2.4. If the address is valid, the `AdminAddressProvider` adds it to the database, a `Notification` is displayed, and the newly added address appears.

When the map is clicked, the `onClickNewAddress` method is also invoked within the `AdminMapComponent`. The method receives the click coordinates as parameters to create the address at the selected location.

### 15.2.2 Edit Address

Existing addresses can be edited by selecting them in either the `AdminMapComponent` or the `DatabaseViewComponent`. The selection fills the `InputFields` with the information of the address, and in this case, the boolean variable `isNewAddress` is set to `false` to indicate that an existing address is being updated.

The administrator can then edit the information and press the "Speichern" button. This triggers the `saveAddress` method, which performs the same validation checks as when adding a new address. The `AdminAddressProvider` updates the selected address in the database, and the `Notification` is displayed.

### 15.2.3 Delete Address

After selecting an address, the administrator can press the "Löschen" button to delete it. This triggers the `deleteAddress` method, which calls the `AdminAddressProvider` to delete the selected addresses.

The method also triggers the `showDeleteDialog` method, which displays an `AlertDialog` to confirm the action and prevent accidental deletions.




Fig. 28: Dialog to confirm deletion

### 15.2.4 Validation

Validation is the process of checking that data meets specific criteria before it is accepted and added to a system or database. This ensures that the data is accurate, consistent, and conforms to required standards. Validation prevents errors and inconsistencies that could arise from invalid or incomplete data, maintaining the integrity and reliability of the system. It helps catch mistakes early, such as missing fields or incorrect data inputs. By ensuring that only valid data is processed, validation plays a crucial role in preserving data quality. [Con25c]

#### 15.2.4.1 isDuplicateAddress

To determine whether an edited or newly added address already exists in the system, the new address is compared against all existing addresses, to detect potential duplicates before the address is saved. The comparison takes place within the `saveAddress` method, which handles the saving operation. If an address is found to be identical to an existing one, the method returns `true`, indicating that the address is a duplicate. If no match is found, it returns `false`, confirming that the address is unique and can be safely added to the database.

A duplicate address is identified by the following criteria:

**street name, postal code, and house number**

### 15.2.4.2 InputField filled Validation

To verify that all required `InputFields` are properly filled, the `validateAddressFields` method is called.

To start the process, a new `Address` object is created and passed to the `validateAddressFields` method. The method checks each field within the `Address`. If a field is missing or incomplete, a `Notification` (see 15.2.5.1) is displayed to inform the user of the missing data, such as "Strasse fehlt" or "Koordinaten fehlen." If all fields are correctly filled out, the method returns `true`, signaling that the address can be saved. However, if any field is incomplete, the method returns `false`, preventing the address from being saved until all required information is provided.

### 15.2.4.3 InputField Coordinates Validation

The `InputField` validates **latitude** and **longitude** inputs ensuring correct coordinates. Validation is applied only when the `isCoordinateInput` parameter is set to `true`. In that case, the `inputFormatter` is passed to the `textfield`. This `inputFormatter` guarantees that only valid inputs are accepted. These are the three validators used:

- A `FilteringTextInputFormatter` with a regular expression is used to restrict the input to digits, decimal points, and an optional minus sign at the beginning.

```
r'^-?[0-9.]'
```

Fig. 29: Regular expression for input validation

- A `TextInputFormatter` prevents multiple decimal points in a single number. If a user attempts to insert a second decimal point, the input is automatically rejected.
- The final `TextInputFormatter` ensures that the number of digits before the decimal point is limited to a maximum of 3 and the value itself does not exceed 180.


### 15.2.5 Additional Functionalities

This section outlines several functionalities that have been integrated to improve the overall usability of the application. These enhancements are specifically designed to simplify tasks while ensuring an intuitive user experience.

#### 15.2.5.1 Notification

To notify the administrator about the success or failure of an operation, a `Notification` is displayed at the bottom left, overlaying the `AdminMapComponent`. This `Notification` appears when:

- An address has been added, edited, or deleted.
- Validation has failed.
- Coordinates are selected on the `AdminMapComponent` (15.4.1.2).



Besonderheit fehlt  
Adresse hinzugefügt  
Adresse gelöscht

Fig. 30: Notification examples

To display this notification, the `showNotification` method is called. This method sets the `notificationVisible` variable to `true` and starts a `Timer` to reset it to `false` after three seconds, causing the notification to disappear shortly after. The method accepts a message as a parameter, which is stored in the `notificationText` variable. When the `notificationVisible` variable is set to `true`, the UI component which shows the notification is rendered.



### 15.2.6 Edit multiple Addresses

To make it easier to edit multiple addresses at once, the control|command key on the keyboard is listened to, meaning the system detects and responds to when the key is pressed. When this key is pressed, the `isCtrlPressed` variable is set to `true`. This variable is passed to the `DatabaseViewComponent` and the `AdminMapComponent` to inform them that multiple addresses are to be selected.

To detect when the control|command key is pressed or released, the predefined `RawKeyboardListener` widget is used. This widget listens for keyboard events and updates the state of the `isCtrlPressed` variable accordingly. When the key is pressed, the widget sets `isCtrlPressed` to `true`, indicating that it is being held down. Alternatively, when the key is released, `isCtrlPressed` is set to `false`, signaling that the key is no longer pressed.

To handle repeated key presses effectively, especially when the CTRL key is held down, a condition is implemented to prevent continuously setting `isCtrlPressed` to `true`. This is achieved by checking the `event.repeat` property, ensuring that the variable is only updated when `event.repeat` is false.

The `markerSelected` method also updates the `InputField` by listing all house numbers of the selected addresses. This ensures that the user is presented with a clear overview of all the selected addresses, making it easier to manage multiple selections.

The `InputField` looks like this:



Fig. 31: House numbers of multiple selected Addresses

The selected addresses are saved in the `selectedAddresses` variable in the `AddressPage`. If multiple addresses are selected, certain `InputFields`, such as house numbers, coordinates, or comments, are disabled, as changing them for all selected addresses would not make sense. This is achieved by setting the `editable` parameter of these `InputFields` to `selectedAddresses.length <= 1`, ensuring that they are only editable when a single address is selected.

### 15.2.7 Edit all Addresses from a Street

All addresses on a street can be edited at once, simplifying bulk modifications. This process is similar to editing multiple addresses (15.2.6), but instead of manually selecting each address, the entire street is selected at once. This allows for quicker adjustments, ensuring consistency across all addresses on the selected street. Once a street is chosen, all associated addresses are automatically included in the selection.

A street can be selected in two ways:

#### 15.2.7.1 Select a Street via AdminMapComponent

Every click on the `AdminMapComponent` is checked to see if it is near a street. Since there is no predefined method to check if a point is on a street, the `isPointNearPolyline` method was implemented. This method checks whether the click was on the street. More information about this method can be found in the `AdminMapComponent` section 15.4.1.




Fig. 32: Street visualization example in AdminMapComponent

#### 15.2.7.2 Select a Street via Button

This was implemented, because, selecting the street directly on the map could be a bit spotty in its working. Through this feature, a reliable way to select a street was available, even though in the final deployment, the street selection via map worked flawlessly.




Fig. 33: Field to select a Street

### 15.2.8 Edit Odd / Even Streets

One requirement was that addresses from a street could be automatically assigned to two areas based on whether the house number is even or odd. This is because it is common for addresses with even house numbers to be on one side of the street and those with odd house numbers on the other side. This division makes it easier to assign the street sides to different areas, so that "Sternsinger" participants don't have to cross the street as often.

To make this possible, the administrator first selects a street in the `AdminMapComponent` (15.4.1.1), and then a blue button appears beneath the `InputFields`.




Fig. 34: Button to split Street

After pressing this button, a dialog appears, where the administrator can select the areas for addresses with even and odd house numbers on this street. The "Speichern" button triggers the `AdminAddressProvider` and displays a `Notification` (15.2.5.1) indicating whether the operation was successful or not. Afterward, the dialog is closed.




Fig. 35: Dialog to split street

### 15.2.9 Filter

With the Filter field, the administrator can filter the addresses displayed. It contains three dropdown menus to set the filter criteria, with one checkbox for each to toggle them. These filters can be combined as desired.




Fig. 36: Filter in AddressPage

## 15.3 ListEditPage

The filter is passed and applied to both the `AdminMapComponent` and the `DatabaseViewComponent`. The criteria and their enabled/disabled state are managed by a series of variables within the `AddressPage` class. These variables control which filters are active and store the selected filter values. They are defined as follows:

The filter is then applied to the addresses within the components. The filtering process is done step-by-step, starting with the area filter, followed by the special feature filter, and finally the street filter. If any of the filter conditions are met, the addresses are filtered accordingly. Only the `filteredAddresses` are displayed in the `AdminMapComponent` and the `DatabaseViewComponent`.

### 15.3 ListEditPage

The `ListEditPage` is used to manage **streets**, **special features**, and **areas**. It allows the administrator to add, edit, and delete these entities. The page is divided into two sections. On the right side, all entities are displayed in a table and can be selected. On the left, there is a dropdown menu for selecting between the three options. The information of the selected item is shown in `InputFields`, where it can be edited, saved, or deleted using the "Speichern" or "Löschen" button.

The screenshot shows the 'Listen bearbeiten' (Edit List) page. On the left, there is a form for editing a selected item. The 'Auswahl:' dropdown is set to 'Straße'. Below it, a green 'Neu' button is visible. The 'Ausgewählt: Straße' section shows the 'Straßenname' field with 'Am Bach' and a 'PLZ' field with '8501'. At the bottom of the form are 'Speichern' (Save) and 'Löschen' (Delete) buttons. On the right, a table displays a list of streets, each followed by the postal code '8501'. The list includes: Am Bach, Am Gries, Am Mühlbach, Am Sonnengrund, Am Waldrand, Am Weiher, Am Wiesengrund, Amselgasse, Angergasse, Arkenweg, Augasse, Bachfeldgasse, and Bachweg.

Street Name	PLZ
Am Bach	8501
Am Gries	8501
Am Mühlbach	8501
Am Sonnengrund	8501
Am Waldrand	8501
Am Weiher	8501
Am Wiesengrund	8501
Amselgasse	8501
Angergasse	8501
Arkenweg	8501
Augasse	8501
Bachfeldgasse	8501
Bachweg	8501

Fig. 37: ListEditPage

### 15.3.1 QR-Code Visualization for Areas

To make it easier for users of the user application to access information about their area, a QR-Code is generated for the selected area, which can be scanned to get all information. The QR-Code contains the name of the area. The currently selected area is saved in the `selectedItem` variable. To display the QR-Code, the predefined `QrImageView` is used.




Fig. 38: QR-Code for Area

### 15.3.2 QR-Code-PDF Download

A PDF containing QR-codes for all areas can be downloaded, making it easier to distribute the information to users. The PDF is generated using the `savePDF` method of the `PDFSaver` class.

To generate the QR-codes, the `generateQRCode` method in the `ListEditPage` class is used. This method takes a `String` as a parameter and converts it into a QR-code using the predefined `QrPainter`, which helps in rendering it [25q]. It then generates an image of the QR-code, converts it into PNG byte data, and transforms the byte data into a list of bytes (`UInt8List`) to be used in the PDF.

Then, the `savePdf` method of the `PDFSaver` class creates a PDF document containing the QR-codes for all areas. It uses the predefined `pdf` package (imported as `pw`) to manage the PDF document [25o]. The function starts by initializing a new PDF using the

`pw.Document()` class and an empty list to store the generated QR-codes. The method then iterates over the list of areas, generating a code for each description of all areas using `generateQRCode` and adding it to the list.

Afterward a page is added to the PDF document using the `pw.MultiPage` widget. This page includes a title and the description of each area along with its corresponding QR-code. Once the page content is built, the PDF data is saved by calling `pdf.save()`. Finally, the `PdfSaver.savePdf` method is called to save the PDF as "Gebiete.pdf."

#### Alle Gebiete:

1a

1b



Fig. 39: PDF with QR-Codes for all Areas

#### 15.3.3 Icon for Special Features

When a special feature is selected, an icon is displayed to visually represent it. The administrator has the option to upload a custom image to use as the icon for the selected special feature. Once the image is uploaded and the "Speicher" button is pressed, it is saved in the database and used as the icon, allowing for easy visual identification of the special feature. This icon is displayed in the user application.




Fig. 40: choose Icon for Special Feature

## 15.4 Components

Components play a key role in structuring the Admin Panel. Each one is designed to handle specific tasks or display certain UI elements, making them reusable throughout the application.

### 15.4.1 AdminMapComponent

This component displays the addresses on a geographic map. The map used is OpenStreetMap, which is free to use for everyone. Although the Admin Panel is not used commercially, OpenStreetMap's attribution rules are followed. The map shows the required copyright notice "© OpenStreetMap contributors" in the bottom-left corner. The word "OpenStreetMap" is clickable and links directly to <https://www.openstreetmap.org/copyright>, opening the official license page in a new tab. This meets OpenStreetMap's license requirements by clearly acknowledging the data source and linking to their terms. [25w]


The image shows the standard OpenStreetMap attribution text, which is "© OpenStreetMap contributors". The text is in a small, sans-serif font, with "OpenStreetMap" in blue and "contributors" in black.

Fig. 41: OpenStreetMap attribution

#### 15.4.1.1 Select a Street

To select a street, the `isPointNearPolyline` method was implemented. This method checks whether the click was on a street. It takes the coordinates of the click as a `LatLng` object and a street as a list of `LatLngs`. After each click on the map, a loop is triggered that calls the `isPointNearPolyline` method for every street, passing the click coordinates during each iteration.

The `isPointNearPolyline` method uses another loop that iterates over all points of the street. Since the street is represented as a list of `LatLng` objects, each pair of consecutive points is connected to form a line segment. During each iteration of the loop, a helper method `isNear` is called to calculate the distance between the click and the currently iterated line segment.

The `isNear` method takes the click point, the two points for the line and the tolerance. If the distance is smaller than the predefined tolerance, the method returns `true`, indicating that the click was on the street.

The method uses the Manhattan distance to determine the distance between the click and the line. The Manhattan distance, also known as taxicab or city block distance, measures the distance between two points in a grid-based system. It is calculated as the sum of the absolute differences of the x- and y-coordinates.

Why the absolutes? The absolute value ensures that the distance is always positive, regardless of the direction. If you were to walk 5 blocks north or 5 blocks south, the distance is the same. It's 5 blocks. This distance is then compared to the tolerance. [Alg25]

$$d_{\text{Manhattan}} = |x_2 - x_1| + |y_2 - y_1|$$

```
bool _isNear(LatLng p, LatLng a, LatLng b, double tol) {
    double dx = b.latitude - a.latitude, dy = b.longitude -
        a.longitude;
    double t = ((p.latitude - a.latitude) * dx + (p.longitude -
        a.longitude) * dy) / (dx * dx + dy * dy);
    t = t.clamp(0, 1);
    return (p.latitude - (a.latitude + t * dx)).abs() +
        (p.longitude - (a.longitude + t * dy)).abs() <= tol;
}
```

Quellcode 1: isNear method

#### 15.4.1.2 Select Coordinates on Map

To select coordinates to the currently selected address, a long press can be done on the map. The method `onCoordinateSelected` is then called via a callback from the `AdminMapComponent`. This sets the coordinates of the address to the coordinates of the click. The `InputFields` are then filled with the new coordinates.

Because it would not make any sense to select coordinates for multiple addresses at once, the length of the `selectedAddresses` list is checked. Only if it is smaller than 2, the coordinates can be selected.



### 15.4.2 DatabaseViewComponent

To display the addresses in a table, this component was implemented. It takes the `selectedAddresses`, the filter variables, and the `isCtrlPressed` variable from the `AddressPage` as parameters. The `isCtrlPressed` variable is used to track whether multiple addresses are being selected. The `selectedAddresses` are shown in the table and can be selected by clicking on them.

Above the table, two fields are displayed: one showing the number of selected addresses and the other showing the total number of found addresses. The table is implemented using the `ListView` widget, a predefined widget in Flutter.

2072 Adressen gefunden					3 Adressen ausgewählt	
Straße	Hausnummer	Ort	Gebiet	Besonderheit	Bereits besucht	Kommentar
Ahorn gasse	4	8501	Default	Wohnhaus	false	
Ahorn gasse	5	8501	Default	Wohnhaus	false	
Ahorn gasse	6	8501	Default	Wohnhaus	false	
Ahorn gasse	8	8501	Default	Wohnhaus	false	
Ahorn gasse	10	8501	Default	Wohnhaus	false	
Ahorn gasse	12	8501	Default	Wohnhaus	false	
Ahorn gasse	14	8501	Default	Wohnhaus	false	

Fig. 42: DatabaseViewComponent

### 15.4.3 PDFSaver

The `PdfSaver` class provides functionality for saving PDF files from a byte array. The static method `savePdf` handles the saving process depending on the platform.

For web applications, it creates a `Blob` containing the PDF data, generates a temporary URL, and triggers a download via an `AnchorElement`. After the download starts, the temporary URL is revoked to free resources.

On non-web platforms, the method utilizes the `FileSaver` package to store the PDF file. The `saveFile` function is used, specifying the file name, byte data, and MIME type to ensure proper file handling.

### 15.4.4 AdminAddressProvider

This class serves as a bridge between the Admin Panel and the backend. It is responsible for all CRUD operations on addresses, streets, special features, and areas. It is used in the `AddressPage` and the `ListEditPage`.

The `AdminAddressProvider` includes the `ChangeNotifier` mixin. A mixin is a way to reuse code across multiple classes without using inheritance, as in Java. [25m] The `ChangeNotifier` mixin is used to notify the UI when the data changes. [25b]

This notification is triggered by calling the `notifyListeners` method. Below is a typical method in the `AdminAddressProvider` class, which demonstrates these functionalities:

- `async` : enables non-blocking operations and ensures that the UI remains responsive while waiting for tasks like network requests to complete.
- `await http.get` : sends a GET request to the server to fetch all streets and waits for the response.
- `jsonDecode` : processes the JSON response from the server.
- `utf8.decode` : transforms the UTF-8 encoded response body into readable text.
- `map` : converts the decoded JSON to a list of `Street` objects.
- `sort` : sorts the list alphabetically.
- `notifyListeners` : notifies the listeners that the data has changed.
- `catch` : catches any errors that occur during the operation.

## 15.5 Models

Models represent and manage data structures within the Admin Panel. They are designed to encapsulate data and provide a structured approach for interacting with it. Various models have been developed to ensure maintainability and efficiency.

### 15.5.1 AreaWithBorder

To associate an area with its border coordinates, the `AreaWithBorder` model was introduced. It stores all border points as a list of `LatLng` objects, which are then used in the `AdminMapComponent` to draw the boundary. This visualization helps to clearly distinguish which addresses belong to which area.

### 15.5.2 ScreenItem

The `ScreenItem` was created to store data related to a menu option in the `AdminNavigation`. It is used to save the title, associated screen, and icon for each navigation item.


## 15.6 Widgets

Widgets are used to build and reuse UI components in Flutter. They help maintain a consistent look and feel across the entire interface, ensuring a seamless user experience. Several custom widgets were implemented for the Admin Panel.

### 15.6.1 InputField

This widget defines a customizable input field. The `InputField` requires a label and a `TextEditingController` to manage the input. Optional parameters include a boolean `editable`, a list of `Strings` called `dropDownOptions`, and a boolean `isCoordinateInput` to specify whether the input should be numeric.

To indicate whether the `InputField` is editable, icons are displayed on the left side of the field. If the field is not editable, a blocked symbol appears. If it is editable, a pencil icon is shown. When the `InputField` is editable and not a dropdown, a cross icon appears on the right side. Pressing this icon clears the content.



The image shows two examples of the `InputField` widget. The first example is labeled "Bereits besucht" and features a blocked symbol (a circle with a diagonal line) on the left side of the input field. The second example is labeled "Breitengrad" and features a pencil icon on the left side, the text "46.97268368067237" in the center, and a cross icon on the right side of the input field.

Fig. 43: InputField examples

If the `dropDownOptions` parameter is provided with a non-empty list of `Strings`, the input field is rendered as a dropdown menu. The selected value is displayed, and users can choose from the available options. The selected dropdown value is automatically synchronized with the `TextEditingController`.

To ensure valid inputs, the `InputField` uses an `inputFormatter` for validation. This formatter is applied only when the `isNumberInput` parameter is set to true. For more details about the validation, refer to 15.2.4.3.

### 15.6.2 FilterRow

The `FilterRow` is a custom widget which combines a label, a toggleable checkbox, and a dropdown menu to enable dynamic data filtering. It requires several parameters, including callbacks. A callback is a method passed as an argument to another function and executed after a specific event. These callbacks are used to handle activating and deactivating the filter, as well as changes to the filter's state and the selected dropdown value. The following parameters are used:

- `label`: Identification string for the filter.
- `tooltipMessage`: Message displayed when hovering over the checkbox.
- `filterValue`: Boolean value tracking the filter's active state.
- `items`: List of strings for the dropdown options.
- `selectedValue`: Manages the selected dropdown value.
- `onFilterChanged`: Callback for updating the filter state.
- `onDropdownChanged`: Callback for updating the selected dropdown value.

Besonderheit: ☐ Besuch nicht gewünscht ▼

Fig. 44: FilterRow

## **16 Final Thoughts**

### **16.1 Leon Edlinger**

### **16.2 Paul Gigler**

### **16.3 Andreas Weissl**

## **17 Meetings**

Protokolle der Meetings, vielleicht auch ein zeitplan wann immer und wie lang

## 18 Working Hours

Arbeitspaket-Nr.	Beschreibung	Dauer
1	Einführung und Einarbeitung	8 h
2	Grundkonzept erstellen	8 h
3	Struktur der App festlegen	6 h
5	Wifi-Socket in App implementieren	39 h
6	Write-Funktionalität in App implementieren	14 h
7	Read-Funktionalität in App implementieren	19 h
8	Trim-Funktionalität in App implementieren	10 h
9	Konfigurationsmöglichkeiten für Flug in App implementieren	16 h
10	Höhenregelung-Funktionalität in App implementieren	14 h
12	Graphische Darstellung der Flugdaten	18 h
14	App testen und debuggen	19 h
26	Gesamtkonzept testen und debuggen	16 h
<b>Summe</b>		<b>187 h</b>

Table 2: Arbeitszeitznachweis

## **19 Source code directory**

Source Code directory, kein plan was des is



## 20 List of figures

1	Dart Logo (Source: <a href="https://dart.dev">https://dart.dev</a> ) . . . . .	4
2	Flutter Logo (Source: <a href="https://flutter.dev/">https://flutter.dev/</a> ) . . . . .	5
3	Java Logo (Source: <a href="https://logodownload.org/java-logo/">https://logodownload.org/java-logo/</a> ) . . .	6
4	Git Logo (Source: <a href="https://git-scm.com/">https://git-scm.com/</a> ) . . . . .	8
5	GitHub Logo (Source: <a href="https://github.com/">https://github.com/</a> ) . . . . .	8
6	OSM Logo (Source: <a href="https://wiki.openstreetmap.org/">https://wiki.openstreetmap.org/</a> ) . . . . .	9
7	GraphHopper Logo (Source: <a href="https://brandfetch.com/graphhopper.com">https://brandfetch.com/graphhopper.com</a> ) . . . . .	10
8	VS Code Logo (Source: <a href="https://code.visualstudio.com/brand">https://code.visualstudio.com/brand</a> ) .	11
9	IntelliJ IDEA Logo (Source: <a href="https://www.jetbrains.com/company/brand/">https://www.jetbrains.com/company/brand/</a> ) . . . . .	11
10	Android Studio Logo (Source: <a href="https://img.icons8.com/?size=100&amp;id=040Frkjznvcd&amp;format=png&amp;color=000000">https://img.icons8.com/?size=100&amp;id=040Frkjznvcd&amp;format=png&amp;color=000000</a> ) . . . . .	12
11	Postman Logo (Source: <a href="https://www.postman.com/legal/logo-usage/">https://www.postman.com/legal/logo-usage/</a> ) . . . . .	12
12	Docker Logo (Source: <a href="https://www.docker.com/">https://www.docker.com/</a> ) . . . . .	13
13	GUI of the Spring Initializr . . . . .	16
14	Layers of Spring Boot . . . . .	20
15	Process of the Convex Hull Algorithm . . . . .	28
16	Difference between a convex/concave polygon . . . . .	29
17	Difference between MBB and Convex Hull . . . . .	33
18	Difference between Alpha Shape and Convex Hull . . . . .	34
19	Mesh of Triangles from Delaunay Triangulation . . . . .	35
20	Starting point of usability example website . . . . .	38
21	Example with better visual Hierarchy through different font size and weight .	39
22	Color wheel with primary, secondary and tertiary colors sorted (Source: <a href="https://www.template.net/editable/114132/simple-color-wheel-chart">https://www.template.net/editable/114132/simple-color-wheel-chart</a> ) . . . . .	40
23	. . . . .	41
24	Regular Expression Example . . . . .	47
25	Fuzzy Matching Example . . . . .	48
26	Navigation in Admin Panel . . . . .	57
27	AddressPage . . . . .	58
28	Dialog to confirm deletion . . . . .	60
29	Regular expression for input validation . . . . .	61
30	Notification examples . . . . .	62
31	House numbers of multiple selected Addresses . . . . .	63
32	Street visualization example in AdminMapComponent . . . . .	64
33	Field to select a Street . . . . .	64
34	Button to split Street . . . . .	65
35	Dialog to split street . . . . .	65
36	Filter in AddressPage . . . . .	65
37	ListEditPage . . . . .	66
38	QR-Code for Area . . . . .	67
39	PDF with QR-Codes for all Areas . . . . .	68
40	choose Icon for Special Feature . . . . .	68

## LIST OF FIGURES

---

41	OpenStreetMap attribution . . . . .	69
42	DatabaseViewComponent . . . . .	71
43	InputField examples . . . . .	73
44	FilterRow . . . . .	74

## 21 List of tables

1	Key color combinations with effects(Source: <a href="https://colorpage.ai/blog/color-theory-for-beginners">https://colorpage.ai/blog/color-theory-for-beginners</a> ) . . . . .	41
2	Arbeitszeitrachweis . . . . .	77

## 22 Bibliography

- [13] *A Closer Look at Alpha Shapes in pgRouting*. [Online; accessed 9. Mar. 2025]. May 2013. URL: <https://anitagraser.com/2011/09/25/a-closer-look-at-alpha-shapes-in-pgrouting>.
- [24a] *Defining JPA Entities | Baeldung*. [Online; accessed 6. Mar. 2025]. May 2024. URL: <https://www.baeldung.com/jpa-entities>.
- [24b] *Figure(5): Minimum Bounding Box*. [Online; accessed 9. Mar. 2025]. Oct. 2024. URL: [https://www.researchgate.net/figure/Figure5-Minimum-Bounding-Box\\_fig1\\_354380006?\\_\\_cf\\_chl\\_rt\\_tk=2cm8jQw.EyF0OgDYrFNdEBrnvCwT54nUX\\_GTrS7TdVI-1741475168-1.0.1.1-48mwHWEjdehyHeTJwbeGswcj05vSDIo8qMxaJz.QPMAC](https://www.researchgate.net/figure/Figure5-Minimum-Bounding-Box_fig1_354380006?__cf_chl_rt_tk=2cm8jQw.EyF0OgDYrFNdEBrnvCwT54nUX_GTrS7TdVI-1741475168-1.0.1.1-48mwHWEjdehyHeTJwbeGswcj05vSDIo8qMxaJz.QPMAC).
- [24c] *Host Your Own Worldwide Route Calculator With GraphHopper - GraphHopper Directions API*. [Online; accessed 30. Jan. 2025]. Apr. 2024. URL: <https://www.graphhopper.com/blog/2022/06/27/host-your-own-worldwide-route-calculator-with-graphhopper>.
- [25a] *About GitHub and Git - GitHub Docs*. [Online; accessed 16. Feb. 2025]. Feb. 2025. URL: <https://docs.github.com/en/get-started/start-your-journey/about-github-and-git>.
- [25b] *ChangeNotifier class - foundation library - Dart API*. [Online; accessed 25. Feb. 2025]. Feb. 2025. URL: <https://api.flutter.dev/flutter/foundation/ChangeNotifier-class.html>.
- [25c] *Color Theory for Beginners: Essential Design Tips*. [Online; accessed 4. Mar. 2025]. Mar. 2025. URL: <https://colorpage.ai/blog/color-theory-for-beginners>.
- [25d] *Common Challenges In Batch Processing And How To Overcome Them - FasterCapital*. [Online; accessed 10. Mar. 2025]. Mar. 2025. URL: <https://fastercapital.com/topics/common-challenges-in-batch-processing-and-how-to-overcome-them.html>.
- [25e] *Convex Hull*. [Online; accessed 8. Mar. 2025]. Mar. 2025. URL: <https://usaco.guide/plat/convex-hull?lang=cpp>.
- [25f] *Convex Hull | Brilliant Math & Science Wiki*. [Online; accessed 8. Mar. 2025]. Mar. 2025. URL: <https://brilliant.org/wiki/convex-hull>.
- [25g] *Convex Polygon - Definition, Formulas, Properties, Examples*. [Online; accessed 8. Mar. 2025]. Mar. 2025. URL: <https://www.cuemath.com/geometry/convex>.
- [25h] *flutter/README.md at master · flutter/flutter*. [Online; accessed 23. Jan. 2025]. Jan. 2025. URL: <https://github.com/flutter/flutter/blob/master/README.md>.
- [25i] *Git - Branching and Merging*. [Online; accessed 16. Feb. 2025]. Feb. 2025. URL: <https://git-scm.com/about/branching-and-merging>.
- [25j] *graphhopper*. [Online; accessed 30. Jan. 2025]. Jan. 2025. URL: <https://github.com/graphhopper/graphhopper>.

- 
- [25k] *IntelliJ IDEA – the Leading Java and Kotlin IDE*. [Online; accessed 30. Jan. 2025]. Jan. 2025. URL: <https://www.jetbrains.com/idea>.
- [25l] *Introduction to Project Lombok | Baeldung*. [Online; accessed 6. Mar. 2025]. Jan. 2025. URL: <https://www.baeldung.com/intro-to-project-lombok>.
- [25m] *Mixins*. [Online; accessed 25. Feb. 2025]. Feb. 2025. URL: <https://dart.dev/language/mixins>.
- [25n] *OSM: The simple map that became a global movement*. [Online; accessed 28. Jan. 2025]. Jan. 2025. URL: <https://web.archive.org/web/20240420144212/https://www.directionsmag.com/article/1163>.
- [25o] *pdf | Dart package*. [Online; accessed 2. Mar. 2025]. Mar. 2025. URL: <https://pub.dev/packages/pdf>.
- [25p] *Persisting Entities :: Spring Data JPA*. [Online; accessed 6. Mar. 2025]. Mar. 2025. URL: <https://docs.spring.io/spring-data/jpa/reference/jpa/entity-persistence.html>.
- [25q] *QrPainter class - qr\_flutter library - Dart API*. [Online; accessed 2. Mar. 2025]. Mar. 2025. URL: [https://pub.dev/documentation/qr\\_flutter/latest/qr\\_flutter/QrPainter-class.html](https://pub.dev/documentation/qr_flutter/latest/qr_flutter/QrPainter-class.html).
- [25r] *Quickstart for GitHub Actions - GitHub Docs*. [Online; accessed 16. Feb. 2025]. Feb. 2025. URL: <https://docs.github.com/en/actions/writing-workflows/quickstart>.
- [25s] *Spring Boot*. [Online; accessed 6. Mar. 2025]. Mar. 2025. URL: <https://spring.io/projects/spring-boot>.
- [25t] *Stable*. [Online; accessed 6. Mar. 2025]. Mar. 2025. URL: <https://projectlombok.org/features>.
- [25u] *Stack Overflow Developer Survey 2022*. [Online; accessed 16. Feb. 2025]. Feb. 2025. URL: <https://survey.stackoverflow.co/2022/#version-control-version-control-system>.
- [25v] *The impact of human error rates in manual data entry across multiple systems*. [Online; accessed 10. Mar. 2025]. Mar. 2025. URL: <https://integrationmadeeasy.com/resources/impact-of-human-error-rates>.
- [25w] *Urheberrecht und Lizenz*. [Online; accessed 27. Feb. 2025]. Feb. 2025. URL: <https://www.openstreetmap.org/copyright>.
- [25x] *Visual Studio Code for the Web*. [Online; accessed 30. Jan. 2025]. Jan. 2025. URL: <https://code.visualstudio.com/docs/editor/vscode-web>.
- [25y] *vscode*. [Online; accessed 30. Jan. 2025]. Jan. 2025. URL: <https://github.com/microsoft/vscode>.
- [25z] *What is the Visual Studio Code editor built on*. [Online; accessed 30. Jan. 2025]. Jan. 2025. URL: <https://stackoverflow.com/questions/29966093/what-is-the-visual-studio-code-editor-built-on>.
-

## REFERENCES

---

- [Alg25] AlgoDaily. *AlgoDaily - What Is The Manhattan Distance?* [Online; accessed 4. Mar. 2025]. Mar. 2025. URL: <https://algodaily.com/lessons/what-is-the-manhattan-distance>.
- [All22] Allyant. “Is Google Maps Accessible?” In: *Allyant* (2022). URL: <https://allyant.com/is-google-maps-accessible/>.
- [Aut02] Autoren der Wikimedia-Projekte. *Regulärer Ausdruck – Wikipedia*. [Online; accessed 10. Mar. 2025]. July 2002. URL: [https://de.wikipedia.org/w/index.php?title=Regul%C3%A4rer\\_Ausdruck&oldid=251213016](https://de.wikipedia.org/w/index.php?title=Regul%C3%A4rer_Ausdruck&oldid=251213016).
- [BG08] Sarah E Battersby and Kirk Goldsberry. “User-centered design for digital map navigation tools”. In: *Cartography and Geographic Information Science* 35.4 (2008), pp. 233–244.
- [Bie19] Alessandro Biessek. *Flutter for Beginners: An introductory guide to building cross-platform mobile applications with Flutter and Dart 2*. Packt Publishing Ltd, 2019.
- [Cim23] Mustafa Ciminli. “Simplifying Database Access with Spring Data JPA: A Comprehensive Overview of its Powerful Features”. In: *Medium* (May 2023). URL: [https://medium.com/@mustafa\\_ciminli/simplifying-database-access-with-spring-data-jpa-a-comprehensive-overview-of-its-powerful-features-620c0de4cb91](https://medium.com/@mustafa_ciminli/simplifying-database-access-with-spring-data-jpa-a-comprehensive-overview-of-its-powerful-features-620c0de4cb91).
- [Cod25] CodingNomads. *Spring Boot Tutorial: Build an App with Spring Initializr*. [Online; accessed 6. Mar. 2025]. Mar. 2025. URL: <https://codingnomads.com/spring-boot-tutorial-build-an-app-with-spring-initializr>.
- [Con24a] Contributors to Wikimedia projects. *Adaptive algorithm – Wikipedia*. [Online; accessed 10. Mar. 2025]. Aug. 2024. URL: [https://en.wikipedia.org/w/index.php?title=Adaptive\\_algorithm&oldid=1242668518](https://en.wikipedia.org/w/index.php?title=Adaptive_algorithm&oldid=1242668518).
- [Con24b] Contributors to Wikimedia projects. *Minimum bounding box – Wikipedia*. [Online; accessed 8. Mar. 2025]. Oct. 2024. URL: [https://en.wikipedia.org/w/index.php?title=Minimum\\_bounding\\_box&oldid=1249919681](https://en.wikipedia.org/w/index.php?title=Minimum_bounding_box&oldid=1249919681).
- [Con25a] Contributors to Wikimedia projects. *Alpha shape – Wikipedia*. [Online; accessed 8. Mar. 2025]. Mar. 2025. URL: [https://en.wikipedia.org/w/index.php?title=Alpha\\_shape&oldid=1278461386](https://en.wikipedia.org/w/index.php?title=Alpha_shape&oldid=1278461386).
- [Con25b] Contributors to Wikimedia projects. *Convex hull – Wikipedia*. [Online; accessed 8. Mar. 2025]. Mar. 2025. URL: [https://en.wikipedia.org/w/index.php?title=Convex\\_hull&oldid=1278659713](https://en.wikipedia.org/w/index.php?title=Convex_hull&oldid=1278659713).
- [Con25c] Contributors to Wikimedia projects. *Data validation – Wikipedia*. [Online; accessed 24. Feb. 2025]. Feb. 2025. URL: [https://en.wikipedia.org/w/index.php?title=Data\\_validation&oldid=1276518123](https://en.wikipedia.org/w/index.php?title=Data_validation&oldid=1276518123).
- [Con25d] Contributors to Wikimedia projects. *Delaunay triangulation – Wikipedia*. [Online; accessed 8. Mar. 2025]. Mar. 2025. URL: [https://en.wikipedia.org/w/index.php?title=Delaunay\\_triangulation&oldid=1278482810](https://en.wikipedia.org/w/index.php?title=Delaunay_triangulation&oldid=1278482810).

- 
- [Con25e] Contributors to Wikimedia projects. *IntelliJ IDEA - Wikipedia*. [Online; accessed 30. Jan. 2025]. Jan. 2025. URL: [https://en.wikipedia.org/w/index.php?title=IntelliJ\\_IDEA&oldid=1272820016](https://en.wikipedia.org/w/index.php?title=IntelliJ_IDEA&oldid=1272820016).
- [Dag19] Lukas Dagne. “Flutter for cross-platform App and SDK development”. In: (2019).
- [De 24a] Kalana De Silva. “Building the Service Layer in Spring Boot - Kalana De Silva - Medium”. In: *Medium* (Nov. 2024). URL: <https://medium.com/@kalanamalshan98/building-the-service-layer-in-spring-boot-dbbc900b0853>.
- [De 24b] Kalana De Silva. “Implementing the Controller Layer in Spring Boot - Kalana De Silva - Medium”. In: *Medium* (Nov. 2024). URL: <https://medium.com/@kalanamalshan98/implementing-the-controller-layer-in-spring-boot-8c4e5928d888>.
- [De 24c] Kalana De Silva. “Repository Layer and Custom Queries in Spring Boot - Kalana De Silva - Medium”. In: *Medium* (Nov. 2024). ISSN: 1263-5458. URL: <https://medium.com/@kalanamalshan98/repository-layer-and-custom-queries-in-spring-boot-1b26d3545c8c>.
- [Enc23] Encora. “Machine Learning: What is Adaptive ML?” In: *Encora* (Nov. 2023). URL: <https://insights.encora.com/insights/machine-learning-what-is-adaptive-ml>.
- [Fro+19] Jon E Froehlich et al. “Grand challenges in accessible maps”. In: *Interactions* 26.2 (2019), pp. 78–81.
- [Gee24a] GeeksforGeeks. “Convex Hull Algorithm”. In: *GeeksforGeeks* (Aug. 2024). URL: <https://www.geeksforgeeks.org/convex-hull-algorithm>.
- [Gee24b] GeeksforGeeks. “Latency vs. Accuracy in System Design”. In: *GeeksforGeeks* (Oct. 2024). URL: <https://www.geeksforgeeks.org/latency-vs-accuracy-in-system-design>.
- [Ham23] Nasrullah Hamidli. “Introduction to UI/UX design: key concepts and principles”. In: *Academia*. URL: [https://www.academia.edu/98036432/Introduction\\_to\\_UI\\_UX\\_Design\\_Key\\_Concepts\\_and\\_Principles](https://www.academia.edu/98036432/Introduction_to_UI_UX_Design_Key_Concepts_and_Principles) [accessed 2024-04-27] (2023).
- [hel24] hello. “Real-time Data Integration Challenges: Explained - Vexdata”. In: *Vexdata* (June 2024). URL: <https://vexdata.io/real-time-data-integration-challenges-explained>.
- [Ibm24] Ibm. *Java Spring Boot*. [Online; accessed 6. Mar. 2025]. Dec. 2024. URL: <https://www.ibm.com/think/topics/java-spring-boot>.
- [Lal23] Vishamber Lal. “Understanding Data Transfer Objects (DTO) in Spring Boot”. In: *Medium* (Dec. 2023). URL: <https://medium.com/@vishamberlal/understanding-data-transfer-objects-dto-in-spring-boot-ac06b575a1d5>.
- [Lim25] Infosys Limited. *The key components of Data integration – glossary | Infosys BPM*. [Online; accessed 10. Mar. 2025]. Mar. 2025. URL: <https://www.infosysbpm.com/glossary/data-integration.html>.
-

## REFERENCES

---

- [Luc25] G. W. Lucas. *Delaunay Triangulation*. [Online; accessed 9. Mar. 2025]. Feb. 2025. URL: <https://gwlucastrig.github.io/TinfourDocs/DelaunayIntro/index.html>.
- [McB25] Martin McBride. *GraphicMaths - Other types of polygon*. [Online; accessed 8. Mar. 2025]. Feb. 2025. URL: <https://graphicmaths.com/gcse/geometry/other-polygons>.
- [Mee24] Meet2sudhakar. “Why we need a service layer in Spring boot rest API application”. In: *Medium* (Nov. 2024). URL: <https://medium.com/@meet2sudhakar/why-we-need-a-service-layer-in-spring-boot-rest-api-application-db20e4b2a027>.
- [Men24] Mendes. “Dependency Injection In Java made easy (With Lombok)”. In: *Medium* (Jan. 2024). URL: <https://medium.com/%40mendesskrillacc/dependency-injection-in-java-made-easy-with-lombok-0dfc0fc34248>.
- [Nie24a] Jakob Nielsen. “Usability 101: Introduction to Usability”. In: *Nielsen Norman Group* (Jan. 2024). URL: <https://www.nngroup.com/articles/usability-101-introduction-to-usability>.
- [Nie24b] Rick Nieters. “Was ist Fuzzy Matching? Eine nicht so fuzzy Erklärung”. In: *Klippa* (Dec. 2024). URL: <https://www.klippa.com/de/blog/informativ/fuzzy-matching-de>.
- [Pat24] Uday Patil. “Spring Boot Architecture - Uday Patil - Medium”. In: *Medium* (Nov. 2024). URL: <https://medium.com/@udaypatil318/spring-boot-architecture-39935654ce5c>.
- [Ran24] Shahab Ranjbary. “Choosing the Right Real-Time Stream Processing Framework”. In: *DEV Community* (Sept. 2024). URL: <https://dev.to/ranjbaryshahab/comparing-top-real-time-stream-processing-frameworks-ek8>.
- [Tri23] Bubu Tripathy. “Best Practices: Entity Class Design with JPA and Spring Boot”. In: *Medium* (Aug. 2023). ISSN: 6703-3393. URL: <https://medium.com/@bubu.tripathy/best-practices-entity-class-design-with-jpa-and-spring-boot-6f703339ab3d>.
- [Wik24] OpenStreetMap Wiki. *Main Page — OpenStreetMap Wiki*. [Online; accessed 28-January-2025]. 2024. URL: [https://wiki.openstreetmap.org/w/index.php?title=Main\\_Page&oldid=2752444](https://wiki.openstreetmap.org/w/index.php?title=Main_Page&oldid=2752444).



## 23 Abbreviation

VCS	Version Control System
API	Application Programming Interface
CI CD	Continuous Integration & Continuous Deployment
OSM	Open Street Map
GIS	Geo Information System
GH	GraphHopper
IDE	Integrated Development Environment
GPS	Global Positioning System
GUI	Graphical User Interface
ADB	Android Debugging Bridge
CRUD	Create Read Update Delete
REST	REpresentational State Transfer
JVM	Java Virtual Machine
RGB	Red Green Blue
CMY	Cyan Magenta Yellow
PDF	Portable Document Format
UI	User Interface
CSV	Comma Separated Values
XML	eXtensible Markup Language
JSON	JavaScript Object Notation
HTML	Hyper Text Markup Language