Gig Performer® 4 SDK Version 4.1
Deskew Technologies, LLC Confidential
NDA required for access
Do not redistribute
November 1st, 2021
Copyright © Deskew Technologies, LLC

Prolog

Before you consider writing a library for use with Gig Performer, please familiarize yourself with the operation of Gig Performer itself so that you have a reasonable understanding of its capabilities and functionality that might impact your library.

Introduction

Starting with Gig Performer 4, Gig Performer (GP from now on) exposes an API that allows third party developers to create libraries that can be used to control GP and to respond to events in GP. The primary purpose of the API is to enable the creation of libraries to manage control surfaces and other hardware that one might want to use with GP. This SDK includes the source code that will need to be included in every third party project as well as some samples that will help to get started.

Fundamentals

1) GP will query all libraries found in /Users/Shared/Gig Performer/ThirdParty (OS X) and in C:\Users\All Users\Gig Performer\ThirdParty (Windows) to collection information (product name, build date, description, etc). This information will be displayed to the user who can decide which libraries should be loaded and used.
2) GP will next load the desired libraries.
3) GP exposes a collection of functions that a library can call to interact with the application. For example, you can set the current value of a widget[1] in a rackspace. You can ask for the number of songs in the current setlist, get the name of each song, get the names of all the song parts in a song, switch from one song to another and so forth. The library can of course also send MIDI events into GP.
4) The GP API supports callbacks into the third party library to notify the library that something "happened". For example, if the user switches from one song to another, a library supporting a keyboard controller with a programmable display could be notified so that it can display the names of the song parts in the new song. If the library is interested in MIDI events coming from a particular piece of hardware, it can be called whenever that hardware sends out MIDI data.

[1] The widget must have a handle defined

Gig Performer® and Own The Stage® are registered trademarks of Deskew Technologies, LLC

Structure of the API

The underlying API is defined as a collection of typedefs and functions in C as this will allow almost any language to be used to develop a library as long as it can make C calls. Simple examples are provided in C++ and shell scripts are included to automate the build process. The example class included for the C++ example will perform some initial operations automatically so that the user does not need to be concerned with low level setup.

Working with the API

When GP is first loaded, it will looked for third party libraries. For each library that it finds, the following sequence of steps will be performed

1) GP will open the library
2) GP will look for a function called GPQueryLibrary. If found, it will be invoked so that the library can return useful information about itself thereby allowing the user to decide whether to use a particular library. The information should be returned as a small XML formatted string.
   `extern "C" EXPORTED void GPQueryLibrary(char* xmlInfoBuffer, int bufferLength);`
3) GP will then close the library
4) For all libraries that the user chooses to load, GP will then open the library again and will look for a function called GPRegister
   `const char* GPRegister(TGetGPFunctionType getGPFunctionAddress, void* handle)`
5) If the function is found, it will be called with two parameters:
   a. **`void* (*TGetGPFunctionType)(void* handle, const char* functionName)`**
      The first parameter is the address of a function that the library can use to call back into GP to request the address of each function that GP exposes to the API.
   b. The second parameter, **`void* handle`**, is an opaque handle whose value should be stored and included as a parameter in all subsequent calls into Gig Performer.
   c. The function should return a string that represents the name of the control surface or whatever product this library supports. That name will show up in a list that the user can view and choose to enable or disable.
6) Your implementation of this function should include calls to get the addresses of all the other available functions exposed by GP so that you can use them later. Note that the C++ wrapper will do this automatically. Here is an example of the raw GPRegister function in raw C along with a single callback

```
extern “C” EXPORTED void GPRegister(TGetGPFunctionType getGPFunctionAddress,
void* handle)
    {
       Handle = handle; Store the handle for future use
       InitializeImportedFunctions(handle, getGPFunctionAddress);

       //You will need to register callbacks to be informed of changes
```

Gig Performer® and Own The Stage® are registered trademarks of Deskew Technologies, LLC

```
        GP_RegisterCallback(handle, "OnSongChanged");
    }

extern “C” EXPORTED void OnSongChanged(int oldIndex, int newIndex)
    {
        char str[255];
        sprintf(str, "Song changed from: %d, to: %d", oldIndex, newIndex);
        GP_Log(Handle, str);
    }
```

7) Register for whatever other callbacks your library will need. However, to keep your library mean and lean, please don’t just arbitrarily register for all callbacks.
8) Your library is now ready to interact with Gig Performer and whatever hardware you are controlling

Gig Performer® and Own The Stage® are registered trademarks of Deskew Technologies, LLC

Function list

Following is a list of C functions exported by GP that can be called from a library

---

`bool GP_RegisterCallback(LibraryHandle h, const char* callbackName);`
Specify the name of the callback function to be called when the respective event occurs. The callback must be implemented in your library as an exported function with a name known to GP

`bool GP_UnregisterCallback(LibraryHandle h, const char* callbackName);`
Inform GP that you no longer want to be called back when the respective event occurs.

`void GP_SetPlayheadState(LibraryHandle h, bool play);`
Enable or disable the global playhead.

`bool GP_GetPlayheadState(LibraryHandle h);`
Get the global playhead state

`void GP_ShowTuner(LibraryHandle h, bool show);`
Switch into or out of tuner view.

`bool GP_TunerShown(LibraryHandle h);`
Indicates whether the tuner is visible.

`int GP_GetPathToMe(LibraryHandle h, char* returnBuffer, int bufferLength);`
Returns the folder path where your library is installed. It is useful when you need to access other resource files installed in the same or a relative location to the library.

`int GP_GetPathToMe(LibraryHandle h, char* returnBuffer, int bufferLength);`
Returns the folder path where your library is installed. It is useful when you need to access other resource files installed in the same or a relative location to the library.

`void GP_SwitchToSetlistView(LibraryHandle h);`
Switch Gig Performer to Setlist View

`void GP_SwitchToWiringView(LibraryHandle h);`
Switch Gig Performer to the plugin wiring view

`void GP_SwitchToPanelView(LibraryHandle h);`
Switch Gig Performer to the front panel and widgets view

Gig Performer® and Own The Stage® are registered trademarks of Deskew Technologies, LLC

```
int GP_GetPluginList(LibraryHandle h, char* returnBuffer,
                     int bufferLength, bool useGlobalRackspace);
```
Get a list of all plugins defined (i.e, with handles) in the currently active rackspace or in the global rackspace. The return value is the actual number of characters needed for the return value.

```
bool GP_PluginExists(LibraryHandle h, const char* pluginHandle, bool
useGlobalRackspace);
```
Returns whether the plugin with the given handle exists in the currently active rackspace or in the global rackspace.

```
bool GP_SetPluginParameter(LibraryHandle h, const char* pluginHandle, int
parameterNumber, double value, bool useGlobalRackspace);
```
Set a parameter value for a plugin with the given handle in the currently active rackspace or in the global rackspace.

```
double GP_GetPluginParameter(LibraryHandle h, const char* pluginHandle, int
parameterNumber, bool useGlobalRackspace);
```
Returns the value of the given parameter in the plugin with the given handle in the currently active rackspace or in the global rackspace.

```
double GP_GetPluginParameterCount(LibraryHandle h, const char* pluginHandle,
bool useGlobalRackspace);
```
Returns the number of parameters exposed by the plugin with the given handle in the currently active rackspace or in the global rackspace.

```
int GP_GetPluginParameterName(LibraryHandle h, const char* pluginHandle, int
parameterNumber, char* returnBuffer, int bufferLength, bool
useGlobalRackspace);
```
Returns the name of the parameter at the specified parameter number of the plugin with the given handle in the currently active rackspace or in the global rackspace.

```
int GP_GetWidgetList(LibraryHandle h, char* returnBuffer,
                     int bufferLength, bool useGlobalRackspace);
```
Get a list of all widgets defined (i.e, with handles) in the currently active rackspace or in the global rackspace. The return value is the actual number of characters needed for the return value.

```
bool GP_WidgetExists(LibraryHandle h, const char*  widgetName);
```
Query GP to see if a widget with the given name exists in the currently active rackspace

---

```
double GP_GetWidgetValue(LibraryHandle h, const char*  widgetName);
```
Get the current value (widget position) of the named widget

Gig Performer® and Own The Stage® are registered trademarks of Deskew Technologies, LLC

```
int GP_GetWidgetTextValue(LibraryHandle h, const char*  widgetName,
                          char* returnBuffer, int bufferLength);
```
Get the current text value of the named widget. The text value may not be numeric if the parameter connected to this widget provides one. The return value is the actual number of characters needed for the return value.

```
bool GP_SetWidgetValue(LibraryHandle h, const char*  widgetName,
                       double newValue);
```
Set the value of a named widget.

```
bool GP_ResetWidgetToDefault(LibraryHandle h, const char*  widgetName,
                             double newDefault);
```
Resets a widget back to its predefined default value if newDefault is -1. If newDefault is between 0.0 and 1.0 then save this as new default value but do not change the widget value

---

```
bool GP_SetWidgetCaption(LibraryHandle h, const char*  widgetName,
                         const char*  newCaption);
```
Set the label for a widget

```
int GP_GetWidgetCaption(LibraryHandle h, CharPtr widgetName,
                        char* returnBuffer, int bufferLength)
```
Get the label for a widget. The library must provide a character buffer and indicate its size. GP will fill in the buffer with the caption. The return value is the actual number of characters needed for the return value.

```
bool GP_ListenForWidget(LibraryHandle h, const char*  widgetName, bool
listen);
```
Tell GP to call (or stop calling) the OnWidgetValueChanged callback for the named widget

---

```
bool GP_ListeningForWidget(LibraryHandle h, const char*  widgetName);
```
Query GP to see if you are listening for widget changes

```
bool GP_ListenForMidi(LibraryHandle h, const char*  deviceName, bool listen);
```
Tell GP to call (or stop calling) the OnMidiIn callback when MIDI events arrive at the specified device name

---

```
bool GP_ListeningForMidi(LibraryHandle h, const char*  deviceName);
```
Query GP to see if you are listening for MIDI events from a specified device name

---

```
int GP_GetMidiInDeviceCount(LibraryHandle h);
```
Query GP for the number of available Midi In devices

Gig Performer® and Own The Stage® are registered trademarks of Deskew Technologies, LLC

```
int GP_GetMidiInDeviceName(LibraryHandle h, int index,
                           char* returnBuffer, int bufferLength);
```

Query GP for the name of a Midi Input device at the specified index (zero-based). The library must provide a character buffer and indicate its size. GP will fill in the buffer with the name. The return value represents the actual length needed to fill the buffer.

```
int GP_GetMidiOutDeviceCount(LibraryHandle h);
```

Query GP for the number of available Midi Out devices

```
int GP_GetMidiOutDeviceName(LibraryHandle h, int index,
                            char* returnBuffer, int bufferLength);
```

Query GP for the name of a Midi Output device at the specified index (zero-based). The library must provide a character buffer and indicate its size. GP will fill in the buffer with the name. The return value represents the actual length needed to fill the buffer.

```
int (*TGP_TextToHexString)(LibraryHandle h, const char* text,
                           uint8_t* returnBuffer, int bufferLength);
```

Convert ascii text into a hex string, suitable for including in a sysex message

---

```
void GP_SendMidiMessageToMidiOutDevice(LibraryHandle h,
                                       const char* deviceName,
                                       const uint8_t* midiData, int length);
```

Send a MIDI message to the specified Midi Output device. It is the library's responsibility to ensure that the message is valid

---

```
void GP_InjectMidiMessageToMidiInputDevice(LibraryHandle h,
                                           const char* deviceName,
                                           const uint8_t* midiData,
                                           int length);
```

Insert a Midi message into Gig Performer such that GP will respond to it as if it actually came from the specified device. It is the library's responsibility to ensure that the message is valid

---

```
void GP_InjectMidiMessageToMidiInputAlias(LibraryHandle h,
                                          const char* rigManagerAlias,
                                          const uint8_t* midiData,
                                          int length);
```

Insert a Midi message into Gig Performer such that GP will respond to it as if it actually came from the specified Rig Manager global name/alias. It is the library's responsibility to ensure that the message is valid.

```
int GP_GetSongCount(LibraryHandle h);
```

Query GP for the list of songs currently available

Gig Performer® and Own The Stage® are registered trademarks of Deskew Technologies, LLC

```
int GP_GetSongName(LibraryHandle h, int atSongIndex,
                   char* returnBuffer, int bufferLength);
```
Query GP for the name of a song at the given index (zero based). The library must provide a character buffer and indicate its size. GP will fill in the buffer with the name. The return value represents the actual length needed to fill the buffer.

```
int GP_GetCurrentSongIndex(LibraryHandle h);
```
Query GP for the index of the currently selected song

```
int GP_GetSongpartCount(LibraryHandle h, int atSongIndex);
```
Query GP for the number of song parts in the song at the given index

---

```
int GP_GetSongpartName(LibraryHandle h, int atSongIndex, int atIndex,
                       char* returnBuffer, int bufferLength);
```
Query GP for the name of the song part at the specified (zero-based) index of the specified song. The library must provide a character buffer and indicate its size. GP will fill in the buffer with the name. The return value represents the actual length needed to fill the buffer.

```
int GP_GetCurrentSongpartIndex(LibraryHandle h);
```
Query GP for the index of the currently selected song part index

---

```
bool GP_InSetlistMode(LibraryHandle h);
```
Query GP to see if it is in setlist mode

```
bool GP_SwitchToSong(LibraryHandle h, int songIndex, int partIndex);
```
Tell GP to switch to the song and song part with the given indices

---

```
bool GP_SwitchToSongPart(LibraryHandle h, int partIndex);
```
Tell GP to switch to the song part with the given index in the current song

---

```
void GP_ConsoleLog(LibraryHandle h, const char*  message);
```
Send the message to the console output (works only when Xcode is open)

```
void GP_ScriptLog(LibraryHandle h, const char*  message, bool openLogWindow);
```
Display the message in the Script Logger window, possibly opening the window if it's not already open

---

```
int GP_GetRackspaceCount(LibraryHandle h);
```
Returns the number of rackspaces in the gig file

```
int GP_GetRackspaceName(LibraryHandle h, int atIndex,
                        char* returnBuffer, int bufferLength);
```
Get the name of rackspace atIndex

Gig Performer® and Own The Stage® are registered trademarks of Deskew Technologies, LLC

```
int GP_GetCurrentRackspaceIndex(LibraryHandle h);
```
Get the rackspace currently in use

```
int GP_GetCurrentVariationIndex(LibraryHandle h);
```
Get the currently selected variation

```
int GP_GetVariationCount(LibraryHandle h, int atRackspaceIndex);
```
Get the number of variations in the given rackspace

```
int GP_GetVariationName(LibraryHandle h,int atRackspaceIndex, int atIndex,
                        char* returnBuffer, int bufferLength);
```
Get the name of a specific variation at the given rackspace index

```
bool GP_SwitchToRackspace(LibraryHandle h, int rackspaceIndex, int
variationIndex);
```
Switch to the given rackspace and variation. Returns whether successful

```
bool GP_SwitchToRackspaceName(LibraryHandle h, const char* rackspaceName,
                              const char* variationName);
```
Switch to the named rackspace and variation. Returns whether successful

```
bool saveGigUnconditionally(bool withTimestamp);
```
Try to save the file (normally overwriting the existing one). However, if withTimestamp is true, then create a subfolder with the same name as the gigfile and save the current file in it, appending the current time to it. (Time Stamp not yet implemented)

```
bool loadGigByIndex(int indexNumber);
```
Look for a gigfile in a special folder (TBD) that has the prefix indexNumber and try to load it. NOT YET IMPLEMENTED

```
void tap();
```
Same as clicking the global TapTempo button

```
void previous();
```
Move to previous variation or rackspace

```
void next();
```
Move to next variation or rackspace

Gig Performer® and Own The Stage® are registered trademarks of Deskew Technologies, LLC

Callbacks list

Following is a list of callbacks that GP can invoke to which your library can respond. You must register the callback by name to be able to receive these callbacks.

```
bool OnMidiIn(const char*  deviceName, const uint8_t* data, int length);
```

Returns whether the midi event should be passed on to the next handler

---

```
void OnClose();
```

Called when Gig Performer is about to shut down

```
void OnEditStateChanged(bool inEditState);
```

Called when user enters or exits widget editing state.

```
void OnSwitchToWiringView();
```

called when the user switches into the plugin wiring view

```
void OnSwitchToPanelView();
```

Called when the user switches into the panel view mode. Note that if you are in the wiring view and you switch directly to setlist mode, there will also be a switch back to panel view call

---

```
void OnModeChanged(int mode);
```

Called when the user switches between Panel/Wiring (0) and Setlist (1) mode

---

```
void OnGigLoaded();
```

Called when a new gig file has finished being loaded

```
void OnMidiDeviceListChanged(const char** inputs, int intputCount,
                             const char** outputs, int outputCount);
```

Called when a MIDI device is connected or disconnected from the computer. You get an array of strings for the input names and for the output names

---

```
void OnOpen();
```

Called when Gig Performer has finished initializing itself

```
void OnRackspaceChanged();
```

Called when user switches to a new rackspace

```
void OnSongChanged(int oldIndex, int newIndex);
```

Called when user switches to a new song in setlist mode

```
void OnSongPartChanged(int oldIndex, int newIndex);
```

Called when we switch to a new song part

Gig Performer® and Own The Stage® are registered trademarks of Deskew Technologies, LLC

`void OnTunerModeChanged(bool visible);`
Called when the user switches in or out of tuner mode

`void OnGlobalPlayStateChanged(bool playing);`
Called when the global play mode switches on or off

`void OnVariationChanged(int oldIndex, int newIndex);`
Called when user switches from one variation to another

`void OnWidgetValueChanged(const char* widgetName, double newValue);`
Called when a widget is turned or otherwise adjusted. The library must register its interest in listening for such changes.

`void OnWidgetCaptionChanged(const char* widgetName, const char* newValue);`
Called when a widget caption is changed. The library must register its interest in listening for such changes.

`void OnWidgetStateChanged(const char* widgetName, int newState);`
Called when a widget handle is defined (newState = 0) or removed (newState = 1). The library must register its interest in listening for such changes.

`void OnSetlistChanged(const char* newSetlistName);`
Called when the user switches the setlist. The library must register its interest in listening for such changes.

Gig Performer® and Own The Stage® are registered trademarks of Deskew Technologies, LLC

Optional functions that your library can provide

Panel support

If your library includes resources such as predefined front panels, you will need to implement the following three functions so that Gig Performer can query your library to get access to the panels that are available through your library. If you are working in C++, make sure you enclose these functions with **extern "C"** so as to ensure the appropriate calling conventions are used.

```
EXPORTED int GetPanelCount();
```

Return the number of panels available from this library

```
EXPORTED int GetPanelName(int index, char* buffer, int bufferLength);
```

Fill the buffer with the name of a panel at the specified index up to the maximum buffer size. The function returns the number of bytes that would be needed for the full panel name and you can call the function again with a larger buffer if necessary.

```
EXPORTED int GetPanelXML(int index, char* buffer, int bufferLength);
```

Fills the buffer with a chunk of XML code representing a predefined panel. You can create these by saving a Gig Performer panel. The function returns the number of bytes that would be needed for the full panel name and you can call the function again with a larger buffer if necessary.

Menu support

Gig Performer allows your library to register menu items that a user can select to invoke functionality implemented in your library. You will need to implement the following three functions for this feature to work. If you are working in C++, make sure you enclose these functions with **extern "C"** so as to ensure the appropriate calling conventions are used.

```
EXPORTED int GetMenuCount();
```

Return the number of menu items available from this library

```
EXPORTED int GetMenuName(int index, char* buffer, int bufferLength);
```

Fill the buffer with the name of a menu at the specified index up to the maximum buffer size. The function returns the number of bytes that would be needed for the full menu name and you can call the function again with a larger buffer if necessary.

```
EXPORTED void InvokeMenu(int index);
```

Invokes the code in your library associated with the provided menu index.

Gig Performer® and Own The Stage® are registered trademarks of Deskew Technologies, LLC

The C++ Wrapper

While the underlying C-style interface will allow developers to use almost any language they wish provided there is a C interface to it, many developers are familiar with C++ and so we provide some C++ classes around the underlying C interface to make it easier to get started. The C++ wrappers include some useful support classes to faciliate the creation of MIDI messages, particularly sysex messages from strings as well as some other generally useful functions. See the contents of the folder GP_SDK/interfaces/CPP for more information.
To use the C++ wrapper, the only file you need to modify is called LibMain.h which must inherit from GigPerformerAPI (defined below). You need only implement the methods for events in which you are interested.

GigPerformerAPI

This class defines all the callbacks to which you can respond.

```
class GigPerformerAPI : public GigPerformerFunctions
{
   public:
      // This MUST be defined in your class to describe your product
      virtual std::string GetProductDescription() = 0;
      // Use this to register callbacks and to do any other setup you need
      virtual void Initialization();
      virtual void OnEditStateChanged(bool inEditState);
      virtual void OnModeChanged(int mode);
      virtual void OnSwitchToPanelView();
      virtual void OnSwitchToWiringView();
      virtual void OnTunerModeChanged(bool visible);
      virtual void OnGlobalPlayStateChanged(bool playing);
      virtual void OnWidgetValueChanged(const std::string & widgetName,
                                        double newValue);
      virtual void OnWidgetCaptionChanged(const std::string & widgetName,
                                        const std::string & newValue);
      virtual void OnWidgetStateChanged(const std::string & widgetName,
                                        int newState);
      virtual void OnMidiDeviceListChanged(std::vector< std::string> & inputs,
                                           std::vector< std::string> & outputs);
      virtual bool OnMidiIn(const std::string & deviceName,
                            const uint8_t* data, int length);
      virtual void OnGigLoaded();
      virtual void OnSetlistChanged(const std::string & newSetlistName);

      virtual void OnSongChanged(int oldIndex, int newIndex);
      virtual void OnSongPartChanged(int oldIndex, int newIndex);
      virtual void OnRackspaceChanged();
      virtual void OnVariationChanged(int oldIndex, int newIndex);
      virtual void OnOpen();
      virtual void OnClose();
```

Gig Performer® and Own The Stage® are registered trademarks of Deskew Technologies, LLC

```
   public:
      virtual int GetPanelCount();
      virtual std::string GetPanelName(int index);
      virtual std::string GetPanelXML(int index);

      virtual int GetMenuCount();
      virtual std::string GetMenuName(int index);
      virtual void InvokeMenu(int itemIndex);

      GigPerformerAPI(LibraryHandle handle) : GigPerformerFunctions(handle) {}
      virtual ~GigPerformerAPI() {}
};
```

This class inherits from a parent class, GigPerformerFunctions, which defines all the functions your library can call to access/manipulate Gig Performer itself.

GigPerformerFunctions

```
class GigPerformerFunctions
{
public:
   GigPerformerFunctions(LibraryHandle handle);
   virtual ~GigPerformerFunctions();

   bool registerCallback(const std::string & callbackName);
   bool unregisterCallback(const std::string & callbackName);

   void setPlayheadState(bool play);
   bool getPlayheadState();

   void showTuner(bool show);
   bool tunerShowing();

   void switchToSetlistView();
   void switchToWiringView();
   void switchToPanelView();

   void getPluginList(std::vector<std::string> & list , bool useGlobalRackspace);
   bool pluginExists(const std::string & pluginHandle, bool useGlobalRackspace);

   void setPluginParameter(const std::string & pluginHandle, int parameterNumber,
double value , bool useGlobalRackspace);
   double getPluginParameter(const std::string & pluginHandle, int parameterNumber,
bool useGlobalRackspace);
```

Gig Performer® and Own The Stage® are registered trademarks of Deskew Technologies, LLC

```
   int getPluginParameterCount(const std::string & pluginHandle, bool
useGlobalRackspace);
   std::string getPluginParameterName(const std::string & pluginHandle, int
parameterIndex, bool useGlobalRackspace);
```

```
   void getWidgetList(std::vector<std::string> & list, bool useGlobalRackspace );
   bool widgetExists(const std::string & widgetName);
   double getWidgetValue(const std::string & widgetName);
   bool setWidgetValue(const std::string & widgetName, double newValue);
   bool  resetWidgetToDefault(const std::string & widgetName, double newDefault = -1);
   bool setWidgetCaption(const std::string &  widgetName, const std::string &
newCaption);
   std::string getWidgetCaption(const std::string &  widgetName);
   bool  listenForWidget(const std::string & widgetName, bool listen);
   bool  listeningForWidget(const std::string & widgetName);

   bool  listenForMidi(const std::string & deviceName, bool listen);
   bool  listeningForMidi(const std::string & deviceName);
   int  getMidiInDeviceCount();
   std::string  getMidiInDeviceName(int index);
   int  getMidiOutDeviceCount();
   std::string  getMidiOutDeviceName(int index);
   void  sendMidiMessageToMidiOutDevice(const std::string & deviceName, const uint8_t*
midiData, int length);
   void  sendMidiMessageToMidiOutDevice(const std::string & deviceName, std::string &
midiData);
   void sendMidiMessageToMidiOutDevice(const std::string & deviceName, const
GPMidiMessage & message);
   std::string  textToHexString(const std::string & text);
   void  injectMidiMessageToMidiInputDevice(const std::string & deviceName, const
uint8_t* midiData, int length);
   void  injectMidiMessageToMidiInputDevice(const std::string & deviceName,
std::string & midiData);
   void  injectMidiMessageToMidiInputAlias(const std::string & rigManagerAlias, const
uint8_t* midiData, int length);
   void  injectMidiMessageToMidiInputAlias(const std::string & rigManagerAlias,
std::string & midiData);

   int  getSongCount();
   std::string GetSongName(int atIndex);
   int  getCurrentSongIndex();
   int  getSongpartCount(int atSongIndex);
   std::string getSongpartName(int atSongIndex, int atIndex);
   int  getCurrentSongpartIndex();
   bool inSetlistMode();
   bool switchToSong(int songIndex, int partIndex);
   bool switchToSongPart(int partIndex);
```

Gig Performer® and Own The Stage® are registered trademarks of Deskew Technologies, LLC

```
   void consoleLog(const char* message);
   void consoleLog(const std::string & message);
   void scriptLog(const char* message, bool openLogWindow);
   void scriptLog(const std::string & message, bool openLogWindow);

   int getRackspaceCount();
   std::string getRackspaceName(int atIndex);
   int getCurrentRackspaceIndex();
   int getCurrentVariationIndex();
   int getVariationCount(int atRackspaceIndex);
   std::string getVariationName(int atRackspaceIndex, int atIndex);
   bool switchToRackspace(int rackspaceIndex, int variationIndex = 0);
   bool switchToRackspaceName(const std::string & rackspace, const std::string &
variation = "");

   bot saveGigUnconditionally(bool withTimestamp);
   bool loadGigByIndex(int indexNumber);

   void tap();
   void previous();
   void next();





private:
   LibraryHandle fHandle;
};
```

Copyright © Deskew Technologies, LLC 2021-2022

Gig Performer® and Own The Stage® are registered trademarks of Deskew Technologies, LLC

Gig Performer® and Own The Stage® are registered trademarks of Deskew Technologies, LLC