

Import relevant packages here.

```
In [7]: import matplotlib.pyplot as plt
import pandas as pd
import numpy as np
```

Load the data and verify it is loaded correctly.

- Print it (head, tail, or specific rows, choose a sensible number of rows).
- Compare it to the source file.

```
In [8]: data = pd.read_csv("cf_data.csv")

#data.head()
data.tail()
```

```
Out[8]:
```

	dv	s	a
73903	5.19874	116.139	-0.795081
73904	5.10428	115.627	-0.314263
73905	5.13764	115.118	0.232283
73906	5.15348	114.599	0.262078
73907	5.25868	113.112	-0.612440

In the ensuing, you will use `numpy`.

Let's create a grid for the values to plot. But first create **two arrays named `dv` and `s`** using `numpy.linspace` that hold the grid values at the relevant indices in their respective dimension of the grid.

Create a **grid named `a`** with zeros using `numpy.zeros` in to which calculated acceleration values can be stored.

Let the grid span:

- Speed difference `dv` [m/s]
 - From -10 till 10
 - With 41 evenly spaced values
- Headway `s` [m]
 - From 0 till 200
 - With 21 evenly spaced values

```
In [9]: dv = np.linspace(-10,10,41)
s = np.linspace(0,200,21)
a = np.zeros((len(dv),len(s)))

# print(a)
```

Create from the imported data 3 separate `numpy` arrays for each column `dv`, `s` and `a`. (We do this for speed reasons later.)

- Make sure to name them differently from the arrays that belong to the grid as above.
- You can access the data of each column in a `DataFrame` using `data.xxx` where `xxx` is the column name (not as a string).
- Use the method `to_numpy()` to convert a column to a `numpy` array.

```
In [10]: DV = data.dv.to_numpy()
S = data.s.to_numpy()
A = data.a.to_numpy()
```

Create an algorithm that calculates all the acceleration values and stores them in the grid. The algorithm is described visually in the last part of the lecture. At each grid point, it calculates a weighted mean of all measurements. The weights are given by an exponential function, based on the 'distance' between the grid point, and the measurement values of `dv` and `s`. To get you started, how many `for`-loops do you need?

For this you will need math.

Use an *upsilon* of 1.5m/s and a *sigma* of 30m.

Warning: This calculation may take some time. So:

- Print a line for each iteration of the outer-most `for`-loop that shows you the progress.
- Test your code by running it only on the first 50 measurements of the data.

```
In [11]: import math

upsilon = 1.5
sigma = 30

for i, grid_point_dv in enumerate(dv):
    print(f"Processed grid row {i+1}")
    for j, grid_point_s in enumerate(s):
```

```

        weighted_sum = 0
        weight_total = 0
        for dv_val, s_val, a_val in zip(DV, S, A):
            weight = math.exp(-abs(dv_val - grid_point_dv) / upsilon - abs(s_val - grid_point_s) / sigma)
            weighted_sum += weight * a_val
            weight_total += weight
        a[i, j] = weighted_sum / weight_total if weight_total != 0 else 0

#print(a)

```

```

Processed grid row 1
Processed grid row 2
Processed grid row 3
Processed grid row 4
Processed grid row 5
Processed grid row 6
Processed grid row 7
Processed grid row 8
Processed grid row 9
Processed grid row 10
Processed grid row 11
Processed grid row 12
Processed grid row 13
Processed grid row 14
Processed grid row 15
Processed grid row 16
Processed grid row 17
Processed grid row 18
Processed grid row 19
Processed grid row 20
Processed grid row 21
Processed grid row 22
Processed grid row 23
Processed grid row 24
Processed grid row 25
Processed grid row 26
Processed grid row 27
Processed grid row 28
Processed grid row 29
Processed grid row 30
Processed grid row 31
Processed grid row 32
Processed grid row 33
Processed grid row 34
Processed grid row 35
Processed grid row 36
Processed grid row 37
Processed grid row 38
Processed grid row 39
Processed grid row 40
Processed grid row 41

```

The following code will plot the data for you. Does it make sense when considering:

- Negative (slower than leader) and positive (faster than leader) speed differences?
- Small and large headways?

```

In [12]: X, Y = np.meshgrid(s, dv)
          axs = plt.axes()
          p = axs.pcolor(X, Y, a, shading='nearest')
          axs.set_title('Acceleration [m/s/s]')
          axs.set_ylabel('Speed difference [m/s]')
          axs.set_xlabel('Headway [m]')
          axs.figure.colorbar(p);
          axs.figure.set_size_inches(10, 7)

```

