Local instance 3306 - Warning - not supported | Local instance 3306 (sys) - Warning - not supported | Local instance 3306 (sys) - Warning - not supported

Administration | Schemas | Query 1 | Context Help | Snippets

SCHEMAS

- sys
  - Tables
  - Views
  - Stored Pr...
  - Functions

Limit to 1000 rows

```
WHERE  DN.test_result = 'Safe'
ORDER BY DN.donation_date;
-- Purpose: Show total available blood units grouped by blood bank and blood group (aggregation).
SELECT BB.bank_name,
       BI.blood_group,
       SUM(BI.quantity_units) AS total_units,
       BI.status
FROM   BLOOD_BANK BB
JOIN   BLOOD_INVENTORY BI ON BB.bank_id = BI.bank_id
GROUP BY BB.bank_name, BI.blood_group, BI.status
ORDER BY BB.bank_name, BI.blood_group;
-- Purpose: Find all critical requests and show which hospital requested from which blood bank.
SELECT BR.request_id,
       H.hospital_name,
       BB.bank_name,
       BR.blood_group,
       BR.units_requested,
```

100% 39:151

Result Grid | Filter Rows: Search | Export:

bank_name	blood_group	total_units	status
HealWell Blood Bank	O-	25	Available
LifeLine Blood Bank	A+	50	Available
LifeLine Blood Bank	B+	30	Available
RedCross Blood Center	AB-	10	Reserved
RedCross Blood Center	O+	70	Available

BLOOD_INVENTORY 1 | Result 23 | Read Only

Automatic context help is disabled. Use the toolbar to manually get help for the current caret position or to toggle automatic help.

Object Info | Session

Name: Local instance 3306
Host: localhost
Port: 3306
Login User: root
Current User: root@localhost
SSL cipher: SSL not used
Server: MySQL Community

Action Output

	Time	Action	Response	Duration / Fetch Time
39	20:41:48	SELECT D.donor_id, CONCAT(D.first_name,' ',D.last_name) AS donor_name, D.blood_gro...	4 row(s) returned	0.0022 sec / 0.00001...
40	20:42:05	SELECT BB.bank_name, BI.blood_group, SUM(BI.quantity_units) AS total_units, BI.st...	5 row(s) returned	0.0057 sec / 0.00000...

Query Completed

Local instance 3306 - Warning - not supported | Local instance 3306 (sys) - Warning - not supported | Local instance 3306 (sys) - Warning - not supported

Administration | Schemas | Query 1 | Context Help | Snippets

SCHEMAS

- sys
  - Tables
  - Views
  - Stored Pr...
  - Functions

Limit to 1000 rows

```
SELECT * FROM HOSPITAL;
SELECT * FROM BLOOD_REQUEST;
SELECT * FROM RECIPIENT;
-- Purpose: Retrieve all successful (safe) donations along with the donor's full name and blood group.
SELECT D.donor_id,
       CONCAT(D.first_name,' ',D.last_name) AS donor_name,
       D.blood_group,
       DN.donation_date,
       DN.quantity_ml,
       DN.test_result
FROM   DONOR D
JOIN   DONATION DN ON D.donor_id = DN.donor_id
WHERE  DN.test_result = 'Safe'
ORDER BY DN.donation_date;
-- Purpose: Show total available blood units grouped by blood bank and blood group (aggregation).
SELECT BB.bank_name,
       BI.blood_group,
```

100% 27:142

Result Grid | Filter Rows: Search | Export:

donor_id	donor_name	blood_group	donation_da...	quantity_ml	test_res...
1	Rahul Sharma	A+	2023-06-01	450	Safe
2	Priya Verma	B+	2023-06-05	450	Safe
3	Amit Singh	O+	2023-06-10	450	Safe
5	Vikas Gupta	O-	2023-06-20	450	Safe

BLOOD_INVENTORY 1 | Result 22 | Read Only

Automatic context help is disabled. Use the toolbar to manually get help for the current caret position or to toggle automatic help.

Object Info | Session

Name: Local instance 3306
Host: localhost
Port: 3306
Login User: root
Current User: root@localhost
SSL cipher: SSL not used
Server: MySQL Community

Action Output

	Time	Action	Response	Duration / Fetch Time
38	20:32:11	SELECT D.donor_id, CONCAT(D.first_name,' ',D.last_name) AS donor_name, D.blood_gro...	4 row(s) returned	0.031 sec / 0.00046...
39	20:41:48	SELECT D.donor_id, CONCAT(D.first_name,' ',D.last_name) AS donor_name, D.blood_gro...	4 row(s) returned	0.0022 sec / 0.00001...

Query Completed

Local instance 3306 - Warning - not supported | Local instance 3306 (sys) - Warning - not supported | Local instance 3306 (sys) - Warning - not supported

Administration | Schemas | Query 1 | Context Help | Snippets

SCHEMAS

- sys
  - Tables
  - Views
  - Stored Pr...
  - Functions

Limit to 1000 rows

```
GROUP BY BB.bank_name, BI.blood_group, BI.status
ORDER BY BB.bank_name, BI.blood_group;
-- Purpose: Find all critical requests and show which hospital requested from which blood bank.
SELECT BR.request_id,
       H.hospital_name,
       BB.bank_name,
       BR.blood_group,
       BR.units_requested,
       BR.request_date,
       BR.status
FROM   BLOOD_REQUEST BR
JOIN   HOSPITAL H    ON BR.hospital_id = H.hospital_id
JOIN   BLOOD_BANK BB ON BR.bank_id     = BB.bank_id
WHERE  BR.urgency = 'Critical'
ORDER BY BR.request_date;
-- Purpose: Aggregation query to find how many donations each blood bank received.
SELECT BB.bank_name,
```

100% 26:164

Result Grid | Filter Rows: Search | Export:

request_id	hospital_name	bank_name	blood_group	units_request...	request_date	status
1	AIIMS Delhi	LifeLine Blood Bank	A+	10	2023-07-01	Fulfilled
3	Fortis Hospital	HealWell Blood Bank	O-	5	2023-07-05	Pending
5	KEM Hospital	LifeLine Blood Bank	AB-	3	2023-07-10	Fulfilled

BLOOD_INVENTORY 1 | Result 24 | Read Only

Automatic context help is disabled. Use the toolbar to manually get help for the current caret position or to toggle automatic help.

Object Info | Session

Name: Local instance 3306
Host: localhost
Port: 3306
Login User: root
Current User: root@localhost
SSL cipher: SSL not used
Server
Product: MySQL Community

Action Output

	Time	Action	Response	Duration / Fetch Time
40	20:42:05	SELECT BB.bank_name, BI.blood_group, SUM(BI.quantity_units) AS total_units, BI.st...	5 row(s) returned	0.0057 sec / 0.00000...
41	20:42:16	SELECT BR.request_id, H.hospital_name, BB.bank_name, BR.blood_group, BR.u...	3 row(s) returned	0.0013 sec / 0.00000...

Query Completed

Local instance 3306 - Warning - not supported | Local instance 3306 (sys) - Warning - not supported | Local instance 3306 (sys) - Warning - not supported

Administration | Schemas | Query 1 | Context Help | Snippets

SCHEMAS

- sys
  - Tables
  - Views
  - Stored Pr...
  - Functions

Limit to 1000 rows

```
WHERE  BR.urgency = 'Critical'
ORDER BY BR.request_date;
-- Purpose: Aggregation query to find how many donations each blood bank received.
SELECT BB.bank_name,
       COUNT(DN.donation_id) AS total_donations,
       SUM(DN.quantity_ml)   AS total_ml_collected
FROM   BLOOD_BANK BB
LEFT JOIN DONATION DN ON BB.bank_id = DN.bank_id
GROUP BY BB.bank_name
ORDER BY total_donations DESC;
-- Purpose: Identify newly registered donors who have not donated yet using a LEFT JOIN.
SELECT D.donor_id,
       CONCAT(D.first_name,' ',D.last_name) AS donor_name,
       D.blood_group,
       D.registration_date
FROM   DONOR D
LEFT JOIN DONATION DN ON D.donor_id = DN.donor_id
```

100% 31:172

Result Grid | Filter Rows: Search | Export:

bank_name	total_donatio...	total_ml_collect...
LifeLine Blood Bank	2	900
RedCross Blood Center	2	900
HealWell Blood Bank	1	450

BLOOD_INVENTORY 1 | Result 25 | Read Only

Automatic context help is disabled. Use the toolbar to manually get help for the current caret position or to toggle automatic help.

Object Info | Session

Name: Local instance 3306
Host: localhost
Port: 3306
Login User: root
Current User: root@localhost
SSL cipher: SSL not used
Server: MySQL Community

Action Output

	Time	Action	Response	Duration / Fetch Time
41	20:42:16	SELECT BR.request_id, H.hospital_name, BB.bank_name, BR.blood_group, BR.u...	3 row(s) returned	0.0013 sec / 0.00000...
42	20:42:23	SELECT BB.bank_name, COUNT(DN.donation_id) AS total_donations, SUM(DN.quantity_...	3 row(s) returned	0.00062 sec / 0.0000...

Query Completed

Local instance 3306 - Warning - not supported | Local instance 3306 (sys) - Warning - not supported | Local instance 3306 (sys) - Warning - not supported

Administration | Schemas | Query 1

SCHEMAS

- sys
  - Tables
  - Views
  - Stored Pr...
  - Functions

Limit to 1000 rows

```
FROM   BLOOD_BANK BB
LEFT JOIN DONATION DN ON BB.bank_id = DN.bank_id
GROUP BY BB.bank_name
ORDER BY total_donations DESC;
-- Purpose: Identify newly registered donors who have not donated yet using a LEFT JOIN.
SELECT D.donor_id,
       CONCAT(D.first_name,' ',D.last_name) AS donor_name,
       D.blood_group,
       D.registration_date
FROM   DONOR D
LEFT JOIN DONATION DN ON D.donor_id = DN.donor_id
WHERE  DN.donation_id IS NULL;
-- Purpose: JOIN query showing all recipients, which hospital admitted them, and blood needed.
SELECT R.recipient_id,
       R.patient_name,
       R.blood_group,
       R.age,
```

100% 1:174

Result Grid | Filter Rows: Search | Export:

donor_id	donor_name	blood_group	registration_d...

BLOOD_INVENTORY 1 | Result 26 | Read Only

Context Help | Snippets

Automatic context help is disabled. Use the toolbar to manually get help for the current caret position or to toggle automatic help.

Object Info | Session

Name: Local instance 3306
Host: localhost
Port: 3306
Login User: root
Current User: root@localhost
SSL cipher: SSL not used
Server: MySQL Community

Action Output

	Time	Action	Response	Duration / Fetch Time
42	20:42:23	SELECT BB.bank_name, COUNT(DN.donation_id) AS total_donations, SUM(DN.quantity_...	3 row(s) returned	0.00062 sec / 0.0000...
43	20:42:36	SELECT D.donor_id, CONCAT(D.first_name,' ',D.last_name) AS donor_name, D.blood_gro...	0 row(s) returned	0.0011 sec / 0.00000...

Query Completed

Local instance 3306 - Warning - not supported | Local instance 3306 (sys) - Warning - not supported | Local instance 3306 (sys) - Warning - not supported

Administration | Schemas | Query 1 | Context Help | Snippets

SCHEMAS

- sys
  - Tables
  - Views
  - Stored Pr...
  - Functions

Limit to 1000 rows

```
        D.registration_date
FROM    DONOR D
LEFT JOIN DONATION DN ON D.donor_id = DN.donor_id
WHERE  DN.donation_id IS NULL;
-- Purpose: JOIN query showing all recipients, which hospital admitted them, and blood needed.
SELECT R.recipient_id,
       R.patient_name,
       R.blood_group,
       R.age,
       H.hospital_name,
       R.medical_condition,
       R.admission_date
FROM   RECIPIENT R
JOIN   HOSPITAL H ON R.hospital_id = H.hospital_id
ORDER BY R.admission_date;
-- Purpose: Alert query to find blood groups running critically low across all banks.
SELECT BB.bank_name,
```

100% 1:192

Result Grid | Filter Rows: Search | Export:

recipient_id	patient_name	blood_group	age	hospital_name	medical_conditi...	admission_date
1	Mohan Das	A+	45	AIIMS Delhi	Surgery	2023-07-01
2	Kamla Nair	O+	62	KEM Hospital	Accident	2023-07-03
3	Raj Malhotra	O-	33	Fortis Hospital	Anemia	2023-07-05
4	Sita Devi	B+	55	AIIMS Delhi	Cancer	2023-07-07
5	Arjun Kapoor	AB-	28	KEM Hospital	Thalassemia	2023-07-10

BLOOD_INVENTORY 1 | Result 27 | Read Only

Result Grid | Form Editor | Field Types

Automatic context help is disabled. Use the toolbar to manually get help for the current caret position or to toggle automatic help.

Object Info | Session

Name: Local instance 3306
Host: localhost
Port: 3306
Login User: root
Current User: root@localhost
SSL cipher: SSL not used
Server: MySQL Community

Action Output

	Time	Action	Response	Duration / Fetch Time
43	20:42:36	SELECT D.donor_id, CONCAT(D.first_name,' ',D.last_name) AS donor_name, D.blood_gro...	0 row(s) returned	0.0011 sec / 0.00000...
44	20:42:50	SELECT R.recipient_id, R.patient_name, R.blood_group, R.age, H.hospital_name...	5 row(s) returned	0.0020 sec / 0.00000...

Query Completed

Local instance 3306 - Warning - not supported | Local instance 3306 (sys) - Warning - not supported | Local instance 3306 (sys) - Warning - not supported

Administration | Schemas | Query 1 | Context Help | Snippets

SCHEMAS

- sys
  - Tables
  - Views
  - Stored Pr...
  - Functions

Limit to 1000 rows

```
FROM   RECIPIENT R
JOIN   HOSPITAL H ON R.hospital_id = H.hospital_id
ORDER BY R.admission_date;
-- Purpose: Alert query to find blood groups running critically low across all banks.
SELECT BB.bank_name,
       BI.blood_group,
       BI.quantity_units,
       BI.expiry_date
FROM   BLOOD_INVENTORY BI
JOIN   BLOOD_BANK BB ON BI.bank_id = BB.bank_id
WHERE  BI.quantity_units < 20
  AND  BI.status = 'Available'
ORDER BY BI.quantity_units ASC;
-- Purpose: Rank donors by total number of donations using GROUP BY and ORDER BY.
SELECT D.donor_id,
       CONCAT(D.first_name,' ',D.last_name) AS donor_name,
       D.blood_group,
```

100% 32:201

Result Grid | Filter Rows: Search | Export:

bank_name	blood_group	quantity_uni...	expiry_date

BLOOD_INVENTORY 1 | Result 28 | Read Only

Automatic context help is disabled. Use the toolbar to manually get help for the current caret position or to toggle automatic help.

Object Info | Session

Name: Local instance 3306
Host: localhost
Port: 3306
Login User: root
Current User: root@localhost
SSL cipher: SSL not used
Server: MySQL Community

Action Output

	Time	Action	Response	Duration / Fetch Time
44	20:42:50	SELECT R.recipient_id, R.patient_name, R.blood_group, R.age, H.hospital_name...	5 row(s) returned	0.0020 sec / 0.00000...
45	20:42:59	SELECT BB.bank_name, BI.blood_group, BI.quantity_units, BI.expiry_date FROM BL...	0 row(s) returned	0.00061 sec / 0.0000...

Query Completed

Local instance 3306 - Warning - not supported | Local instance 3306 (sys) - Warning - not supported | Local instance 3306 (sys) - Warning - not supported

Administration | Schemas | Query 1 | Context Help | Snippets

SCHEMAS

- sys
  - Tables
  - Views
  - Stored Pr...
  - Functions

Limit to 1000 rows

```
JOIN   BLOOD_BANK BB ON BI.bank_id = BB.bank_id
WHERE  BI.quantity_units < 20
  AND  BI.status = 'Available'
ORDER BY BI.quantity_units ASC;
-- Purpose: Rank donors by total number of donations using GROUP BY and ORDER BY.
SELECT D.donor_id,
       CONCAT(D.first_name,' ',D.last_name) AS donor_name,
       D.blood_group,
       COUNT(DN.donation_id) AS times_donated
FROM   DONOR D
JOIN   DONATION DN ON D.donor_id = DN.donor_id
WHERE  DN.test_result = 'Safe'
GROUP BY D.donor_id, donor_name, D.blood_group
ORDER BY times_donated DESC;

SELECT * FROM DONOR
```

100% 29:211

Automatic context help is disabled. Use the toolbar to manually get help for the current caret position or to toggle automatic help.

Result Grid | Filter Rows: Search | Export:

donor_id	donor_name	blood_group	times_donated
1	Rahul Sharma	A+	1
2	Priya Verma	B+	1
3	Amit Singh	O+	1
5	Vikas Gupta	O-	1

BLOOD_INVENTORY 1 | Result 29 | Read Only

Object Info | Session

Name: Local instance 3306
Host: localhost
Port: 3306
Login User: root
Current User: root@localhost
SSL cipher: SSL not used
Server: MySQL Community

Action Output

	Time	Action	Response	Duration / Fetch Time
45	20:42:59	SELECT BB.bank_name, BI.blood_group, BI.quantity_units, BI.expiry_date FROM BL...	0 row(s) returned	0.00061 sec / 0.0000...
46	20:43:09	SELECT D.donor_id, CONCAT(D.first_name,' ',D.last_name) AS donor_name, D.blood_gro...	4 row(s) returned	0.0010 sec / 0.00000...

Query Completed