To be done

Recommendations from the session that set up the "session operator" (2026-10-21).
Most of them wait for the cloud experiment (`claude/2026-10-21--tmp-transition-to-operator/`) to finish.

The cloud environment's setup script (claude.ai UI)

The environment has a setup script that installs Node 26 into `/opt/node26`. It never puts it on `PATH`, so it has no effect:
`node` in a cloud session is still the default Node 22, and nothing in the repo uses `/opt/node26`.
It cannot block a session (it always exits 0), but after each cache expiry (~7 days) it downloads Node again at session start.

- [ ] Decide whether Node 26 is needed at all:
  - Not needed: delete the setup script.
  - Needed: make it take effect, e.g. add `ln -sf /opt/node26/bin/* /usr/local/bin/`.
- [ ] Keep a reference copy of the environment's UI-only settings in the repo - e.g. `claude/cloud-environment/`:
  the setup script, and the network allowlist (the hosts to add, from the options' `NEEDED_DOMAINS` / `domains.txt`).
  Note there that both must be pasted into the claude.ai UI by hand.
- [ ] Use the setup script for tools the repo needs but the default image lacks - e.g. `gawk` (used by `scripts/build-prompt.sh`),
  if the experiment's findings confirm it is missing. Not for git syncing: the operator's hook does that.

Bun projects in cloud sessions

The TypeScript projects (`_DELIBERATION-ROOM`, `_RTL-EDITOR`) are Bun projects: Node only runs `tsc`, and the compile result
is the same on Node 22 and Node 24 (checked).

- [ ] A fresh cloud clone has no `node_modules`: a session that runs these projects must run `bun install` first.
  The docs mention known Bun proxy issues in cloud sessions - if `bun install` fails, fall back to `npm install`.
  Add this to the operator's knowledge (e.g. `claude/operator/README.md`) once an option needs these projects in cloud.

`_RTL-EDITOR` type errors (old, unrelated to the cloud)

Nothing runs `tsc` in `_RTL-EDITOR` (it has no `check` script), and Bun does not type-check - so these do not block anything.

- [ ] `public/` (the browser code, type-checked as JavaScript by its `tsconfig.json`): 86 errors - mostly strictness
  ("possibly null", argument types) in `markdown-editor.js`, `tables.js`, `app.js`, `links.js`, `tab-data.js`.
- [ ] `src/` and `tests/` are not in its `tsconfig.json` at all. Checked separately, they have about 24 errors - e.g. `findLast`
  (needs `lib` ES2023 or later; the target is ES2022), and implicit `any`s.
- [ ] Consider a `check` script (like `_DELIBERATION-ROOM`'s `tsc --noEmit`) that covers `src/` and `tests/` too.

After the cloud experiment (Phase 4 of its README)

- [ ] Refine the operator by the findings; keep what was learned in the operator's comments or a `claude/operator/README.md`.
- [ ] Delete `claude/2026-10-21--tmp-transition-to-operator/`, and the `tmp/operator-experiment` branch on origin
  (`git push origin --delete tmp/operator-experiment` - the cloud's git proxy cannot delete branches).
- [ ] Optional: delete the test state files left in `.git/operator-state/` (`T1.head`, `T2.*`, `R1.*`, ...) and the
  old `.git/operator-choices/` folder - harmless, but leftovers from local testing.