

Contents

1 Basic	1
1.1 Default code	1
1.2 Pragma	1
1.3 readchar	1
1.4 debug	1
1.5 vimrc	1
1.6 black magic	1
2 Graph	1
2.1 SCC	1
2.2 Bridge	2
2.3 BCC Vertex	2
2.4 2SAT	2
2.5 Dominator Tree	2
2.6 MinimumMeanCycle	3
2.7 Virtual Tree	3
2.8 Maximum Clique Dyn	3
2.9 NumberofMaximalClique	3
2.10 MinimumSteinerTree	3
2.11 Minimum Arborescence	4
2.12 Minimum Clique Cover	4
3 Data Structure	4
3.1 discrete trick	4
3.2 BITkth	4
3.3 IntervalContainer	4
3.4 KDTree	5
3.5 min heap	5
3.6 LiChaoST	5
3.7 Treap	5
3.8 link cut tree	6
3.9 Centroid Decomposition	6
3.10 Heavy light Decomposition	7
4 Flow Matching	7
4.1 Model	7
4.2 Dinic	7
4.3 Maximum Simple Graph Matching	8
4.4 Kuhn Munkres	8
4.5 General Matching Random	8
4.6 isap	9
4.7 Gomory Hu tree	9
4.8 MincostMaxflow	9
4.9 SW-mincut	10
4.10 Bipartite Matching	10
4.11 BoundedFlow	10
5 String	10
5.1 Smallest Rotation	10
5.2 KMP	11
5.3 Manacher	11
5.4 De Bruijn sequence	11
5.5 Aho-Corasick Automatan	11
5.6 Suffix Array	11
5.7 SAM	11
5.8 Z-value	12
5.9 MainLorentz	12
6 Math	12
6.1 numbers	12
6.2 Estimation	12
6.3 chineseRemainder	12
6.4 Prime Count	12
6.5 floor sum	13
6.6 QuadraticResidue	13
6.7 floor enumeration	13
6.8 ax+by=gcd	13
6.9 cantor expansion	13
6.10 Generating function	13
6.11 Fraction	14

1 Basic

1.1 Default code [c21a25]

```
1 typedef long long ll;
2 typedef pair<int, int> pii;
3 typedef pair<ll, ll> pll;
4 #define X first
5 #define Y second
6 #define SZ(a) ((int)a.size())
7 #define ALL(v) v.begin(), v.end()
8 #define pb push_back
9 #define eb emplace_back
10 #define mkp make_pair
11 #define IO ios_base::sync_with_stdio(0)
```

1.2 Pragma [5feb8b]

```
1 #pragma GCC optimize("Ofast,no-stack-protector")
2 #pragma GCC optimize("no-math-errno,unroll-loops")
3 #pragma GCC target("sse,sse2,sse3,ssse3,sse4")
```

6.12 Gaussian gcd	14
6.13 Theorem	14
6.14 Determinant	14
6.15 ModMin	15
6.16 Simultaneous Equations	15
6.17 Big number	15
6.18 Euclidean	16
6.19 Primes	16
6.20 Miller Rabin	16
6.21 Pollard Rho	16
6.22 Berlekamp-Massey	16
6.23 Floor ceil	16
6.24 fac no p	17
6.25 DiscreteLog	17
6.26 SimplexConstruction	17
6.27 Simplex Algorithm	17

7 Polynomial

7.1 Fast Walsh Transform	17
7.2 NTT	17
7.3 FFT	18
7.4 Newton	18

8 Geometry

8.1 Default code	18
8.2 Default code int	18
8.3 Convex hull	19
8.4 PointInConvex	19
8.5 PolyUnion	19
8.6 external bisector	19
8.7 Convexhull3D	19
8.8 Triangulation Voronoi	20
8.9 Polar Angle Sort	20
8.10 Intersection of polygon and circle	20
8.11 Tangent line of two circles	20
8.12 CircleCover	21
8.13 Heart	21
8.14 PointSegDist	21
8.15 Minkowski Sum	21
8.16 TangentPointToHull	21
8.17 Intersection of two circles	21
8.18 Intersection of line and circle	21
8.19 point in circle	22
8.20 PolyCut	22
8.21 minDistOfTwoConvex	22
8.22 rotatingSweepLine	22
8.23 Intersection of line and convex	22
8.24 3Dpoint	22
8.25 minMaxEnclosingRectangle	22
8.26 Half plane intersection	23
8.27 Vector in poly	23
8.28 Minimum Enclosing Circle	23

9 Else

9.1 ManhattanMST	23
9.2 Mos Algorithm With modification	23
9.3 BitsetLCS	23
9.4 BinarySearchOnFraction	24
9.5 SubsetSum	24
9.6 DynamicMST	24
9.7 Matroid	24
9.8 HilbertCurve	24
9.9 Mos Algorithm On Tree	24
9.10 Mos Algorithm	25
9.11 min plus convolution	25
9.12 NQueens	25
9.13 simulated annealing	25
9.14 tree hash	25
9.15 tree knapsack	25

```
4 #pragma GCC target("popcnt,abm,mmx,avx,arch=skylake")
5 __builtin_ia32_ldmxcsr(
6 __builtin_ia32_stmxcsr() | 0x8040)
```

1.3 readchar [dacef1]

```
inline char readchar() {
1 static const size_t bufsize = 65536;
2 static char buf[bufsize];
3 static char *p = buf, *end = buf;
4 if (p == end)
5     end = buf + fread_unlocked(buf, 1, bufsize, stdin),
6     p = buf;
7 return *p++;
8 }
9 }
```

1.4 debug [8f6825]

```
void abc() { cerr << endl; }
template <typename T, typename... U>
void abc(T a, U... b) {
1 cerr << a << ' ', abc(b...);
2 }
3 #ifdef debug
4 #define
5     test(args...) abc("[ " + string(#args) + "]", args)
6 #else
7 #define test(args...) void(0)
8 #endif
```

1.5 vimrc [471718]

```
set nu ai hls et ru ic is sc cul
set re=1 ts=4 sts=4 sw=4 ls=2 mouse=a
set timeoutlen=300
hi cursorline cterm=none
"Select region and type :Hash to hash your selection."
ca Hash w !cpp -dD -P -fpreprocessed
1 \ | tr -d '[:space:]' \ | md5sum \ | cut -c-6
2 map <F9> :w !clear && g++ -std=c++17
3 -Ddebug -O2 -Wall -lm -g % && ./a.out<CR>
```

1.6 black magic [107dde]

```
1 #include <ext/pb_ds/assoc_container.hpp> // rb_tree
2 #include <ext/pb_ds/priority_queue.hpp>
3 #include <ext/rope> // rope
4 using namespace __gnu_pbds;
5 using namespace __gnu_cxx; // rope
6 typedef __gnu_pbds::priority_queue<int> heap;
7 int main() {
8     heap h1, h2; // max heap
9     h1.push(1), h1.push(3), h2.push(2), h2.push(4);
10    h1.join(h2); // h1 = {1, 2, 3, 4}, h2 = {};
11    tree<ll, null_type, less<ll>, rb_tree_tag,
12        tree_order_statistics_node_update>
13        st;
14    tree<ll, ll, less<ll>, rb_tree_tag,
15        tree_order_statistics_node_update>
16        mp;
17    for (int x : {0, 3, 20, 50}) st.insert(x);
18    assert(st.order_of_key(3) == 1 &&
19        st.order_of_key(4) == 2);
20    assert(*st.find_by_order(2) == 20 &&
21        *st.lower_bound(4) == 20);
22    rope<char> *root[10]; // nsqrt(n)
23    root[0] = new rope<char>();
24    root[1] = new rope<char>(*root[0]);
25    // root[1]->insert(pos, 'a');
26    // root[1]->at(pos); 0-base
27    // root[1]->erase(pos, size);
28 }
29 // __int128_t, __float128_t
30 // for (int i = bs._Find_first(); i < bs.size(); i =
31 // bs._Find_next(i));
```

2 Graph

2.1 SCC [517e91]

```
1 struct SCC { // 0-base
2     int n, dft, nscc;
3     vector<int> low, dfn, bln, instack, stk;
4     vector<vector<int>>> G;
5     void dfs(int u) {
6         low[u] = dfn[u] = ++dft;
7         instack[u] = 1, stk.pb(u);
8         for (int v : G[u])
```

```

9     if (!dfn[v])
10         dfs(v), low[u] = min(low[u], low[v]);
11     else if (instack[v] && dfn[v] < dfn[u])
12         low[u] = min(low[u], dfn[v]);
13     if (low[u] == dfn[u]) {
14         for (; stk.back() != u; stk.pop_back())
15             bln[stk.back()] = nsc,
16             instack[stk.back()] = 0;
17         instack[u] = 0, bln[u] = nsc++, stk.pop_back();
18     }
19 }
20 SCC(int _n)
21 : n(_n), dft(), nsc(), low(n), dfn(n), bln(n),
22   instack(n), G(n) {}
23 void add_edge(int u, int v) { G[u].pb(v); }
24 void solve() {
25     for (int i = 0; i < n; ++i)
26         if (!dfn[i]) dfs(i);
27 }
28 }; // scc_id(i): bln[i]

```

2.2 Bridge [f72ae7]

```

1 struct ECC { // 0-base
2     int n, dft, ecnt, necc;
3     vector<int> low, dfn, bln, is_bridge, stk;
4     vector<vector<pii>> G;
5     void dfs(int u, int f) {
6         dfn[u] = low[u] = ++dft, stk.pb(u);
7         for (auto [v, e] : G[u])
8             if (!dfn[v])
9                 dfs(v, e), low[u] = min(low[u], low[v]);
10            else if (e != f) low[u] = min(low[u], dfn[v]);
11        if (low[u] == dfn[u]) {
12            if (f != -1) is_bridge[f] = 1;
13            for (; stk.back() != u; stk.pop_back())
14                bln[stk.back()] = necc;
15            bln[u] = necc++, stk.pop_back();
16        }
17    }
18    ECC(int _n)
19    : n(_n), dft(), ecnt(), necc(), low(n), dfn(n),
20      bln(n), G(n) {}
21    void add_edge(int u, int v) {
22        G[u].pb(pii(v, ecnt)), G[v].pb(pii(u, ecnt++));
23    }
24    void solve() {
25        is_bridge.resize(ecnt);
26        for (int i = 0; i < n; ++i)
27            if (!dfn[i]) dfs(i, -1);
28    }
29 }; // ecc_id(i): bln[i]

```

2.3 BCC Vertex [f56bab]

```

1 struct BCC { // 0-base
2     int n, dft, nbcc;
3     vector<int> low, dfn, bln, stk, is_ap, cir;
4     vector<vector<int>> G, bcc, nG;
5     void make_bcc(int u) {
6         bcc.emplace_back(1, u);
7         for (; stk.back() != u; stk.pop_back())
8             bln[stk.back()] = nbcc, bcc[nbcc].pb(stk.back());
9         stk.pop_back(), bln[u] = nbcc++;
10    }
11    void dfs(int u, int f) {
12        int child = 0;
13        low[u] = dfn[u] = ++dft, stk.pb(u);
14        for (int v : G[u])
15            if (!dfn[v]) {
16                dfs(v, u), ++child;
17                low[u] = min(low[u], low[v]);
18                if (dfn[u] <= low[v]) {
19                    is_ap[u] = 1, bln[u] = nbcc;
20                    make_bcc(v), bcc.back().pb(u);
21                }
22            } else if (dfn[v] < dfn[u] && v != f)
23                low[u] = min(low[u], dfn[v]);
24        if (f == -1 && child < 2) is_ap[u] = 0;
25        if (f == -1 && child == 0) make_bcc(u);
26    }
27    BCC(int _n)
28    : n(_n), dft(), nbcc(), low(n), dfn(n), bln(n),
29      is_ap(n), G(n) {}
30    void add_edge(int u, int v) {
31        G[u].pb(v), G[v].pb(u);
32    }

```

```

33 void solve() {
34     for (int i = 0; i < n; ++i)
35         if (!dfn[i]) dfs(i, -1);
36 }
37 void block_cut_tree() {
38     cir.resize(nbcc);
39     for (int i = 0; i < n; ++i)
40         if (is_ap[i]) bln[i] = nbcc++;
41     cir.resize(nbcc, 1), nG.resize(nbcc);
42     for (int i = 0; i < nbcc && !cir[i]; ++i)
43         for (int j : bcc[i])
44             if (is_ap[j])
45                 nG[i].pb(bln[j]), nG[bln[j]].pb(i);
46 } // up to 2 * n - 2 nodes!! bln[i] for id
47 };

```

2.4 2SAT [d0abc7]

```

1 struct SAT { // 0-base
2     int n;
3     vector<bool> istrue;
4     SCC scc;
5     SAT(int _n) : n(_n), istrue(n + n), scc(n + n) {}
6     int rv(int a) { return a >= n ? a - n : a + n; }
7     void add_clause(int a, int b) {
8         scc.add_edge(rv(a), b), scc.add_edge(rv(b), a);
9     }
10    bool solve() {
11        scc.solve();
12        for (int i = 0; i < n; ++i) {
13            if (scc.bln[i] == scc.bln[i + n]) return false;
14            istrue[i] = scc.bln[i] < scc.bln[i + n];
15            istrue[i + n] = !istrue[i];
16        }
17        return true;
18    }
19 };

```

2.5 Dominator Tree [p15f9c]

```

1 struct dominator_tree { // 1-base
2     vector<int> G[N], rG[N];
3     int n, pa[N], dfn[N], id[N], Time;
4     int semi[N], idom[N], best[N];
5     vector<int> tree[N]; // dominator_tree
6     void init(int _n) {
7         n = _n;
8         for (int i = 1; i <= n; ++i)
9             G[i].clear(), rG[i].clear();
10    }
11    void add_edge(int u, int v) {
12        G[u].pb(v), rG[v].pb(u);
13    }
14    void dfs(int u) {
15        id[dfn[u] = ++Time] = u;
16        for (auto v : G[u])
17            if (!dfn[v]) dfs(v), pa[dfn[v]] = dfn[u];
18    }
19    int find(int y, int x) {
20        if (y <= x) return y;
21        int tmp = find(pa[y], x);
22        if (semi[best[y]] > semi[best[pa[y]]])
23            best[y] = best[pa[y]];
24        return pa[y] = tmp;
25    }
26    void tarjan(int root) {
27        Time = 0;
28        for (int i = 1; i <= n; ++i) {
29            dfn[i] = idom[i] = 0;
30            tree[i].clear();
31            best[i] = semi[i] = i;
32        }
33        dfs(root);
34        for (int i = Time; i > 1; --i) {
35            int u = id[i];
36            for (auto v : rG[u])
37                if (v = dfn[v]) {
38                    find(v, i);
39                    semi[i] = min(semi[i], semi[best[v]]);
40                }
41            tree[semi[i]].pb(i);
42            for (auto v : tree[pa[i]]) {
43                find(v, pa[i]);
44                idom[v] =
45                    semi[best[v]] == pa[i] ? pa[i] : best[v];
46            }
47            tree[pa[i]].clear();

```

```

48     }
49     for (int i = 2; i <= Time; ++i) {
50         if (idom[i] != semi[i]) idom[i] = idom[idom[i]];
51         tree[id[idom[i]]].pb(id[i]);
52     }
53 }
54 };

```

2.6 MinimumMeanCycle [e8ed41]

```

1 ll road[N][N]; // input here
2 struct MinimumMeanCycle {
3     ll dp[N + 5][N], n;
4     pll solve() {
5         ll a = -1, b = -1, L = n + 1;
6         for (int i = 2; i <= L; ++i)
7             for (int k = 0; k < n; ++k)
8                 for (int j = 0; j < n; ++j)
9                     dp[i][j] =
10                        min(dp[i - 1][k] + road[k][j], dp[i][j]);
11         for (int i = 0; i < n; ++i) {
12             if (dp[L][i] >= INF) continue;
13             ll ta = 0, tb = 1;
14             for (int j = 1; j < n; ++j)
15                 if (dp[j][i] < INF &&
16                     ta * (L - j) < (dp[L][i] - dp[j][i]) * tb)
17                     ta = dp[L][i] - dp[j][i], tb = L - j;
18             if (ta == 0) continue;
19             if (a == -1 || a * tb > ta * b) a = ta, b = tb;
20         }
21         if (a != -1) {
22             ll g = __gcd(a, b);
23             return pll(a / g, b / g);
24         }
25         return pll(-1LL, -1LL);
26     }
27     void init(int _n) {
28         n = _n;
29         for (int i = 0; i < n; ++i)
30             for (int j = 0; j < n; ++j) dp[i + 2][j] = INF;
31     }
32 };

```

2.7 Virtual Tree [551777]

```

1 vector<int> vG[N];
2 int top, st[N];
3 void insert(int u) {
4     if (top == -1) return st[++top] = u, void();
5     int p = LCA(st[top], u);
6     if (p == st[top]) return st[++top] = u, void();
7     while (top >= 1 && dep[st[top - 1]] >= dep[p])
8         vG[st[top - 1]].pb(st[top]), --top;
9     if (st[top] != p)
10        vG[p].pb(st[top]), --top, st[++top] = p;
11    st[++top] = u;
12 }
13 void reset(int u) {
14     for (int i : vG[u]) reset(i);
15     vG[u].clear();
16 }
17 void solve(vector<int> &v) {
18     top = -1;
19     sort(ALL(v),
20          [&](int a, int b) { return dfn[a] < dfn[b]; });
21     for (int i : v) insert(i);
22     while (top > 0) vG[st[top - 1]].pb(st[top]), --top;
23     // do something
24     reset(v[0]);
25 }

```

2.8 Maximum Clique Dyn [09472e]

```

1 struct MaxClique { // fast when N <= 100
2     bitset<N> G[N], cs[N];
3     int ans, sol[N], q, cur[N], d[N], n;
4     void init(int _n) {
5         n = _n;
6         for (int i = 0; i < n; ++i) G[i].reset();
7     }
8     void add_edge(int u, int v) {
9         G[u][v] = G[v][u] = 1;
10    }
11    void pre_dfs(vector<int> &r, int l, bitset<N> mask) {
12        if (l < 4) {
13            for (int i : r) d[i] = (G[i] & mask).count();
14            sort(ALL(r),

```

```

15            [&](int x, int y) { return d[x] > d[y]; });
16        }
17        vector<int> c(SZ(r));
18        int lft = max(ans - q + 1, 1), rgt = 1, tp = 0;
19        cs[1].reset(), cs[2].reset();
20        for (int p : r) {
21            int k = 1;
22            while ((cs[k] & G[p]).any()) ++k;
23            if (k > rgt) cs[++rgt + 1].reset();
24            cs[k][p] = 1;
25            if (k < lft) r[tp++] = p;
26        }
27        for (int k = lft; k <= rgt; ++k)
28            for (int p = cs[k]._Find_first(); p < N;
29                p = cs[k]._Find_next(p))
30                r[tp] = p, c[tp] = k, ++tp;
31        dfs(r, c, l + 1, mask);
32    }
33    void dfs(vector<int> &r, vector<int> &c, int l,
34            bitset<N> mask) {
35        while (!r.empty()) {
36            int p = r.back();
37            r.pop_back(), mask[p] = 0;
38            if (q + c.back() <= ans) return;
39            cur[q++] = p;
40            vector<int> nr;
41            for (int i : r)
42                if (G[p][i]) nr.pb(i);
43            if (!nr.empty()) pre_dfs(nr, l, mask & G[p]);
44            else if (q > ans) ans = q, copy_n(cur, q, sol);
45            c.pop_back(), --q;
46        }
47    }
48    int solve() {
49        vector<int> r(n);
50        ans = q = 0, iota(ALL(r), 0);
51        pre_dfs(r, 0, bitset<N>(string(n, '1')));
52        return ans;
53    }
54 };

```

2.9 NumberofMaximalClique [66fef5]

```

1 struct BronKerbosch { // 1-base
2     int n, a[N], g[N][N];
3     int S, all[N][N], some[N][N], none[N][N];
4     void init(int _n) {
5         n = _n;
6         for (int i = 1; i <= n; ++i)
7             for (int j = 1; j <= n; ++j) g[i][j] = 0;
8     }
9     void add_edge(int u, int v) {
10        g[u][v] = g[v][u] = 1;
11    }
12    void dfs(int d, int an, int sn, int nn) {
13        if (S > 1000) return; // pruning
14        if (sn == 0 && nn == 0) ++S;
15        int u = some[d][0];
16        for (int i = 0; i < sn; ++i) {
17            int v = some[d][i];
18            if (g[u][v]) continue;
19            int tsn = 0, tnn = 0;
20            copy_n(all[d], an, all[d + 1]);
21            all[d + 1][an] = v;
22            for (int j = 0; j < sn; ++j)
23                if (g[v][some[d][j]])
24                    some[d + 1][tsn++] = some[d][j];
25            for (int j = 0; j < nn; ++j)
26                if (g[v][none[d][j]])
27                    none[d + 1][tnn++] = none[d][j];
28            dfs(d + 1, an + 1, tsn, tnn);
29            some[d][i] = 0, none[d][nn++] = v;
30        }
31    }
32    int solve() {
33        iota(some[0], some[0] + n, 1);
34        S = 0, dfs(0, 0, n, 0);
35        return S;
36    }
37 };

```

2.10 MinimumSteinerTree [e6662f]

```

1 struct SteinerTree { // 0-base
2     int n, dst[N][N], dp[1 << T][N], tdst[N];
3     int vcst[N]; // the cost of vertices
4     void init(int _n) {

```

```

5   n = _n;
6   for (int i = 0; i < n; ++i) {
7       fill_n(dst[i], n, INF);
8       dst[i][i] = vcst[i] = 0;
9   }
10  }
11  void chmin(int &x, int val) { x = min(x, val); }
12  void add_edge(int ui, int vi, int wi) {
13      chmin(dst[ui][vi], wi);
14  }
15  void shortest_path() {
16      for (int k = 0; k < n; ++k)
17          for (int i = 0; i < n; ++i)
18              for (int j = 0; j < n; ++j)
19                  chmin(dst[i][j], dst[i][k] + dst[k][j]);
20  }
21  int solve(const vector<int> &ter) {
22      shortest_path();
23      int t = SZ(ter), full = (1 << t) - 1;
24      for (int i = 0; i <= full; ++i)
25          fill_n(dp[i], n, INF);
26      copy_n(vcst, n, dp[0]);
27      for (int msk = 1; msk <= full; ++msk) {
28          if (!(msk & (msk - 1))) {
29              int who = __lg(msk);
30              for (int i = 0; i < n; ++i)
31                  dp[msk][i] =
32                      vcst[ter[who]] + dst[ter[who]][i];
33          }
34          for (int i = 0; i < n; ++i)
35              for (int sub = (msk - 1) & msk; sub;
36                  sub = (sub - 1) & msk)
37                  chmin(dp[msk][i],
38                      dp[sub][i] + dp[msk ^ sub][i] - vcst[i]);
39          for (int i = 0; i < n; ++i) {
40              tdst[i] = INF;
41              for (int j = 0; j < n; ++j)
42                  chmin(tdst[i], dp[msk][j] + dst[j][i]);
43          }
44          copy_n(tdst, n, dp[msk]);
45      }
46      return *min_element(dp[full], dp[full] + n);
47  }
48  }; // O(V 3^AT + V^2 2^AT)

```

2.11 Minimum Arborescence [4c8d8d]

```

1  struct zhu_liu { // O(VE)
2      struct edge {
3          int u, v;
4          ll w;
5      };
6      vector<edge> E; // 0-base
7      int pe[N], id[N], vis[N];
8      ll in[N];
9      void init() { E.clear(); }
10     void add_edge(int u, int v, ll w) {
11         if (u != v) E.pb(edge{u, v, w});
12     }
13     ll build(int root, int n) {
14         ll ans = 0;
15         for (;;) {
16             fill_n(in, n, INF);
17             for (int i = 0; i < SZ(E); ++i)
18                 if (E[i].u != E[i].v && E[i].w < in[E[i].v])
19                     pe[E[i].v] = i, in[E[i].v] = E[i].w;
20             for (int u = 0; u < n; ++u) // no solution
21                 if (u != root && in[u] == INF) return -INF;
22             int cntnode = 0;
23             fill_n(id, n, -1), fill_n(vis, n, -1);
24             for (int u = 0; u < n; ++u) {
25                 if (u != root) ans += in[u];
26                 int v = u;
27                 while (vis[v] != u && !~id[v] && v != root)
28                     vis[v] = u, v = E[pe[v]].u;
29                 if (v != root && !~id[v]) {
30                     for (int x = E[pe[v]].u; x != v;
31                         x = E[pe[x]].u)
32                         id[x] = cntnode;
33                     id[v] = cntnode++;
34                 }
35             }
36             if (!cntnode) break; // no cycle
37             for (int u = 0; u < n; ++u)
38                 if (!~id[u]) id[u] = cntnode++;
39             for (int i = 0; i < SZ(E); ++i) {
40                 int v = E[i].v;

```

```

41                 E[i].u = id[E[i].u], E[i].v = id[E[i].v];
42                 if (E[i].u != E[i].v) E[i].w -= in[v];
43             }
44             n = cntnode, root = id[root];
45         }
46         return ans;
47     }
48 };

```

2.12 Minimum Clique Cover [745700]

```

1  struct Clique_Cover { // 0-base, O(n2^n)
2      int co[1 << N], n, E[N];
3      int dp[1 << N];
4      void init(int _n) {
5          n = _n, fill_n(dp, 1 << n, 0);
6          fill_n(E, n, 0), fill_n(co, 1 << n, 0);
7      }
8      void add_edge(int u, int v) {
9          E[u] |= 1 << v, E[v] |= 1 << u;
10     }
11     int solve() {
12         for (int i = 0; i < n; ++i)
13             co[1 << i] = E[i] | (1 << i);
14         co[0] = (1 << n) - 1;
15         dp[0] = (n & 1) * 2 - 1;
16         for (int i = 1; i < (1 << n); ++i) {
17             int t = i & -i;
18             dp[i] = -dp[i ^ t];
19             co[i] = co[i ^ t] & co[t];
20         }
21         for (int i = 0; i < (1 << n); ++i)
22             co[i] = (co[i] & i) == i;
23         fwt(co, 1 << n, 1);
24         for (int ans = 1; ans < n; ++ans) {
25             int sum = 0; // probabilistic
26             for (int i = 0; i < (1 << n); ++i)
27                 sum += (dp[i] * co[i]);
28             if (sum) return ans;
29         }
30         return n;
31     }
32 };

```

3 Data Structure

3.1 discrete trick [2062d6]

```

1  vector<int> val;
2  // build
3  sort(ALL(val)),
4  val.resize(unique(ALL(val)) - val.begin());
5  // index of x
6  upper_bound(ALL(val), x) - val.begin();
7  // max idx <= x
8  upper_bound(ALL(val), x) - val.begin();
9  // max idx < x
10 lower_bound(ALL(val), x) - val.begin();

```

3.2 BIT kth [7de9a0]

```

1  int bit[N + 1]; // N = 2 ^ k
2  int query_kth(int k) {
3      int res = 0;
4      for (int i = N >> 1; i >= 1; i >>= 1)
5          if (bit[res + i] < k) k -= bit[res += i];
6      return res + 1;
7  }

```

3.3 IntervalContainer [dbcccd]

```

1  /* Add and remove intervals from a set of disjoint
2   * intervals. Will merge the added interval with any
3   * overlapping intervals in the set when adding.
4   * Intervals are [inclusive, exclusive). */
5  set<pii>::iterator addInterval(
6      set<pii> &is, int L, int R) {
7      if (L == R) return is.end();
8      auto it = is.lower_bound({L, R}), before = it;
9      while (it != is.end() && it->X <= R) {
10         R = max(R, it->Y);
11         before = it = is.erase(it);
12     }
13     if (it != is.begin() && (--it)->Y >= L) {
14         L = min(L, it->X);
15         R = max(R, it->Y);
16         is.erase(it);
17     }

```

```

18     return is.insert(before, pii(L, R));
19 }
20 void removeInterval(set<pii> &is, int L, int R) {
21     if (L == R) return;
22     auto it = addInterval(is, L, R);
23     auto r2 = it->Y;
24     if (it->X == L) is.erase(it);
25     else (int &)it->Y = L;
26     if (R != r2) is.emplace(R, r2);
27 }

```

3.4 KDTree [85f231]

```

1 namespace kdt {
2     int root, lc[maxn], rc[maxn], xl[maxn], xr[maxn],
3         yl[maxn], yr[maxn];
4     point p[maxn];
5     int build(int l, int r, int dep = 0) {
6         if (l == r) return -1;
7         function<bool(const point &, const point &)> f =
8             [dep](const point &a, const point &b) {
9                 if (dep & 1) return a.x < b.x;
10                else return a.y < b.y;
11            };
12         int m = (l + r) >> 1;
13         nth_element(p + l, p + m, p + r, f);
14         xl[m] = xr[m] = p[m].x;
15         yl[m] = yr[m] = p[m].y;
16         lc[m] = build(l, m, dep + 1);
17         if (~lc[m]) {
18             xl[m] = min(xl[m], xl[lc[m]]);
19             xr[m] = max(xr[m], xr[lc[m]]);
20             yl[m] = min(yl[m], yl[lc[m]]);
21             yr[m] = max(yr[m], yr[lc[m]]);
22         }
23         rc[m] = build(m + 1, r, dep + 1);
24         if (~rc[m]) {
25             xl[m] = min(xl[m], xl[rc[m]]);
26             xr[m] = max(xr[m], xr[rc[m]]);
27             yl[m] = min(yl[m], yl[rc[m]]);
28             yr[m] = max(yr[m], yr[rc[m]]);
29         }
30         return m;
31     }
32     bool bound(const point &q, int o, long long d) {
33         double ds = sqrt(d + 1.0);
34         if (q.x < xl[o] - ds || q.x > xr[o] + ds ||
35             q.y < yl[o] - ds || q.y > yr[o] + ds)
36             return false;
37         return true;
38     }
39     long long dist(const point &a, const point &b) {
40         return (a.x - b.x) * 1ll * (a.x - b.x) +
41             (a.y - b.y) * 1ll * (a.y - b.y);
42     }
43     void dfs(
44         const point &q, long long &d, int o, int dep = 0) {
45         if (!bound(q, o, d)) return;
46         long long cd = dist(p[o], q);
47         if (cd != 0) d = min(d, cd);
48         if ((dep & 1) && q.x < p[o].x ||
49             !(dep & 1) && q.y < p[o].y) {
50             if (~lc[o]) dfs(q, d, lc[o], dep + 1);
51             if (~rc[o]) dfs(q, d, rc[o], dep + 1);
52         } else {
53             if (~rc[o]) dfs(q, d, rc[o], dep + 1);
54             if (~lc[o]) dfs(q, d, lc[o], dep + 1);
55         }
56     }
57     void init(const vector<point> &v) {
58         for (int i = 0; i < v.size(); ++i) p[i] = v[i];
59         root = build(0, v.size());
60     }
61     long long nearest(const point &q) {
62         long long res = 1e18;
63         dfs(q, res, root);
64         return res;
65     }
66 } // namespace kdt

```

3.5 min heap [b3de3d]

```

1 template <class T, class Info> struct min_heap {
2     priority_queue<pair<T, Info>, vector<pair<T, Info>>,
3         greater<pair<T, Info>>>
4     pq;
5     T lazy = 0;

```

```

6     void push(pair<T, Info> v) {
7         pq.emplace(v.X - lazy, v.Y);
8     }
9     pair<T, Info> top() {
10        return make_pair(pq.top().X + lazy, pq.top().Y);
11    }
12    void join(min_heap &rgt) {
13        if (SZ(pq) < SZ(rgt.pq)) {
14            swap(pq, rgt.pq);
15            swap(lazy, rgt.lazy);
16        }
17        while (!rgt.pq.empty()) {
18            push(rgt.top());
19            rgt.pop();
20        }
21    }
22    void pop() { pq.pop(); }
23    bool empty() { return pq.empty(); }
24    void add_lazy(T v) { lazy += v; }
25 };

```

3.6 LiChaoST [2c55c3]

```

1 struct L {
2     ll m, k, id;
3     L() : id(-1) {}
4     L(ll a, ll b, ll c) : m(a), k(b), id(c) {}
5     ll at(ll x) { return m * x + k; }
6 };
7 class LiChao { // maintain max
8 private:
9     int n;
10    vector<L> nodes;
11    void insert(int l, int r, int rt, L ln) {
12        int m = (l + r) >> 1;
13        if (nodes[rt].id == -1)
14            return nodes[rt] = ln, void();
15        bool atLeft = nodes[rt].at(l) < ln.at(l);
16        if (nodes[rt].at(m) < ln.at(m))
17            atLeft ^= 1, swap(nodes[rt], ln);
18        if (r - l == 1) return;
19        if (atLeft) insert(l, m, rt << 1, ln);
20        else insert(m, r, rt << 1 | 1, ln);
21    }
22    ll query(int l, int r, int rt, ll x) {
23        int m = (l + r) >> 1;
24        ll ret = -INF;
25        if (nodes[rt].id != -1) ret = nodes[rt].at(x);
26        if (r - l == 1) return ret;
27        if (x < m)
28            return max(ret, query(l, m, rt << 1, x));
29        return max(ret, query(m, r, rt << 1 | 1, x));
30    }
31 public:
32     LiChao(int n_) : n(n_), nodes(n * 4) {}
33     void insert(L ln) { insert(0, n, 1, ln); }
34     ll query(ll x) { return query(0, n, 1, x); }
35 };

```

3.7 Treap [4a5ee3]

```

1 struct node {
2     int data, sz;
3     node *l, *r;
4     node(int k) : data(k), sz(1), l(0), r(0) {}
5     void up() {
6         sz = 1;
7         if (l) sz += l->sz;
8         if (r) sz += r->sz;
9     }
10    void down() {}
11 };
12 int sz(node *a) { return a ? a->sz : 0; }
13 node *merge(node *a, node *b) {
14     if (!a || !b) return a ? a : b;
15     if (rand() % (sz(a) + sz(b)) < sz(a))
16         return a->down(), a->r = merge(a->r, b), a->up(),
17             a;
18     return b->down(), b->l = merge(a, b->l), b->up(), b;
19 }
20 void split(node *o, node *&a, node *&b, int k) {
21     if (!o) return a = b = 0, void();
22     o->down();
23     if (o->data <= k)
24         a = o, split(o->r, a->r, b, k), a->up();
25     else b = o, split(o->l, a, b->l, k), b->up();

```



```

26 }
27 void split2(node *o, node *&a, node *&b, int k) {
28     if (sz(o) <= k) return a = o, b = 0, void();
29     o->down();
30     if (sz(o->l) + 1 <= k)
31         a = o, split2(o->r, a->r, b, k - sz(o->l) - 1);
32     else b = o, split2(o->l, a, b->l, k);
33     o->up();
34 }
35 node *kth(node *o, int k) {
36     if (k <= sz(o->l)) return kth(o->l, k);
37     if (k == sz(o->l) + 1) return o;
38     return kth(o->r, k - sz(o->l) - 1);
39 }
40 int Rank(node *o, int key) {
41     if (!o) return 0;
42     if (o->data < key)
43         return sz(o->l) + 1 + Rank(o->r, key);
44     else return Rank(o->l, key);
45 }
46 bool erase(node *&o, int k) {
47     if (!o) return 0;
48     if (o->data == k) {
49         node *t = o;
50         o->down(), o = merge(o->l, o->r);
51         delete t;
52         return 1;
53     }
54     node *&t = k < o->data ? o->l : o->r;
55     return erase(t, k) ? o->up(), 1 : 0;
56 }
57 void insert(node *&o, int k) {
58     node *a, *b;
59     split(o, a, b, k),
60     o = merge(a, merge(new node(k), b));
61 }
62 void interval(node *&o, int l, int r) {
63     node *a, *b, *c;
64     split2(o, a, b, l - 1), split2(b, b, c, r);
65     // operate
66     o = merge(a, merge(b, c));
67 }

```

3.8 link cut tree [831293]

```

1 struct SplayTree {
2     struct Node {
3         int ch[2] = {0, 0}, p = 0;
4         long long self = 0, path = 0; // Path aggregates
5         long long sub = 0, vir = 0; // Subtree aggregates
6         bool flip = 0; // Lazy tags
7     }; vector<Node> T;
8     SplayTree(int n) : T(n + 1) {}
9     void push(int x) {
10         if (!x || !T[x].flip) return;
11         int l = T[x].ch[0], r = T[x].ch[1];
12         T[l].flip ^= 1, T[r].flip ^= 1;
13         swap(T[x].ch[0], T[x].ch[1]), T[x].flip = 0;
14     }
15     void pull(int x) {
16         int l = T[x].ch[0], r = T[x].ch[1];
17         push(l), push(r);
18         T[x].path = T[l].path + T[x].self + T[r].path;
19         T[x].sub = T[x].vir + T[l].sub + T[r].sub + T[x].self;
20     }
21     void set(int x, int d, int y) {
22         T[x].ch[d] = y, T[y].p = x, pull(x);
23     }
24     void splay(int x) {
25         auto dir = [&](int x) {
26             int p = T[x].p; if (!p) return -1;
27             return T[p].ch[0] == x ? 0 : T[p].ch[1] == x ? 1 : -1;
28         };
29         auto rotate = [&](int x) {
30             int y =
31                 T[x].p, z = T[y].p, dx = dir(x), dy = dir(y);
32             set(y, dx, T[x].ch[!dx]), set(x, !dx, y);
33             if (~dy) set(z, dy, x); T[x].p = z;
34         };
35         for (push(x); ~dir(x);) {
36             int y = T[x].p, z = T[y].p;
37             push(z), push(y), push(x);
38             int dx = dir(x), dy = dir(y);
39             if (~dy) rotate(dx != dy ? x : y);
40             rotate(x);
41         }

```

```

41     }
42 };
43
44 struct LinkCut : SplayTree {
45     LinkCut(int n) : SplayTree(n) {}
46     int access(int x) {
47         int u = x, v = 0;
48         for (; u; v = u, u = T[u].p) {
49             splay(u); int &ov = T[u].ch[1];
50             T[u].vir += T[ov].sub, T[u].vir -= T[v].sub;
51             ov = v, pull(u);
52         }
53         return splay(x), v;
54     }
55     void reroot(int x) {
56         access(x), T[x].flip ^= 1, push(x);
57     }
58     void Link(int u, int v) {
59         reroot(u), access(v);
60         T[v].vir += T[u].sub; T[u].p = v, pull(v);
61     }
62     void Cut(int u, int v) {
63         reroot(u), access(v);
64         T[v].ch[0] = T[u].p = 0; pull(v);
65     }
66     // Rooted tree LCA. 0 if u and v arent connected.
67     int LCA(int u, int v) {
68         if (u == v) return u; access(u);
69         int ret = access(v);
70         return T[u].p ? ret : 0;
71     }
72     // Query subtree of u where v is outside the subtree.
73     long long Subtree(int u, int v) {
74         reroot(v), access(u);
75         return T[u].vir + T[u].self;
76     }
77     // Query path [u..v]
78     long long Path(int u, int v) {
79         reroot(u), access(v); return T[v].path;
80     }
81     // Find root on original tree
82     int Find(int x) {
83         access(x), splay(x);
84         while (T[x].ch[0]) x = T[x].ch[0], push(x);
85         splay(x); return x;
86     }
87     // Update vertex u with value v
88     void Update(int u, long long v) {
89         access(u), T[u].self = v, pull(u);
90     }
91 };

```

3.9 Centroid Decomposition [6971c7]

```

1 struct Cent_Dec { // 1-base
2     vector<pll> G[N];
3     pll info[N]; // store info. of itself
4     pll upinfo[N]; // store info. of climbing up
5     int n, pa[N], layer[N], sz[N], done[N];
6     ll dis[_lg(N) + 1][N];
7     void init(int _n) {
8         n = _n, layer[0] = -1;
9         fill_n(pa + 1, n, 0), fill_n(done + 1, n, 0);
10        for (int i = 1; i <= n; ++i) G[i].clear();
11    }
12    void add_edge(int a, int b, int w) {
13        G[a].pb(pll(b, w)), G[b].pb(pll(a, w));
14    }
15    void get_cent(
16        int u, int f, int &mx, int &c, int num) {
17        int mxsz = 0;
18        sz[u] = 1;
19        for (pll e : G[u])
20            if (!done[e.X] && e.X != f) {
21                get_cent(e.X, u, mx, c, num);
22                sz[u] += sz[e.X], mxsz = max(mxsz, sz[e.X]);
23            }
24        if (mx > max(mxsz, num - sz[u]))
25            mx = max(mxsz, num - sz[u]), c = u;
26    }
27    void dfs(int u, int f, ll d, int org) {
28        // if required, add self info or climbing info
29        dis[layer[org]][u] = d;
30        for (pll e : G[u])
31            if (!done[e.X] && e.X != f)
32                dfs(e.X, u, d + e.Y, org);
33    }

```

```

34 int cut(int u, int f, int num) {
35     int mx = 1e9, c = 0, lc;
36     get_cent(u, f, mx, c, num);
37     done[c] = 1, pa[c] = f, layer[c] = layer[f] + 1;
38     for (pll e : G[c])
39         if (!done[e.X]) {
40             if (sz[e.X] > sz[c])
41                 lc = cut(e.X, c, num - sz[c]);
42             else lc = cut(e.X, c, sz[e.X]);
43             upinfo[lc] = pll(), dfs(e.X, c, e.Y, c);
44         }
45     return done[c] = 0, c;
46 }
47 void build() { cut(1, 0, n); }
48 void modify(int u) {
49     for (int a = u, ly = layer[a]; a;
50         a = pa[a], --ly) {
51         info[a].X += dis[ly][u], ++info[a].Y;
52         if (pa[a])
53             upinfo[a].X += dis[ly - 1][u], ++upinfo[a].Y;
54     }
55 }
56 ll query(int u) {
57     ll rt = 0;
58     for (int a = u, ly = layer[a]; a;
59         a = pa[a], --ly) {
60         rt += info[a].X + info[a].Y * dis[ly][u];
61         if (pa[a])
62             rt -= upinfo[a].X + upinfo[a].Y * dis[ly - 1][u];
63     }
64     return rt;
65 }
66 }
67 };

```

3.10 Heavy light Decomposition [b91cf9]

```

1 struct Heavy_light_Decomposition { // 1-base
2     int n, ulink[N], deep[N], mxson[N], w[N], pa[N];
3     int t, pl[N], data[N], val[N]; // val: vertex data
4     vector<int> G[N];
5     void init(int _n) {
6         n = _n;
7         for (int i = 1; i <= n; ++i)
8             G[i].clear(), mxson[i] = 0;
9     }
10    void add_edge(int a, int b) {
11        G[a].pb(b), G[b].pb(a);
12    }
13    void dfs(int u, int f, int d) {
14        w[u] = 1, pa[u] = f, deep[u] = d++;
15        for (int &i : G[u])
16            if (i != f) {
17                dfs(i, u, d), w[u] += w[i];
18                if (w[mxson[u]] < w[i]) mxson[u] = i;
19            }
20    }
21    void cut(int u, int link) {
22        data[pl[u] = ++t] = val[u], ulink[u] = link;
23        if (!mxson[u]) return;
24        cut(mxson[u], link);
25        for (int i : G[u])
26            if (i != pa[u] && i != mxson[u]) cut(i, i);
27    }
28    void build() { dfs(1, 1, 1), cut(1, 1), /*build*/; }
29    int query(int a, int b) {
30        int ta = ulink[a], tb = ulink[b], res = 0;
31        while (ta != tb) {
32            if (deep[ta] > deep[tb])
33                swap(ta, tb), swap(a, b);
34            // query(pl[tb], pl[b])
35            tb = ulink[b = pa[tb]];
36        }
37        if (pl[a] > pl[b]) swap(a, b);
38        // query(pl[a], pl[b])
39    }
40 };

```

4 Flow Matching

4.1 Model

- Maximum/Minimum flow with lower bound / Circulation problem

- Construct super source S and sink T .
- For each edge (x, y, l, u) , connect $x \rightarrow y$ with capacity $u - l$.
- For each vertex v , denote by $in(v)$ the difference between the sum of incoming lower bounds and the sum of outgoing lower bounds.

- If $in(v) > 0$, connect $S \rightarrow v$ with capacity $in(v)$, otherwise, connect $v \rightarrow T$ with capacity $-in(v)$.
 - To maximize, connect $t \rightarrow s$ with capacity ∞ (skip this in circulation problem), and let f be the maximum flow from S to T . If $f \neq \sum_{v \in V, in(v) > 0} in(v)$, there's no solution. Otherwise, the maximum flow from s to t is the answer.
 - To minimize, let f be the maximum flow from S to T . Connect $t \rightarrow s$ with capacity ∞ and let the flow from S to T be f' . If $f + f' \neq \sum_{v \in V, in(v) > 0} in(v)$, there's no solution. Otherwise, f' is the answer.
- The solution of each edge e is $l_e + f_e$, where f_e corresponds to the flow of edge e on the graph.
- Construct minimum vertex cover from maximum matching M on bipartite graph (X, Y)
 - Redirect every edge: $y \rightarrow x$ if $(x, y) \in M$, $x \rightarrow y$ otherwise.
 - DFS from unmatched vertices in X .
 - $x \in X$ is chosen iff x is unvisited.
 - $y \in Y$ is chosen iff y is visited.
- Minimum cost cyclic flow
 - Construct super source S and sink T
 - For each edge (x, y, c) , connect $x \rightarrow y$ with $(cost, cap) = (c, 1)$ if $c > 0$, otherwise connect $y \rightarrow x$ with $(cost, cap) = (-c, 1)$
 - For each edge with $c < 0$, sum these cost as K , then increase $d(y)$ by 1, decrease $d(x)$ by 1
 - For each vertex v with $d(v) > 0$, connect $S \rightarrow v$ with $(cost, cap) = (0, d(v))$
 - For each vertex v with $d(v) < 0$, connect $v \rightarrow T$ with $(cost, cap) = (0, -d(v))$
 - Flow from S to T , the answer is the cost of the flow $C + K$
- Maximum density induced subgraph
 - Binary search on answer, suppose we're checking answer T
 - Construct a max flow model, let K be the sum of all weights
 - Connect source $s \rightarrow v, v \in G$ with capacity K
 - For each edge (u, v, w) in G , connect $u \rightarrow v$ and $v \rightarrow u$ with capacity w
 - For $v \in G$, connect it with sink $v \rightarrow t$ with capacity $K + 2T - (\sum_{e \in E(v)} w(e)) - 2w(v)$
 - T is a valid answer if the maximum flow $f < K|V|$
- Minimum weight edge cover
 - For each $v \in V$ create a copy v' , and connect $u' \rightarrow v'$ with weight $w(u, v)$.
 - Connect $v \rightarrow v'$ with weight $2\mu(v)$, where $\mu(v)$ is the cost of the cheapest edge incident to v .
 - Find the minimum weight perfect matching on G' .
- Project selection problem
 - If $p_v > 0$, create edge (s, v) with capacity p_v ; otherwise, create edge (v, t) with capacity $-p_v$.
 - Create edge (u, v) with capacity w with w being the cost of choosing u without choosing v .
 - The mincut is equivalent to the maximum profit of a subset of projects.
- Dual of minimum cost maximum flow
 - Capacity c_{uv} , Flow f_{uv} , Cost w_{uv} , Required Flow difference for vertex b_u .
 - If all w_{uv} are integers, then optimal solution can happen when all p_u are integers.

$$\min \sum_{uv} w_{uv} f_{uv} \quad \min \sum_u b_u p_u + \sum_{uv} c_{uv} \max(0, p_v - p_u - w_{uv})$$

$$-f_{uv} \geq -c_{uv} \Leftrightarrow \sum_v f_{vu} - \sum_v f_{uv} = -b_u \quad p_u \geq 0$$

4.2 Dinic [ba0999]

```

1 struct MaxFlow { // 0-base
2     struct edge {
3         int to, cap, flow, rev;
4     };
5     vector<edge> G[MAXN];
6     int s, t, dis[MAXN], cur[MAXN], n;
7     int dfs(int u, int cap) {
8         if (u == t || !cap) return cap;
9         for (int &i = cur[u]; i < (int)G[u].size(); ++i) {
10             edge &e = G[u][i];
11             if (dis[e.to] == dis[u] + 1 && e.flow != e.cap) {
12                 int df = dfs(e.to, min(e.cap - e.flow, cap));
13                 if (df) {
14                     e.flow += df; G[e.to][e.rev].flow -= df;
15                     return df;
16                 }
17             }
18         }
19         dis[u] = -1;
20         return 0;
21     }
22     bool bfs() {
23         fill_n(dis, n, -1);
24         queue<int> q;

```

```

25 q.push(s), dis[s] = 0;
26 while (!q.empty()) {
27     int tmp = q.front(); q.pop();
28     for (auto &u : G[tmp])
29         if (!dis[u.to] && u.flow != u.cap) {
30             q.push(u.to); dis[u.to] = dis[tmp] + 1;
31         }
32     }
33     return dis[t] != -1;
34 }
35 int maxflow(int _s, int _t) {
36     s = _s, t = _t;
37     int flow = 0, df;
38     while (bfs()) {
39         fill_n(cur, n, 0);
40         while ((df = dfs(s, INF))) flow += df;
41     }
42     return flow;
43 }
44 void init(int _n) {
45     n = _n;
46     for (int i = 0; i < n; ++i) G[i].clear();
47 }
48 void reset() {
49     for (int i = 0; i < n; ++i)
50         for (auto &j : G[i]) j.flow = 0;
51 }
52 void add_edge(int u, int v, int cap) {
53     G[u].pb(edge{v, cap, 0, (int)G[v].size()});
54     G[v].pb(edge{u, 0, 0, (int)G[u].size() - 1});
55 }
56 };

```

4.3 Maximum Simple Graph Matching [390d20]

```

1 struct Matching { // 0-base
2     queue<int> q;
3     int n;
4     vector<int> fa, s, vis, pre, match;
5     vector<vector<int>> G;
6     int Find(int u) {
7         return u == fa[u] ? u : fa[u] = Find(fa[u]);
8     }
9     int LCA(int x, int y) {
10         static int tk = 0;
11         tk++;
12         x = Find(x);
13         y = Find(y);
14         for (; swap(x, y))
15             if (x != n) {
16                 if (vis[x] == tk) return x;
17                 vis[x] = tk;
18                 x = Find(pre[match[x]]);
19             }
20     }
21     void Blossom(int x, int y, int l) {
22         for (; Find(x) != l; x = pre[y]) {
23             pre[x] = y, y = match[x];
24             if (s[y] == 1) q.push(y), s[y] = 0;
25             for (int z : {x, y})
26                 if (fa[z] == z) fa[z] = l;
27         }
28     }
29     bool Bfs(int r) {
30         iota(ALL(fa), 0);
31         fill(ALL(s), -1);
32         q = queue<int>();
33         q.push(r);
34         s[r] = 0;
35         for (; !q.empty(); q.pop()) {
36             for (int x = q.front(); int u : G[x])
37                 if (s[u] == -1) {
38                     if (pre[u] = x, s[u] = 1, match[u] == n) {
39                         for (int a = u, b = x, last; b != n;
40                             a = last, b = pre[a])
41                             last = match[b], match[b] = a,
42                             match[a] = b;
43                         return true;
44                     }
45                     q.push(match[u]);
46                     s[match[u]] = 0;
47                 } else if (!s[u] && Find(u) != Find(x)) {
48                     int l = LCA(u, x);
49                     Blossom(x, u, l);
50                     Blossom(u, x, l);
51                 }
52             }
53         }
54     }
55 };

```

```

53     return false;
54 }
55 Matching(int _n)
56     : n(_n), fa(n + 1), s(n + 1), vis(n + 1),
57       pre(n + 1, n), match(n + 1, n), G(n) {}
58 void add_edge(int u, int v) {
59     G[u].pb(v), G[v].pb(u);
60 }
61 int solve() {
62     int ans = 0;
63     for (int x = 0; x < n; ++x)
64         if (match[x] == n) ans += Bfs(x);
65     return ans;
66 } // match[x] == n means not matched
67 };

```

4.4 Kuhn Munkres [61bbd0]

```

1 struct KM { // 0-base, maximum matching
2     ll w[N][N], hl[N], hr[N], slk[N];
3     int fl[N], fr[N], pre[N], qu[N], ql, qr, n;
4     bool vl[N], vr[N];
5     void init(int _n) {
6         n = _n;
7         for (int i = 0; i < n; ++i) fill_n(w[i], n, -INF);
8     }
9     void add_edge(int a, int b, ll wei) {
10         w[a][b] = wei;
11     }
12     bool Check(int x) {
13         if (vl[x] = 1, ~fl[x])
14             return vr[qu[qr++]] = fl[x] = 1;
15         while (~x) swap(x, fr[fl[x] = pre[x]]);
16         return 0;
17     }
18     void bfs(int s) {
19         fill_n(slk, n, INF), fill_n(vl, n, 0),
20         fill_n(vr, n, 0);
21         ql = qr = 0, qu[qr++] = s, vr[s] = 1;
22         for (ll d;;) {
23             while (ql < qr)
24                 for (int x = 0, y = qu[ql++]; x < n; ++x)
25                     if (!vl[x] &&
26                         slk[x] >= (d = hl[x] + hr[y] - w[x][y])) {
27                         if (pre[x] = y, d) slk[x] = d;
28                         else if (!Check(x)) return;
29                     }
30             d = INF;
31             for (int x = 0; x < n; ++x)
32                 if (!vl[x] && d > slk[x]) d = slk[x];
33             for (int x = 0; x < n; ++x) {
34                 if (vl[x]) hl[x] += d;
35                 else slk[x] -= d;
36                 if (vr[x]) hr[x] -= d;
37             }
38             for (int x = 0; x < n; ++x)
39                 if (!vl[x] && !slk[x] && !Check(x)) return;
40         }
41     }
42     ll solve() {
43         fill_n(fl, n, -1), fill_n(fr, n, -1),
44         fill_n(hr, n, 0);
45         for (int i = 0; i < n; ++i)
46             hl[i] = *max_element(w[i], w[i] + n);
47         for (int i = 0; i < n; ++i) bfs(i);
48         ll res = 0;
49         for (int i = 0; i < n; ++i) res += w[i][fl[i]];
50         return res;
51     }
52 };

```

4.5 General Matching Random [d19c20]

```

1 struct GenearlMatching { // 1-base
2     int n, ans;
3     vector<vector<int>> G; // adjacency matrix
4     vector<int> vis, linked, p, q, anslink;
5     GenearlMatching(int n_) : n(n_), ans(0),
6     G(n+1,
7         vector<int>(n+1, 0)), vis(n+1), linked(n+1),
8     p(n+1), q(n+1), anslink(n+1) {}
9     void add_edge(int u, int v) { G[u][v] = G[v][u] = 1; }
10    void update(int tmp) {
11        ans = tmp;
12        for (int i = 1; i <= n; i++)
13            anslink[i] = linked[i];
14    }
15 };

```



```

13 }
14 bool match(int u) {
15     vis[u] = 1;
16     for (int i = 1; i <= n; i++) {
17         int v = q[i];
18         if (vis[v] || !G[u][v]) continue; vis[v] = 1;
19         if (!linked[v] || match(linked[v])) {
20             linked[v] = u; linked[u] = v; return true;
21         }
22     }
23     return false;
24 }
25 void work() {
26     fill(ALL(linked), 0);
27     int tmp = 0;
28     for (int i = 1; i <= n; i++)
29         if (!linked[p[i]])
30             for (int t = 1; t <= 5; t++) {
31                 fill(ALL(vis), 0);
32                 if (match(p[i])) {
33                     tmp++; break;
34                 } else {
35                     for (int j = 1; j <= n; j++) {
36                         int k = j + rand() % (n - j + 1);
37                         swap(q[j], q[k]);
38                     }
39                 }
40             }
41     if (tmp > ans)
42         update(tmp);
43 }
44 void solve(int testtimes = 5) {
45     srand(541213);
46     for (int i = 1; i <= n; i++)
47         p[i] = q[i] = i;
48     while (testtimes--) {
49         for (int i = 1; i <= n; i++) {
50             int j = i + rand() % (n - i + 1);
51             swap(p[i], p[j]);
52             j = i + rand() % (n - i + 1);
53             swap(q[i], q[j]);
54         }
55         work();
56     }
57 }
58 vector<pair<int, int>> get_answer() {
59     vector<pair<int, int>> ans;
60     for (int i = 1; i <= n; i++) {
61         if (anslink[i] > i)
62             ans.emplace_back(i, anslink[i]);
63     }
64     return ans;
65 }
66 };

```

4.6 isap [a2dc77]

```

1 struct Maxflow {
2     static const int MAXV = 20010;
3     static const int INF = 1000000;
4     struct Edge {
5         int v, c, r;
6         Edge(int _v, int _c, int _r)
7             : v(_v), c(_c), r(_r) {}
8     };
9     int s, t;
10    vector<Edge> G[MAXV * 2];
11    int iter[MAXV * 2], d[MAXV * 2], gap[MAXV * 2], tot;
12    void init(int x) {
13        tot = x + 2;
14        s = x + 1, t = x + 2;
15        for (int i = 0; i <= tot; i++) {
16            G[i].clear();
17            iter[i] = d[i] = gap[i] = 0;
18        }
19    }
20    void addEdge(int u, int v, int c) {
21        G[u].push_back(Edge(v, c, SZ(G[v])));
22        G[v].push_back(Edge(u, 0, SZ(G[u]) - 1));
23    }
24    int dfs(int p, int flow) {
25        if (p == t) return flow;
26        for (int &i = iter[p]; i < SZ(G[p]); i++) {
27            Edge &e = G[p][i];
28            if (e.c > 0 && d[p] == d[e.v] + 1) {
29                int f = dfs(e.v, min(flow, e.c));
30                if (f) {

```

```

31                    e.c -= f;
32                    G[e.v][e.r].c += f;
33                    return f;
34                }
35            }
36        }
37        if ((--gap[d[p]]) == 0) d[s] = tot;
38        else {
39            d[p]++;
40            iter[p] = 0;
41            ++gap[d[p]];
42        }
43        return 0;
44    }
45    int solve() {
46        int res = 0;
47        gap[0] = tot;
48        for (res = 0; d[s] < tot; res += dfs(s, INF));
49        return res;
50    }
51 } flow;

```

4.7 Gomory Hu tree [62c88c]

```

1 MaxFlow Dinic;
2 int g[MAXN];
3 void GomoryHu(int n) { // 0-base
4     fill_n(g, n, 0);
5     for (int i = 1; i < n; ++i) {
6         Dinic.reset();
7         add_edge(i, g[i], Dinic.maxflow(i, g[i]));
8         for (int j = i + 1; j <= n; ++j)
9             if (g[j] == g[i] && ~Dinic.dis[j]) g[j] = i;
10    }
11 }

```

4.8 MincostMaxflow [0722e9]

```

1 struct MinCostMaxFlow { // 0-base
2     struct Edge {
3         ll from, to, cap, flow, cost, rev;
4     } *past[N];
5     vector<Edge> G[N];
6     int inq[N], n, s, t;
7     ll dis[N], up[N], pot[N];
8     bool BellmanFord() {
9         fill_n(dis, n, INF), fill_n(inq, n, 0);
10        queue<int> q;
11        auto relax = [&](int u, ll d, ll cap, Edge *e) {
12            if (cap > 0 && dis[u] > d) {
13                dis[u] = d, up[u] = cap, past[u] = e;
14                if (!inq[u]) inq[u] = 1, q.push(u);
15            }
16        };
17        relax(s, 0, INF, 0);
18        while (!q.empty()) {
19            int u = q.front();
20            q.pop(), inq[u] = 0;
21            for (auto &e : G[u]) {
22                ll d2 = dis[u] + e.cost + pot[u] - pot[e.to];
23                relax(e.to, d2, min(up[u], e.cap - e.flow), &e);
24            }
25        }
26        return dis[t] != INF;
27    }
28    void solve(int _s, int _t, ll &flow, ll &cost,
29        bool neg = true) {
30        s = _s, t = _t, flow = 0, cost = 0;
31        if (neg) BellmanFord(), copy_n(dis, n, pot);
32        for (; BellmanFord(); copy_n(dis, n, pot)) {
33            for (int i = 0; i < n; ++i)
34                dis[i] += pot[i] - pot[s];
35            flow += up[t], cost += up[t] * dis[t];
36            for (int i = t; past[i]; i = past[i]->from) {
37                auto &e = *past[i];
38                e.flow += up[t], G[e.to][e.rev].flow -= up[t];
39            }
40        }
41    }
42    void init(int _n) {
43        n = _n, fill_n(pot, n, 0);
44        for (int i = 0; i < n; ++i) G[i].clear();
45    }
46    void add_edge(ll a, ll b, ll cap, ll cost) {
47        G[a].pb(Edge{a, b, cap, 0, cost, SZ(G[b])});
48        G[b].pb(Edge{b, a, 0, 0, -cost, SZ(G[a]) - 1});
49    }

```

```
50 }
51 };
```

4.9 SW-mincut [8e90f0]

```
1 struct SW { // global min cut, O(V^3)
2 #define REP for (int i = 0; i < n; ++i)
3 static const int MXN = 514, INF = 2147483647;
4 int vst[MXN], edge[MXN][MXN], wei[MXN];
5 void init(int n) { REP fill_n(edge[i], n, 0); }
6 void addEdge(int u, int v, int w) {
7     edge[u][v] += w;
8     edge[v][u] += w;
9 }
10 int search(int &s, int &t, int n) {
11     fill_n(vst, n, 0), fill_n(wei, n, 0);
12     s = t = -1;
13     int mx, cur;
14     for (int j = 0; j < n; ++j) {
15         mx = -1, cur = 0;
16         REP if (wei[i] > mx) cur = i, mx = wei[i];
17         vst[cur] = 1, wei[cur] = -1;
18         s = t;
19         t = cur;
20         REP if (!vst[i]) wei[i] += edge[cur][i];
21     }
22     return mx;
23 }
24 int solve(int n) {
25     int res = INF;
26     for (int x, y; n > 1; n--) {
27         res = min(res, search(x, y, n));
28         REP edge[i][x] = (edge[x][i] + edge[y][i]);
29         REP {
30             edge[y][i] = edge[n - 1][i];
31             edge[i][y] = edge[i][n - 1];
32         } // edge[y][y] = 0;
33     }
34     return res;
35 }
36 } SW;
```

4.10 Bipartite Matching [623c76]

```
1 struct Bipartite_Matching { // 0-base
2 int mp[N], mq[N], dis[N + 1], cur[N], l, r;
3 vector<int> G[N + 1];
4 bool dfs(int u) {
5     for (int &i = cur[u]; i < SZ(G[u]); ++i) {
6         int e = G[u][i];
7         if (mq[e] == l ||
8             (dis[mq[e]] == dis[u] + 1 && dfs(mq[e])))
9             return mp[mq[e] = u] = e, 1;
10    }
11    return dis[u] = -1, 0;
12 }
13 bool bfs() {
14     queue<int> q;
15     fill_n(dis, l + 1, -1);
16     for (int i = 0; i < l; ++i)
17         if (!mp[i]) q.push(i), dis[i] = 0;
18     while (!q.empty()) {
19         int u = q.front();
20         q.pop();
21         for (int e : G[u])
22             if (!dis[mq[e]])
23                 q.push(mq[e]), dis[mq[e]] = dis[u] + 1;
24     }
25     return dis[l] != -1;
26 }
27 int matching() {
28     int res = 0;
29     fill_n(mp, l, -1), fill_n(mq, r, l);
30     while (bfs()) {
31         fill_n(cur, l, 0);
32         for (int i = 0; i < l; ++i)
33             res += (!mp[i] && dfs(i));
34     }
35     return res; // (i, mp[i] != -1)
36 }
37 void add_edge(int s, int t) { G[s].pb(t); }
38 void init(int _l, int _r) {
39     l = _l, r = _r;
40     for (int i = 0; i <= l; ++i) G[i].clear();
41 }
42 };
```

4.11 BoundedFlow [e8670b]

```
1 struct BoundedFlow { // 0-base
2     struct edge {
3         int to, cap, flow, rev;
4     };
5     vector<edge> G[N];
6     int n, s, t, dis[N], cur[N], cnt[N];
7     void init(int _n) {
8         n = _n;
9         for (int i = 0; i < n + 2; ++i)
10             G[i].clear(), cnt[i] = 0;
11    }
12    void add_edge(int u, int v, int lcap, int rcap) {
13        cnt[u] -= lcap, cnt[v] += lcap;
14        G[u].pb(edge{v, rcap, lcap, SZ(G[v])});
15        G[v].pb(edge{u, 0, 0, SZ(G[u]) - 1});
16    }
17    void add_edge(int u, int v, int cap) {
18        G[u].pb(edge{v, cap, 0, SZ(G[v])});
19        G[v].pb(edge{u, 0, 0, SZ(G[u]) - 1});
20    }
21    int dfs(int u, int cap) {
22        if (u == t || !cap) return cap;
23        for (int &i = cur[u]; i < SZ(G[u]); ++i) {
24            edge &e = G[u][i];
25            if (dis[e.to] == dis[u] + 1 && e.cap != e.flow) {
26                int df = dfs(e.to, min(e.cap - e.flow, cap));
27                if (df) {
28                    e.flow += df, G[e.to][e.rev].flow -= df;
29                    return df;
30                }
31            }
32        }
33        dis[u] = -1;
34        return 0;
35    }
36    bool bfs() {
37        fill_n(dis, n + 3, -1);
38        queue<int> q;
39        q.push(s), dis[s] = 0;
40        while (!q.empty()) {
41            int u = q.front();
42            q.pop();
43            for (edge &e : G[u])
44                if (!dis[e.to] && e.flow != e.cap)
45                    q.push(e.to), dis[e.to] = dis[u] + 1;
46        }
47        return dis[t] != -1;
48    }
49    int maxflow(int _s, int _t) {
50        s = _s, t = _t;
51        int flow = 0, df;
52        while (bfs()) {
53            fill_n(cur, n + 3, 0);
54            while ((df = dfs(s, INF))) flow += df;
55        }
56        return flow;
57    }
58    bool solve() {
59        int sum = 0;
60        for (int i = 0; i < n; ++i)
61            if (cnt[i] > 0)
62                add_edge(n + 1, i, cnt[i]), sum += cnt[i];
63            else if (cnt[i] < 0) add_edge(i, n + 2, -cnt[i]);
64        if (sum != maxflow(n + 1, n + 2)) sum = -1;
65        for (int i = 0; i < n; ++i)
66            if (cnt[i] > 0)
67                G[n + 1].pop_back(), G[i].pop_back();
68            else if (cnt[i] < 0)
69                G[i].pop_back(), G[n + 2].pop_back();
70        return sum != -1;
71    }
72    int solve(int _s, int _t) {
73        add_edge(_t, _s, INF);
74        if (!solve()) return -1; // invalid flow
75        int x = G[_t].back().flow;
76        return G[_t].pop_back(), G[_s].pop_back(), x;
77    }
78 };
```

5 String

5.1 Smallest Rotation [d69462]

```
1 string mcp(string s) {
2     int n = SZ(s), i = 0, j = 1;
```

```

3   s += s;
4   while (i < n && j < n) {
5       int k = 0;
6       while (k < n && s[i + k] == s[j + k]) ++k;
7       if (s[i + k] <= s[j + k]) j += k + 1;
8       else i += k + 1;
9       if (i == j) ++j;
10  }
11  int ans = i < n ? i : j;
12  return s.substr(ans, n);
13 }

```

5.2 KMP [32f229]

```

1  int F[MAXN];
2  vector<int> match(string A, string B) {
3      vector<int> ans;
4      F[0] = -1, F[1] = 0;
5      for (int i = 1, j = 0; i < SZ(B); F[++i] = ++j) {
6          if (B[i] == B[j]) F[i] = F[j]; // optimize
7          while (j != -1 && B[i] != B[j]) j = F[j];
8      }
9      for (int i = 0, j = 0; i < SZ(A); ++i) {
10         while (j != -1 && A[i] != B[j]) j = F[j];
11         if (++j == SZ(B)) ans.pb(i + 1 - j), j = F[j];
12     }
13     return ans;
14 }

```

5.3 Manacher [11ebce]

```

1  int z[MAXN]; // 0-base
2  /* center i: radius z[i * 2 + 1] / 2
3     center i, i + 1: radius z[i * 2 + 2] / 2
4     both aba, abba have radius 2 */
5  void Manacher(string tmp) {
6      string s = "%";
7      int l = 0, r = 0;
8      for (char c : tmp) s.pb(c), s.pb('%');
9      for (int i = 0; i < SZ(s); ++i) {
10         z[i] = r > i ? min(z[2 * l - i], r - i) : 1;
11         while (i - z[i] >= 0 && i + z[i] < SZ(s) &&
12             s[i + z[i]] == s[i - z[i]])
13             ++z[i];
14         if (z[i] + i > r) r = z[i] + i, l = i;
15     }
16 }

```

5.4 De Bruijn sequence [151f80]

```

1  constexpr int MAXC = 10, MAXN = 1e5 + 10;
2  struct DBSeq {
3      int C, N, K, L, buf[MAXC * MAXN]; // K <= C^N
4      void dfs(int *out, int t, int p, int &ptr) {
5          if (ptr >= L) return;
6          if (t > N) {
7              if (N % p) return;
8              for (int i = 1; i <= p && ptr < L; ++i)
9                  out[ptr++] = buf[i];
10         } else {
11             buf[t] = buf[t - p], dfs(out, t + 1, p, ptr);
12             for (int j = buf[t - p] + 1; j < C; ++j)
13                 buf[t] = j, dfs(out, t + 1, t, ptr);
14         }
15     }
16     void solve(int _c, int _n, int _k, int *out) {
17         int p = 0;
18         C = _c, N = _n, K = _k, L = N + K - 1;
19         dfs(out, 1, 1, p);
20         if (p < L) fill(out + p, out + L, 0);
21     }
22 } dbs;

```

5.5 Aho-Corasick Automatan [60b685]

```

1  struct auto_AC_machine {
2      static const int mxN = 5e5 + 5;
3      int trie[mxN][26], ed[mxN], fail[mxN], dp[mxN], tot;
4      inline int insert(string &s) {
5          int u = 0;
6          for (auto i : s) {
7              if (!trie[u][i - 'a']) trie[u][i - 'a'] = ++tot;
8              u = trie[u][i - 'a'];
9          }
10         ed[u]++; return u;
11     }
12     int topo[mxN], tp;
13     inline void build() {

```

```

14     queue<int> q; q.push(0); tp = 0;
15     while (!q.empty()) {
16         int u = q.front(); q.pop(); topo[tp++] = u;
17         for (int i = 0; i < 26; i++) {
18             int &to = trie[u][i];
19             if (to) {
20                 fail[to] = (u == 0 ? 0 : trie[fail[u]][i]);
21                 q.push(to);
22             } else to = trie[fail[u]][i];
23         }
24     }
25 }
26 inline void DP() {
27     for (int i = tp - 1; i >= 0; i--) {
28         int u = topo[i];
29     }
30 }
31 } AC;

```

5.6 Suffix Array [b981d5]

```

1  struct suffix_array {
2      int box[MAXN], tp[MAXN], m;
3      bool not_equ(int a, int b, int k, int n) {
4          return ra[a] != ra[b] || a + k >= n ||
5             b + k >= n || ra[a + k] != ra[b + k];
6      }
7      void radix(int *key, int *it, int *ot, int n) {
8          fill_n(box, m, 0);
9          for (int i = 0; i < n; ++i) ++box[key[i]];
10         partial_sum(box, box + m, box);
11         for (int i = n - 1; i >= 0; --i)
12             ot[--box[key[it[i]]]] = it[i];
13     }
14     void make_sa(const string &s, int n) {
15         int k = 1;
16         for (int i = 0; i < n; ++i) ra[i] = s[i];
17         do {
18             iota(tp, tp + k, n - k), iota(sa + k, sa + n, 0);
19             radix(ra + k, sa + k, tp + k, n - k);
20             radix(ra, tp, sa, n);
21             tp[sa[0]] = 0, m = 1;
22             for (int i = 1; i < n; ++i) {
23                 m += not_equ(sa[i], sa[i - 1], k, n);
24                 tp[sa[i]] = m - 1;
25             }
26             copy_n(tp, n, ra);
27             k *= 2;
28         } while (k < n && m != n);
29     }
30     void make_he(const string &s, int n) {
31         for (int j = 0, k = 0; j < n; ++j) {
32             if (ra[j])
33                 for (; s[j + k] == s[sa[ra[j] - 1] + k]; ++k);
34             he[ra[j]] = k, k = max(0, k - 1);
35         }
36     }
37     int sa[MAXN], ra[MAXN], he[MAXN];
38     void build(const string &s) {
39         int n = SZ(s);
40         fill_n(sa, n, 0), fill_n(ra, n, 0),
41             fill_n(he, n, 0);
42         fill_n(box, n, 0), fill_n(tp, n, 0), m = 256;
43         make_sa(s, n), make_he(s, n);
44     }
45 };

```

5.7 SAM [4d0baa]

```

1  const int MAXM = 1000010;
2  struct SAM {
3      int tot, root, lst, mom[MAXM], mx[MAXM];
4      int nxt[MAXM][33], cnt[MAXM], in[MAXM];
5      int newNode() {
6          int res = ++tot;
7          fill(nxt[res], nxt[res] + 33, 0);
8          mom[res] = mx[res] = cnt[res] = in[res] = 0;
9          return res;
10     }
11     void init() {
12         tot = 0;
13         root = newNode();
14         mom[root] = 0, mx[root] = 0;
15         lst = root;
16     }
17     void push(int c) {
18         int p = lst;

```

```

19  int np = newNode();
20  mx[np] = mx[p] + 1;
21  for (; p && nxt[p][c] == 0; p = mom[p])
22    nxt[p][c] = np;
23  if (p == 0) mom[np] = root;
24  else {
25    int q = nxt[p][c];
26    if (mx[p] + 1 == mx[q]) mom[np] = q;
27    else {
28      int nq = newNode();
29      mx[nq] = mx[p] + 1;
30      for (int i = 0; i < 33; i++)
31        nxt[nq][i] = nxt[q][i];
32      mom[nq] = mom[q];
33      mom[q] = nq;
34      mom[np] = nq;
35      for (; p && nxt[p][c] == q; p = mom[p])
36        nxt[p][c] = nq;
37    }
38  }
39  lst = np, cnt[np] = 1;
40 }
41 void push(char *str) {
42   for (int i = 0; str[i]; i++)
43     push(str[i] - 'a' + 1);
44 }
45 void count() {
46   for (int i = 1; i <= tot; ++i) ++in[mom[i]];
47   queue<int> q;
48   for (int i = 1; i <= tot; ++i)
49     if (!in[i]) q.push(i);
50   while (!q.empty()) {
51     int u = q.front();
52     q.pop();
53     cnt[mom[u]] += cnt[u];
54     if (!--in[mom[u]]) q.push(mom[u]);
55   }
56 }
57 } sam;

```

5.8 Z-value [2e5c4c]

```

1  int z[MAXn];
2  void make_z(const string &s) {
3    int l = 0, r = 0;
4    for (int i = 1; i < SZ(s); ++i) {
5      for (z[i] = max(0, min(r - i + 1, z[i - l]));
6           i + z[i] < SZ(s) && s[i + z[i]] == s[z[i]];
7           ++z[i]);
8      if (i + z[i] - 1 > r) l = i, r = i + z[i] - 1;
9    }
10 }

```

5.9 MainLorentz [2981c4]

```

1  vector<pair<int, int>> rep[kN]; // 0-base [l, r]
2  void main_lorentz(const string &s, int sft = 0) {
3    const int n = s.size();
4    if (n == 1) return;
5    const int nu = n / 2, nv = n - nu;
6    const string u = s.substr(0, nu), v = s.substr(nu),
7      ru(u.rbegin(), u.rend()),
8      rv(v.rbegin(), v.rend());
9    main_lorentz(u, sft), main_lorentz(v, sft + nu);
10   const auto z1 = Zalgo(ru), z2 = Zalgo(v + '#' + u),
11     z3 = Zalgo(ru + '#' + rv), z4 = Zalgo(v);
12   auto get_z = [](const vector<int> &z, int i) {
13     return (0 <= i and i < (int)z.size()) ? z[i] : 0;
14   };
15   auto add_rep = [&](bool left, int c, int l, int k1,
16     int k2) {
17     const int L = max(1, l - k2),
18       R = min(l - left, k1);
19     if (L > R) return;
20     if (left)
21       rep[l].emplace_back(sft + c - R, sft + c - L);
22     else
23       rep[l].emplace_back(
24         sft + c - R - l + 1, sft + c - L - l + 1);
25   };
26   for (int cnt = 0; cnt < n; cnt++) {
27     int l, k1, k2;
28     if (cnt < nu) {
29       l = nu - cnt;
30       k1 = get_z(z1, nu - cnt);
31       k2 = get_z(z2, nv + 1 + cnt);
32     } else {

```

```

33     l = cnt - nu + 1;
34     k1 = get_z(z3, nu + 1 + nv - 1 - (cnt - nu));
35     k2 = get_z(z4, (cnt - nu) + 1);
36   }
37   if (k1 + k2 >= l)
38     add_rep(cnt < nu, cnt, l, k1, k2);
39 }
40 } // p \in [l, r] => s[p, p + i) = s[p + i, p + 2i)

```

6 Math

6.1 numbers

- Bernoulli numbers

$$B_0 = 1, B_1^{\pm} = \pm \frac{1}{2}, B_2 = \frac{1}{6}, B_3 = 0$$

$$\sum_{j=0}^m \binom{m+1}{j} B_j = 0, \text{EGF is } B(x) = \frac{x}{e^x - 1} = \sum_{n=0}^{\infty} B_n \frac{x^n}{n!}.$$

$$S_m(n) = \sum_{k=1}^n k^m = \frac{1}{m+1} \sum_{k=0}^m \binom{m+1}{k} B_k^+ n^{m+1-k}$$

- Stirling numbers of the second kind Partitions of n distinct elements into exactly k groups.

$$S(n, k) = S(n-1, k-1) + kS(n-1, k), S(n, 1) = S(n, n) = 1$$

$$S(n, k) = \frac{1}{k!} \sum_{i=0}^k (-1)^{k-i} \binom{k}{i} i^n$$

$$x^n = \sum_{i=0}^n S(n, i) (x)_i$$

- Pentagonal number theorem

$$\prod_{n=1}^{\infty} (1 - x^n) = 1 + \sum_{k=1}^{\infty} (-1)^k \left(x^{k(3k+1)/2} + x^{k(3k-1)/2} \right)$$

- Catalan numbers

$$C_n^{(k)} = \frac{1}{(k-1)n+1} \binom{kn}{n}$$

$$C^{(k)}(x) = 1 + x[C^{(k)}(x)]^k$$

- Eulerian numbers

Number of permutations $\pi \in S_n$ in which exactly k elements are greater than the previous element. k, j s.t. $\pi(j) > \pi(j+1)$, $k+1, j$ s.t. $\pi(j) \geq j, k, j$ s.t. $\pi(j) > j$.

$$E(n, k) = (n-k)E(n-1, k-1) + (k+1)E(n-1, k)$$

$$E(n, 0) = E(n, n-1) = 1$$

$$E(n, k) = \sum_{j=0}^k (-1)^j \binom{n+1}{j} (k+1-j)^n$$

6.2 Estimation

n	2	3	4	5	6	7	8	9	20	30	40	50	100		
$p(n)$	2	3	5	7	11	15	22	30	627	5604	4e4	2e5	2e8		
n	100	1e3	1e6	1e9	1e12	1e15	1e18								
$d(i)$	12	32	240	1344	6720	26880	103680								
n	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
$\binom{2n}{n}$	2	6	20	70	252	924	3432	12870	48620	184756	7e5	2e6	1e7	4e7	1.5e8
n	2	3	4	5	6	7	8	9	10	11	12	13			
B_n	2	5	15	52	203	877	4140	21147	115975	7e5	4e6	3e7			

6.3 chineseRemainder [0e2467]

```

1  ll solve(ll x1, ll m1, ll x2, ll m2) {
2    ll g = gcd(m1, m2);
3    if ((x2 - x1) % g) return -1; // no sol
4    m1 /= g;
5    m2 /= g;
6    pll p = exgcd(m1, m2);
7    ll lcm = m1 * m2 * g;
8    ll res = p.first * (x2 - x1) * m1 + x1;
9    // be careful with overflow
10   return (res % lcm + lcm) % lcm;
11 }

```

6.4 Pirime Count [29fb4b]

```

1  ll PrimeCount(ll n) { // n ~ 10^13 => < 2s
2    if (n <= 1) return 0;
3    int v = sqrt(n), s = (v + 1) / 2, pc = 0;
4    vector<int> smalls(v + 1), skip(v + 1), roughs(s);
5    vector<ll> larges(s);
6    for (int i = 2; i <= v; ++i) smalls[i] = (i + 1) / 2;
7    for (int i = 0; i < s; ++i) {
8      roughs[i] = 2 * i + 1;
9      larges[i] = (n / (2 * i + 1) + 1) / 2;
10   }
11   for (int p = 3; p <= v; ++p) {
12     if (smalls[p] > smalls[p - 1]) {
13       int q = p * p;
14       ++pc;
15       if (1LL * q * q > n) break;
16       skip[p] = 1;
17       for (int i = q; i <= v; i += 2 * p) skip[i] = 1;
18       int ns = 0;
19       for (int k = 0; k < s; ++k) {
20         int i = roughs[k];

```

```

21     if (skip[i]) continue;
22     ll d = 1LL * i * p;
23     larges[ns] = larges[k] -
24         (d <= v ? larges[smalls[d] - pc]
25           : smalls[n / d]) +
26         pc;
27     roughs[ns++] = i;
28 }
29 s = ns;
30 for (int j = v / p; j >= p; --j) {
31     int c = smalls[j] - pc,
32         e = min(j * p + p, v + 1);
33     for (int i = j * p; i < e; ++i) smalls[i] -= c;
34 }
35 }
36 for (int k = 1; k < s; ++k) {
37     const ll m = n / roughs[k];
38     ll t = larges[k] - (pc + k - 1);
39     for (int l = 1; l < k; ++l) {
40         int p = roughs[l];
41         if (1LL * p * p > m) break;
42         t -= smalls[m / p] - (pc + l - 1);
43     }
44     larges[0] -= t;
45 }
46 return larges[0];
47 }

```

6.5 floor sum [f931f3]

```

1 ll floor_sum(ll n, ll m, ll a, ll b) {
2     ll ans = 0;
3     if (a >= m) ans += (n - 1) * n * (a / m) / 2, a %= m;
4     if (b >= m) ans += n * (b / m), b %= m;
5     ll y_max = (a * n + b) / m, x_max = (y_max * m - b);
6     if (y_max == 0) return ans;
7     ans += (n - (x_max + a - 1) / a) * y_max;
8     ans += floor_sum(y_max, a, m, (a - x_max % a) % a);
9     return ans;
10 } // sum^{n-1}_0 floor((a * i + b) / m) in log(n + m +
11 // a + b)

```

6.6 QuadraticResidue [0b50c4]

```

1 int Jacobi(int a, int m) {
2     int s = 1;
3     for (; m > 1;) {
4         a %= m;
5         if (a == 0) return 0;
6         const int r = __builtin_ctz(a);
7         if ((r & 1) && ((m + 2) & 4)) s = -s;
8         a >>= r;
9         if (a & m & 2) s = -s;
10        swap(a, m);
11    }
12    return s;
13 }
14 int QuadraticResidue(int a, int p) {
15     if (p == 2) return a & 1;
16     const int jc = Jacobi(a, p);
17     if (jc == 0) return 0;
18     if (jc == -1) return -1;
19     int b, d;
20     for (;;) {
21         b = rand() % p;
22         d = (1LL * b * b + p - a) % p;
23         if (Jacobi(d, p) == -1) break;
24     }
25     int f0 = b, f1 = 1, g0 = 1, g1 = 0, tmp;
26     for (int e = (1LL + p) >> 1; e; e >>= 1) {
27         if (e & 1) {
28             tmp = (1LL * g0 * f0 +
29                 1LL * d * (1LL * g1 * f1 % p)) %
30                 p;
31             g1 = (1LL * g0 * f1 + 1LL * g1 * f0) % p;
32             g0 = tmp;
33         }
34         tmp =
35             (1LL * f0 * f0 + 1LL * d * (1LL * f1 * f1 % p)) %
36             p;
37         f1 = (2LL * f0 * f1) % p;
38         f0 = tmp;
39     }
40     return g0;
41 }

```

6.7 floor enumeration [fc55c8]

```

1 // enumerating x = floor(n / i), [l, r]
2 for (int l = 1, r; l <= n; l = r + 1) {
3     int x = n / l;
4     r = n / x;
5 }

```

6.8 ax+by=gcd [43bd81]

```

1 pll exgcd(ll a, ll b) {
2     if (b == 0) return pll(1, 0);
3     ll p = a / b;
4     pll q = exgcd(b, a % b);
5     return pll(q.Y, q.X - q.Y * p);
6 }
7 /* ax+by=res, let x be minimum non-negative
8 g, p = gcd(a, b), exgcd(a, b) * res / g
9 if p.X < 0: t = (abs(p.X) + b / g - 1) / (b / g)
10 else: t = -(p.X / (b / g))
11 p += (b / g, -a / g) * t */

```

6.9 cantor expansion [2d801a]

```

1 #define MAXN 11
2 int factorial[MAXN];
3 inline void init() {
4     factorial[0] = 1;
5     for (int i = 1; i <= MAXN; ++i) {
6         factorial[i] = factorial[i - 1] * i;
7     }
8 }
9 inline int encode(const std::vector<int> &s) {
10    int n = s.size(), res = 0;
11    for (int i = 0; i < n; ++i) {
12        int t = 0;
13        for (int j = i + 1; j < n; ++j) {
14            if (s[j] < s[i]) ++t;
15        }
16        res += t * factorial[n - i - 1];
17    }
18    return res;
19 }
20 inline std::vector<int> decode(int a, int n) {
21    std::vector<int> res;
22    std::vector<bool> vis(n, 0);
23    for (int i = n - 1; i >= 0; --i) {
24        int t = a / factorial[i], j;
25        for (j = 0; j < n; ++j) {
26            if (!vis[j]) {
27                if (t == 0) break;
28                --t;
29            }
30        }
31        res.push_back(j);
32        vis[j] = 1;
33        a %= factorial[i];
34    }
35    return res;
36 }

```

6.10 Generating function

- Ordinary Generating Function $A(x) = \sum_{i \geq 0} a_i x^i$
 - $A(rx) \Rightarrow r^n a_n$
 - $A(x) + B(x) \Rightarrow a_n + b_n$
 - $A(x)B(x) \Rightarrow \sum_{i=0}^n a_i b_{n-i}$
 - $A(x)^k \Rightarrow \sum_{i_1+i_2+\dots+i_k=n} a_{i_1} a_{i_2} \dots a_{i_k}$
 - $x A(x)' \Rightarrow n a_n$
 - $\frac{A(x)}{1-x} \Rightarrow \sum_{i=0}^n a_i$
- Exponential Generating Function $A(x) = \sum_{i \geq 0} \frac{a_i}{i!} x^i$
 - $A(x) + B(x) \Rightarrow a_n + b_n$
 - $A^{(k)}(x) \Rightarrow a_{n+k}$
 - $A(x)B(x) \Rightarrow \sum_{i=0}^n \binom{n}{i} a_i b_{n-i}$
 - $A(x)^k \Rightarrow \sum_{i_1+i_2+\dots+i_k=n} \binom{n}{i_1, i_2, \dots, i_k} a_{i_1} a_{i_2} \dots a_{i_k}$
 - $x A(x) \Rightarrow n a_n$
- Special Generating Function
 - $(1+x)^n = \sum_{i \geq 0} \binom{n}{i} x^i$
 - $\frac{1}{(1-x)^n} = \sum_{i \geq 0} \binom{i+n-1}{n-1} x^i$

6.11 Fraction [666134]

```

1 struct fraction {
2     ll n, d;
3     fraction(const ll &n = 0, const ll &d = 1)
4         : n(_n), d(_d) {
5         ll t = gcd(n, d);
6         n /= t, d /= t;
7         if (d < 0) n = -n, d = -d;
8     }
9     fraction operator-(const fraction &b) const {
10         return fraction(-n, d);
11     }
12     fraction operator+(const fraction &b) const {
13         return fraction(n * b.d + b.n * d, d * b.d);
14     }
15     fraction operator-(const fraction &b) const {
16         return fraction(n * b.d - b.n * d, d * b.d);
17     }
18     fraction operator*(const fraction &b) const {
19         return fraction(n * b.n, d * b.d);
20     }
21     fraction operator/(const fraction &b) const {
22         return fraction(n * b.d, d * b.n);
23     }
24     void print() {
25         cout << n;
26         if (d != 1) cout << "/" << d;
27     }
28 };

```

6.12 Gaussian gcd [616465]

```

1 cpx gaussian_gcd(cpx a, cpx b) {
2     #define rnd(a, b)
3         ((a >= 0 ? a * 2 + b : a * 2 - b) / (b * 2))
4     ll c = a.real() * b.real() + a.imag() * b.imag();
5     ll d = a.imag() * b.real() - a.real() * b.imag();
6     ll r = b.real() * b.real() + b.imag() * b.imag();
7     if (c % r == 0 && d % r == 0) return b;
8     return gaussian_gcd(
9         b, a - cpx(rnd(c, r), rnd(d, r)) * b);
10 }

```

6.13 Theorem

- Cramer's rule

$$\begin{aligned}
 ax + by &= e \\
 cx + dy &= f
 \end{aligned}
 \Rightarrow
 \begin{aligned}
 x &= \frac{ed - bf}{ad - bc} \\
 y &= \frac{af - ec}{ad - bc}
 \end{aligned}$$

- Vandermonde's Identity

$$C(n+m, k) = \sum_{i=0}^k C(n, i) C(m, k-i)$$

- Kirchhoff's Theorem

Denote L be a $n \times n$ matrix as the Laplacian matrix of graph G , where $L_{ii} = d(i)$, $L_{ij} = -c$ where c is the number of edge (i, j) in G .

- The number of undirected spanning in G is $|\det(\tilde{L}_{11})|$.
- The number of directed spanning tree rooted at r in G is $|\det(\tilde{L}_{rr})|$.

- Tutte's Matrix

Let D be a $n \times n$ matrix, where $d_{ij} = x_{ij}$ (x_{ij} is chosen uniformly at random) if $i < j$ and $(i, j) \in E$, otherwise $d_{ij} = -d_{ji}$. $\frac{\text{rank}(D)}{2}$ is the maximum matching on G .

- Cayley's Formula

- Given a degree sequence d_1, d_2, \dots, d_n for each labeled vertices, there are $\frac{(n-2)!}{(d_1-1)!(d_2-1)!\dots(d_n-1)!}$ spanning trees.
- Let $T_{n,k}$ be the number of labeled forests on n vertices with k components, such that vertex $1, 2, \dots, k$ belong to different components. Then $T_{n,k} = kn^{n-k-1}$.

- Erdős–Gallai theorem

A sequence of nonnegative integers $d_1 \geq \dots \geq d_n$ can be represented as the degree sequence of a finite simple graph on n vertices if and only if

$$d_1 + \dots + d_n \text{ is even and } \sum_{i=1}^k d_i \leq k(k-1) + \sum_{i=k+1}^n \min(d_i, k) \text{ holds for every } 1 \leq k \leq n.$$

- Gale–Ryser theorem

A pair of sequences of nonnegative integers $a_1 \geq \dots \geq a_n$ and b_1, \dots, b_n

is bigraphic if and only if $\sum_{i=1}^n a_i = \sum_{i=1}^n b_i$ and $\sum_{i=1}^k a_i \leq \sum_{i=1}^n \min(b_i, k)$ holds for every $1 \leq k \leq n$.

- Fulkerson–Chen–Anstee theorem

A sequence $(a_1, b_1), \dots, (a_n, b_n)$ of nonnegative integer pairs with $a_1 \geq \dots \geq a_n$ is digraphic if and only if $\sum_{i=1}^n a_i = \sum_{i=1}^n b_i$ and

$$\sum_{i=1}^k a_i \leq \sum_{i=1}^k \min(b_i, k-1) + \sum_{i=k+1}^n \min(b_i, k) \text{ holds for every } 1 \leq k \leq n.$$

- Pick's theorem

For simple polygon, when points are all integer, we have $A = \#\{\text{lattice points in the interior}\} + \frac{\#\{\text{lattice points on the boundary}\}}{2} - 1$.

- Möbius inversion formula

$$\begin{aligned}
 - f(n) &= \sum_{d|n} g(d) \Leftrightarrow g(n) = \sum_{d|n} \mu(d) f\left(\frac{n}{d}\right) \\
 - f(n) &= \sum_{n|d} g(d) \Leftrightarrow g(n) = \sum_{n|d} \mu\left(\frac{d}{n}\right) f(d)
 \end{aligned}$$

- Spherical cap

- A portion of a sphere cut off by a plane.
- r : sphere radius, a : radius of the base of the cap, h : height of the cap, θ : $\arcsin(a/r)$.
- Volume $= \pi h^2(3r - h)/3 = \pi h(3a^2 + h^2)/6 = \pi r^3(2 + \cos\theta)(1 - \cos\theta)^2/3$.
- Area $= 2\pi r h = \pi(a^2 + h^2) = 2\pi r^2(1 - \cos\theta)$.

- Lagrange multiplier

- Optimize $f(x_1, \dots, x_n)$ when k constraints $g_i(x_1, \dots, x_n) = 0$.
- Lagrangian function $\mathcal{L}(x_1, \dots, x_n, \lambda_1, \dots, \lambda_k) = f(x_1, \dots, x_n) - \sum_{i=1}^k \lambda_i g_i(x_1, \dots, x_n)$.
- The solution corresponding to the original constrained optimization is always a saddle point of the Lagrangian function.

- Nearest points of two skew lines

- Line 1: $v_1 = p_1 + t_1 d_1$
- Line 2: $v_2 = p_2 + t_2 d_2$
- $n = d_1 \times d_2$
- $n_1 = d_1 \times n$
- $n_2 = d_2 \times n$
- $c_1 = p_1 + \frac{(p_2 - p_1) \cdot n_2}{d_1 \cdot n_2} d_1$
- $c_2 = p_2 + \frac{(p_1 - p_2) \cdot n_1}{d_2 \cdot n_1} d_2$

- Derivatives/Integrals

$$\begin{aligned}
 \text{Integration by parts: } \int_a^b f(x)g(x)dx &= [F(x)g(x)]_a^b - \int_a^b F(x)g'(x)dx \\
 \left| \frac{d}{dx} \sin^{-1}x = \frac{1}{\sqrt{1-x^2}} \right| & \left| \frac{d}{dx} \cos^{-1}x = -\frac{1}{\sqrt{1-x^2}} \right| & \left| \frac{d}{dx} \tan^{-1}x = \frac{1}{1+x^2} \right| \\
 \frac{d}{dx} \tan x &= 1 + \tan^2 x & \int \tan ax &= -\frac{\ln|\cos ax|}{a} \\
 \int e^{-x^2} &= \frac{\sqrt{\pi}}{2} \text{erf}(x) & \int x e^{ax} dx &= \frac{e^{ax}}{a^2} (ax - 1) \\
 \int \sqrt{a^2 + x^2} &= \frac{1}{2} \left(x\sqrt{a^2 + x^2} + a^2 \text{asinh}(x/a) \right)
 \end{aligned}$$

- Spherical Coordinate

$$(x, y, z) = (r \sin\theta \cos\phi, r \sin\theta \sin\phi, r \cos\theta)$$

$$(r, \theta, \phi) = (\sqrt{x^2 + y^2 + z^2}, \arccos(z/\sqrt{x^2 + y^2 + z^2}), \text{atan2}(y, x))$$

- Rotation Matrix

$$M(\theta) = \begin{bmatrix} \cos\theta & -\sin\theta \\ \sin\theta & \cos\theta \end{bmatrix}, R_x(\theta_x) = \begin{bmatrix} 1 & 0 & 0 \\ 0 & \cos\theta_x & -\sin\theta_x \\ 0 & \sin\theta & \cos\theta \end{bmatrix}$$

6.14 Determinant [a4d696]

```

1 struct Matrix {
2     int n, m;
3     ll M[MAXN][MAXN];
4     int row_swap(int i, int j) {
5         if (i == j) return 0;
6         for (int k = 0; k < m; ++k) swap(M[i][k], M[j][k]);
7         return 1;
8     }
9     ll det() { // return the number of swaps
10        int rt = 0;
11        for (int i = 0; i < n; ++i) {
12            int piv = i;
13            while (piv < n && !M[piv][i]) ++piv;
14            if (piv == n) continue;
15            rt += row_swap(i, piv);
16            for (int j = i + 1; j < n; ++j) {
17                while (M[j][i]) {
18                    int tmp = M[i][i] / M[j][i];
19                    for (int k = i; k < m; ++k)
20                        M[i][k] = (M[j][k] * tmp + M[i][k]) % P;
21                    rt += row_swap(i, j);
22                }
23            }
24        }
25    }
26 }

```

```

25     rt = (rt & 1) ? P - 1 : 1;
26     for (int i = 0; i < n; ++i) rt = rt * M[i][i] % P;
27     return rt;
28     // round(rt) if using double to cal. int. det
29 }
30 };

```

6.15 ModMin [05065e]

```

1 // min{k | l <= ((ak) mod m) <= r}, no solution -> -1
2 ll mod_min(ll a, ll m, ll l, ll r) {
3     if (a == 0) return l ? -1 : 0;
4     if (ll k = (l + a - 1) / a; k * a <= r) return k;
5     ll b = m / a, c = m % a;
6     if (ll y = mod_min(c, a, a - r % a, a - l % a))
7         return (l + y * c + a - 1) / a + y * b;
8     return -1;
9 }

```

6.16 Simultaneous Equations [b8b03f]

```

1 struct matrix { // m variables, n equations
2     int n, m;
3     fraction M[MAXN][MAXN + 1], sol[MAXN];
4     int solve() { // -1: inconsistent, >= 0: rank
5         for (int i = 0; i < n; ++i) {
6             int piv = 0;
7             while (piv < m && !M[i][piv].n) ++piv;
8             if (piv == m) continue;
9             for (int j = 0; j < n; ++j) {
10                if (i == j) continue;
11                fraction tmp = -M[j][piv] / M[i][piv];
12                for (int k = 0; k <= m; ++k)
13                    M[j][k] = tmp * M[i][k] + M[j][k];
14            }
15        }
16        int rank = 0;
17        for (int i = 0; i < n; ++i) {
18            int piv = 0;
19            while (piv < m && !M[i][piv].n) ++piv;
20            if (piv == m && M[i][m].n) return -1;
21            else if (piv < m)
22                ++rank, sol[piv] = M[i][m] / M[i][piv];
23        }
24        return rank;
25    }
26 };

```

6.17 Big number [1c17ab]

```

1 template <typename T>
2 inline string to_string(const T &x) {
3     stringstream ss;
4     return ss << x, ss.str();
5 }
6 struct bigN : vector<ll> {
7     const static int base = 1000000000,
8         width = log10(base);
9     bool negative;
10    bigN(const_iterator a, const_iterator b)
11        : vector<ll>(a, b) {}
12    bigN(string s) {
13        if (s.empty()) return;
14        if (s[0] == '-') negative = 1, s = s.substr(1);
15        else negative = 0;
16        for (int i = int(s.size()) - 1; i >= 0;
17             i -= width) {
18            ll t = 0;
19            for (int j = max(0, i - width + 1); j <= i; ++j)
20                t = t * 10 + s[j] - '0';
21            push_back(t);
22        }
23        trim();
24    }
25    template <typename T>
26    bigN(const T &x) : bigN(to_string(x)) {}
27    bigN() : negative(0) {}
28    void trim() {
29        while (size() && !back()) pop_back();
30        if (empty()) negative = 0;
31    }
32    void carry(int _base = base) {
33        for (size_t i = 0; i < size(); ++i) {
34            if (at(i) >= 0 && at(i) < _base) continue;
35            if (i + 1u == size()) push_back(0);
36            int r = at(i) % _base;
37            if (r < 0) r += _base;

```

```

        at(i + 1) += (at(i) - r) / _base, at(i) = r;
    }
}
int abscmp(const bigN &b) const {
    if (size() > b.size()) return 1;
    if (size() < b.size()) return -1;
    for (int i = int(size()) - 1; i >= 0; --i) {
        if (at(i) > b[i]) return 1;
        if (at(i) < b[i]) return -1;
    }
    return 0;
}
int cmp(const bigN &b) const {
    if (negative != b.negative)
        return negative ? -1 : 1;
    return negative ? -abscmp(b) : abscmp(b);
}
bool operator<(const bigN &b) const {
    return cmp(b) < 0;
}
bool operator>(const bigN &b) const {
    return cmp(b) > 0;
}
bool operator<=(const bigN &b) const {
    return cmp(b) <= 0;
}
bool operator>=(const bigN &b) const {
    return cmp(b) >= 0;
}
bool operator==(const bigN &b) const {
    return !cmp(b);
}
bool operator!=(const bigN &b) const {
    return cmp(b) != 0;
}
bigN abs() const {
    bigN res = *this;
    return res.negative = 0, res;
}
bigN operator-() const {
    bigN res = *this;
    return res.negative = !negative, res.trim(), res;
}
bigN operator+(const bigN &b) const {
    if (negative) return -(-(*this) + (-b));
    if (b.negative) return *this - (-b);
    bigN res = *this;
    if (b.size() > size()) res.resize(b.size());
    for (size_t i = 0; i < b.size(); ++i)
        res[i] += b[i];
    return res.carry(), res.trim(), res;
}
bigN operator-(const bigN &b) const {
    if (negative) return -(-(*this) - (-b));
    if (b.negative) return *this + (-b);
    if (abscmp(b) < 0) return -(b - (*this));
    bigN res = *this;
    if (b.size() > size()) res.resize(b.size());
    for (size_t i = 0; i < b.size(); ++i)
        res[i] -= b[i];
    return res.carry(), res.trim(), res;
}
bigN operator*(const bigN &b) const {
    bigN res;
    res.negative = negative != b.negative;
    res.resize(size() + b.size());
    for (size_t i = 0; i < size(); ++i)
        for (size_t j = 0; j < b.size(); ++j)
            if ((res[i + j] += at(i) * b[j]) >= base) {
                res[i + j + 1] += res[i + j] / base;
                res[i + j] %= base;
            } // %k*carry·|·,|
    return res.trim(), res;
}
bigN operator/(const bigN &b) const {
    int norm = base / (b.back() + 1);
    bigN x = abs() * norm;
    bigN y = b.abs() * norm;
    bigN q, r;
    q.resize(x.size());
    for (int i = int(x.size()) - 1; i >= 0; --i) {
        r = r * base + x[i];
        int s1 = r.size() <= y.size() ? 0 : r[y.size()];
        int s2 =
            r.size() < y.size() ? 0 : r[y.size() - 1];
        int d = (ll(base) * s1 + s2) / y.back();

```

```

124     r = r - y * d;
125     while (r.negative) r = r + y, --d;
126     q[i] = d;
127 }
128 q.negative = negative != b.negative;
129 return q.trim(), q;
130 }
131 bigN operator%(const bigN &b) const {
132     return *this - (*this / b) * b;
133 }
134 friend istream &operator>>(istream &ss, bigN &b) {
135     string s;
136     return ss >> s, b = s, ss;
137 }
138 friend ostream &operator<<(
139     ostream &ss, const bigN &b) {
140     if (b.negative) ss << '-';
141     ss << (b.empty() ? 0 : b.back());
142     for (int i = int(b.size()) - 2; i >= 0; --i)
143         ss << setw(width) << setfill('0') << b[i];
144     return ss;
145 }
146 template <typename T> operator T() {
147     stringstream ss;
148     ss << *this;
149     T res;
150     return ss >> res, res;
151 }
152 };

```

6.18 Euclidean

- $m = \lfloor \frac{an+b}{c} \rfloor$
- Time complexity: $O(\log n)$

$$f(a, b, c, n) = \sum_{i=0}^n \lfloor \frac{ai+b}{c} \rfloor$$

$$= \begin{cases} \lfloor \frac{a}{c} \rfloor \cdot \frac{n(n+1)}{2} + \lfloor \frac{b}{c} \rfloor \cdot (n+1) \\ + f(a \bmod c, b \bmod c, c, n), & a \geq c \vee b \geq c \\ 0, & n < 0 \vee a = 0 \\ nm - f(c, c-b-1, a, m-1), & \text{otherwise} \end{cases}$$

$$g(a, b, c, n) = \sum_{i=0}^n i \lfloor \frac{ai+b}{c} \rfloor$$

$$= \begin{cases} \lfloor \frac{a}{c} \rfloor \cdot \frac{n(n+1)(2n+1)}{6} + \lfloor \frac{b}{c} \rfloor \cdot \frac{n(n+1)}{2} \\ + g(a \bmod c, b \bmod c, c, n), & a \geq c \vee b \geq c \\ 0, & n < 0 \vee a = 0 \\ \frac{1}{2} \cdot (n(n+1)m - f(c, c-b-1, a, m-1) \\ - h(c, c-b-1, a, m-1)), & \text{otherwise} \end{cases}$$

$$h(a, b, c, n) = \sum_{i=0}^n \lfloor \frac{ai+b}{c} \rfloor^2$$

$$= \begin{cases} \lfloor \frac{a}{c} \rfloor^2 \cdot \frac{n(n+1)(2n+1)}{6} + \lfloor \frac{b}{c} \rfloor^2 \cdot (n+1) \\ + \lfloor \frac{a}{c} \rfloor \cdot \lfloor \frac{b}{c} \rfloor \cdot n(n+1) \\ + h(a \bmod c, b \bmod c, c, n) \\ + 2 \lfloor \frac{a}{c} \rfloor \cdot g(a \bmod c, b \bmod c, c, n) \\ + 2 \lfloor \frac{b}{c} \rfloor \cdot f(a \bmod c, b \bmod c, c, n), & a \geq c \vee b \geq c \\ 0, & n < 0 \vee a = 0 \\ nm(m+1) - 2g(c, c-b-1, a, m-1) \\ - 2f(c, c-b-1, a, m-1) - f(a, b, c, n), & \text{otherwise} \end{cases}$$

6.19 Primes [2464ae]

```

1 /* 12721 13331 14341 75577 123457 222557 556679 999983
2  * 1097774749 1076767633 100102021 999997771 1001010013
3  * 1000512343 987654361 999991231 999888733 98789101
4  * 987777733 999991921 1010101333 1010102101
5  * 1000000000039 1000000000000037 2305843009213693951
6  * 4611686018427387847 9223372036854775783
7  * 18446744073709551557 */

```

6.20 Miller Rabin [566584]

```

1 // n < 4,759,123,141      3 : 2, 7, 61
2 // n < 1,122,004,669,633  4 : 2, 13, 23, 1662803
3 // n < 3,474,749,660,383  6 : primes <= 13
4 // 7 : 2, 325, 9375, 28178, 450775, 9780504, 1795265022
5 #define llu unsigned long long
6 llu add(llu
7     a, llu b, llu c) { return (__int128{a} + b) % c; }
8
9 llu mul(llu
10    a, llu b, llu c) { return __int128{a} * b % c; }

```

```

8 llu mpow(llu a, llu b, llu c) {
9     llu res = 1;
10    while (b) {
11        if (b & 1) res = mul(res, a, c);
12        a = mul(a, a, c); b >>= 1;
13    }
14    return res;
15 }
16 inline bool isprime(llu x) {
17     static auto witn = [] (llu a, llu n, int t) {
18         if (!a) return false;
19         while (t--) {
20             llu a2 = mul(a, a, n);
21             if (a2 == 1 && a != 1 && a != n - 1) return true;
22             a = a2;
23         }
24         return a != 1; };
25     if (x < 2) return false; if (!(x & 1)) return x == 2;
26     int t
27         = __builtin_ctzll(x - 1); llu odd = (x - 1) >> t;
28     for (llu m: {2,
29         325, 9375, 28178, 450775, 9780504, 1795265022})
30         if (witn(mpow(m % x, odd, x), x, t)) return false;
31     return true;
32 }

```

6.21 Pollard Rho [6422b1]

```

1 // when n is prime return any non-trivial factor
2 llu f(llu x, llu m) { return (mul(x, x, m) + 1) % m; }
3 llu pollard_rho(llu n) { // don't input 1
4     if (!(n & 1)) return 2;
5     while (true) {
6         llu y = 2, x = rand() % (n - 1) + 1, res = 1;
7         for (int sz = 2; res == 1; sz *= 2) {
8             for (int i = 0; i < sz && res <= 1; i++) {
9                 x = f(x, n);
10                res = gcd(x - y >= 0 ? x - y : y - x, n);
11            }
12            y = x;
13        }
14        if (res != 0 && res != n) return res;
15    }
16 }
17 void fac(llu x, vector<llu> &ans) {
18     if (isprime(x)) ans.emplace_back(x);
19     else {
20         llu p = pollard_rho(x);
21         fac(x / p, ans); fac(p, ans);
22     }
23 }

```

6.22 Berlekamp-Massey [cddb091]

```

1 template <typename T>
2 vector<T> BerlekampMassey(const vector<T> &output) {
3     vector<T> d(SZ(output) + 1), me, he;
4     for (int f = 0, i = 1; i <= SZ(output); ++i) {
5         for (int j = 0; j < SZ(me); ++j)
6             d[i] += output[i - j - 2] * me[j];
7         if ((d[i] -= output[i - 1]) == 0) continue;
8         if (me.empty()) {
9             me.resize(f + i);
10            continue;
11        }
12        vector<T> o(i - f - 1);
13        T k = -d[i] / d[f];
14        o.pb(-k);
15        for (T x : he) o.pb(x * k);
16        o.resize(max(SZ(o), SZ(me)));
17        for (int j = 0; j < SZ(me); ++j) o[j] += me[j];
18        if (i - f + SZ(he) >= SZ(me)) he = me, f = i;
19        me = o;
20    }
21    return me;
22 }

```

6.23 floor ceil [f84849]

```

1 int floor(int a, int b) {
2     return a / b - (a % b && (a < 0) ^ (b < 0));
3 }
4 int ceil(int a, int b) {
5     return a / b + (a % b && (a < 0) ^ (b > 0));
6 }

```

6.24 fac no p [86ad89]

```

1 // 0(p^k + log^2 n), pk = p^k
2 ll prod[MAXP];
3 ll fac_no_p(ll n, ll p, ll pk) {
4     prod[0] = 1;
5     for (int i = 1; i <= pk; ++i)
6         if (i % p) prod[i] = prod[i - 1] * i % pk;
7         else prod[i] = prod[i - 1];
8     ll rt = 1;
9     for (; n; n /= p) {
10         rt = rt * mpow(prod[pk], n / pk, pk) % pk;
11         rt = rt * prod[n % pk] % pk;
12     }
13     return rt;
14 } // (n! without factor p) % p^k

```

6.25 DiscreteLog [21f791]

```

1 int DiscreteLog(int s, int x, int y, int m) {
2     constexpr int kStep = 32000;
3     unordered_map<int, int> p;
4     int b = 1;
5     for (int i = 0; i < kStep; ++i) {
6         p[y] = i;
7         y = 1LL * y * x % m;
8         b = 1LL * b * x % m;
9     }
10    for (int i = 0; i < m + 10; i += kStep) {
11        s = 1LL * s * b % m;
12        if (p.find(s) != p.end()) return i + kStep - p[s];
13    }
14    return -1;
15 }
16 int DiscreteLog(int x, int y, int m) {
17     if (m == 1) return 0;
18     int s = 1;
19     for (int i = 0; i < 100; ++i) {
20         if (s == y) return i;
21         s = 1LL * s * x % m;
22     }
23     if (s == y) return 100;
24     int p = 100 + DiscreteLog(s, x, y, m);
25     if (fpow(x, p, m) != y) return -1;
26     return p;
27 }

```

6.26 SimplexConstruction

Primal	Dual
Maximize $c^T x$ s.t. $Ax \leq b, x \geq 0$	Minimize $b^T y$ s.t. $A^T y \geq c, y \geq 0$
Maximize $c^T x$ s.t. $Ax \leq b$	Minimize $b^T y$ s.t. $A^T y = c, y \geq 0$
Maximize $c^T x$ s.t. $Ax = b, x \geq 0$	Minimize $b^T y$ s.t. $A^T y \geq c$

\bar{x} and \bar{y} are optimal if and only if for all $i \in [1, n]$, either $\bar{x}_i = 0$ or $\sum_{j=1}^m A_{ji} \bar{y}_j = c_i$ holds and for all $i \in [1, m]$ either $\bar{y}_i = 0$ or $\sum_{j=1}^n A_{ij} \bar{x}_j = b_j$ holds.

- In case of minimization, let $c'_i = -c_i$
- $\sum_{1 \leq i \leq n} A_{ji} x_i \geq b_j \rightarrow \sum_{1 \leq i \leq n} -A_{ji} x_i \leq -b_j$
- $\sum_{1 \leq i \leq n} A_{ji} x_i = b_j$
 - $\sum_{1 \leq i \leq n} A_{ji} x_i \leq b_j$
 - $\sum_{1 \leq i \leq n} A_{ji} x_i \geq b_j$
- If x_i has no lower bound, replace x_i with $x_i - x'_i$

6.27 Simplex Algorithm [ad99b3]

```

1 const int MAXN = 11000, MAXM = 405;
2 const double eps = 1E-10;
3 double a[MAXN][MAXM], b[MAXN], c[MAXN];
4 double d[MAXN][MAXM], x[MAXN];
5 int ix[MAXN + MAXM]; // !!! array all indexed from 0
6 // max{cx} subject to {Ax<=b,x>=0}
7 // n: constraints, m: vars !!!
8 // x[] is the optimal solution vector
9 // usage :
10 // value = simplex(a, b, c, N, M);
11 double simplex(int n, int m) {
12     ++m;
13     fill_n(d[n], m + 1, 0);
14     fill_n(d[n + 1], m + 1, 0);
15     iota(ix, ix + n + m, 0);
16     int r = n, s = m - 1;
17     for (int i = 0; i < n; ++i) {
18         for (int j = 0; j < m - 1; ++j) d[i][j] = -a[i][j];
19         d[i][m - 1] = 1;
20         d[i][m] = b[i];
21         if (d[r][m] > d[i][m]) r = i;
22     }
23 }

```

```

23 copy_n(c, m - 1, d[n]);
24 d[n + 1][m - 1] = -1;
25 for (double dd;;) {
26     if (r < n) {
27         swap(ix[s], ix[r + m]);
28         d[r][s] = 1.0 / d[r][s];
29         for (int j = 0; j <= m; ++j)
30             if (j != s) d[r][j] *= -d[r][s];
31         for (int i = 0; i <= n + 1; ++i)
32             if (i != r) {
33                 for (int j = 0; j <= m; ++j)
34                     if (j != s) d[i][j] += d[r][j] * d[i][s];
35                 d[i][s] *= d[r][s];
36             }
37     }
38     r = s = -1;
39     for (int j = 0; j < m; ++j)
40         if (s < 0 || ix[s] > ix[j]) {
41             if (d[n + 1][j] > eps ||
42                 (d[n + 1][j] > -eps && d[n][j] > eps))
43                 s = j;
44         }
45     if (s < 0) break;
46     for (int i = 0; i < n; ++i)
47         if (d[i][s] < -eps) {
48             if (r < 0 ||
49                 (dd = d[r][m] / d[r][s] -
50                  d[i][m] / d[i][s]) < -eps ||
51                 (dd < eps && ix[r + m] > ix[i + m]))
52                 r = i;
53         }
54     if (r < 0) return -1; // not bounded
55 }
56 if (d[n + 1][m] < -eps) return -1; // not executable
57 double ans = 0;
58 fill_n(x, m, 0);
59 for (int i = m; i < n + m;
60      ++i) { // the missing enumerated x[i] = 0
61     if (ix[i] < m - 1) {
62         ans += d[i - m][m] * c[ix[i]];
63         x[ix[i]] = d[i - m][m];
64     }
65 }
66 return ans;
67 }

```

7 Polynomial

7.1 Fast Walsh Transform [820c20]

```

1 /* x: a[j], y: a[j + (L >> 1)]
2 or: (y += x * op), and: (x += y * op)
3 xor: (x, y = (x + y) * op, (x - y) * op)
4 invop: or, and, xor = -1, -1, 1/2 */
5 void fwt(int *a, int n, int op) { // or
6     for (int L = 2; L <= n; L <= 1)
7         for (int i = 0; i < n; i += L)
8             for (int j = i; j < i + (L >> 1); ++j)
9                 a[j + (L >> 1)] += a[j] * op;
10 }
11 const int N = 21;
12 int f[N][1 << N], g[N][1 << N], h[N][1 << N],
13     ct[1 << N];
14 void subset_convolution(
15     int *a, int *b, int *c, int L) {
16     // c_k = \sum_{i | j = k, i & j = 0} a_i * b_j
17     int n = 1 << L;
18     for (int i = 1; i < n; ++i)
19         ct[i] = ct[i & (i - 1)] + 1;
20     for (int i = 0; i < n; ++i)
21         f[ct[i]][i] = a[i], g[ct[i]][i] = b[i];
22     for (int i = 0; i <= L; ++i)
23         fwt(f[i], n, 1), fwt(g[i], n, 1);
24     for (int i = 0; i <= L; ++i)
25         for (int j = 0; j <= i; ++j)
26             for (int x = 0; x < n; ++x)
27                 h[i][x] += f[j][x] * g[i - j][x];
28     for (int i = 0; i <= L; ++i) fwt(h[i], n, -1);
29     for (int i = 0; i < n; ++i) c[i] = h[ct[i]][i];
30 }

```

7.2 NTT [ef061c]

```

1 // 1:2615053605667*(2^18)+1,3 | 2:15*(2^27)+1,31
2 // 3:479*(2^21)+1,3 | 4:7*17*(2^23)+1,3
3 // 5:3*3*211*(2^19)+1,5 | 6:25*(2^22)+1,3
4 template<typename T, typename VT=vector<T> >

```

```

5 struct NTT {
6     const T P, G;
7     NTT(T p=(1<<23)*7*17+1,T g=3):P(p),G(g){}
8     unsigned bit_reverse(unsigned a,int len) {
9         a=((a&0x55555555U)<<1)|((a&0xAAAAAAAAU)>>1);
10        a=((a&0x33333333U)<<2)|((a&0xCCCCCCCCU)>>2);
11        a=((a&0x0F0F0F0FU)<<4)|((a&0xFF0F0F0FU)>>4);
12        a=((a&0x00FF00FFU)<<8)|((a&0xFFFF0000U)>>8);
13        a=((a&0x0000FFFFU)<<16)|((a&0xFFFF0000U)>>16);
14        return a>>(32-len);
15    }
16    T pow_mod(T n,T k,T m){
17        T ans=1;
18        for(n=(n>=m?n%m:n);k;k>>=1){
19            if(k&1)ans=ans*n%m; n=n*n%m;
20        }
21        return ans;
22    }
23    void ntt(bool is_inv,VT &in,VT &out,int N){
24        int bitlen=__lg(N);
25        for(int i=0;i<N;++i)out[bit_reverse(i,bitlen)]=in[i];
26        for(int step=2,id=1;step<=N;step<=1,++id){
27            T wn=pow_mod(G,(P-1)>>id,P),wi=1,u,t;
28            const int mh=step>>1;
29            for(int i=0;i<mh;++i){
30                for(int j=i;j<N;j+=step){
31                    u=out[j],t=wi*out[j+mh]%P;
32                    out[j]=u+t; out[j+mh]=u-t;
33                    if(out[j]>=P)out[j]-=P;
34                    if(out[j+mh]<0)out[j+mh]+=P;
35                }
36                wi=wi*wn%P;
37            }
38            if(is_inv){
39                for(int i=1;i<N/2;++i)swap(out[i],out[N-i]);
40                T invn=pow_mod(N,P-2,P);
41                for(int i=0;i<N;++i)out[i]=out[i]*invn%P;
42            }
43        }
44        VT convolution(VT &a, VT &b) {
45            int len = 1<<(__lg(SZ(a) + SZ(b)) + 1);
46            a.resize(len); b.resize(len);
47            vector<int> d1(len), d2(len), c(len), res(len);
48            ntt(false, a, d1, len); ntt(false, b, d2, len);
49            for (int i = 0; i < len; i++) c[i] = d1[i] * d2[i] % P;
50            ntt(true, c, res, len);
51            return res;
52        }
53    };

```

7.3 FFT [18c689]

```

1 #define rep(i, a, b) for (int i = a; i < (b); ++i)
2 typedef complex<double> C;
3 void fft(vector<C> &a) {
4     int n = SZ(a), L = 31 - __builtin_clz(n);
5     static vector<complex<long double>> R(2, 1);
6     static
7         vector<C> rt(2, 1); // (^ 10% faster if double)
8     for (static int k = 2; k < n; k *= 2) {
9         R.resize(n); rt.resize(n);
10        auto x = polar(1.0L, acos(-1.0L) / k);
11        rep(i, k, 2 * k)
12            rt[i] = R[i] = i & 1 ? R[i / 2] * x : R[i / 2];
13    }
14    vi rev(n);
15    rep(i, 0, n) rev[i]=(rev[i/2] | (i&1) << L) / 2;
16    rep(i, 0, n) if (i < rev[i]) swap(a[i], a[rev[i]]);
17    for (int k = 1; k < n; k *= 2)
18        for (int i = 0; i < n; i += 2 * k) rep(j, 0, k) {
19            auto x = (double *)&rt[j + k],
20                y = (double *)&a[i + j + k];
21            C z(x[0] * y[0] - x[1] * y[1],
22                x[0] * y[1] + x[1] * y[0]);
23            a[i + j + k] = a[i + j] - z; a[i + j] += z;
24        }
25    typedef vector<ll> vl;
26    template <int M> vl convMod(const vl &a, const vl &b) {
27        if (a.empty() || b.empty()) return {};
28        vl res(SZ(a) + SZ(b) - 1);
29        int B = 32 - __builtin_clz(SZ(res)), n = (1<<B),
30            cut = int(sqrt(M));
31        vector<C> L(n), R(n), outs(n), outl(n);

```

```

32    rep(i, 0, SZ(a))
33        L[i] = C((int)a[i] / cut, (int)a[i] % cut);
34    rep(i, 0, SZ(b))
35        R[i] = C((int)b[i] / cut, (int)b[i] % cut);
36    fft(L), fft(R);
37    rep(i, 0, n) {
38        int j = -i & (n - 1);
39        outl[j] = (L[i]+conj(L[j])) * R[i] / (2.0*n);
40        outs[j] = (L[i]-conj(L[j])) * R[i] / (2.0*n)/1i;
41    }
42    fft(outl), fft(outs);
43    rep(i, 0, SZ(res)) {
44        ll av = ll(real(outl[i]) + .5),
45            cv = ll(imag(outs[i]) + .5);
46        ll bv = ll(imag(outl[i]) + .5) +
47            ll(real(outs[i]) + .5);
48        res[i] = ((av % M * cut + bv) % M * cut + cv) % M;
49    }
50    return res;
51 }

```

7.4 Newton

Given $F(x)$ where

$$F(x) = \sum_{i=0}^{\infty} \alpha_i (x - \beta)^i$$

for β being some constant. Polynomial P such that $F(P) = 0$ can be found iteratively. Denote by Q_k the polynomial such that $F(Q_k) = 0 \pmod{x^{2^k}}$, then

$$Q_{k+1} = Q_k - \frac{F(Q_k)}{F'(Q_k)} \pmod{x^{2^{k+1}}}$$

8 Geometry

8.1 Default code [3efc61]

```

1 typedef pair<double, double> pdd;
2 typedef pair<pdd, pdd> Line;
3 struct Cir {
4     pdd O;
5     double R;
6 };
7 const double eps = 1e-8;
8 pdd operator+(pdd a, pdd b) {
9     return pdd(a.X + b.X, a.Y + b.Y);
10 }
11 pdd operator-(pdd a, pdd b) {
12     return pdd(a.X - b.X, a.Y - b.Y);
13 }
14 pdd operator*(pdd a, double b) {
15     return pdd(a.X * b, a.Y * b);
16 }
17 pdd operator/(pdd a, double b) {
18     return pdd(a.X / b, a.Y / b);
19 }
20 double dot(pdd a, pdd b) {
21     return a.X * b.X + a.Y * b.Y;
22 }
23 double cross(pdd a, pdd b) {
24     return a.X * b.Y - a.Y * b.X;
25 }
26 double abs2(pdd a) { return dot(a, a); }
27 double abs(pdd a) { return sqrt(dot(a, a)); }
28 int sign(double a) {
29     return fabs(a) < eps ? 0 : a > 0 ? 1 : -1;
30 }
31 int ori(pdd a, pdd b, pdd c) {
32     return sign(cross(b - a, c - a));
33 }
34 bool collinearity(pdd p1, pdd p2, pdd p3) {
35     return sign(cross(p1 - p3, p2 - p3)) == 0;
36 }
37 bool btw(pdd p1, pdd p2, pdd p3) {
38     if (!collinearity(p1, p2, p3)) return 0;
39     return sign(dot(p1 - p3, p2 - p3)) <= 0;
40 }
41 bool seg_intersect(pdd p1, pdd p2, pdd p3, pdd p4) {
42     int a123 = ori(p1, p2, p3);
43     int a124 = ori(p1, p2, p4);
44     int a341 = ori(p3, p4, p1);
45     int a342 = ori(p3, p4, p2);
46     if (a123 == 0 && a124 == 0)
47         return btw(p1, p2, p3) || btw(p1, p2, p4) ||
48            btw(p3, p4, p1) || btw(p3, p4, p2);

```



```

49 return a123 * a124 <= 0 && a341 * a342 <= 0;
50 }
51 pdd intersect(pdd p1, pdd p2, pdd p3, pdd p4) {
52     double a123 = cross(p2 - p1, p3 - p1);
53     double a124 = cross(p2 - p1, p4 - p1);
54     return (p4 * a123 - p3 * a124) /
55         (a123 - a124); // C^3 / C^2
56 }
57 pdd perp(pdd p1) { return pdd(-p1.Y, p1.X); }
58 pdd projection(pdd p1, pdd p2, pdd p3) {
59     return p1 +
60         (p2 - p1) * dot(p3 - p1, p2 - p1) / abs2(p2 - p1);
61 }
62 pdd reflection(pdd p1, pdd p2, pdd p3) {
63     return p3 +
64         perp(p2 - p1) * cross(p3 - p1, p2 - p1) /
65         abs2(p2 - p1) * 2;
66 }
67 pdd linearTransformation(
68     pdd p0, pdd p1, pdd q0, pdd q1, pdd r) {
69     pdd dp = p1 - p0, dq = q1 - q0,
70         num(cross(dp, dq), dot(dp, dq));
71     return q0 +
72         pdd(cross(r - p0, num), dot(r - p0, num)) /
73         abs2(dp);
74 } // from line p0--p1 to q0--q1, apply to r

```

8.2 Default code int [111a95]

```

1 typedef pair<double, double> pdd;
2 typedef pair<pll, pll> line;
3 pll operator+(pll a, pll b) {
4     return pll(a.X + b.X, a.Y + b.Y);
5 }
6 pll operator-(pll a, pll b) {
7     return pll(a.X - b.X, a.Y - b.Y);
8 }
9 pll operator*(pll a, ll b) {
10    return pll(a.X * b, a.Y * b);
11 }
12 pll operator/(pll a, ll b) {
13    return pll(a.X / b, a.Y / b);
14 }
15 pdd operator/(pll a, double b) {
16    return pdd(a.X / b, a.Y / b);
17 }
18 ll dot(pll a, pll b) { return a.X * b.X + a.Y * b.Y; }
19 ll cross(pll a, pll b) {
20     return a.X * b.Y - a.Y * b.X;
21 }
22 ll abs2(pll a) { return dot(a, a); }
23 int sign(ll a) { return a == 0 ? 0 : a > 0 ? 1 : -1; }
24 int ori(pll a, pll b, pll c) {
25     return sign(cross(b - a, c - a));
26 }
27 bool collinearity(pll p1, pll p2, pll p3) {
28     return sign(cross(p1 - p3, p2 - p3)) == 0;
29 }
30 bool btw(pll p1, pll p2, pll p3) {
31     if (!collinearity(p1, p2, p3)) return 0;
32     return sign(dot(p1 - p3, p2 - p3)) <= 0;
33 }
34 bool seg_intersect(pll p1, pll p2, pll p3, pll p4) {
35     int a123 = ori(p1, p2, p3);
36     int a124 = ori(p1, p2, p4);
37     int a341 = ori(p3, p4, p1);
38     int a342 = ori(p3, p4, p2);
39     if (a123 == 0 && a124 == 0)
40         return btw(p1, p2, p3) || btw(p1, p2, p4) ||
41             btw(p3, p4, p1) || btw(p3, p4, p2);
42     return a123 * a124 <= 0 && a341 * a342 <= 0;
43 }
44 pdd intersect(pll p1, pll p2, pll p3, pll p4) {
45     ll a123 = cross(p2 - p1, p3 - p1);
46     ll a124 = cross(p2 - p1, p4 - p1);
47     return (p4 * a123 - p3 * a124) /
48         double(a123 - a124); // C^3 / C^2
49 }
50 pll perp(pll p1) { return pll(-p1.Y, p1.X); }

```

8.3 Convex hull [2a3008]

```

1 void hull(vector<pll> &dots) { // n=1 => ans = {}
2     sort(dots.begin(), dots.end());
3     vector<pll> ans(1, dots[0]);
4     for (int ct = 0; ct < 2; ++ct, reverse(ALL(dots)))
5         for (int i = 1, t = SZ(ans); i < SZ(dots);

```

```

6         ans.pb(dots[i++]))
7         while (SZ(ans) > t &&
8             ori(ans[SZ(ans) - 2], ans.back(), dots[i]) <=
9             0)
10             ans.pop_back();
11         ans.pop_back(), ans.swap(dots);
12     }

```

8.4 PointInConvex [9136f4]

```

1 bool PointInConvex(
2     const vector<pll> &C, pll p, bool strict = true) {
3     int a = 1, b = SZ(C) - 1, r = !strict;
4     if (SZ(C) == 0) return false;
5     if (SZ(C) < 3) return r && btw(C[0], C.back(), p);
6     if (ori(C[0], C[a], C[b]) > 0) swap(a, b);
7     if (ori(C[0], C[a], p) >= r ||
8         ori(C[0], C[b], p) <= -r)
9         return false;
10    while (abs(a - b) > 1) {
11        int c = (a + b) / 2;
12        (ori(C[0], C[c], p) > 0 ? b : a) = c;
13    }
14    return ori(C[a], C[b], p) < r;
15 }

```

8.5 PolyUnion [bf776d]

```

1 double rat(pll a, pll b) {
2     return sign(b.X) ? (double)a.X / b.X
3         : (double)a.Y / b.Y;
4 } // all poly. should be ccw
5 double polyUnion(vector<vector<pll>> &poly) {
6     double res = 0;
7     for (auto &p : poly)
8         for (int a = 0; a < SZ(p); ++a) {
9             pll A = p[a], B = p[(a + 1) % SZ(p)];
10            vector<pair<double, int>> segs = {
11                {0, 0}, {1, 0}};
12            for (auto &q : poly) {
13                if (&p == &q) continue;
14                for (int b = 0; b < SZ(q); ++b) {
15                    pll C = q[b], D = q[(b + 1) % SZ(q)];
16                    int sc = ori(A, B, C), sd = ori(A, B, D);
17                    if (sc != sd && min(sc, sd) < 0) {
18                        double sa = cross(D - C, A - C),
19                            sb = cross(D - C, B - C);
20                        segs.emplace_back(
21                            sa / (sa - sb), sign(sc - sd));
22                    }
23                    if (!sc && !sd && &q < &p &&
24                        sign(dot(B - A, D - C)) > 0) {
25                        segs.emplace_back(rat(C - A, B - A), 1);
26                        segs.emplace_back(rat(D - A, B - A), -1);
27                    }
28                }
29            }
30            sort(ALL(segs));
31            for (auto &s : segs) s.X = clamp(s.X, 0.0, 1.0);
32            double sum = 0;
33            int cnt = segs[0].second;
34            for (int j = 1; j < SZ(segs); ++j) {
35                if (!cnt) sum += segs[j].X - segs[j - 1].X;
36                cnt += segs[j].Y;
37            }
38            res += cross(A, B) * sum;
39        }
40    return res / 2;
41 }

```

8.6 external bisector [f088cc]

```

1 pdd external_bisector(pdd p1, pdd p2, pdd p3) { // 213
2     pdd L1 = p2 - p1, L2 = p3 - p1;
3     L2 = L2 * abs(L1) / abs(L2);
4     return L1 + L2;
5 }

```

8.7 Convexhull3D [fc330d]

```

1 struct convex_hull_3D {
2     struct Face {
3         int a, b, c;
4         Face(int ta, int tb, int tc)
5             : a(ta), b(tb), c(tc) {}
6     }; // return the faces with pt indexes
7     vector<Face> res;
8     vector<Point> P;

```

```

9  convex_hull_3D(const vector<Point> &_P)
10 : res(), P(_P) {
11     // all points coplanar case will WA, O(n^2)
12     int n = SZ(P);
13     if (n <= 2) return; // be careful about edge case
14     // ensure first 4 points are not coplanar
15     swap(P[1], *find_if(ALL(P), [&](auto p) {
16         return sign(abs2(P[0] - p)) != 0;
17     }));
18     swap(P[2], *find_if(ALL(P), [&](auto p) {
19         return sign(abs2(cross3(p, P[0], P[1]))) != 0;
20     }));
21     swap(P[3], *find_if(ALL(P), [&](auto p) {
22         return sign(volume(P[0], P[1], P[2], p)) != 0;
23     }));
24     vector<vector<int>> flag(n, vector<int>(n));
25     res.emplace_back(0, 1, 2);
26     res.emplace_back(2, 1, 0);
27     for (int i = 3; i < n; ++i) {
28         vector<Face> next;
29         for (auto f : res) {
30             int d =
31                 sign(volume(P[f.a], P[f.b], P[f.c], P[i]));
32             if (d <= 0) next.pb(f);
33             int ff = (d > 0) - (d < 0);
34             flag[f.a][f.b] = flag[f.b][f.c] =
35                 flag[f.c][f.a] = ff;
36         }
37         for (auto f : res) {
38             auto F = [&](int x, int y) {
39                 if (flag[x][y] > 0 && flag[y][x] <= 0)
40                     next.emplace_back(x, y, i);
41             };
42             F(f.a, f.b);
43             F(f.b, f.c);
44             F(f.c, f.a);
45         }
46         res = next;
47     }
48 }
49 bool same(Face s, Face t) {
50     if (sign(volume(P[s.a], P[s.b], P[s.c], P[t.a])) !=
51         0)
52         return 0;
53     if (sign(volume(P[s.a], P[s.b], P[s.c], P[t.b])) !=
54         0)
55         return 0;
56     if (sign(volume(P[s.a], P[s.b], P[s.c], P[t.c])) !=
57         0)
58         return 0;
59     return 1;
60 }
61 int polygon_face_num() {
62     int ans = 0;
63     for (int i = 0; i < SZ(res); ++i)
64         ans += none_of(res.begin(), res.begin() + i,
65             [&](Face g) { return same(res[i], g); });
66     return ans;
67 }
68 double get_volume() {
69     double ans = 0;
70     for (auto f : res)
71         ans +=
72             volume(Point(0, 0, 0), P[f.a], P[f.b], P[f.c]);
73     return fabs(ans / 6);
74 }
75 double get_dis(Point p, Face f) {
76     Point p1 = P[f.a], p2 = P[f.b], p3 = P[f.c];
77     double a = (p2.y - p1.y) * (p3.z - p1.z) -
78         (p2.z - p1.z) * (p3.y - p1.y);
79     double b = (p2.z - p1.z) * (p3.x - p1.x) -
80         (p2.x - p1.x) * (p3.z - p1.z);
81     double c = (p2.x - p1.x) * (p3.y - p1.y) -
82         (p2.y - p1.y) * (p3.x - p1.x);
83     double d = 0 - (a * p1.x + b * p1.y + c * p1.z);
84     return fabs(a * p.x + b * p.y + c * p.z + d) /
85         sqrt(a * a + b * b + c * c);
86 }
87 };
88 // n^2 delaunay: facets with negative z normal of
89 // convexhull of (x, y, x^2 + y^2), use a pseudo-point
90 // (0, 0, inf) to avoid degenerate case

```

8.8 Triangulation Voronoi [a4c07f]

```

1 // all coord. is even, you may want to call
2 // halfPlaneInter after then

```

```

3 vector<vector<Line>> vec;
4 void build_voronoi_line(int n, pll *arr) {
5     tool.init(n, arr); // Delaunay
6     vec.clear(), vec.resize(n);
7     for (int i = 0; i < n; ++i)
8         for (auto e : tool.head[i]) {
9             int u = tool.oidx[i], v = tool.oidx[e.id];
10             pll m = (arr[v] + arr[u]) / 2LL,
11                 d = perp(arr[v] - arr[u]);
12             vec[u].pb(Line(m, m + d));
13         }
14 }

```

8.9 Polar Angle Sort [2804b5]

```

1 int cmp(pll a, pll b, bool same = true) {
2     #define is_neg(k)
3     (sign(k.Y) < 0 || (sign(k.Y) == 0 && sign(k.X) < 0))
4     int A = is_neg(a), B = is_neg(b);
5     if (A != B) return A < B;
6     if (sign(cross(a, b)) == 0)
7         return same ? abs2(a) < abs2(b) : -1;
8     return sign(cross(a, b)) > 0;
9 }

```

8.10 Intersection of polygon and circle [cbe8f5]

```

1 // Divides into multiple triangle, and sum up
2 const double PI = acos(-1);
3 double _area(pdd pa, pdd pb, double r) {
4     if (abs(pa) < abs(pb)) swap(pa, pb);
5     if (abs(pb) < eps) return 0;
6     double S, h, theta;
7     double a = abs(pb), b = abs(pa), c = abs(pb - pa);
8     double cosB = dot(pb, pb - pa) / a / c,
9         B = acos(cosB);
10    double cosC = dot(pa, pb) / a / b, C = acos(cosC);
11    if (a > r) {
12        S = (C / 2) * r * r;
13        h = a * b * sin(C) / c;
14        if (h < r && B < PI / 2)
15            S -= (acos(h / r) * r * r -
16                h * sqrt(r * r - h * h));
17    } else if (b > r) {
18        theta = PI - B - asin(sin(B) / r * a);
19        S = .5 * a * r * sin(theta) +
20            (C - theta) / 2 * r * r;
21    } else S = .5 * sin(C) * a * b;
22    return S;
23 }
24 double area_poly_circle(const vector<pdd> poly,
25     const pdd &0, const double r) {
26     double S = 0;
27     for (int i = 0; i < SZ(poly); ++i)
28         S += _area(poly[i] - 0,
29             poly[(i + 1) % SZ(poly)] - 0, r) *
30             ori(0, poly[i], poly[(i + 1) % SZ(poly)]);
31     return fabs(S);
32 }

```

8.11 Tangent line of two circles [5ad86c]

```

1 vector<Line> go(
2     const Cir &c1, const Cir &c2, int sign1) {
3     // sign1 = 1 for outer tang, -1 for inter tang
4     vector<Line> ret;
5     double d_sq = abs2(c1.0 - c2.0);
6     if (sign(d_sq) == 0) return ret;
7     double d = sqrt(d_sq);
8     pdd v = (c2.0 - c1.0) / d;
9     double c = (c1.R - sign1 * c2.R) / d;
10    if (c * c > 1) return ret;
11    double h = sqrt(max(0.0, 1.0 - c * c));
12    for (int sign2 = 1; sign2 >= -1; sign2 -= 2) {
13        pdd n = pdd(v.X * c - sign2 * h * v.Y,
14            v.Y * c + sign2 * h * v.X);
15        pdd p1 = c1.0 + n * c1.R;
16        pdd p2 = c2.0 + n * (c2.R * sign1);
17        if (sign(p1.X - p2.X) == 0 and
18            sign(p1.Y - p2.Y) == 0)
19            p2 = p1 + perp(c2.0 - c1.0);
20        ret.pb(Line(p1, p2));
21    }
22    return ret;
23 }

```

8.12 CircleCover [1d09aa]

```

1 const int N = 1021;
2 struct CircleCover {
3     int C;
4     Cir c[N];
5     bool g[N][N], overlap[N][N];
6     // Area[i] : area covered by at least i circles
7     double Area[N];
8     void init(int _C) { C = _C; }
9     struct Teve {
10         pdd p;
11         double ang;
12         int add;
13         Teve() {}
14         Teve(pdd _a, double _b, int _c)
15             : p(_a), ang(_b), add(_c) {}
16         bool operator<(const Teve &a) const {
17             return ang < a.ang;
18         }
19     } eve[N * 2];
20     // strict: x = 0, otherwise x = -1
21     bool disjunct(Cir &a, Cir &b, int x) {
22         return sign(abs(a.O - b.O) - a.R - b.R) > x;
23     }
24     bool contain(Cir &a, Cir &b, int x) {
25         return sign(a.R - b.R - abs(a.O - b.O)) > x;
26     }
27     bool contain(int i, int j) {
28         /* c[j] is non-strictly in c[i]. */
29         return (sign(c[i].R - c[j].R) > 0 ||
30             (sign(c[i].R - c[j].R) == 0 && i < j)) &&
31             contain(c[i], c[j], -1);
32     }
33     void solve() {
34         fill_n(Area, C + 2, 0);
35         for (int i = 0; i < C; ++i)
36             for (int j = 0; j < C; ++j)
37                 overlap[i][j] = contain(i, j);
38         for (int i = 0; i < C; ++i)
39             for (int j = 0; j < C; ++j)
40                 g[i][j] = !(overlap[i][j] || overlap[j][i] ||
41                     disjunct(c[i], c[j], -1));
42         for (int i = 0; i < C; ++i) {
43             int E = 0, cnt = 1;
44             for (int j = 0; j < C; ++j)
45                 if (j != i && overlap[j][i]) ++cnt;
46             for (int j = 0; j < C; ++j)
47                 if (i != j && g[i][j]) {
48                     pdd aa, bb;
49                     CCinter(c[i], c[j], aa, bb);
50                     double A =
51                         atan2(aa.Y - c[i].O.Y, aa.X - c[i].O.X);
52                     double B =
53                         atan2(bb.Y - c[i].O.Y, bb.X - c[i].O.X);
54                     eve[E++] = Teve(bb, B, 1);
55                     eve[E++] = Teve(aa, A, -1);
56                     if (B > A) ++cnt;
57                 }
58             if (E == 0) Area[cnt] += pi * c[i].R * c[i].R;
59             else {
60                 sort(eve, eve + E);
61                 eve[E] = eve[0];
62                 for (int j = 0; j < E; ++j) {
63                     cnt += eve[j].add;
64                     Area[cnt] +=
65                         cross(eve[j].p, eve[j + 1].p) * .5;
66                     double theta = eve[j + 1].ang - eve[j].ang;
67                     if (theta < 0) theta += 2. * pi;
68                     Area[cnt] += (theta - sin(theta)) * c[i].R *
69                         c[i].R * .5;
70                 }
71             }
72         }
73     }
74 };

```

8.13 Heart [4698ba]

```

1 pdd circenter(
2     pdd p0, pdd p1, pdd p2) { // radius = abs(center)
3     p1 = p1 - p0, p2 = p2 - p0;
4     double x1 = p1.X, y1 = p1.Y, x2 = p2.X, y2 = p2.Y;
5     double m = 2. * (x1 * y2 - y1 * x2);
6     center.X = (x1 * x1 * y2 - x2 * x2 * y1 +
7         y1 * y2 * (y1 - y2)) /
8     m;

```

```

9     center.Y = (x1 * x2 * (x2 - x1) - y1 * y1 * x2 +
10         x1 * y2 * y2) /
11     m;
12     return center + p0;
13 }
14 pdd incenter(
15     pdd p1, pdd p2, pdd p3) { // radius = area / s * 2
16     double a = abs(p2 - p3), b = abs(p1 - p3),
17         c = abs(p1 - p2);
18     double s = a + b + c;
19     return (a * p1 + b * p2 + c * p3) / s;
20 }
21 pdd masscenter(pdd p1, pdd p2, pdd p3) {
22     return (p1 + p2 + p3) / 3;
23 }
24 pdd orthcenter(pdd p1, pdd p2, pdd p3) {
25     return masscenter(p1, p2, p3) * 3 -
26         circenter(p1, p2, p3) * 2;
27 }

```

8.14 PointSegDist [5ee686]

```

1 double PointSegDist(pdd q0, pdd q1, pdd p) {
2     if (sign(abs(q0 - q1)) == 0) return abs(q0 - p);
3     if (sign(dot(q1 - q0, p - q0)) >= 0 &&
4         sign(dot(q0 - q1, p - q1)) >= 0)
5         return fabs(cross(q1 - q0, p - q0) / abs(q0 - q1));
6     return min(abs(p - q0), abs(p - q1));
7 }

```

8.15 Minkowski Sum [95f4a0]

```

1 vector<pll> Minkowski(
2     vector<pll> A, vector<pll> B) { // |A|, |B| >= 3
3     hull(A), hull(B);
4     vector<pll> C(1, A[0] + B[0]), s1, s2;
5     for (int i = 0; i < SZ(A); ++i)
6         s1.pb(A[(i + 1) % SZ(A)] - A[i]);
7     for (int i = 0; i < SZ(B); ++i)
8         s2.pb(B[(i + 1) % SZ(B)] - B[i]);
9     for (int i = 0, j = 0; i < SZ(A) || j < SZ(B);)
10         if (j >= SZ(B) ||
11             (i < SZ(A) && cross(s1[i], s2[j]) >= 0))
12             C.pb(B[j % SZ(B)] + A[i++]);
13         else C.pb(A[i % SZ(A)] + B[j++]);
14     return hull(C, C);
15 }

```

8.16 TangentPointToHull [5668cc]

```

1 /* The point should be strictly out of hull
2    return arbitrary point on the tangent line */
3 pii get_tangent(vector<pll> &C, pll p) {
4     auto gao = [&](int s) {
5         return cyc_tsearch(SZ(C), [&](int x, int y) {
6             return ori(p, C[x], C[y]) == s;
7         });
8     };
9     return pii(gao(1), gao(-1));
10 } // return (a, b), ori(p, C[a], C[b]) >= 0

```

8.17 Intersection of two circles [b062ba]

```

1 bool CCinter(Cir &a, Cir &b, pdd &p1, pdd &p2) {
2     pdd o1 = a.O, o2 = b.O;
3     double r1 = a.R, r2 = b.R, d2 = abs2(o1 - o2),
4         d = sqrt(d2);
5     if (d < max(r1, r2) - min(r1, r2) || d > r1 + r2)
6         return 0;
7     pdd u = (o1 + o2) * 0.5 +
8         (o1 - o2) * ((r2 * r2 - r1 * r1) / (2 * d2));
9     double A = sqrt((r1 + r2 + d) * (r1 - r2 + d) *
10         (r1 + r2 - d) * (-r1 + r2 + d));
11     pdd v =
12         pdd(o1.Y - o2.Y, -o1.X + o2.X) * A / (2 * d2);
13     p1 = u + v, p2 = u - v;
14     return 1;
15 }

```

8.18 Intersection of line and circle [894afd]

```

1 vector<pdd> circleLine(pdd c, double r, pdd a, pdd b) {
2     pdd p =
3         a + (b - a) * dot(c - a, b - a) / abs2(b - a);
4     double s = cross(b - a, c - a),
5         h2 = r * r - s * s / abs2(b - a);
6     if (h2 < 0) return {};
7     if (h2 == 0) return {p};
8     pdd h = (b - a) / abs(b - a) * sqrt(h2);
9     return {p - h, p + h};
10 }

```

8.19 point in circle [882728]

```

1 // return q's relation with circumcircle of
2 // tri(p[0],p[1],p[2])
3 bool in_cc(const array<pll, 3> &p, pll q) {
4     __int128 det = 0;
5     for (int i = 0; i < 3; ++i)
6         det += __int128(abs2(p[i]) - abs2(q)) *
7             cross(p[(i + 1) % 3] - q, p[(i + 2) % 3] - q);
8     return det > 0; // in: >0, on: =0, out: <0
9 }

```

8.20 PolyCut [417264]

```

1 vector<pdd> cut(vector<pdd> poly, pdd s, pdd e) {
2     vector<pdd> res;
3     for (int i = 0; i < SZ(poly); ++i) {
4         pdd cur = poly[i],
5             prv = i ? poly[i - 1] : poly.back();
6         bool side = ori(s, e, cur) < 0;
7         if (side != (ori(s, e, prv) < 0))
8             res.pb(intersect(s, e, cur, prv));
9         if (side) res.pb(cur);
10    }
11    return res;
12 }

```

8.21 minDistOfTwoConvex [d62c1f]

```

1 double ConvexHullDist(vector<pdd> A, vector<pdd> B) {
2     for (auto &p : B) p = {-p.X, -p.Y};
3     auto C = Minkowski(A, B); // assert SZ(C) > 0
4     if (PointInConvex(C, pdd(0, 0))) return 0;
5     double ans = PointSegDist(C.back(), C[0], pdd(0, 0));
6     for (int i = 0; i + 1 < SZ(C); ++i) {
7         ans = min(
8             ans, PointSegDist(C[i], C[i + 1], pdd(0, 0)));
9     }
10    return ans;
11 }

```

8.22 rotatingSweepLine [374fec]

```

1 void rotatingSweepLine(vector<pii> &ps) {
2     int n = SZ(ps), m = 0;
3     vector<int> id(n), pos(n);
4     vector<pii> line(n * (n - 1));
5     for (int i = 0; i < n; ++i)
6         for (int j = 0; j < n; ++j)
7             if (i != j) line[m++] = pii(i, j);
8     sort(ALL(line), [&](pii a, pii b) {
9         return cmp(ps[a.Y] - ps[a.X], ps[b.Y] - ps[b.X]);
10    }); // cmp(): polar angle compare
11    iota(ALL(id), 0);
12    sort(ALL(id), [&](int a, int b) {
13        if (ps[a].Y != ps[b].Y) return ps[a].Y < ps[b].Y;
14        return ps[a] < ps[b];
15    }); // initial order, since (1, 0) is the smallest
16    for (int i = 0; i < n; ++i) pos[id[i]] = i;
17    for (int i = 0; i < m; ++i) {
18        auto l = line[i];
19        // do something
20        tie(
21            pos[l.X], pos[l.Y], id[pos[l.X]], id[pos[l.Y]]) = 44;
22        make_tuple(pos[l.Y], pos[l.X], l.Y, l.X);
23    }
24 }

```

8.23 Intersection of line and convex [e14a5c]

```

1 int TangentDir(vector<pll> &C, pll dir) {
2     return cyc_tsearch(SZ(C), [&](int a, int b) {
3         return cross(dir, C[a]) > cross(dir, C[b]);
4     });
5 }
6 #define cmpL(i) sign(cross(C[i] - a, b - a))
7 pii lineHull(pll a, pll b, vector<pll> &C) {
8     int A = TangentDir(C, a - b);
9     int B = TangentDir(C, b - a);
10    int n = SZ(C);
11    if (cmpL(A) < 0 || cmpL(B) > 0)
12        return pii(-1, -1); // no collision
13    auto gao = [&](int l, int r) {
14        for (int t = l; (l + 1) % n != r; r) {
15            int m = ((l + r + (l < r ? 0 : n)) / 2) % n;
16            (cmpL(m) == cmpL(t) ? l : r) = m;
17        }
18        return (l + !cmpL(r)) % n;
19    };

```

```

19 };
20 pii res = pii(gao(B, A), gao(A, B)); // (i, j)
21 if (res.X == res.Y) // touching the corner i
22     return pii(res.X, -1);
23 if (!cmpL(res.X) &&
24     !cmpL(res.Y)) // along side i, i+1
25     switch ((res.X - res.Y + n + 1) % n) {
26     case 0: return pii(res.X, res.X);
27     case 2: return pii(res.Y, res.Y);
28     }
29 /* crossing sides (i, i+1) and (j, j+1)
30 crossing corner i is treated as side (i, i+1)
31 returned in the same order as the line hits the
32 convex */
33 return res;
34 } // convex cut: (r, l]

```

8.24 3Dpoint [90da48]

```

1 struct Point {
2     double x, y, z;
3     Point(double _x = 0, double _y = 0, double _z = 0)
4         : x(_x), y(_y), z(_z) {}
5     Point(pdd p) { x = p.X, y = p.Y, z = abs2(p); }
6 };
7 Point operator-(Point p1, Point p2) {
8     return Point(p1.x - p2.x, p1.y - p2.y, p1.z - p2.z);
9 }
10 Point operator+(Point p1, Point p2) {
11     return Point(p1.x + p2.x, p1.y + p2.y, p1.z + p2.z);
12 }
13 Point operator*(Point p1, double v) {
14     return Point(p1.x * v, p1.y * v, p1.z * v);
15 }
16 Point operator/(Point p1, double v) {
17     return Point(p1.x / v, p1.y / v, p1.z / v);
18 }
19 Point cross(Point p1, Point p2) {
20     return Point(p1.y * p2.z - p1.z * p2.y,
21                 p1.z * p2.x - p1.x * p2.z,
22                 p1.x * p2.y - p1.y * p2.x);
23 }
24 double dot(Point p1, Point p2) {
25     return p1.x * p2.x + p1.y * p2.y + p1.z * p2.z;
26 }
27 double abs(Point a) { return sqrt(dot(a, a)); }
28 Point cross3(Point a, Point b, Point c) {
29     return cross(b - a, c - a);
30 }
31 double area(Point a, Point b, Point c) {
32     return abs(cross3(a, b, c));
33 }
34 double volume(Point a, Point b, Point c, Point d) {
35     return dot(cross3(a, b, c), d - a);
36 }
37 // Azimuthal angle (longitude) to x-axis in interval
38 // [-pi, pi]
39 double phi(Point p) { return atan2(p.y, p.x); }
40 // Zenith angle (latitude) to the z-axis in interval
41 // [0, pi]
42 double theta(Point p) {
43     return atan2(sqrt(p.x * p.x + p.y * p.y), p.z);
44 }
45 Point masscenter(Point a, Point b, Point c, Point d) {
46     return (a + b + c + d) / 4;
47 }
48 pdd proj(Point a, Point b, Point c, Point u) {
49     // proj. u to the plane of a, b, and c
50     Point e1 = b - a;
51     Point e2 = c - a;
52     e1 = e1 / abs(e1);
53     e2 = e2 - e1 * dot(e2, e1);
54     e2 = e2 / abs(e2);
55     Point p = u - a;
56     return pdd(dot(p, e1), dot(p, e2));
57 }
58 Point rotate_around(
59     Point p, double angle, Point axis) {
60     double s = sin(angle), c = cos(angle);
61     Point u = axis / abs(axis);
62     return u * dot(u, p) * (1 - c) + p * c +
63         cross(u, p) * s;
64 }

```

8.25 minMaxEnclosingRectangle [d47db9]

```

1 const double INF = 1e18, qi = acos(-1) / 2 * 3;

```

```

2 pdd solve(vector<pll> &dots) {
3 #define diff(u, v) (dots[u] - dots[v])
4 #define vec(v) (dots[v] - dots[i])
5 hull(dots);
6 double Max = 0, Min = INF, deg;
7 int n = SZ(dots);
8 dots.pb(dots[0]);
9 for (int i = 0, u = 1, r = 1, l = 1; i < n; ++i) {
10 pll nw = vec(i + 1);
11 while (cross(nw, vec(u + 1)) > cross(nw, vec(u)))
12 u = (u + 1) % n;
13 while (dot(nw, vec(r + 1)) > dot(nw, vec(r)))
14 r = (r + 1) % n;
15 if (!i) l = (r + 1) % n;
16 while (dot(nw, vec(l + 1)) < dot(nw, vec(l)))
17 l = (l + 1) % n;
18 Min = min(Min,
19 (double)(dot(nw, vec(r)) - dot(nw, vec(l))) *
20 cross(nw, vec(u)) / abs2(nw));
21 deg = acos(dot(diff(r, l), vec(u)) /
22 abs(diff(r, l)) / abs(vec(u)));
23 deg = (pi - deg) / 2;
24 Max = max(Max,
25 abs(diff(r, l)) * abs(vec(u)) * sin(deg) *
26 sin(deg));
27 }
28 return pdd(Min, Max);
29 }

```

8.26 Half plane intersection [c3e180]

```

1 pll area_pair(Line a, Line b) {
2 return pll(cross(a.Y - a.X, b.X - a.X),
3 cross(a.Y - a.X, b.Y - a.X));
4 }
5 bool isin(Line l0, Line l1, Line l2) {
6 // Check inter(l1, l2) strictly in l0
7 auto [a02X, a02Y] = area_pair(l0, l2);
8 auto [a12X, a12Y] = area_pair(l1, l2);
9 if (a12X - a12Y < 0) a12X *= -1, a12Y *= -1;
10 return (__int128)a02Y * a12X -
11 (__int128)a02X * a12Y >
12 0;
13 }
14 /* Having solution, check size > 2 */
15 /* --- Line.X --- Line.Y --- */
16 vector<Line> halfPlaneInter(vector<Line> arr) {
17 sort(ALL(arr), [&](Line a, Line b) -> int {
18 if (cmp(a.Y - a.X, b.Y - b.X, 0) != -1)
19 return cmp(a.Y - a.X, b.Y - b.X, 0);
20 return ori(a.X, a.Y, b.Y) < 0;
21 });
22 deque<Line> dq(1, arr[0]);
23 auto pop_back = [&](int t, Line p) {
24 while (SZ(dq) >= t &&
25 !isin(p, dq[SZ(dq) - 2], dq.back()))
26 dq.pop_back();
27 };
28 auto pop_front = [&](int t, Line p) {
29 while (SZ(dq) >= t && !isin(p, dq[0], dq[1]))
30 dq.pop_front();
31 };
32 for (auto p : arr)
33 if (cmp(dq.back().Y - dq.back().X, p.Y - p.X, 0) !=
34 -1)
35 pop_back(2, p), pop_front(2, p), dq.pb(p);
36 pop_back(3, dq[0]), pop_front(3, dq.back());
37 return vector<Line>(ALL(dq));
38 }

```

8.27 Vector in poly [6d98e8]

```

1 // ori(a, b, c) >= 0, valid: "strict" angle from a-b to
2 // a-c
3 bool btwangle(pll a, pll b, pll c, pll p, int strict) {
4 return ori(a, b, p) >= strict &&
5 ori(a, p, c) >= strict;
6 }
7 // whether vector{cur, p} in counter-clockwise order
8 // prv, cur, nxt
9 bool inside(
10 pll prv, pll cur, pll nxt, pll p, int strict) {
11 if (ori(cur, nxt, prv) >= 0)
12 return btwangle(cur, nxt, prv, p, strict);
13 return !btwangle(cur, prv, nxt, p, !strict);
14 }

```

8.28 Minimum Enclosing Circle [5f3cdb]

```

1 pdd Minimum_Enclosing_Circle(
2 vector<pdd> dots, double &r) {
3 pdd cent;
4 random_shuffle(ALL(dots));
5 cent = dots[0], r = 0;
6 for (int i = 1; i < SZ(dots); ++i)
7 if (abs(dots[i] - cent) > r) {
8 cent = dots[i], r = 0;
9 for (int j = 0; j < i; ++j)
10 if (abs(dots[j] - cent) > r) {
11 cent = (dots[i] + dots[j]) / 2;
12 r = abs(dots[i] - cent);
13 for (int k = 0; k < j; ++k)
14 if (abs(dots[k] - cent) > r)
15 cent =
16 excenter(dots[i], dots[j], dots[k], r);
17 }
18 }
19 return cent;
20 }

```

9 Else

9.1 ManhattanMST [90cf5a]

```

1 void solve(Point *a, int n) {
2 sort(a, a + n, [](const Point &p, const Point &q) {
3 return p.x + p.y < q.x + q.y;
4 });
5 set<Point> st; // greater<Point::x>
6 for (int i = 0; i < n; ++i) {
7 for (auto it = st.lower_bound(a[i]);
8 it != st.end(); it = st.erase(it)) {
9 if (it->x - it->y < a[i].x - a[i].y) break;
10 es.push_back({it->u, a[i].u, dist(*it, a[i])});
11 }
12 st.insert(a[i]);
13 }
14 }
15 void MST(Point *a, int n) {
16 for (int t = 0; t < 2; ++t) {
17 solve(a, n);
18 for (int i = 0; i < n; ++i) swap(a[i].x, a[i].y);
19 solve(a, n);
20 for (int i = 0; i < n; ++i) a[i].x = -a[i].x;
21 }
22 }

```

9.2 Mos Algorithm With modification [021725]

```

1 /*
2 Mo's Algorithm With modification
3 Block: N^{2/3}, Complexity: N^{5/3}
4 */
5 struct Query {
6 int L, R, LBid, RBid, T;
7 Query(int l, int r, int t)
8 : L(l), R(r), LBid(l / blk), RBid(r / blk), T(t) {}
9 bool operator<(const Query &q) const {
10 if (LBid != q.LBid) return LBid < q.LBid;
11 if (RBid != q.RBid) return RBid < q.RBid;
12 return T < b.T;
13 }
14 };
15 void solve(vector<Query> query) {
16 sort(ALL(query));
17 int L = 0, R = 0, T = -1;
18 for (auto q : query) {
19 while (T < q.T) addTime(L, R, ++T); // TODO
20 while (T > q.T) subTime(L, R, T--); // TODO
21 while (R < q.R) add(arr[++R]); // TODO
22 while (L > q.L) add(arr[--L]); // TODO
23 while (R > q.R) sub(arr[R--]); // TODO
24 while (L < q.L) sub(arr[L--]); // TODO
25 // answer query
26 }
27 }

```

9.3 BitsetLCS [027ab4]

```

1 cin >> n >> m;
2 for (int i = 1, x; i <= n; ++i) cin >> x, p[x].set(i);
3 for (int i = 1, x; i <= m; ++i) {
4 cin >> x, (g = f) |= p[x];
5 f.shiftLeftByOne(), f.set(0);
6 ((f = g - f) ^= g) &= g;
7 }
8 cout << f.count() << '\n';

```


9.4 BinarySearchOnFraction [dec1bd]

```

1 struct Q {
2     ll p, q;
3     Q go(Q b, ll d) {
4         return {p + b.p * d, q + b.q * d};
5     }
6 };
7 bool pred(Q);
8 // returns smallest p/q in [lo, hi] such that
9 // pred(p/q) is true, and 0 <= p,q <= N
10 Q frac_bs(ll N) {
11     Q lo{0, 1}, hi{1, 0};
12     if (pred(lo)) return lo;
13     assert(pred(hi));
14     bool dir = 1, L = 1, H = 1;
15     for (; L || H; dir = !dir) {
16         ll len = 0, step = 1;
17         for (int t = 0;
18              t < 2 && (t ? step /= 2 : step *= 2);)
19             if (Q mid = hi.go(lo, len + step);
20                 mid.p > N || mid.q > N || dir ^ pred(mid))
21                 t++;
22             else len += step;
23         swap(lo, hi = hi.go(lo, len));
24         (dir ? L : H) = !!len;
25     }
26     return dir ? hi : lo;
27 }

```

9.5 SubsetSum [8fa070]

```

1 template <size_t S> // sum(a) < S
2 bitset<S> SubsetSum(const int *a, int n) {
3     vector<int> c(S);
4     bitset<S> dp;
5     dp[0] = 1;
6     for (int i = 0; i < n; ++i) ++c[a[i]];
7     for (size_t i = 1; i < S; ++i) {
8         while (c[i] > 2) c[i] -= 2, ++c[i * 2];
9         while (c[i]--) dp |= dp << i;
10    }
11    return dp;
12 }

```

9.6 DynamicMST [a5e63b]

```

1 int cnt[maxn], cost[maxn], st[maxn], ed[maxn];
2 pair<int, int> qr[maxn];
3 // qr[i].first = id of edge to be changed, qr[i].second
4 // = weight after operation cnt[i] = number of
5 // operation on edge i call solve(0, q - 1, v, 0),
6 // where v contains edges i such that cnt[i] == 0
7
8 void contract(int l, int r, vector<int> v,
9               vector<int> &x, vector<int> &y) {
10     sort(v.begin(), v.end(), [&](int i, int j) {
11         if (cost[i] == cost[j]) return i < j;
12         return cost[i] < cost[j];
13     });
14     djs.save();
15     for (int i = l; i <= r; ++i)
16         djs.merge(st[qr[i].first], ed[qr[i].first]);
17     for (int i = 0; i < (int)v.size(); ++i) {
18         if (djs.find(st[v[i]]) != djs.find(ed[v[i]])) {
19             x.push_back(v[i]);
20             djs.merge(st[v[i]], ed[v[i]]);
21         }
22     }
23     djs.undo();
24     djs.save();
25     for (int i = 0; i < (int)x.size(); ++i)
26         djs.merge(st[x[i]], ed[x[i]]);
27     for (int i = 0; i < (int)v.size(); ++i) {
28         if (djs.find(st[v[i]]) != djs.find(ed[v[i]])) {
29             y.push_back(v[i]);
30             djs.merge(st[v[i]], ed[v[i]]);
31         }
32     }
33     djs.undo();
34 }
35
36 void solve(int l, int r, vector<int> v, long long c) {
37     if (l == r) {
38         cost[qr[l].first] = qr[l].second;
39         if (st[qr[l].first] == ed[qr[l].first]) {
40             printf("%lld\n", c);

```

```

41         return;
42     }
43     int minv = qr[l].second;
44     for (int i = 0; i < (int)v.size(); ++i)
45         minv = min(minv, cost[v[i]]);
46     printf("%lld\n", c + minv);
47     return;
48 }
49 int m = (l + r) >> 1;
50 vector<int> lv = v, rv = v;
51 vector<int> x, y;
52 for (int i = m + 1; i <= r; ++i) {
53     cnt[qr[i].first]--;
54     if (cnt[qr[i].first] == 0)
55         lv.push_back(qr[i].first);
56 }
57 contract(l, m, lv, x, y);
58 long long lc = c, rc = c;
59 djs.save();
60 for (int i = 0; i < (int)x.size(); ++i) {
61     lc += cost[x[i]];
62     djs.merge(st[x[i]], ed[x[i]]);
63 }
64 solve(l, m, y, lc);
65 djs.undo();
66 x.clear(), y.clear();
67 for (int i = m + 1; i <= r; ++i) cnt[qr[i].first]++;
68 for (int i = l; i <= m; ++i) {
69     cnt[qr[i].first]--;
70     if (cnt[qr[i].first] == 0)
71         rv.push_back(qr[i].first);
72 }
73 contract(m + 1, r, rv, x, y);
74 djs.save();
75 for (int i = 0; i < (int)x.size(); ++i) {
76     rc += cost[x[i]];
77     djs.merge(st[x[i]], ed[x[i]]);
78 }
79 solve(m + 1, r, y, rc);
80 djs.undo();
81 for (int i = l; i <= m; ++i) cnt[qr[i].first]++;
82 }

```

9.7 Matroid

Start from $S = \emptyset$. In each iteration, let

- $Y_1 = \{x \notin S \mid S \cup \{x\} \in I_1\}$
- $Y_2 = \{x \notin S \mid S \cup \{x\} \in I_2\}$

If there exists $x \in Y_1 \cap Y_2$, insert x into S . Otherwise for each $x \in S, y \notin S$, create edges

- $x \rightarrow y$ if $S - \{x\} \cup \{y\} \in I_1$.
- $y \rightarrow x$ if $S - \{x\} \cup \{y\} \in I_2$.

Find a *shortest* path (with BFS) starting from a vertex in Y_1 and ending at a vertex in Y_2 which doesn't pass through any other vertices in Y_2 , and alternate the path. The size of S will be incremented by 1 in each iteration. For the weighted case, assign weight $w(x)$ to vertex x if $x \in S$ and $-w(x)$ if $x \notin S$. Find the path with the minimum number of edges among all minimum length paths and alternate it.

9.8 HilbertCurve [bc6dec]

```

1 ll hilbert(int n, int x, int y) {
2     ll res = 0;
3     for (int s = n / 2; s; s >>= 1) {
4         int rx = (x & s) > 0;
5         int ry = (y & s) > 0;
6         res += s * 1ll * s * ((3 * rx) ^ ry);
7         if (ry == 0) {
8             if (rx == 1) x = s - 1 - x, y = s - 1 - y;
9             swap(x, y);
10        }
11    }
12    return res;
13 } // n = 2^k

```

9.9 Mos Algorithm On Tree [90ac22]

```

1 /*
2 Mo's Algorithm On Tree
3 Preprocess:
4 1) LCA
5 2) dfs with in[u] = dft++, out[u] = dft++
6 3) ord[in[u]] = ord[out[u]] = u
7 4) bitset<MAXN> inset
8 */
9 struct Query {
10     int L, R, Lbid, lca;
11     Query(int u, int v) {
12         int c = LCA(u, v);

```

```

13     if (c == u || c == v)
14         q.lca = -1, q.L = out[c ^ u ^ v], q.R = out[c];
15     else if (out[u] < in[v])
16         q.lca = c, q.L = out[u], q.R = in[v];
17     else q.lca = c, q.L = out[v], q.R = in[u];
18     q.Lid = q.L / blk;
19 }
20 bool operator<(const Query &q) const {
21     if (LBid != q.LBid) return LBid < q.LBid;
22     return R < q.R;
23 }
24 };
25 void flip(int x) {
26     if (inset[x]) sub(arr[x]); // TODO
27     else add(arr[x]); // TODO
28     inset[x] = ~inset[x];
29 }
30 void solve(vector<Query> query) {
31     sort(ALL(query));
32     int L = 0, R = 0;
33     for (auto q : query) {
34         while (R < q.R) flip(ord[++R]);
35         while (L > q.L) flip(ord[--L]);
36         while (R > q.R) flip(ord[R--]);
37         while (L < q.L) flip(ord[L++]);
38         if (~q.lca) add(arr[q.lca]);
39         // answer query
40         if (~q.lca) sub(arr[q.lca]);
41     }
42 }

```

9.10 Mos Algorithm

- Mo's Algorithm With Addition Only
 - Sort queries same as the normal Mo's algorithm.
 - For each query $[l, r]$:
 - If $l/blk = r/blk$, brute-force.
 - If $l/blk \neq curL/blk$, initialize $curL := (l/blk + 1) \cdot blk$, $curR := curL - 1$
 - If $r > curR$, increase $curR$
 - decrease $curL$ to fit l , and then undo after answering
- Mo's Algorithm With Offline Second Time
 - Require: Changing answer \equiv adding $f([l, r], r+1)$.
 - Require: $f([l, r], r+1) = f([1, r], r+1) - f([1, l], r+1)$.
 - Part1: Answer all $f([1, r], r+1)$ first.
 - Part2: Store $curR \rightarrow R$ for $curL$ (reduce the space to $O(N)$), and then answer them by the second offline algorithm.
 - Note: You must do the above symmetrically for the left boundaries.

9.11 min plus convolution [b08f6f]

```

1 // a is convex a[i+1]-a[i] <= a[i+2]-a[i+1]
2 vector<int> min_plus_convolution(
3     vector<int> &a, vector<int> &b) {
4     int n = SZ(a), m = SZ(b);
5     vector<int> c(n + m - 1, INF);
6     auto dc = [&](auto Y, int l, int r, int jl, int jr) {
7         if (l > r) return;
8         int mid = (l + r) / 2, from = -1, &best = c[mid];
9         for (int j = jl; j <= jr; ++j)
10             if (int i = mid - j; i >= 0 && i < n)
11                 if (best > a[i] + b[j])
12                     best = a[i] + b[j], from = j;
13         Y(Y, l, mid - 1, jl, from),
14         Y(Y, mid + 1, r, from, jr);
15     };
16     return dc(dc, 0, n - 1 + m - 1, 0, m - 1), c;
17 }

```

9.12 NQueens [68bc5d]

```

1 void solve(
2     vector<int> &ret, int n) { // no sol when n=2,3
3     if (n % 6 == 2) {
4         for (int i = 2; i <= n; i += 2) ret.pb(i);
5         ret.pb(3);
6         ret.pb(1);
7         for (int i = 7; i <= n; i += 2) ret.pb(i);
8         ret.pb(5);
9     } else if (n % 6 == 3) {
10        for (int i = 4; i <= n; i += 2) ret.pb(i);
11        ret.pb(2);
12        for (int i = 5; i <= n; i += 2) ret.pb(i);
13        ret.pb(1);
14        ret.pb(3);
15    } else {
16        for (int i = 2; i <= n; i += 2) ret.pb(i);
17        for (int i = 1; i <= n; i += 2) ret.pb(i);
18    }
19 }

```

9.13 simulated annealing [60768d]

```

1 double factor = 100000;
2 const int base = 1e9; // remember to run ~ 10 times
3 for (int it = 1; it <= 1000000; ++it) {
4     // ans: answer, nw: current value, rnd(): mt19937
5     // rnd()
6     if (exp(-(nw - ans) / factor) >=
7         (double)(rnd() % base) / base)
8         ans = nw;
9     factor *= 0.99995;
10 }

```

9.14 tree hash [95e839]

```

1 ull seed;
2 ull shift(ull x) {
3     x ^= x << 13; x ^= x >> 7; x ^= x << 17;
4     return x;
5 }
6 ull dfs(int u, int f) {
7     ull sum = seed;
8     for (int i : G[u])
9         if (i != f) sum += shift(dfs(i, u));
10    return sum;
11 }

```

9.15 tree knapsack [e59e4f]

```

1 void dfs(int u, int p) {
2     sz[u] = 1;
3     for (int v : tree[u]) if (v != p) {
4         dfs(v, u);
5         for (int i = sz[u] + sz[v]; i >= 1; i--)
6             for (int j = max(1, i - sz[u]); j <= i && j <= sz[v]; j++)
7                 dp[u][i] = min(dp[u][i], dp[u][i-j] + dp[v][j]);
8         sz[u] += sz[v];
9     }
10 }

```