

Universidad Autónoma de Nuevo León Facultad de
Ingeniería Mecánica y Eléctrica

Artificial Intelligence

Assignment 2: Processing Datasets in Python

Matrícula	Nombre
2093442	Leonardo Saavedra de León
2110633	Gilberto Rubén Cabral Martíne
2097046	Rocío Gabriela Escalera Mireles

Hora: N3

Grupo: 001

Semestre: Agosto – Diciembre 2026

Cd. Universitaria, San Nicolás de los Garza, N.L.

Explanation

The Pima Indians Diabetes dataset was processed through a structured pipeline to prepare clinical records for future machine learning modeling. The dataset contains 768 entries, and an initial exploratory data analysis confirmed that while there were no missing values labeled as null, several features contained biologically impossible zeros. Specifically, critical medical indicators like Glucose, BloodPressure, SkinThickness, Insulin, and BMI presented zero values, which represent missing or unrecorded data points rather than valid medical measurements.

To clean the dataset without sacrificing valuable clinical samples, missingness was addressed through median imputation. The zero values in the affected columns were replaced with the median of their non-zero entries, effectively mitigating bias while preserving overall sample size. Following data cleaning, feature normalization was applied using Min-Max scaling to map all feature variables onto a uniform range between 0 and 1. This step is essential because raw clinical metrics exist on drastically different scales, which could cause larger numerical values like Insulin to disproportionately influence machine learning optimization steps or distance calculations.

Data visualization validated the transformations and revealed key dataset characteristics. Histograms comparing Glucose levels before and after normalization confirmed that Min-Max scaling successfully rescaled the data while maintaining the original distribution shape. Scatter plots examining Glucose against BMI highlighted a positive correlation of 0.231, illustrating that higher glucose levels generally align with diabetic outcomes. Finally, inspecting the target variable showed an imbalanced class distribution consisting of 500 non-diabetic patients and 268 diabetic patients.

Questions

What impact do missing values have on data analysis? Missing data reduces the overall statistical power of your study and can distort sample distributions. If missingness is ignored, algorithms might treat a lack of reported information as a real diagnostic signal, leading to biased results—especially if sicker patients are more likely to miss follow-up visits.

How can we detect and handle outliers in biomedical datasets? Outliers in medical data can represent either dangerous hardware errors or rare clinical events. Statistical methods like Z-scores evaluate how far a value strays from the mean, while the Interquartile Range sets boundary thresholds using dataset quartiles. For complex data, multi-dimensional tools like Isolation Forests isolate anomalies across several metrics at once. To handle them safely, you can cap extreme values through Winsorization, filter out biologically impossible numbers, or use robust algorithms that are less sensitive to extreme points.

What are some common causes of missing or incorrect data in biomedical studies? Data issues in healthcare usually stem from four main sources. First, hardware failures like disconnected sensors or signal dropouts can disrupt recordings. Second, operational mistakes occur when clinicians use non-standardized coding or make manual transcription errors.

Third, patient non-adherence leads to missed appointments or incomplete logs. Finally, chemical assays sometimes fail to measure values that fall outside standard laboratory detection limits.

How does normalizing data improve the performance of Machine Learning models?Scaling features to a uniform range prevents variables with naturally larger numbers from overwhelming smaller ones. In distance-based algorithms like K-Nearest Neighbors, normalization ensures every variable contributes equally to distance calculations. For neural networks, it prevents erratic optimization steps, leading to faster and smoother convergence during training. It also ensures that regularization penalties treat all features fairly rather than punishing larger scales.

Why is visualizing data an important step before applying Machine Learning models?Visualizing data before training models helps reveal patterns, distributions, and hidden errors that basic summary statistics might miss. Exploratory Data Analysis allows you to uncover structural skewness, spot data leakage, and select the best model architecture for your specific dataset.

Why is preprocessing critical when working with medical datasets?Data preprocessing is a vital first step in biomedical data science because clinical information is often noisy, incomplete, and highly sensitive. Proper handling ensures that your models remain reliable, statistically accurate, and safe for clinical use. Medical datasets often contain wide variations and inconsistent formatting across different patients, so skipping preprocessing leads to biased predictions, inaccurate diagnoses, and models that fail when applied in real clinical settings.

What ethical concerns should be considered when handling patient data?Handling clinical records requires strict adherence to ethical principles. Patients must give informed consent regarding how their information will be used and shared. Data must be anonymized using secure techniques to prevent re-identification, ensuring compliance with privacy laws. Finally, developers must ensure training data is diverse so models do not inherit demographic biases that could harm underrepresented patient groups.

Conclusion

In conclusion, this data processing workflow successfully transformed a noisy, raw clinical dataset into a standardized, high-quality input space fully ready for predictive modeling. Addressing biologically impossible zero values through median imputation resolved critical missingness issues without shrinking the overall sample size or losing valuable patient records. Applying Min-Max scaling ensured that every clinical variable operates on a uniform scale between 0 and 1, preventing high-magnitude features from dominating model training and improving the convergence stability of gradient-based or distance-based algorithms. Exploratory visual analyses confirmed that these preprocessing steps preserved the intrinsic statistical distributions and underlying biological relationships within the data, such as the positive correlation between glucose and BMI. Ultimately, this comprehensive preparation establishes a reliable foundation for training machine learning models that can achieve optimal diagnostic accuracy, generalization performance, and stability when classifying diabetes outcomes.

URL: [AssignmentsAF2_Data_Processing.ipynb/Assignments/AF2_Data_Processing.ipynb at main · gilberto7martinezr-spec/AssignmentsAF2_Data_Processing.ipynb](#)